

Lidong Chen

List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/7028974/publications.pdf>

Version: 2024-02-01

506
papers

41,571
citations

2311

98
h-index

3312

184
g-index

518
all docs

518
docs citations

518
times ranked

18400
citing authors

#	ARTICLE	IF	CITATIONS
1	Convergence of electronic bands for high performance bulk thermoelectrics. <i>Nature</i> , 2011, 473, 66-69.	13.7	3,306
2	Copper ion liquid-like thermoelectrics. <i>Nature Materials</i> , 2012, 11, 422-425.	13.3	1,700
3	Multiple-Filled Skutterudites: High Thermoelectric Figure of Merit through Separately Optimizing Electrical and Thermal Transports. <i>Journal of the American Chemical Society</i> , 2011, 133, 7837-7846.	6.6	1,242
4	Research progress on conducting polymer based supercapacitor electrode materials. <i>Nano Energy</i> , 2017, 36, 268-285.	8.2	1,035
5	Realizing high figure of merit in heavy-band p-type half-Heusler thermoelectric materials. <i>Nature Communications</i> , 2015, 6, 8144.	5.8	893
6	High Thermoelectric Performance in Non-toxic Earth-Abundant Copper Sulfide. <i>Advanced Materials</i> , 2014, 26, 3974-3978.	11.1	631
7	Enhanced Thermoelectric Performance of Single-Walled Carbon Nanotubes/Polyaniline Hybrid Nanocomposites. <i>ACS Nano</i> , 2010, 4, 2445-2451.	7.3	605
8	High-entropy-stabilized chalcogenides with high thermoelectric performance. <i>Science</i> , 2021, 371, 830-834.	6.0	546
9	Evaluation of Half-Heusler Compounds as Thermoelectric Materials Based on the Calculated Electrical Transport Properties. <i>Advanced Functional Materials</i> , 2008, 18, 2880-2888.	7.8	486
10	Flexible Thermoelectric Materials and Generators: Challenges and Innovations. <i>Advanced Materials</i> , 2019, 31, e1807916.	11.1	419
11	Anomalous barium filling fraction and n-type thermoelectric performance of $\text{Ba}_x\text{Co}_4\text{Sb}_{12}$. <i>Journal of Applied Physics</i> , 2001, 90, 1864-1868.	1.1	418
12	Low-Symmetry Rhombohedral GeTe Thermoelectrics. <i>Joule</i> , 2018, 2, 976-987.	11.7	402
13	On the tuning of electrical and thermal transport in thermoelectrics: an integrated theory-experiment perspective. <i>Npj Computational Materials</i> , 2016, 2, .	3.5	399
14	Ultrahigh Thermoelectric Performance by Electron and Phonon Critical Scattering in $\text{Cu}_2\text{Se}_{1-x}\text{I}_x$. <i>Advanced Materials</i> , 2013, 25, 6607-6612.	11.1	394
15	Recent advances in high-performance bulk thermoelectric materials. <i>International Materials Reviews</i> , 2016, 61, 379-415.	9.4	394
16	Enhanced Seebeck coefficient through energy-barrier scattering in PbTe nanocomposites. <i>Physical Review B</i> , 2009, 79, .	1.1	389
17	Stabilizing the Optimal Carrier Concentration for High Thermoelectric Efficiency. <i>Advanced Materials</i> , 2011, 23, 5674-5678.	11.1	378
18	Strain field fluctuation effects on lattice thermal conductivity of ZrNiSn-based thermoelectric compounds. <i>Applied Physics Letters</i> , 2004, 85, 1140-1142.	1.5	368

#	ARTICLE	IF	CITATIONS
19	Low thermal conductivity and high thermoelectric figure of merit in n-type $Ba_xYb_yCo_4Sb_{12}$ double-filled skutterudites. <i>Applied Physics Letters</i> , 2008, 92, .	1.5	366
20	High efficiency Bi_2Te_3 -based materials and devices for thermoelectric power generation between 100 and 300 Å°C. <i>Energy and Environmental Science</i> , 2016, 9, 3120-3127.	15.6	358
21	Effects of partial substitution of Ni by Pd on the thermoelectric properties of ZrNiSn-based half-Heusler compounds. <i>Applied Physics Letters</i> , 2001, 79, 4165-4167.	1.5	355
22	Lattice Strain Advances Thermoelectrics. <i>Joule</i> , 2019, 3, 1276-1288.	11.7	333
23	Preparation and electrical properties of graphene nanosheet/ Al_2O_3 composites. <i>Carbon</i> , 2010, 48, 1743-1749.	5.4	315
24	Thermoelectrics: Direct Solar Thermal Energy Conversion. <i>MRS Bulletin</i> , 2008, 33, 366-368.	1.7	312
25	Improved Thermoelectric Properties of Cu-Doped Quaternary Chalcogenides of $Cu_2CdSnSe_4$. <i>Advanced Materials</i> , 2009, 21, 3808-3812.	11.1	312
26	Deposition and electrical properties of Na-In codoped p-type ZnO films by ultrasonic spray pyrolysis. <i>Applied Physics Letters</i> , 2004, 84, 541-543.	1.5	310
27	Thermoelectric Devices for Power Generation: Recent Progress and Future Challenges. <i>Advanced Engineering Materials</i> , 2016, 18, 194-213.	1.6	307
28	Ultrahigh thermoelectric performance in Cu_2Se -based hybrid materials with highly dispersed molecular CNTs. <i>Energy and Environmental Science</i> , 2017, 10, 1928-1935.	15.6	298
29	A wide-band-gap p-type thermoelectric material based on quaternary chalcogenides of Cu_2ZnSnQ_4 (Q=S,Se). <i>Applied Physics Letters</i> , 2009, 94, .	1.5	292
30	High performance n-type Ag_2Se film on nylon membrane for flexible thermoelectric power generator. <i>Nature Communications</i> , 2019, 10, 841.	5.8	291
31	Abnormally enhanced thermoelectric transport properties of SWNT/PANI hybrid films by the strengthened PANI molecular ordering. <i>Energy and Environmental Science</i> , 2014, 7, 3801-3807.	15.6	285
32	Measuring thermoelectric transport properties of materials. <i>Energy and Environmental Science</i> , 2015, 8, 423-435.	15.6	275
33	Realizing a thermoelectric conversion efficiency of 12% in bismuth telluride/skutterudite segmented modules through full-parameter optimization and energy-loss minimized integration. <i>Energy and Environmental Science</i> , 2017, 10, 956-963.	15.6	274
34	High-Performance Pseudocubic Thermoelectric Materials from Non-cubic Chalcopyrite Compounds. <i>Advanced Materials</i> , 2014, 26, 3848-3853.	11.1	269
35	Room-temperature ductile inorganic semiconductor. <i>Nature Materials</i> , 2018, 17, 421-426.	13.3	262
36	Skutterudite with graphene-modified grain-boundary complexion enhances zT enabling high-efficiency thermoelectric device. <i>Energy and Environmental Science</i> , 2017, 10, 183-191.	15.6	252

#	ARTICLE	IF	CITATIONS
37	Cu-based thermoelectric materials. <i>Energy Storage Materials</i> , 2016, 3, 85-97.	9.5	247
38	Improved Thermoelectric Performance of Silver Nanoparticles@Dispersed Bi ₂ Te ₃ Composites Deriving from Hierarchical Two-Phase Heterostructure. <i>Advanced Functional Materials</i> , 2015, 25, 966-976.	7.8	243
39	Enhanced thermoelectric properties of CNT/PANI composite nanofibers by highly orienting the arrangement of polymer chains. <i>Journal of Materials Chemistry</i> , 2012, 22, 17612.	6.7	236
40	Thermoelectric materials step up. <i>Nature Materials</i> , 2016, 15, 691-692.	13.3	236
41	Thermoelectric properties of then-type filled skutterudite Ba _{0.3} Co ₄ Sb ₁₂ doped with Ni. <i>Journal of Applied Physics</i> , 2002, 91, 3698-3705.	1.1	232
42	PANI/graphene nanocomposite films with high thermoelectric properties by enhanced molecular ordering. <i>Journal of Materials Chemistry A</i> , 2015, 3, 7086-7092.	5.2	224
43	Thermoelectric properties of tetrahedrally bonded wide-gap stannite compounds Cu ₂ ZnSn _{1-x} In _x Se ₄ . <i>Applied Physics Letters</i> , 2009, 94, .	1.5	221
44	Ternary compound CuInTe ₂ : a promising thermoelectric material with diamond-like structure. <i>Chemical Communications</i> , 2012, 48, 3818.	2.2	221
45	Entropy as a Gene-like Performance Indicator Promoting Thermoelectric Materials. <i>Advanced Materials</i> , 2017, 29, 1702712.	11.1	218
46	Dual-frequency resonant phonon scattering in Ba _x RyCo ₄ Sb ₁₂ (R=La, Ce, and Sr). <i>Applied Physics Letters</i> , 2007, 90, 192111.	1.5	213
47	On the Design of High-Efficiency Thermoelectric Clathrates through a Systematic Cross-Substitution of Framework Elements. <i>Advanced Functional Materials</i> , 2010, 20, 755-763.	7.8	195
48	Ultrahigh Thermoelectric Performance in Mosaic Crystals. <i>Advanced Materials</i> , 2015, 27, 3639-3644.	11.1	195
49	Sulfide bornite thermoelectric material: a natural mineral with ultralow thermal conductivity. <i>Energy and Environmental Science</i> , 2014, 7, 4000-4006.	15.6	193
50	Cu-Se Bond Network and Thermoelectric Compounds with Complex Diamondlike Structure. <i>Chemistry of Materials</i> , 2010, 22, 6029-6031.	3.2	189
51	Flexible thermoelectrics: from silver chalcogenides to full-inorganic devices. <i>Energy and Environmental Science</i> , 2019, 12, 2983-2990.	15.6	188
52	Enhanced Thermoelectric Performance through Tuning Bonding Energy in Cu ₂ Se _{1-x} S _x Liquid-like Materials. <i>Chemistry of Materials</i> , 2017, 29, 6367-6377.	3.2	179
53	Filling Fraction Limit for Intrinsic Voids in Crystals: Doping in Skutterudites. <i>Physical Review Letters</i> , 2005, 95, 185503.	2.9	177
54	High thermoelectric performance of Yb _{0.26} Co ₄ Sb ₁₂ /yGaSb nanocomposites originating from scattering electrons of low energy. <i>Acta Materialia</i> , 2010, 58, 3995-4002.	3.8	170

#	ARTICLE	IF	CITATIONS
55	High thermoelectric performance in copper telluride. NPG Asia Materials, 2015, 7, e210-e210.	3.8	170
56	Resonant level-induced high thermoelectric response in indium-doped GeTe. NPG Asia Materials, 2017, 9, e343-e343.	3.8	170
57	Ultrahigh power factor and flexible silver selenide-based composite film for thermoelectric devices. Energy and Environmental Science, 2020, 13, 1240-1249.	15.6	165
58	Exceptional plasticity in the bulk single-crystalline van der Waals semiconductor InSe. Science, 2020, 369, 542-545.	6.0	163
59	Synthesis and thermoelectric properties of $\text{KyCo}_4\text{Sb}_{12}$. Applied Physics Letters, 2006, 89, 221107.	1.5	153
60	Good Performance and Flexible PEDOT:PSS/ Cu_2Se Nanowire Thermoelectric Composite Films. ACS Applied Materials & Interfaces, 2019, 11, 12819-12829.	4.0	153
61	Fabrication and thermoelectric performance of textured n-type $\text{Bi}_2(\text{Te,Se})_3$ by spark plasma sintering. Materials Science and Engineering B: Solid-State Materials for Advanced Technology, 2005, 117, 334-338.	1.7	151
62	Suppression of atom motion and metal deposition in mixed ionic electronic conductors. Nature Communications, 2018, 9, 2910.	5.8	148
63	Recent Advances in Liquid-Like Thermoelectric Materials. Advanced Functional Materials, 2020, 30, 1903867.	7.8	148
64	Thermoelectric transport of Se-rich Ag_2Se in normal phases and phase transitions. Applied Physics Letters, 2014, 104, .	1.5	142
65	Enhanced thermoelectric performance of dual-element-filled skutterudites $\text{BaxCeyCo}_4\text{Sb}_{12}$. Acta Materialia, 2009, 57, 3135-3139.	3.8	140
66	Densification of Al_2O_3 Powder Using Spark Plasma Sintering. Journal of Materials Research, 2000, 15, 982-987.	1.2	139
67	High-efficiency half-Heusler thermoelectric modules enabled by self-propagating synthesis and topologic structure optimization. Energy and Environmental Science, 2019, 12, 3390-3399.	15.6	135
68	Synthesis and thermoelectric properties of p-type- and n-type-filled skutterudite $\text{RyMxCo}_4\text{Sb}_{12}$ (R:Ce,Ba,Y;M:Fe,Ni). Journal of Applied Physics, 2005, 97, 093712.	1.1	133
69	Transport Properties of Bulk Thermoelectrics: An International Round-Robin Study, Part II: Thermal Diffusivity, Specific Heat, and Thermal Conductivity. Journal of Electronic Materials, 2013, 42, 1073-1084.	1.0	131
70	Highly anisotropic P3HT films with enhanced thermoelectric performance via organic small molecule epitaxy. NPG Asia Materials, 2016, 8, e292-e292.	3.8	131
71	Realizing high-performance thermoelectric power generation through grain boundary engineering of skutterudite-based nanocomposites. Nano Energy, 2017, 41, 501-510.	8.2	130
72	Ultrahigh thermoelectric performance in Cu_2Se liquid-like materials. Materials Today Physics, 2017, 1, 14-23.	2.9	130

#	ARTICLE	IF	CITATIONS
73	Rationalizing phonon dispersion for lattice thermal conductivity of solids. National Science Review, 2018, 5, 888-894.	4.6	129
74	High-temperature thermoelectric properties of Ca ₃ Co ₄ O ₉ + δ with Eu substitution. Solid State Communications, 2004, 129, 615-618.	0.9	128
75	PbTe nanocomposites synthesized from PbTe nanocrystals. Applied Physics Letters, 2007, 90, 222112.	1.5	127
76	Forming-free colossal resistive switching effect in rare-earth-oxide Gd ₂ O ₃ films for memristor applications. Journal of Applied Physics, 2009, 106, .	1.1	126
77	The synergic regulation of conductivity and Seebeck coefficient in pure polyaniline by chemically changing the ordered degree of molecular chains. Journal of Materials Chemistry A, 2014, 2, 2634-2640.	5.2	126
78	High-Efficiency and Stable Thermoelectric Module Based on Liquid-Like Materials. Joule, 2019, 3, 1538-1548.	11.7	126
79	Large thermoelectric power factor in polyaniline/graphene nanocomposite films prepared by solution-assistant dispersing method. Journal of Materials Chemistry A, 2014, 2, 11107.	5.2	120
80	Superlow Thermal Conductivity 3D Carbon Nanotube Network for Thermoelectric Applications. ACS Applied Materials & Interfaces, 2012, 4, 81-86.	4.0	117
81	Phase diagram of In-Co-Sb system and thermoelectric properties of In-containing skutterudites. Energy and Environmental Science, 2014, 7, 812-819.	15.6	116
82	Thermoelectric properties of p-type (Bi ₂ Te ₃) _x (Sb ₂ Te ₃) _{1-x} crystals prepared via zone melting. Journal of Crystal Growth, 2005, 277, 258-263.	0.7	115
83	Transport Properties of Bulk Thermoelectrics—An International Round-Robin Study, Part I: Seebeck Coefficient and Electrical Resistivity. Journal of Electronic Materials, 2013, 42, 654-664.	1.0	115
84	Upconversion Luminescence in Er ³⁺ Doped and Yb ³⁺ /Er ³⁺ Codoped Yttria Nanocrystalline Powders. Journal of the American Ceramic Society, 2004, 87, 1072-1075.	1.9	114
85	Thermoelectric properties of p-type Fe-doped TiCoSb half-Heusler compounds. Journal of Applied Physics, 2007, 102, .	1.1	113
86	Microwave-assisted rapid synthesis of Sb ₂ Te ₃ nanosheets and thermoelectric properties of bulk samples prepared by spark plasma sintering. Journal of Materials Chemistry, 2010, 20, 1976.	6.7	112
87	Realization of high thermoelectric performance in n-type partially filled skutterudites. Journal of Materials Research, 2011, 26, 1745-1754.	1.2	112
88	Ultralow Lattice Thermal Conductivity and Superhigh Thermoelectric Figure of Merit in (Mg, Bi) Co-doped GeTe. Advanced Materials, 2021, 33, e2008773.	11.1	112
89	Copper chalcogenide thermoelectric materials. Science China Materials, 2019, 62, 8-24.	3.5	111
90	Solid-State Explosive Reaction for Nanoporous Bulk Thermoelectric Materials. Advanced Materials, 2017, 29, 1701148.	11.1	110

#	ARTICLE	IF	CITATIONS
91	Thermoelectric properties of textured p-type (Bi,Sb) ₂ Te ₃ fabricated by spark plasma sintering. Scripta Materialia, 2005, 52, 347-351.	2.6	108
92	Assembly of one-dimensional nanorods into Bi ₂ S ₃ films with enhanced thermoelectric transport properties. Applied Physics Letters, 2007, 90, 112106.	1.5	108
93	Charge-Compensated Compound Defects in Ga-containing Thermoelectric Skutterudites. Advanced Functional Materials, 2013, 23, 3194-3203.	7.8	108
94	Enhanced thermoelectric figure of merit of CoSb ₃ via large-defect scattering. Applied Physics Letters, 2004, 84, 2301-2303.	1.5	107
95	Engineering carrier scattering at the interfaces in polyaniline based nanocomposites for high thermoelectric performances. Materials Chemistry Frontiers, 2017, 1, 741-748.	3.2	107
96	Effect of TiC content on the microstructure and properties of Ti ₃ SiC ₂ -TiC composites in situ fabricated by spark plasma sintering. Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing, 2008, 487, 137-143.	2.6	106
97	Effect of antisite defects on band structure and thermoelectric performance of ZrNiSn half-Heusler alloys. Applied Physics Letters, 2010, 96, .	1.5	106
98	Cu ₂ Se-Based liquid-like thermoelectric materials: looking back and stepping forward. Energy and Environmental Science, 2020, 13, 3307-3329.	15.6	106
99	Evaluating the potential for high thermoelectric efficiency of silver selenide. Journal of Materials Chemistry C, 2013, 1, 7568.	2.7	105
100	Thermoelectric transport properties of diamond-like Cu _{1-x} Fe _{1+x} S ₂ tetrahedral compounds. Journal of Applied Physics, 2014, 116, .	1.1	104
101	Significant enhancement of figure-of-merit in carbon-reinforced Cu ₂ Se nanocrystalline solids. Nano Energy, 2017, 41, 164-171.	8.2	103
102	Fabrication and microstructure of p-type transparent conducting CuS thin film and its application in dye-sensitized solar cell. Applied Physics Letters, 2008, 93, .	1.5	102
103	Electrode interface optimization advances conversion efficiency and stability of thermoelectric devices. Nature Communications, 2020, 11, 2723.	5.8	101
104	High efficiency GeTe-based materials and modules for thermoelectric power generation. Energy and Environmental Science, 2021, 14, 995-1003.	15.6	101
105	Investigation of the Anisotropic Thermoelectric Properties of Oriented Polycrystalline SnSe. Energies, 2015, 8, 6275-6285.	1.6	99
106	Dense nanostructured solid electrolyte with high Li-ion conductivity by spark plasma sintering technique. Materials Research Bulletin, 2008, 43, 2334-2341.	2.7	97
107	Superior performance and high service stability for GeTe-based thermoelectric compounds. National Science Review, 2019, 6, 944-954.	4.6	96
108	Cu ₈ GeSe ₆ -based thermoelectric materials with an argyrodite structure. Journal of Materials Chemistry C, 2017, 5, 943-952.	2.7	93

#	ARTICLE	IF	CITATIONS
109	Enhanced stability and thermoelectric figure-of-merit in copper selenide by lithium doping. <i>Materials Today Physics</i> , 2017, 1, 7-13.	2.9	93
110	Enhanced thermoelectric performance by the combination of alloying and doping in TiCoSb-based half-Heusler compounds. <i>Journal of Applied Physics</i> , 2009, 106, .	1.1	92
111	p-Type skutterudites $R_xMyFe_3CoSb_{12}$ (R, M = Ba, Ce, Nd, and Yb): Effectiveness of double-filling for the lattice thermal conductivity reduction. <i>Intermetallics</i> , 2011, 19, 1747-1751.	1.8	92
112	Engineered Molecular Chain Ordering in Single-Walled Carbon Nanotubes/Polyaniline Composite Films for High-Performance Organic Thermoelectric Materials. <i>Chemistry - an Asian Journal</i> , 2016, 11, 1804-1810.	1.7	90
113	Electronic quality factor for thermoelectrics. <i>Science Advances</i> , 2020, 6, .	4.7	88
114	Extremely low thermal conductivity and high thermoelectric performance in liquid-like $Cu_2Se_{1-x}S_x$ polymorphic materials. <i>Journal of Materials Chemistry A</i> , 2017, 5, 18148-18156.	5.2	86
115	Nanoscale pores plus precipitates rendering high-performance thermoelectric $SnTe_{1-x}Se_x$ with refined band structures. <i>Nano Energy</i> , 2019, 60, 1-7.	8.2	86
116	Effects of partial substitution of transition metals for cobalt on the high-temperature thermoelectric properties of $Ca_3Co_4O_9$. <i>Journal of Applied Physics</i> , 2005, 97, 103905.	1.1	85
117	Half-Heusler Thermoelectric Module with High Conversion Efficiency and High Power Density. <i>Advanced Energy Materials</i> , 2020, 10, 2000888.	10.2	85
118	The thermoelectric performance of $ZrNiSn/ZrO_2$ composites. <i>Solid State Communications</i> , 2004, 130, 181-185.	0.9	84
119	Rapid fabrication of Ti_3SiC_2 -SiC nanocomposite using the spark plasma sintering-reactive synthesis (SPS-RS) method. <i>Scripta Materialia</i> , 2007, 56, 241-244.	2.6	84
120	An argyrodite-type Ag_9GaSe_6 liquid-like material with ultralow thermal conductivity and high thermoelectric performance. <i>Chemical Communications</i> , 2017, 53, 11658-11661.	2.2	84
121	Experiment on thermal uniformity and pressure drop of exhaust heat exchanger for automotive thermoelectric generator. <i>Energy</i> , 2013, 54, 372-377.	4.5	81
122	Numerical and experimental analysis for exhaust heat exchangers in automobile thermoelectric generators. <i>Case Studies in Thermal Engineering</i> , 2014, 4, 99-112.	2.8	81
123	The ϵ -electron crystal-behavior in copper chalcogenides Cu_2X (X = Se, S). <i>Journal of Materials Chemistry A</i> , 2017, 5, 5098-5105.	5.2	81
124	Interfacial evolution behavior and reliability evaluation of $CoSb_3/Ti/Mo$ -Cu thermoelectric joints during accelerated thermal aging. <i>Journal of Alloys and Compounds</i> , 2009, 477, 425-431.	2.8	80
125	Multiformity and fluctuation of Cu ordering in Cu_2Se thermoelectric materials. <i>Journal of Materials Chemistry A</i> , 2015, 3, 6901-6908.	5.2	80
126	Thermal Conductivity during Phase Transitions. <i>Advanced Materials</i> , 2019, 31, e1806518.	11.1	80

#	ARTICLE	IF	CITATIONS
127	Preparation and thermoelectric properties of SWCNT/PEDOT:PSS coated tellurium nanorod composite films. <i>Journal of Alloys and Compounds</i> , 2019, 778, 163-169.	2.8	80
128	Preparation and thermoelectric properties of PEDOT:PSS coated Te nanorod/PEDOT:PSS composite films. <i>Organic Electronics</i> , 2019, 64, 79-85.	1.4	80
129	Effect of plasma activated sintering (PAS) parameters on densification of copper powder. <i>Materials Research Bulletin</i> , 2000, 35, 619-628.	2.7	77
130	Moderate-temperature thermoelectric properties of TiCoSb-based half-Heusler compounds $Ti_{1-x}Ta_xCoSb$. <i>Journal of Applied Physics</i> , 2007, 101, 113714.	1.1	77
131	Optimized thermoelectric properties of Mo_3Sb_7-xTex with significant phonon scattering by electrons. <i>Energy and Environmental Science</i> , 2011, 4, 4086.	15.6	77
132	Stacking faults modulation for scattering optimization in GeTe-based thermoelectric materials. <i>Nano Energy</i> , 2020, 68, 104347.	8.2	77
133	Enhanced Thermoelectric Performance in n-Type Bi_2Te_3 -Based Alloys via Suppressing Intrinsic Excitation. <i>ACS Applied Materials & Interfaces</i> , 2018, 10, 21372-21380.	4.0	76
134	Structure-transformation-induced abnormal thermoelectric properties in semiconductor copper selenide. <i>Materials Letters</i> , 2013, 93, 121-124.	1.3	75
135	Effects of Ce filling fraction and Fe content on the thermoelectric properties of Co-rich $Ce_yFe_xCo_{4-x}Sb_{12}$. <i>Journal of Materials Research</i> , 2001, 16, 837-843.	1.2	74
136	Two-dimensional thermoelectrics with Rashba spin-split bands in bulk BiTeI. <i>Physical Review B</i> , 2014, 90, .	1.1	74
137	Recent Developments in Flexible Thermoelectric Devices. <i>Small Science</i> , 2021, 1, 2100005.	5.8	74
138	High thermoelectric performance and low thermal conductivity in $Cu_2-yS_1/3Se_1/3Te_1/3$ liquid-like materials with nanoscale mosaic structures. <i>Nano Energy</i> , 2017, 42, 43-50.	8.2	73
139	Are Cu_2Te -Based Compounds Excellent Thermoelectric Materials?. <i>Advanced Materials</i> , 2019, 31, e1903480.	11.1	72
140	Fabrication and thermoelectric properties of $Ca_3-xDyxCo_4O_{9+x}$ system. <i>Journal of Alloys and Compounds</i> , 2004, 376, 58-61.	2.8	71
141	Construction of a 3D-rGO network-wrapping architecture in a $Yb_yCo_4Sb_{12}$ /rGO composite for enhancing the thermoelectric performance. <i>Journal of Materials Chemistry A</i> , 2015, 3, 8643-8649.	5.2	71
142	Joining of Mo to $CoSb_3$ by spark plasma sintering by inserting a Ti interlayer. <i>Materials Letters</i> , 2004, 58, 3876-3878.	1.3	70
143	Effects of nano-TiO ₂ dispersion on the thermoelectric properties of filled-skutterudite $Ba_{0.22}Co_4Sb_{12}$. <i>Solid State Sciences</i> , 2009, 11, 1612-1616.	1.5	70
144	Thermoelectric properties of $Cu_2Se_{1-x}Te_x$ solid solutions. <i>Journal of Materials Chemistry A</i> , 2018, 6, 6977-6986.	5.2	70

#	ARTICLE	IF	CITATIONS
145	Electrical Transport Properties of Filled CoSb ₃ Skutterudites: A Theoretical Study. Journal of Electronic Materials, 2009, 38, 1397-1401.	1.0	69
146	Strong anisotropy in thermoelectric properties of CNT/PANI composites. Carbon, 2017, 114, 1-7.	5.4	69
147	High temperature sublimation behavior of antimony in CoSb ₃ thermoelectric material during thermal duration test. Journal of Alloys and Compounds, 2011, 509, 3166-3171.	2.8	68
148	Enhanced thermoelectric performance in Cd doped CuInTe ₂ compounds. Journal of Applied Physics, 2014, 115, .	1.1	68
149	Thermoelectric properties of copper-deficient Cu ₂ -Se (0.05 at% x at% 0.25) binary compounds. Ceramics International, 2017, 43, 11142-11148.	2.3	67
150	Conformal organic-inorganic semiconductor composites for flexible thermoelectrics. Energy and Environmental Science, 2020, 13, 511-518.	15.6	67
151	Dielectric properties of SrBi ₂ xPrxNb ₂ O ₉ ceramics (x=0, 0.04 and 0.2). Solid State Communications, 2005, 133, 375-379.	0.9	66
152	Effects of partial substitution of Co by Ni on the high-temperature thermoelectric properties of TiCoSb-based half-Heusler compounds. Journal of Alloys and Compounds, 2005, 391, 194-197.	2.8	66
153	Preparation of dense \hat{I}^2 -CaSiO ₃ ceramic with high mechanical strength and HAp formation ability in simulated body fluid. Journal of the European Ceramic Society, 2006, 26, 1701-1706.	2.8	66
154	Dominant red emission (4F _{9/2} → \hat{I}^2) via upconversion in YAG (Y ₃ Al ₅ O ₁₂):Yb ³⁺ ,Er ³⁺ nanopowders. Optical Materials, 2007, 29, 1352-1357.	1.7	66
155	Intrinsically High Thermoelectric Performance in AgInSe ₂ n-Type Diamond-Like Compounds. Advanced Science, 2018, 5, 1700727.	5.6	66
156	Investigation of thermoelectric properties of Cu ₂ GaxSn _{1-x} Se ₃ diamond-like compounds by hot pressing and spark plasma sintering. Acta Materialia, 2013, 61, 4297-4304.	3.8	65
157	Crystal structure across the \hat{I}^2 to \hat{I}^\pm phase transition in thermoelectric Cu ₂ xSe. IUCr, 2017, 4, 476-485.	1.0	65
158	How to Measure Thermoelectric Properties Reliably. Joule, 2018, 2, 2183-2188.	11.7	65
159	Ductile Ag ₂₀ S ₇ Te ₃ with Excellent Shape-Conformability and High Thermoelectric Performance. Advanced Materials, 2021, 33, e2007681.	11.1	65
160	New Monoclinic Phase at the Composition Cu ₂ SnSe ₃ and Its Thermoelectric Properties. Inorganic Chemistry, 2013, 52, 11067-11074.	1.9	64
161	A Device-to-Material Strategy Guiding the Double-High Thermoelectric Module. Joule, 2020, 4, 2475-2483.	11.7	64
162	Thermoelectric performance of p-type Bi-Sb-Te materials prepared by spark plasma sintering. Journal of Alloys and Compounds, 2005, 390, 208-211.	2.8	62

#	ARTICLE	IF	CITATIONS
163	Enhanced thermoelectric properties of n-type Bi ₂ Te ₃ -based nanocomposite fabricated by spark plasma sintering. <i>Journal of Alloys and Compounds</i> , 2011, 509, 4769-4773.	2.8	62
164	The High Thermoelectric Properties of Conducting Polyaniline with Special Submicron-fibre Structure. <i>Chemistry Letters</i> , 2005, 34, 522-523.	0.7	61
165	Effect of Te ₄ content on the thermoelectric properties of n-type Bi _{1-x} Te _x Se crystals prepared by zone melting. <i>Materials Chemistry and Physics</i> , 2005, 92, 39-42.	2.0	61
166	Rapidly sintering nanosized SiC particle reinforced TiC composites by the spark plasma sintering (SPS) technique. <i>Journal of Materials Science</i> , 2004, 39, 4515-4519.	1.7	60
167	Retention behavior of the electric-pulse-induced reversible resistance change effect in Ag _{0.7} La _{0.3} MnO ₃ –Pt sandwiches. <i>Applied Physics Letters</i> , 2005, 86, 172107.	1.5	60
168	High temperature reliability evaluation of CoSb ₃ /electrode thermoelectric joints. <i>Intermetallics</i> , 2009, 17, 136-141.	1.8	60
169	Controllable synthesis and electrochemical hydrogen storage properties of Bi ₂ Se ₃ architectural structures. <i>Chemical Communications</i> , 2010, 46, 3101.	2.2	60
170	Influence of fullerene dispersion on high temperature thermoelectric properties of Bi ₂ Te ₃ -based composites. <i>Journal of Applied Physics</i> , 2007, 102, 103709.	1.1	59
171	Electrical and thermal transports of binary copper sulfides Cu _x S with <i>x</i> from 1.8 to 1.96. <i>APL Materials</i> , 2016, 4, .	2.2	59
172	Infrared to visible upconversion luminescence in Er ³⁺ :Y ₂ O ₃ transparent ceramics. <i>Journal of Luminescence</i> , 2007, 122-123, 8-10.	1.5	58
173	Microstructure and properties of Ti ₃ SiC ₂ /SiC nanocomposites fabricated by spark plasma sintering. <i>Composites Science and Technology</i> , 2008, 68, 499-505.	3.8	58
174	Compound defects and thermoelectric properties in ternary CuAgSe-based materials. <i>Journal of Materials Chemistry A</i> , 2015, 3, 13662-13670.	5.2	58
175	Optimized thermoelectric properties in pseudocubic diamond-like CuGaTe ₂ compounds. <i>Journal of Materials Chemistry A</i> , 2016, 4, 1277-1289.	5.2	57
176	Significantly optimized thermoelectric properties in high-symmetry cubic Cu ₇ PSe ₆ compounds via entropy engineering. <i>Journal of Materials Chemistry A</i> , 2018, 6, 6493-6502.	5.2	55
177	Room-temperature plastic inorganic semiconductors for flexible and deformable electronics. <i>Informa-Materially</i> , 2021, 3, 22-35.	8.5	55
178	Crystalline Structure-Dependent Mechanical and Thermoelectric Performance in Ag ₂ Se _{1-x} S _x System. <i>Research</i> , 2020, 2020, 6591981.	2.8	55
179	Fabrication of a CoSb ₃ -based thermoelectric module. <i>Materials Science in Semiconductor Processing</i> , 2010, 13, 221-224.	1.9	54
180	State of boron in chemical vapour-deposited SiC-B composite powders. <i>Journal of Materials Science Letters</i> , 1990, 9, 997-999.	0.5	53

#	ARTICLE	IF	CITATIONS
181	Reduction of thermal conductivity by low energy multi-Einstein optic modes. Journal of Materiomics, 2016, 2, 187-195.	2.8	53
182	Disorder scattering effect on the high-temperature lattice thermal conductivity of TiCoSb-based half-Heusler compounds. Journal of Applied Physics, 2005, 98, 013708.	1.1	52
183	Syntheses, crystal and electronic structure, and some optical and transport properties of LnCuOTe (Ln=La, Ce, Nd). Journal of Solid State Chemistry, 2007, 180, 62-69.	1.4	52
184	Effects of Ge doping on the thermoelectric properties of TiCoSb-based p-type half-Heusler compounds. Journal of Alloys and Compounds, 2009, 467, 590-594.	2.8	52
185	Facile Chemical Synthesis of Nanocrystalline Thermoelectric Alloys Based on Bi ₂ Sb ₂ Te ₃ Se. Crystal Growth and Design, 2010, 10, 3983-3989.	1.4	52
186	Micron-thick highly conductive PEDOT films synthesized via self-inhibited polymerization: roles of anions. NPG Asia Materials, 2017, 9, e405-e405.	3.8	52
187	Microstructure Contact Studies for Skutterudite Thermoelectric Devices. International Journal of Applied Ceramic Technology, 2012, 9, 733-741.	1.1	51
188	Microstructural evolution of the interfacial layer in the Ti ₂ Al/Yb _{0.6} Co ₄ Sb ₁₂ thermoelectric joints at high temperature. Journal of Alloys and Compounds, 2014, 610, 665-670.	2.8	51
189	Roles of Cu in the Enhanced Thermoelectric Properties in Bi _{0.5} Sb _{1.5} Te ₃ . Materials, 2017, 10, 251.	1.3	51
190	Enhanced thermoelectric properties of copper phthalocyanine/single-walled carbon nanotubes hybrids. Carbon, 2020, 159, 471-477.	5.4	51
191	Synergistically Improved Molecular Doping and Carrier Mobility by Copolymerization of Donor-Acceptor and Donor-Donor Building Blocks for Thermoelectric Application. Advanced Functional Materials, 2020, 30, 2004378.	7.8	51
192	Microstructure and properties of Al ₂ O ₃ -TiC nanocomposites fabricated by spark plasma sintering from high-energy ball milled reactants. Journal of the European Ceramic Society, 2006, 26, 3393-3397.	2.8	49
193	Microwave-assisted synthesis and characterization of Bi ₂ Te ₃ nanosheets and nanotubes. Journal of Alloys and Compounds, 2009, 481, 91-95.	2.8	49
194	Thermoelectric properties of p-type YbxLayFe _{2.7} Co _{1.3} Sb ₁₂ double-filled skutterudites. Intermetallics, 2013, 32, 209-213.	1.8	49
195	International Round-Robin Study of the Thermoelectric Transport Properties of an n-Type Half-Heusler Compound from 300ÅK to 773ÅK. Journal of Electronic Materials, 2015, 44, 4482-4491.	1.0	49
196	Suppressed intrinsic excitation and enhanced thermoelectric performance in Ag _x Bi _{0.5} Sb _{1.5} Te ₃ . Journal of Materials Chemistry C, 2017, 5, 12619-12628.	2.7	49
197	Giant enhancement of the figure-of-merit over a broad temperature range in nano-boron incorporated Cu ₂ Se. Journal of Materials Chemistry A, 2018, 6, 18409-18416.	5.2	49
198	High temperature electrical and thermal properties of the bulk carbon nanotube prepared by SPS. Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing, 2006, 420, 208-211.	2.6	48

#	ARTICLE	IF	CITATIONS
199	Rapid Reactive Synthesis and Sintering of Submicron TiC/SiC Composites through Spark Plasma Sintering. <i>Journal of the American Ceramic Society</i> , 2004, 87, 1157-1160.	1.9	47
200	Relaxor Behavior of Sr _{1-x} BaxBi ₂ Nb ₂ O ₉ Ceramics. <i>Journal of the American Ceramic Society</i> , 2006, 89, 328-331.	1.9	47
201	High temperature oxidation behavior of cobalt triantimonide thermoelectric material. <i>Journal of Alloys and Compounds</i> , 2010, 504, 552-558.	2.8	47
202	High Performance and Flexible Polyvinylpyrrolidone/Ag/Ag ₂ Te Ternary Composite Film for Thermoelectric Power Generator. <i>ACS Applied Materials & Interfaces</i> , 2019, 11, 33254-33262.	4.0	47
203	Ultrahigh figure of merit of Cu ₂ Se incorporated with carbon coated boron nanoparticles. <i>Informa Mater</i> , 2019, 1, 108-115.	8.5	47
204	Fabrication of high purity Ti ₃ SiC ₂ from Ti/Si/C with the aids of Al by spark plasma sintering. <i>Journal of Alloys and Compounds</i> , 2007, 437, 203-207.	2.8	46
205	Recent Advances in n-type Thermoelectric Nanocomposites. <i>Advanced Electronic Materials</i> , 2019, 5, 1800943.	2.6	46
206	Enhanced Thermoelectric Performance and Service Stability of Cu ₂ Se Via Tailoring Chemical Compositions at Multiple Atomic Positions. <i>Advanced Functional Materials</i> , 2020, 30, 1908315.	7.8	46
207	Title is missing!. <i>Journal of Materials Science Letters</i> , 1999, 18, 1119-1121.	0.5	44
208	Thermoelectric performance of Cu _{1-x} Ag _x InTe ₂ diamond-like materials with a pseudocubic crystal structure. <i>Inorganic Chemistry Frontiers</i> , 2016, 3, 1167-1177.	3.0	44
209	Properties of undoped n-type ZnO film and N-doped p-type ZnO film deposited by ultrasonic spray pyrolysis. <i>Chemical Physics Letters</i> , 2004, 393, 256-259.	1.2	43
210	Discovery of high-performance thermoelectric copper chalcogenide using modified diffusion-couple high-throughput synthesis and automated histogram analysis technique. <i>Energy and Environmental Science</i> , 2020, 13, 3041-3053.	15.6	43
211	Fabrication and characterization of nano-SiC particles reinforced TiC/SiC nano composites. <i>Materials Letters</i> , 2004, 58, 1401-1404.	1.3	42
212	A promising p-type transparent conducting material: Layered oxysulfide [Cu ₂ S ₂][Sr ₃ Sc ₂ O ₅]. <i>Journal of Applied Physics</i> , 2007, 102, 116108.	1.1	42
213	Effect of holding time and pressure on properties of ZrB ₂ -SiC composite fabricated by the spark plasma sintering reactive synthesis method. <i>International Journal of Refractory Metals and Hard Materials</i> , 2009, 27, 177-180.	1.7	42
214	Composition optimization of p-type skutterudites Ce _y Fe _x Co _{4-x} Sb ₁₂ and Y _{by} Fe _x Co _{4-x} Sb ₁₂ . <i>Journal of Materials Research</i> , 2011, 26, 1813-1819.	1.2	42
215	Synthesis of filled skutterudite compounds: Ba _y Fe _x Co _{4-x} Sb ₁₂ . <i>Journal of Materials Research</i> , 2000, 15, 2276-2279.	1.2	41
216	High-temperature thermoelectric properties of n-type Ba _y Ni _x Co _{4-x} Sb ₁₂ . <i>Journal of Materials Research</i> , 2001, 16, 3343-3346.	1.2	41

#	ARTICLE	IF	CITATIONS
217	Synthesis and characterization of nanostructured bismuth selenide thin films. Dalton Transactions, 2010, 39, 10883.	1.6	41
218	Mechanical properties and bioactivity of \hat{f}^2 -Ca ₂ SiO ₄ ceramics synthesized by spark plasma sintering. Ceramics International, 2011, 37, 2459-2465.	2.3	41
219	Upconversion luminescence of Y ₃ Al ₅ O ₁₂ (YAG):Yb ³⁺ , Tm ³⁺ nanocrystals. Optical Materials, 2007, 30, 370-374.	1.7	40
220	Systematic Study of the Multiple-Element Filling in Caged Skutterudite CoSb ₃ . Chemistry of Materials, 2010, 22, 2384-2394.	3.2	40
221	p-type Plastic Inorganic Thermoelectric Materials. Advanced Energy Materials, 2021, 11, 2100883.	10.2	40
222	Enhanced thermoelectric performance of Se-doped PbTe bulk materials via nanostructuring and multi-scale hierarchical architecture. Journal of Alloys and Compounds, 2017, 725, 563-572.	2.8	40
223	Low temperature fabrication and characterizations of \hat{f}^2 -CaSiO ₃ ceramics. Ceramics International, 2006, 32, 457-460.	2.3	39
224	Enhanced thermoelectric performance in In _{1-x} Ga _x Sb originating from the scattering of point defects and nanoinclusion. Journal of Materials Chemistry, 2011, 21, 12398.	6.7	39
225	Quaternary Pseudocubic Cu ₂ TMSnSe ₄ (TM = Mn, Fe, Co) Chalcopyrite Thermoelectric Materials. Advanced Electronic Materials, 2016, 2, 1600312.	2.6	39
226	Microstructure of Ti ₅ Si ₃ â€“TiCâ€“Ti ₃ SiC ₂ and Ti ₅ Si ₃ â€“TiC nanocomposites in situ synthesized by spark plasma sintering. Journal of Materials Research, 2004, 19, 3004-3008.	1.2	38
227	Thermodynamic analysis of the filling fraction limits for impurities in CoSb ₃ based on ab initio calculations. Acta Materialia, 2008, 56, 1733-1740.	3.8	38
228	Improved oxidation resistance of thermoelectric skutterudites coated with composite glass. Ceramics International, 2013, 39, 4551-4557.	2.3	38
229	One-step Synthesis and Enhanced Thermoelectric Properties of Polymer-Quantum Dot Composite Films. Angewandte Chemie - International Edition, 2018, 57, 8037-8042.	7.2	38
230	Largely Enhanced Seebeck Coefficient and Thermoelectric Performance by the Distortion of Electronic Density of States in Ge ₂ Sb ₂ Te ₅ . ACS Applied Materials & Interfaces, 2019, 11, 34046-34052.	4.0	38
231	Enhanced Thermoelectric Performance of Quaternary Cu ₂ â€“Ag ₂ Se ₁ S _x Liquid-like Chalcogenides. ACS Applied Materials & Interfaces, 2019, 11, 13433-13440.	4.0	38
232	Temperature dependence of current-voltage characteristics of Agâ€“La _{0.7} Ca _{0.3} MnO ₃ â€“Pt heterostructures. Applied Physics Letters, 2006, 89, 172102.	1.5	37
233	Low thermal conductivity and enhanced thermoelectric performance of Gd-filled skutterudites. Journal of Applied Physics, 2011, 109, 023719.	1.1	37
234	Low Contact Resistivity and Interfacial Behavior of p-Type NbFeSb/Mo Thermoelectric Junction. ACS Applied Materials & Interfaces, 2019, 11, 14182-14190.	4.0	37

#	ARTICLE	IF	CITATIONS
235	Enhanced Molecular Doping for High Conductivity in Polymers with Volume Freed for Dopants. <i>Macromolecules</i> , 2019, 52, 9804-9812.	2.2	37
236	Investigation on Low-Temperature Thermoelectric Properties of Ag ₂ Se Polycrystal Fabricated by Using Zone-Melting Method. <i>Journal of Physical Chemistry Letters</i> , 2021, 12, 8246-8255.	2.1	37
237	Template synthesis of heterostructured polyaniline/Bi ₂ Te ₃ nanowires. <i>Journal of Solid State Chemistry</i> , 2005, 178, 2163-2166.	1.4	36
238	“Positive” and “negative” electric-pulse-induced reversible resistance switching effect in Pr _{0.7} Ca _{0.3} MnO ₃ films. <i>Applied Physics A: Materials Science and Processing</i> , 2007, 86, 357-360.	1.1	36
239	In Situ Assembly of Cu _x S Quantum-Dots into Thin Film: A Highly Conductive P-Type Transparent Film. <i>Journal of Physical Chemistry C</i> , 2008, 112, 12085-12088.	1.5	36
240	High-temperature thermoelectric properties of Cu _{1.97} Ag _{0.03} Se _{1+y} . <i>Materials for Renewable and Sustainable Energy</i> , 2014, 3, 1.	1.5	36
241	Decoupling Thermoelectric Performance and Stability in Liquid-Like Thermoelectric Materials. <i>Advanced Science</i> , 2020, 7, 1901598.	5.6	36
242	Entropy engineering induced exceptional thermoelectric and mechanical performances in Cu ₂ -Ag _{Te₁₋₂S} Se. <i>Acta Materialia</i> , 2022, 224, 117512.	3.8	36
243	Thermoelectric properties of Te-doped ternary CuAgSe compounds. <i>Journal of Materials Chemistry A</i> , 2015, 3, 22454-22461.	5.2	35
244	Structure family and polymorphous phase transition in the compounds with soft sublattice: Cu ₂ Se as an example. <i>Journal of Chemical Physics</i> , 2016, 144, 194502.	1.2	35
245	Thermoelectric properties of non-stoichiometric Cu _{2+x} Sn _{1-x} S ₃ compounds. <i>Journal of Applied Physics</i> , 2019, 126, .	1.1	35
246	Non-epitaxial pulsed laser deposition of Ag ₂ Se thermoelectric thin films for near-room temperature applications. <i>Ceramics International</i> , 2016, 42, 12490-12495.	2.3	34
247	Dopant-Dependent Increase in Seebeck Coefficient and Electrical Conductivity in Blended Polymers with Offset Carrier Energies. <i>Advanced Electronic Materials</i> , 2019, 5, 1800618.	2.6	34
248	Thermoelectric properties of ZrNiSn-based half-Heusler compounds by solid state reaction method. <i>Journal of Materials Science Letters</i> , 2001, 20, 2197-2199.	0.5	33
249	Alumina-nickel composites densified by spark plasma sintering. <i>Materials Letters</i> , 2005, 59, 2314-2318.	1.3	33
250	Enhanced Thermoelectric Performance in Cu-Intercalated BiTeI by Compensation Weakening Induced Mobility Improvement. <i>Scientific Reports</i> , 2015, 5, 14319.	1.6	33
251	Study on the interfacial stability of p-type Ti/Ce Fe Co ₄ Sb ₁₂ thermoelectric joints at high temperature. <i>Journal of Alloys and Compounds</i> , 2016, 671, 238-244.	2.8	33
252	Cotton-based wearable poly(3-hexylthiophene) electronic device for thermoelectric application with cross-plane temperature gradient. <i>Thin Solid Films</i> , 2018, 667, 59-63.	0.8	33

#	ARTICLE	IF	CITATIONS
253	Sb ₂ Te ₃ nanostructures with various morphologies: rapid microwave solvothermal synthesis and Seebeck coefficients. <i>CrystEngComm</i> , 2011, 13, 6811.	1.3	32
254	Preparation of nano-sized Bi ₂ Te ₃ thermoelectric material powders by cryogenic grinding. <i>Progress in Natural Science: Materials International</i> , 2012, 22, 201-206.	1.8	32
255	The effect of short carbon fibers on the thermoelectric and mechanical properties of p-type CeFe ₄ Sb ₁₂ skutterudite composites. <i>Materials & Design</i> , 2015, 67, 379-384.	5.1	32
256	Self-propagation high-temperature synthesis of half-Heusler thermoelectric materials: reaction mechanism and applicability. <i>Journal of Materials Chemistry A</i> , 2018, 6, 19470-19478.	5.2	32
257	Comparison of space- and ground-grown Bi ₂ Se _{0.21} Te _{2.79} thermoelectric crystals. <i>Journal of Crystal Growth</i> , 2010, 312, 775-780.	0.7	31
258	Effects of Sn-doping on the electrical and thermal transport properties of p-type Cerium filled skutterudites. <i>Journal of Alloys and Compounds</i> , 2011, 509, 1101-1105.	2.8	31
259	Fabrication and thermal aging behavior of skutterudites with silica-based composite protective coatings. <i>Journal of Alloys and Compounds</i> , 2012, 527, 247-251.	2.8	31
260	Electrical and thermal transport properties of Yb _x Co ₄ Sb ₁₂ filled skutterudites with ultrahigh carrier concentrations. <i>AIP Advances</i> , 2015, 5, .	0.6	31
261	Fabrication and reliability evaluation of Yb _{0.3} Co ₄ Sb ₁₂ /MoTi/MoCu/Ni thermoelectric joints. <i>Ceramics International</i> , 2015, 41, 7590-7595.	2.3	31
262	Enhanced thermoelectric performance in rare-earth filled-skutterudites. <i>Journal of Materials Chemistry C</i> , 2016, 4, 4374-4379.	2.7	31
263	Nanoscale Behavior and Manipulation of the Phase Transition in Single-Crystal Cu ₂ Se. <i>Advanced Materials</i> , 2019, 31, e1804919.	11.1	31
264	Phase-modulated mechanical and thermoelectric properties of Ag ₂ S _{1-x} Te _x ductile semiconductors. <i>Journal of Materiomics</i> , 2022, 8, 656-661.	2.8	31
265	Thermoelectric properties of n-type Sr _x M _y Co ₄ Sb ₁₂ (M=Yb, Ba) double-filled skutterudites. <i>Applied Physics A: Materials Science and Processing</i> , 2010, 100, 1109-1114.	1.1	30
266	Integrating large-area perovskite solar module with thermoelectric generator for enhanced and stable power output. <i>Nano Energy</i> , 2019, 65, 104009.	8.2	30
267	Agularite Ag ₄ S ₂ Se Thermoelectric Material: Natural Mineral with Low Lattice Thermal Conductivity. <i>ACS Applied Materials & Interfaces</i> , 2019, 11, 12632-12638.	4.0	30
268	Refined band structure plus enhanced phonon scattering realizes thermoelectric performance optimization in CuMn codoped SnTe. <i>Journal of Materials Chemistry A</i> , 2021, 9, 13065-13070.	5.2	30
269	Bismuth Sulfide Thin Films with Low Resistivity on Self-Assembled Monolayers. <i>Journal of Physical Chemistry B</i> , 2006, 110, 24054-24061.	1.2	29
270	Predication of an ultrahigh filling fraction for K in CoSb ₃ . <i>Applied Physics Letters</i> , 2006, 89, 112105.	1.5	29

#	ARTICLE	IF	CITATIONS
271	Growth and thermoelectric properties of Ba ₈ Ga ₁₆ Ge ₃₀ clathrate crystals. <i>Journal of Alloys and Compounds</i> , 2009, 482, 544-547.	2.8	29
272	Complex doping of group 13 elements In and Ga in caged skutterudite CoSb ₃ . <i>Acta Materialia</i> , 2015, 85, 112-121.	3.8	29
273	Effect of starting SiC particle size on in situ fabrication of Ti ₅ Si ₃ /TiC composites. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2006, 425, 219-224.	2.6	28
274	Microwave-assisted Preparation of Bi ₂ Te ₃ Hollow Nanospheres. <i>Chemistry Letters</i> , 2007, 36, 382-383.	0.7	28
275	Dielectric Relaxation in Layer-Structured SrBi _{2-x} Nd _x Nb ₂ O ₉ Ceramics (x=0, 0.05, 0.2, 0.35). <i>Journal of the American Ceramic Society</i> , 2007, 90, 322-326.	1.9	28
276	Thermoelectric properties of (Fe _{1-x} Co _x) ₂ VAl Heusler-type compounds. <i>Journal of Alloys and Compounds</i> , 2009, 484, 812-815.	2.8	28
277	Lattice thermal transport in Ba _x RE _y Co ₄ Sb ₁₂ (RE=Ce, Yb, and Eu) double-filled skutterudites. <i>Applied Physics Letters</i> , 2010, 96, .	1.5	28
278	Electrical properties and microcosmic study on compound defects in Ga-containing thermoelectric skutterudites. <i>Journal of Materials Chemistry A</i> , 2014, 2, 10952.	5.2	28
279	Crystal Structure and Physical Properties of Ternary Phases around the Composition Cu ₅ Sn ₂ Se ₇ with Tetrahedral Coordination of Atoms. <i>Chemistry of Materials</i> , 2014, 26, 5244-5251.	3.2	28
280	Synthesis and Thermoelectric Properties of Charge-Compensated S _y Pd _x Co _{4-x} Sb ₁₂ Skutterudites. <i>ACS Applied Materials & Interfaces</i> , 2018, 10, 625-634.	4.0	28
281	In-situ synthesized Ti ₅ Si ₃ /TiC composites by spark plasma sintering technology. <i>Journal of Materials Science</i> , 2006, 41, 3831-3835.	1.7	27
282	Quick Fabrication and Thermoelectric Properties of Cu ₁₂ Sb ₄ S ₁₃ Tetrahedrite. <i>Journal of Electronic Materials</i> , 2016, 45, 2274-2277.	1.0	27
283	Compound Defects and Thermoelectric Properties of Self-Charge Compensated Skutterudites Se _y Co ₄ Sb _{12-x} Se _x . <i>ACS Applied Materials & Interfaces</i> , 2017, 9, 22713-22724.	4.0	27
284	Three-dimensional tubular graphene/polyaniline composites as high-performance elastic thermoelectrics. <i>Composites Science and Technology</i> , 2017, 150, 135-140.	3.8	27
285	Improved electrical transport properties and optimized thermoelectric figure of merit in lithium-doped copper sulfides. <i>Rare Metals</i> , 2018, 37, 282-289.	3.6	27
286	Thermoelectric materials with crystal-amorphicity duality induced by large atomic size mismatch. <i>Joule</i> , 2021, 5, 1183-1195.	11.7	27
287	Formation of a unique glass by spark plasma sintering of a zeolite. <i>Journal of Materials Research</i> , 2009, 24, 3241-3245.	1.2	26
288	Structural evolution and thermoelectric properties of Cu _{3-x} Sn _x Se ₃ compounds with diamond-like crystal structures. <i>Dalton Transactions</i> , 2014, 43, 16788-16794.	1.6	26

#	ARTICLE	IF	CITATIONS
289	Photo-induced enhancement of the power factor of Cu ₂ S thermoelectric films. <i>Scientific Reports</i> , 2015, 5, 16291.	1.6	26
290	Thermoelectric properties of n-type Cu ₄ Sn ₇ S ₁₆ -based compounds. <i>RSC Advances</i> , 2019, 9, 7826-7832.	1.7	26
291	Preparation of silicon carbide powders by chemical vapour deposition of the SiH ₄ -CH ₄ -H ₂ system. <i>Journal of Materials Science</i> , 1989, 24, 3824-3830.	1.7	25
292	Relaxor behavior of layer structured SrBi _{1.65} La _{0.35} Nb ₂ O ₉ . <i>Journal of Applied Physics</i> , 2006, 99, 076104.	1.1	25
293	Thermoelectric and transport properties of La _{0.95} Sr _{0.05} CoO ₃ . <i>Journal of Crystal Growth</i> , 2006, 286, 1-5.	0.7	25
294	High temperature oxidation behavior and mechanism of Ti ₃ SiC ₂ @SiC nanocomposites in air. <i>Composites Science and Technology</i> , 2008, 68, 1531-1538.	3.8	25
295	Enhancement of thermoelectric performance in slightly charge-compensated Ce _y Co ₄ Sb ₁₂ skutterudites. <i>Applied Physics Letters</i> , 2013, 103, .	1.5	25
296	Enhanced Thermoelectric Properties of Polyaniline Nanofilms Induced by Self-Assembled Supramolecules. <i>Chemistry - an Asian Journal</i> , 2016, 11, 1955-1962.	1.7	25
297	Novel Fabrication Route to Al ₂ O ₃ -TiN Nanocomposites Via Spark Plasma Sintering. <i>Journal of the American Ceramic Society</i> , 2006, 89, 1540-1543.	1.9	24
298	Anomalous Dual-Element Filling in Partially Filled Skutterudites. <i>Journal of the American Chemical Society</i> , 2009, 131, 5560-5563.	6.6	24
299	Self-limited kinetics of electron doping in correlated oxides. <i>Applied Physics Letters</i> , 2015, 107, .	1.5	24
300	Improved Thermoelectric Performance in Nonstoichiometric Cu ₂ Mn ₁ SnSe ₄ Quaternary Diamondlike Compounds. <i>ACS Applied Materials & Interfaces</i> , 2018, 10, 10123-10131.	4.0	24
301	Leveraging bipolar effect to enhance transverse thermoelectricity in semimetal Mg ₂ Pb for cryogenic heat pumping. <i>Nature Communications</i> , 2021, 12, 3837.	5.8	24
302	Effect of substitution of Nd ³⁺ for Bi ³⁺ on the dielectric properties and structures of SrBi ₂ Nd ₁ Nb ₂ O ₉ bismuth layer-structured ceramics. <i>Journal of Applied Physics</i> , 2007, 101, 084102.	1.1	23
303	Tellurization: An Alternative Strategy to Construct Thermoelectric Bi ₂ Te ₃ Films. <i>Journal of Physical Chemistry C</i> , 2011, 115, 16167-16171.	1.5	23
304	Quasi-two-dimensional GeSbTe compounds as promising thermoelectric materials with anisotropic transport properties. <i>Applied Physics Letters</i> , 2019, 114, .	1.5	23
305	Enhanced Thermoelectric and Mechanical Performances in Sintered Bi _{0.48} Sb _{1.52} Te ₃ @AgSbSe ₂ Composite. <i>ACS Applied Materials & Interfaces</i> , 2021, 13, 24937-24944.	4.0	23
306	A low-cost and eco-friendly Br-doped Cu ₇ Sn ₃ S ₁₀ thermoelectric compound with <i>zT</i> around unity. <i>Journal of Materials Chemistry A</i> , 2021, 9, 7946-7954.	5.2	23

#	ARTICLE	IF	CITATIONS
307	Stable bipolar resistance switching behaviour induced by a soft breakdown process at the Al/La _{0.7} Ca _{0.3} MnO ₃ interface. Journal Physics D: Applied Physics, 2009, 42, 175408.	1.3	22
308	High-Temperature Oxidation Behavior of Filled Skutterudites Yb _y Co ₄ Sb ₁₂ . Journal of Electronic Materials, 2012, 41, 2225-2231.	1.0	22
309	Influence of electronic type of SWNTs on the thermoelectric properties of SWNTs/PANI composite films. Organic Electronics, 2016, 39, 146-152.	1.4	22
310	Enhanced thermoelectric performance in the Rashba semiconductor BiTeI through band gap engineering. Journal of Physics Condensed Matter, 2016, 28, 085801.	0.7	22
311	Enhanced thermoelectric performance of CNT/P3HT composites with low CNT content. RSC Advances, 2018, 8, 33855-33863.	1.7	22
312	Good stability and high thermoelectric performance of Fe doped Cu _{1.80} S. Physical Chemistry Chemical Physics, 2020, 22, 7374-7380.	1.3	22
313	Anion-Dependent Molecular Doping and Charge Transport in Ferric Salt-Doped P3HT for Thermoelectric Application. ACS Applied Electronic Materials, 2021, 3, 1252-1259.	2.0	22
314	Enhanced thermoelectric performance in ductile Ag ₂ S-based materials via doping iodine. Applied Physics Letters, 2021, 119, .	1.5	22
315	Tough multilayered \pm Si ₃ N ₄ ceramics prepared by spark plasma sintering. Materials Letters, 2001, 49, 239-243.	1.3	21
316	Phase assembly and microstructure of CeO ₂ -doped ZrO ₂ ceramics prepared by spark plasma sintering. Journal of the European Ceramic Society, 2005, 25, 3437-3442.	2.8	21
317	Preparation and upconversion luminescence of YAG(Y ₃ Al ₅ O ₁₂): Yb ³⁺ , Ho ³⁺ nanocrystals. Journal of Rare Earths, 2009, 27, 66-70.	2.5	21
318	Enhancing thermoelectric performance of bismuth selenide films by constructing a double-layer nanostructure. CrystEngComm, 2010, 12, 2672.	1.3	21
319	Quantitative description on structure–property relationships of Li-ion battery materials for high-throughput computations. Science and Technology of Advanced Materials, 2017, 18, 134-146.	2.8	21
320	Ultrahigh Thermoelectric Performance in SrNb _{0.2} Ti _{0.8} O ₃ Oxide Films at a Submicrometer-Scale Thickness. ACS Energy Letters, 2017, 2, 915-921.	8.8	21
321	Doubled Thermoelectric Figure of Merit in p-Type $\hat{2}$ -FeSi ₂ via Synergistically Optimizing Electrical and Thermal Transports. ACS Applied Materials & Interfaces, 2020, 12, 12901-12909.	4.0	21
322	Transparent Power-Generating Windows Based on Solar-Thermal-Electric Conversion. Advanced Energy Materials, 2021, 11, 2101213.	10.2	21
323	Enhanced Thermoelectric Properties of Bi _{0.5} Sb _{1.5} Te ₃ Films by Chemical Vapor Transport Process. ACS Applied Materials & Interfaces, 2011, 3, 1390-1393.	4.0	20
324	Enhanced power factor of higher manganese silicide via melt spin synthesis method. Journal of Applied Physics, 2014, 116, .	1.1	20

#	ARTICLE	IF	CITATIONS
325	(001)-oriented Cu _{2-y} Se thin films with tunable thermoelectric performances grown by pulsed laser deposition. <i>Ceramics International</i> , 2015, 41, 7439-7445.	2.3	20
326	Interfacial structure and stability in Ni/SKD/Ti/Ni skutterudite thermoelements. <i>Surface and Coatings Technology</i> , 2016, 285, 312-317.	2.2	20
327	Multiple nanostructures in high performance Cu ₂ S _{0.5} Te _{0.5} thermoelectric materials. <i>Ceramics International</i> , 2017, 43, 7866-7869.	2.3	20
328	Semiconducting polymer contributes favorably to the Seebeck coefficient in multi-component, high-performance n-type thermoelectric nanocomposites. <i>Journal of Materials Chemistry A</i> , 2020, 8, 9797-9805.	5.2	20
329	Novel meta-phase arising from large atomic size mismatch. <i>Matter</i> , 2022, 5, 605-615.	5.0	20
330	Structural Modularization of Cu ₂ Te Leading to High Thermoelectric Performance near the Mott–Ioffe–Regel Limit. <i>Advanced Materials</i> , 2022, 34, e2108573.	11.1	20
331	Carrier Concentration Dependence of Thermal Conductivity of Iodine-Doped n-Type PbTe. <i>Materials Transactions, JIM</i> , 2000, 41, 1282-1286.	0.9	19
332	Structural modifications and non-monotonic carrier concentration in Bi ₂ Se _{0.3} Te _{2.7} by reversible electrochemical lithium reactions. <i>Acta Materialia</i> , 2013, 61, 1508-1517.	3.8	19
333	Fabrication and contact resistivity of W–Si ₃ N ₄ /TiB ₂ –Si ₃ N ₄ /p–SiGe thermoelectric joints. <i>Ceramics International</i> , 2016, 42, 8044-8050.	2.3	19
334	Thermal transport in thermoelectric materials with chemical bond hierarchy. <i>Journal of Physics Condensed Matter</i> , 2019, 31, 183002.	0.7	19
335	High-performance n-type Ta ₄ SiTe ₄ /polyvinylidene fluoride (PVDF)/graphdiyne organic–inorganic flexible thermoelectric composites. <i>Energy and Environmental Science</i> , 2021, 14, 6586-6594.	15.6	19
336	Optimized Thermoelectric Properties of Bi _{0.48} Sb _{1.52} Te ₃ through AgCuTe Doping for Low-Grade Heat Harvesting. <i>ACS Applied Materials & Interfaces</i> , 2021, 13, 57514-57520.	4.0	19
337	Effect of Sn Content on the Electrical Properties and Thermal Conductivity of Pb _{1-x} Sn _x Te. <i>Materials Transactions, JIM</i> , 2000, 41, 1196-1201.	0.9	18
338	Synthesis and thermoelectric properties of p-type barium-filled skutterudite Ba _y Fe _x Co _{4-x} Sb ₁₂ . <i>Journal of Materials Research</i> , 2002, 17, 2953-2959.	1.2	18
339	Solution-Processed p-Type Transparent Conducting BaCu ₂ S ₂ Thin Film. <i>Chemistry of Materials</i> , 2007, 19, 3102-3104.	3.2	18
340	Dielectric tunability and imprint effect in Pb(Mg _{1/3} Nb _{2/3})O ₃ -PbTiO ₃ ceramics. <i>Ceramics International</i> , 2007, 33, 815-819.	2.3	18
341	Preparation and properties of Î ² -CaSiO ₃ /ZrO ₂ (3Y) nanocomposites. <i>Journal of the European Ceramic Society</i> , 2008, 28, 2883-2887.	2.8	18
342	A general strategy to bismuth chalcogenide films by chemical vapor transport. <i>Journal of Materials Chemistry</i> , 2011, 21, 2351-2355.	6.7	18

#	ARTICLE	IF	CITATIONS
343	Thermopower enhancement in quantum wells with the Rashba effect. <i>Applied Physics Letters</i> , 2014, 105, .	1.5	18
344	Optimizing the Thermoelectric Performance of Poly(3-hexylthiophene) through Molecular Weight Engineering. <i>Chemistry - an Asian Journal</i> , 2018, 13, 3246-3253.	1.7	18
345	Consolidation of Nano-Sized TiN Powders by Spark Plasma Sintering. <i>Journal of the American Ceramic Society</i> , 2006, 89, 060601012420003-???	1.9	17
346	Syntheses, Crystal Structures, and Physical Properties of La ₅ Cu ₆ O ₄ S ₇ and La ₅ Cu _{6.33} O ₄ S ₇ . <i>Inorganic Chemistry</i> , 2008, 47, 4368-4374.	1.9	17
347	The Influence of Molecular Configuration on the Thermoelectrical Properties of Poly(3-hexylthiophene). <i>Journal of Electronic Materials</i> , 2016, 45, 1389-1396.	1.0	17
348	Understanding the Intrinsic Carrier Transport in Highly Oriented Poly(3-hexylthiophene): Effect of Side Chain Regioregularity. <i>Polymers</i> , 2018, 10, 815.	2.0	17
349	Ru Alloying Induced Enhanced Thermoelectric Performance in FeSi ₂ -Based Compounds. <i>ACS Applied Materials & Interfaces</i> , 2019, 11, 32151-32158.	4.0	17
350	Exceptionally Heavy Doping Boosts the Performance of Iron Silicide for Refractory Thermoelectrics. <i>Advanced Energy Materials</i> , 2022, 12, .	10.2	17
351	Electrodeposition of Sb ₂ Te ₃ Films on Si(100) and Ag Substrates. <i>Electrochemical and Solid-State Letters</i> , 2006, 9, C147.	2.2	16
352	Top-down fabrication of nano-scaled Bi ₂ Se _{0.3} Te _{2.7} associated by electrochemical Li intercalation. <i>Dalton Transactions</i> , 2011, 40, 340-343.	1.6	16
353	Investigation of the thermal conductivities across metal-insulator transition in polycrystalline VO ₂ . <i>Science Bulletin</i> , 2012, 57, 3393-3396.	1.7	16
354	Laser deposition and direct-writing of thermoelectric misfit cobaltite thin films. <i>Applied Physics Letters</i> , 2014, 104, 231907.	1.5	16
355	Scanning laser melting for rapid and massive fabrication of filled skutterudites with high thermoelectric performance. <i>Journal of Materials Chemistry A</i> , 2018, 6, 6772-6779.	5.2	16
356	Thermoelectric Properties of Ce ₂ Sb ₂ Fe ₂ Co ₄ Prepared by a Solid State Reaction. <i>Nippon Kinzoku Gakkaishi/Journal of the Japan Institute of Metals</i> , 1999, 63, 1412-1415.	0.2	16
357	Fatigue behavior of the electric pulse induced reversible resistance change effect in AgLa _{0.7} Ca _{0.3} MnO ₃ Pt sandwich. <i>Applied Physics A: Materials Science and Processing</i> , 2005, 80, 13-16.	1.1	15
358	Effect of Interfacial Thermal Resistance on Effective Thermal Conductivity of MoSi ₂ /SiC Composites. <i>Materials Transactions</i> , 2006, 47, 1247-1249.	0.4	15
359	Bioinspired Bi ₂ S ₃ Thin Films on 4-Mercaptobenzoic Acid Functionalized Self-Assembled Monolayers. <i>Crystal Growth and Design</i> , 2007, 7, 639-643.	1.4	15
360	Improvement of resistive switching property in a noncrystalline and low-resistance La _{0.7} Ca _{0.3} MnO ₃ thin film by using an Ag-Al alloy electrode. <i>Journal Physics D: Applied Physics</i> , 2008, 41, 215409.	1.3	15

#	ARTICLE	IF	CITATIONS
361	Thermoelectric properties of $MxMo_6Te_8$ (M=Ag, Cu). Transactions of Nonferrous Metals Society of China, 2009, 19, 642-645.	1.7	15
362	Improved resistive switching properties in stacked structures. Solid State Communications, 2010, 150, 137-141.	0.9	15
363	Creation of Yb_2O_3 Nanoprecipitates Through an Oxidation Process in Bulk Yb-Filled Skutterudites. Journal of Electronic Materials, 2013, 42, 382-388.	1.0	15
364	Preparation and structural evolution of Mo/SiO_x protective coating on $CoSb_3$ -based filled skutterudite thermoelectric material. Journal of Alloys and Compounds, 2014, 604, 94-99.	2.8	15
365	Thermodynamics, kinetics and electronic properties of point defects in \hat{I}^2 - $FeSi_2$. Physical Chemistry Chemical Physics, 2019, 21, 10497-10504.	1.3	15
366	A high-throughput strategy to screen interfacial diffusion barrier materials for thermoelectric modules. Journal of Materials Research, 2019, 34, 1179-1187.	1.2	15
367	Crystal Structure and Thermoelectric Properties of $Cu_2Fe_1Mn_xSn_4$ Diamond-like Chalcogenides. ACS Applied Energy Materials, 2020, 3, 2137-2146.	2.5	15
368	Expand band gap and suppress bipolar excitation to optimize thermoelectric performance of $Bi_{0.35}Sb_{1.65}Te_3$ sintered materials. Materials Today Physics, 2021, 21, 100544.	2.9	15
369	Thermoelectric properties and service stability of Ag-containing Cu_2Se . Materials Today Physics, 2021, 21, 100550.	2.9	15
370	Design and fabrication of W-Mo-Ti-TiAl-Al system functionally graded material. Metallurgical and Materials Transactions A: Physical Metallurgy and Materials Science, 2000, 31, 2369-2376.	1.1	14
371	Microstructure Characterization and Mechanical Properties of $TiSi_2-SiC-Ti_3Si_2$ Composites Prepared by Spark Plasma Sintering. Materials Transactions, 2006, 47, 845-848.	0.4	14
372	Piezoelectric and ferroelectric properties of $SrBi_2(Nb_{1-x}Ta_x)_{2O_9}$ ceramics. Materials Science and Engineering B: Solid-State Materials for Advanced Technology, 2006, 135, 60-64.	1.7	14
373	“Pesting”-like oxidation phenomenon of p-type filled skutterudite $Ce_{0.9}Fe_3CoSb_{12}$. Journal of Alloys and Compounds, 2014, 612, 365-371.	2.8	14
374	Constructing nanoporous carbon nanotubes/ Bi_2Te_3 composite for synchronous regulation of the electrical and thermal performances. Journal of Applied Physics, 2017, 121, .	1.1	14
375	Study on the High Temperature Interfacial Stability of $Ti/Mo/Yb_{0.3}Co_4Sb_{12}$ Thermoelectric Joints. Applied Sciences (Switzerland), 2017, 7, 952.	1.3	14
376	Thermoelectric properties of polycrystalline palladium sulfide. RSC Advances, 2018, 8, 13154-13158.	1.7	14
377	A novel hydrophilic pyridinium salt polymer/SWCNTs composite film for high thermoelectric performance. Polymer, 2018, 136, 149-156.	1.8	14
378	Effect of Fabrication Method on Microstructure and Properties of Al_2O_3-TiC Composites. Materials Transactions, 2005, 46, 2015-2019.	0.4	13

#	ARTICLE	IF	CITATIONS
379	Direct tuning of electrical properties in nano-structured Bi ₂ Se _{0.3} Te _{2.7} by reversible electrochemical lithium reactions. <i>Chemical Communications</i> , 2011, 47, 12173.	2.2	13
380	Thermoelectric nanocomposite from the metastable void filling in caged skutterudite. <i>Journal of Materials Research</i> , 2011, 26, 1848-1856.	1.2	13
381	Fabrication, Microstructure and Mechanical Properties of TiC/Ti ₂ AlC/TiAl ₃ in situ Composite. <i>Journal of Materials Science and Technology</i> , 2011, 27, 239-244.	5.6	13
382	Oxidation Behavior of Filled Skutterudite CeFe ₄ Sb ₁₂ in Air. <i>Journal of Electronic Materials</i> , 2014, 43, 1639-1644.	1.0	13
383	Number mismatch between cations and anions as an indicator for low lattice thermal conductivity in chalcogenides. <i>Npj Computational Materials</i> , 2020, 6, .	3.5	13
384	High-Throughput Screening for Thermoelectric Semiconductors with Desired Conduction Types by Energy Positions of Band Edges. <i>Journal of the American Chemical Society</i> , 2022, 144, 8030-8037.	6.6	13
385	Solid solubility of Ir and Rh at the Co sites of skutterudites. <i>Journal of Applied Physics</i> , 2007, 101, 123525.	1.1	12
386	Reversible multilevel resistance switching of Ag/La _{0.7} Ca _{0.3} MnO ₃ /Pt heterostructures. <i>Journal of Materials Research</i> , 2008, 23, 302-307.	1.2	12
387	Post-annealing Effect on Microstructures and Thermoelectric Properties of Bi _{0.45} Sb _{1.55} Te ₃ Thin Films Deposited by Co-sputtering. <i>Journal of Electronic Materials</i> , 2012, 41, 3068-3072.	1.0	12
388	Thermoelectric properties of layered Sr _{0.29} CoO ₂ crystals. <i>Journal of Alloys and Compounds</i> , 2013, 576, 247-249.	2.8	12
389	Synthesis and physical properties of layered Ba _x Co ₂ . <i>Dalton Transactions</i> , 2014, 43, 15414-15418.	1.6	12
390	Phase Diagram and Thermoelectric Property of Si-B System Ceramics.. <i>Funtai Oyobi Fumatsu Yakin/Journal of the Japan Society of Powder and Powder Metallurgy</i> , 1994, 41, 1299-1303.	0.1	11
391	Synthesis and Thermoelectric Properties of Boron-rich Silicon Borides. <i>Materials Transactions, JIM</i> , 1996, 37, 1182-1185.	0.9	11
392	Microstructures of W-Mo functionally graded material. <i>Journal of Materials Science Letters</i> , 2000, 19, 955-958.	0.5	11
393	Effects of filling atoms Ba, Ce, Y and substituting atoms Fe, Ni on lattice thermal conductivity of RyM _x Co ₄ Sb ₁₂ . <i>Journal of Alloys and Compounds</i> , 2005, 394, 259-264.	2.8	11
394	Asymmetric fatigue and its endurance improvement in resistance switching of Ag/La _{0.7} Ca _{0.3} MnO ₃ /Pt heterostructures. <i>Journal Physics D: Applied Physics</i> , 2007, 40, 5373-5376.	1.3	11
395	Multiform Resistance Switching Effects in the Al/La _{0.7} Ca _{0.3} MnO ₃ /Pt Structure. <i>Electrochemical and Solid-State Letters</i> , 2009, 12, H281.	2.2	11
396	Resistance-switching properties of La _{0.67} Ca _{0.33} MnO ₃ thin films with Ag/Al alloy top electrodes. <i>Applied Physics A: Materials Science and Processing</i> , 2009, 97, 85-90.	1.1	11

#	ARTICLE	IF	CITATIONS
397	Growth and luminescence properties of undoped strontium iodide crystals. Journal of Alloys and Compounds, 2013, 568, 49-54.	2.8	11
398	Defect-enhanced void filling and novel filled phases of open-structure skutterudites. Chemical Communications, 2015, 51, 10823-10826.	2.2	11
399	Lattice dynamics of thermoelectric palladium sulfide. Journal of Alloys and Compounds, 2019, 798, 484-492.	2.8	11
400	The order-disorder transition in Cu_2Se and medium-range ordering in the high-temperature phase. Acta Crystallographica Section B: Structural Science, Crystal Engineering and Materials, 2020, 76, 201-207.	0.5	11
401	Electronic origin of the enhanced thermoelectric efficiency of Cu_2Se . Science Bulletin, 2020, 65, 1888-1893.	4.3	11
402	Thermoelectric Properties of Nano-grained Mooihoekite $\text{Cu}_9\text{Fe}_9\text{S}_{16}$. Zeitschrift Fur Anorganische Und Allgemeine Chemie, 2020, 646, 1116-1121.	0.6	11
403	Preparation and pressureless sintering of chemical vapour deposited SiC-B composite powder. Journal of Materials Science, 1996, 31, 679-683.	1.7	10
404	Preparation and Properties of p-Type $(\text{Bi}_2\text{Te}_3)_x(\text{Sb}_2\text{Te}_3)_{1-x}$ Thermoelectric Materials. Materials Transactions, 2005, 46, 959-962.	0.4	10
405	Low temperature synthesis of Bi_2Te_3 nanosheets and thermal conductivity of nanosheet-contained composites. Materials Chemistry and Physics, 2010, 121, 138-141.	2.0	10
406	Realizing phase segregation in the $\text{Ba}_{0.2}(\text{Co}_{1-x}\text{Ir}_x)_4\text{Sb}_{12}$ ($x=0, 0.1, 0.2$) filled skutterudite system. Scripta Materialia, 2010, 62, 93-96.	2.6	10
407	Thermoelectric Transport Properties of $\text{RFe}_3\text{NiSb}_{12}$ ($\text{R}=\text{Ba}, \text{Nd}$ and Yb). Journal of Materials Science and Technology, 2014, 30, 1134-1140.	5.6	10
408	Composition control of pulsed laser deposited copper (I) chalcogenide thin films via plasma/Ar interactions. Science China Materials, 2015, 58, 263-268.	3.5	10
409	Multiple phase transitions and structural oscillations in thermoelectric Cu_2S at elevating temperatures. Ceramics International, 2018, 44, 13076-13081.	2.3	10
410	One-step Synthesis and Enhanced Thermoelectric Properties of Polymer-Quantum Dot Composite Films. Angewandte Chemie, 2018, 130, 8169-8174.	1.6	10
411	16.1 Functionally Graded Materials. , 2003, , 445-464.		9
412	Dielectric and Piezoelectric Properties of $\text{SrBi}_2\text{Sm}_x\text{Nb}_2\text{O}_9$ ($x=0, 0.05, 0.1$), $T_j \leq T_c \leq T_m$ / Overl	1.0	9
413	Fabrication and Characterization of Tricalcium Silicate Bioceramics with High Mechanical Properties by Spark Plasma Sintering. International Journal of Applied Ceramic Technology, 2011, 8, 501-510.	1.1	9
414	Nano-scaled top-down of bismuth chalcogenides based on electrochemical lithium intercalation. Journal of Nanoparticle Research, 2011, 13, 6569-6578.	0.8	9

#	ARTICLE	IF	CITATIONS
415	Low-Temperature Magnetic and Thermoelectric Properties of Layered $\text{Ca}_{0.33}\text{Co}_2$ Crystals. <i>Journal of the Physical Society of Japan</i> , 2011, 80, 074802.	0.7	9
416	Interface Microstructure and Performance of Sb Contacts in Bismuth Telluride-Based Thermoelectric Elements. <i>Journal of Electronic Materials</i> , 2013, 42, 1219-1224.	1.0	9
417	THERMOELECTRIC PROPERTIES OF MANGANESE-DOPED p-TYPE SKUTTERUDITES $\text{CeyFe}_{4-x}\text{MnxSb}_{12}$. <i>Functional Materials Letters</i> , 2013, 06, 1340003.	0.7	9
418	Organic thermoelectric materials. , 2021, , 183-219.		9
419	A high-efficiency GeTe-based thermoelectric module for low-grade heat recovery. <i>Journal of Materials Chemistry A</i> , 2022, 10, 7677-7683.	5.2	9
420	Preparation of silicon carbide powders by chemical vapour deposition of the $(\text{CH}_3)_2\text{SiCl}_2\text{-H}_2$ system. <i>Journal of Materials Science</i> , 1990, 25, 4614-4621.	1.7	8
421	Solid state reaction synthesis of filled skutterudite compounds $(\text{Ce or Y})_y\text{FexCo}_{4-x}\text{Sb}_{12}$ and the effect of filling atoms Ce or Y on lattice thermal conductivity. <i>Science in China Series B: Chemistry</i> , 2000, 43, 306-312.	0.8	8
422	Analysis of relaxor mechanism and structural distortion for $\text{SrBi}_{1.6}\text{Nd}_{0.4}\text{Nb}_2\text{O}_9$ bismuth-layer-structured ceramics. <i>Applied Physics Letters</i> , 2007, 91, .	1.5	8
423	In situ synthesis of SiC/MoSi_2 composite through SPS process. <i>Journal of Alloys and Compounds</i> , 2008, 462, 170-174.	2.8	8
424	Mechanical Properties of $\text{CaSiO}_3/\text{TiSi}_3/\text{SiC}$; Composites and Hydroxyapatite Forming Ability in Simulated Body Fluid. <i>Materials Transactions</i> , 2008, 49, 2310-2314.	0.4	8
425	Solution Route to PbSe Films with Enhanced Thermoelectric Transport Properties. <i>European Journal of Inorganic Chemistry</i> , 2010, 2010, 4321-4324.	1.0	8
426	Pressure-induced superconductivity in palladium sulfide. <i>Journal of Physics Condensed Matter</i> , 2018, 30, 155703.	0.7	8
427	Enhanced Thermoelectric Performance in $\text{Ge}_{0.955}\text{Sb}_x\text{Te}/\text{FeGe}_2$ Composites Enabled by Hierarchical Defects. <i>Small</i> , 2021, 17, e2100915.	5.2	8
428	Congruent Growth of Cu_2Se Thermoelectric Thin Films Enabled by Using High Ablation Fluence During Pulsed Laser Deposition. <i>Wuji Cailiao Xuebao/Journal of Inorganic Materials</i> , 2015, 30, 1115.	0.6	8
429	Microstructures and thermoelectric properties of p-type $\text{Bi}_x\text{Sb}_{2-x}\text{Te}_3$ thin films with various compositions. <i>Electronic Materials Letters</i> , 2013, 9, 709-713.	1.0	7
430	Study on the spectroscopic properties of Pb^{2+} doped SrI_2 single crystals. <i>Journal of Alloys and Compounds</i> , 2014, 597, 249-257.	2.8	7
431	Genomic Effects of the Quenching Process on the Microstructure and Thermoelectric Properties of $\text{Yb}_{0.3}\text{Co}_4\text{Sb}_{12}$. <i>Journal of Electronic Materials</i> , 2015, 44, 1890-1895.	1.0	7
432	Scanning thermoelectric microscopy of local thermoelectric behaviors in $(\text{Bi,Sb})_2\text{Te}_3$ films. <i>Physica B: Condensed Matter</i> , 2015, 457, 156-159.	1.3	7

#	ARTICLE	IF	CITATIONS
433	Enhanced thermoelectric properties in $\text{Bi}_{0.4}\text{Sb}_{1.6}\text{Te}_3$ alloy by combining incorporation and doping using multi-scale CuAlO_2 particles. <i>Physica Status Solidi (A) Applications and Materials Science</i> , 2017, 214, 1600451.	0.8	7
434	Intrinsic lamellar defects containing atomic Cu in Cu_2X (X = S, Se) thermoelectric materials. <i>Journal of Materials Chemistry C</i> , 2021, 9, 4173-4181.	2.7	7
435	Filled Skutterudites: from Single to Multiple Filling. <i>Journal of the Korean Ceramic Society</i> , 2010, 47, 54-60.	1.1	7
436	Enhanced Thermoelectric Properties of Cu_xSe (1.75% x 2.10) during Phase Transitions. <i>Chinese Physics Letters</i> , 2021, 38, 117201.	1.3	7
437	Effect of order-disordered nano-domains on the dielectric and electrical properties of PMNT ceramics. <i>Journal of Alloys and Compounds</i> , 2006, 422, 244-248.	2.8	6
438	Fabrication of Micro/Nano-Structured Bi_2Te_3 Bulk Materials with Low Thermal Conductivity by Spark Plasma Sintering. <i>Journal of the American Ceramic Society</i> , 2012, 95, 2096-2099.	1.9	6
439	Interface characterization of Cu - Mo coating deposited on Ti - Al alloys by arc spraying. <i>Functional Materials Letters</i> , 2015, 08, 1550048.	0.7	6
440	Step distribution of Yb filling fraction during microstructural evolution in skutterudites. <i>Journal of Advanced Ceramics</i> , 2019, 8, 62-71.	8.9	6
441	Enhanced thermal stability and oxidation resistance in La_3Te_4 by compositing metallic nickel particles. <i>Acta Materialia</i> , 2022, 224, 117526.	3.8	6
442	Phase Transition Behaviors and Thermoelectric Properties of $\text{CuAgTe}_x\text{Se}_{1-x}$ near 400 K. <i>ACS Applied Materials & Interfaces</i> , 2022, 14, 1015-1023.	4.0	6
443	High-Performance and Stable (Ag, Cd)-Containing ZnSb Thermoelectric Compounds. <i>ACS Applied Materials & Interfaces</i> , 2022, 14, 26662-26670.	4.0	6
444	Preparation of $\text{SiC-W}_2\text{C}$ nano-composite powders by chemical vapour deposition of the $\text{SiH}_4\text{-CH}_4\text{-WF}_6\text{-H}_2$ system. <i>Journal of Materials Science</i> , 1993, 28, 5543-5547.	1.7	5
445	Effect of Composition on the Electrical Properties and Thermal Conductivity of $\text{Pb}_{1-x}\text{Sn}_x\text{Te}$. <i>Nippon Kinzoku Gakkaishi/Journal of the Japan Institute of Metals</i> , 1999, 63, 1423-1428.	0.2	5
446	Stepwise graded refractive-index profiles for design of a narrow-bandpass filter. <i>Applied Optics</i> , 2001, 40, 3746.	2.1	5
447	Field-induced resistance-switching of $\text{La}_{0.7}\text{Ca}_{0.3}\text{MnO}_3$ films epitaxially grown on Ir/MgO buffered Si (001) substrates. <i>Thin Solid Films</i> , 2005, 488, 98-102.	0.8	5
448	Effect of Ge Doping on Thermoelectric Properties of $\text{Sr}_y\text{Co}_4\text{Sb}_{12-x}\text{Ge}_x$. <i>Japanese Journal of Applied Physics</i> , 2008, 47, 7470.	0.8	5
449	Reversible change in magnetic moment and specific heat of $\text{La}_{0.9}\text{Ca}_{0.1}\text{MnO}_3$ at different resistance states. <i>Journal Physics D: Applied Physics</i> , 2008, 41, 115001.	1.3	5
450	Modeling Temperature Gradient Evolution of CoSb_3 Material for Thermoelectric Devices during Spark Plasma Sintering. <i>Materials Transactions</i> , 2009, 50, 782-790.	0.4	5

#	ARTICLE	IF	CITATIONS
451	Topotactic synthesis of alternately stacked $\text{Ca}_3\text{Co}_4\text{O}_9/\text{Na}_0.66\text{CoO}_2$ composite with nanoscale layer structure. <i>CrystEngComm</i> , 2010, 12, 4080.	1.3	5
452	Structural properties and resistive switching behaviour in $\text{Mg}_x\text{Zn}_{1-x}\text{O}$ alloy films grown by pulsed laser deposition. <i>Journal Physics D: Applied Physics</i> , 2011, 44, 015302.	1.3	5
453	Microstructure and contact resistivity of $(\text{Bi}, \text{Sb})_2\text{Te}_3/\text{Sb}$ interface. , 2012, , .		5
454	Synergistically Optimized Electrical and Thermal Transport Properties in Copper Phthalocyanine-Based Organic Small Molecule with Nanoscale Phase Separations. <i>ACS Applied Materials & Interfaces</i> , 2021, 13, 15064-15072.	4.0	5
455	Significantly Enhanced Thermoelectric Properties of Copper Phthalocyanine/Single-Walled Carbon Nanotube Hybrids by Iodine Doping. <i>ACS Applied Materials & Interfaces</i> , 2021, 13, 55156-55163.	4.0	5
456	Unusually high Seebeck coefficient arising from temperature-dependent carrier concentration in $\text{PbSe}/\text{AgSbSe}_2$ alloys. <i>Journal of Materials Chemistry C</i> , 2021, 9, 17365-17370.	2.7	5
457	Optimized thermoelectric properties of $\text{Bi}_{0.48}\text{Sb}_{1.52}\text{Te}_3/\text{BN}$ composites. <i>Journal of Materials Chemistry C</i> , 2022, 10, 3172-3177.	2.7	5
458	Electrical and thermal transport properties of $\text{Ba}_6\text{C}_6\text{O}$ compound. <i>Physica B: Condensed Matter</i> , 2005, 369, 28-32.	1.3	4
459	Influence of Ir substitution on the thermoelectric properties of $\text{Ba}_{0.3}(\text{Ir}_x\text{Co}_{1-x})_4\text{Sb}_{12}$ solid solutions. <i>Applied Physics A: Materials Science and Processing</i> , 2006, 85, 451-455.	1.1	4
460	Effects of oxygen partial pressure on the resistance switching properties of $\text{La}_{0.7}\text{Ca}_{0.3}\text{MnO}_3$ thin films prepared by pulsed laser deposition method. <i>Proceedings of SPIE</i> , 2008, , .	0.8	4
461	Deoxidization of V_2O_5 Powder into VO_2 Assisted by an Electrochemical Lithium Intercalation Technique. <i>International Journal of Applied Ceramic Technology</i> , 2012, 9, 942-946.	1.1	4
462	Electrical transportation performances of Nb/SrTiO_3 regulated by the anion related chemical atmospheres. <i>Materials and Design</i> , 2016, 97, 7-12.	3.3	4
463	Protective Properties of Electrochemically Deposited Al-Based Coatings on $\text{Yb}_{0.3}\text{Co}_4\text{Sb}_{12}$ Skutterudite. <i>Journal of Electronic Materials</i> , 2019, 48, 5523-5531.	1.0	4
464	Resistance switching driven by polarity and voltage of electric pulse in $\text{AgLa}_{0.7}\text{Ca}_{0.3}\text{MnO}_3/\text{Pt}$ sandwiches. <i>Applied Physics A: Materials Science and Processing</i> , 2005, 81, 265-268.	1.1	3
465	Influence of Ru Substitution on the Thermoelectric Properties of $\text{Ce}(\text{Fe}_{1-x}\text{Ru}_x)_4\text{Sb}_{12}$ Solid Solutions. <i>Journal of the Physical Society of Japan</i> , 2013, 82, 124608.	0.7	3
466	Preparation and Thermoelectric Properties of Semiconducting Single-Walled Carbon Nanotubes/Regioregular Poly(3-dodecylthiophene) Composite Films. <i>Polymers</i> , 2020, 12, 2720.	2.0	3
467	Ternary Compounds Cu_3RTe_3 ($\text{R} = \text{Y}, \text{Sm}, \text{and Dy}$): A Family of New Thermoelectric Materials with Trigonal Structures. <i>ACS Applied Materials & Interfaces</i> , 2020, 12, 40486-40494.	4.0	3
468	Effect of Cu-doping on the magnetic and electrical transport properties of three-quarter Heusler alloy $\text{ZrCo}_{1.5}\text{Sn}$. <i>Journal of Applied Physics</i> , 2021, 129, 125106.	1.1	3

#	ARTICLE	IF	CITATIONS
469	Nano-scale compositional oscillation and phase intergrowth in Cu ₂ S _{0.5} Se _{0.5} and their role in thermal transport. <i>Journal of Materials Science and Technology</i> , 2021, 79, 222-229.	5.6	3
470	“ $\frac{1}{2}$ ” μ — ζ ” ζ 。 <i>Chinese Science Bulletin</i> , 2013, 58, 2603-2608.	0.4	3
471	Vapor phase polymerization of Ag QD-embedded PEDOT film with enhanced thermoelectric and antibacterial properties. <i>NPG Asia Materials</i> , 2022, 14, .	3.8	3
472	Microstructure and Thermoelectric Property of Arc-melted Silicon Borides.. <i>Funtai Oyobi Fummatsumu Yakin/Journal of the Japan Society of Powder and Powder Metallurgy</i> , 1997, 44, 55-59.	0.1	2
473	Synthesis and Thermoelectric Properties of Filled Skutterudite by a Solid Reaction Method.. <i>Funtai Oyobi Fummatsumu Yakin/Journal of the Japan Society of Powder and Powder Metallurgy</i> , 1999, 46, 921-926.	0.1	2
474	Synthesis and Electrical Properties of BayFexCo _{4-x} Sb ₁₂ .. <i>Funtai Oyobi Fummatsumu Yakin/Journal of the Japan Society of Powder and Powder Metallurgy</i> , 2000, 47, 1165-1169.	0.1	2
475	Recent advances in filled skutterudite systems. , 0, , .		2
476	Electric-field-induced resistance behavior in $\text{Ag/Pr}_{1-x}\text{Ca}_x\text{MnO}_3/\text{Pt}$ ($x=0,0.3,1.0$) heterostructures. <i>Applied Physics A: Materials Science and Processing</i> , 2009, 96, 643-653.	1.1	2
477	Temperature dependence of microstructure and physical properties of CuInSe ₂ prepared by rapid synthesis reaction. <i>Materials Research Bulletin</i> , 2012, 47, 3908-3911.	2.7	2
478	Influence of high energy γ -radiation on thermoelectric performance of filled skutterudites compounds. <i>Journal of Alloys and Compounds</i> , 2015, 640, 388-392.	2.8	2
479	Interfacial behaviors of p-type CeyFexCo _{4-x} Sb ₁₂ /Nb thermoelectric joints. <i>Functional Materials Letters</i> , 2020, 13, 2051020.	0.7	2
480	Design and fabrication of thermoelectric devices. , 2021, , 221-267.		2
481	Oxidation Behavior of Oxidation-resistive Glass-coated PbTe.. <i>Funtai Oyobi Fummatsumu Yakin/Journal of the Japan Society of Powder and Powder Metallurgy</i> , 1997, 44, 653-657.	0.1	1
482	Effects of Y Filling Fraction on Thermoelectric Properties of YyFexCo _{4-x} Sb ₁₂ .. <i>Funtai Oyobi Fummatsumu Yakin/Journal of the Japan Society of Powder and Powder Metallurgy</i> , 2000, 47, 958-962.	0.1	1
483	Fabrication of a 33-layer optical reflection filter with stepwise graded refractive index profiles. <i>Journal of Materials Research</i> , 2000, 15, 274-277.	1.2	1
484	Corrosion Behavior of Glass Coated Hastelloy-XR in Boiling Sulfuric Acid. <i>Materials Transactions</i> , 2001, 42, 2093-2097.	0.4	1
485	DIELECTRIC PROPERTIES OF MnO ₂ -DOPED 0.9PMN-0.1PT CERAMICS UNDER A DC BIAS FIELD. <i>Integrated Ferroelectrics</i> , 2005, 74, 45-51.	0.3	1
486	RESISTANCE SWITCHING EFFECT OF Ag/Ln _{1-x} CaxMnO ₃ /Pt SANDWICH STRUCTURE. <i>Integrated Ferroelectrics</i> , 2006, 78, 207-213.	0.3	1

#	ARTICLE	IF	CITATIONS
487	Microstructures and mechanical properties of TiN-TiB ₂ -Ti ₅ Si ₃ composites in-situ fabricated by spark plasma sintering. Journal of the Ceramic Society of Japan, 2009, 117, 1085-1088.	0.5	1
488	Thermoelectric Properties of Heavy Rare Earth Filled Skutterudites Dy _y Fe _x Co _{4-\hat{x}} Sb ₁₂ . Journal of Electronic Materials, 2012, 41, 3402-3410.	1.0	1
489	Temperature-dependent photoluminescence study of Pb ²⁺ doped strontium iodide. , 2013, , .		1
490	High rate dry etching of (BiSb) ₂ Te ₃ film by CH ₄ /H ₂ -based plasma. Applied Surface Science, 2014, 317, 457-461.	3.1	1
491	Fabrication and Thermoelectric Properties of PEDOT Films and Their Composites. , 2019, , 69-96.		1
492	Strategies to optimize thermoelectric performance. , 2021, , 19-50.		1
493	Review of inorganic thermoelectric materials. , 2021, , 81-145.		1
494	Segmented modules. , 2021, , 469-492.		1
495	Deoxidization of V ₂ O ₅ Powder into VO ₂ Assisted by an Electrochemical Lithium Intercalation Technique. International Journal of Applied Ceramic Technology, 2011, 9, n/a-n/a.	1.1	1
496	Influence of Solvent-Dependent Morphology on Molecular Doping and Charge Transport in Conductive Thiophene Polymer. Materials, 2022, 15, 3293.	1.3	1
497	Fabrication and Thermoelectric Properties of Ca _{3-x} Dy _x Co ₄ O _{9+$\hat{1}$} System.. ChemInform, 2004, 35, no.	0.1	0
498	EFFECT OF La ³⁺ AND Zn ²⁺ CODOPING ON THE DIELECTRIC RESPONSES AND STABILITY OF Pb(Mg _{1/3} Nb _{2/3})O ₃ CERAMICS. Integrated Ferroelectrics, 2005, 75, 27-34.	0.3	0
499	Effect of nickel substitution on thermoelectric properties of Sr _y Co ₄ Sb ₁₂ . , 2006, , .		0
500	Effect of annealing treatment on thermoelectric properties of n-type Bi-Te-Se sintered materials. , 2007, , .		0
501	Enhanced thermoelectric properties in PbTe Nanocomposites. Materials Research Society Symposia Proceedings, 2009, 1166, 27.	0.1	0
502	Plastic Inorganic Semiconductors for Flexible Electronics. , 0, , .		0
503	Measurement of thermoelectric properties. , 2021, , 51-80.		0
504	Low-dimensional and nanocomposite thermoelectric materials. , 2021, , 147-182.		0

#	ARTICLE	IF	CITATIONS
505	High thermoelectric performance in flexible Bi ₂ Te ₃ /CNT thin films. Chinese Science Bulletin, 2019, 64, 2-3.	0.4	0
506	Weak donor-like effect to enhance the thermoelectric performance of Bi ₂ Te _{2.79} Se _{0.21} near room temperature. Functional Materials Letters, 2022, 15, .	0.7	0