Tzyy-Sheng Jason Horng

List of Publications by Year in descending order

Source: https://exaly.com/author-pdf/7095608/publications.pdf Version: 2024-02-01



#	Article	IF	CITATIONS
1	Hybrid Continuous-Wave and Self-Injection-Locking Monopulse Radar for Posture and Fall Detection. IEEE Transactions on Microwave Theory and Techniques, 2022, 70, 1686-1695.	2.9	5
2	Chest-Worn Heart Rate Variability Monitor With a Self-Injection-Locked Oscillator Tag. IEEE Transactions on Microwave Theory and Techniques, 2022, 70, 2851-2860.	2.9	6
3	A Wireless-Frequency-Locked-Loop-Based Vital Sign Sensor With Quadrature Tracking and Phase-Noise Reduction Capability. IEEE Sensors Journal, 2021, 21, 9706-9715.	2.4	4
4	2-D Self-Injection-Locked Doppler Radar for Locating Multiple People and Monitoring Their Vital Signs. IEEE Transactions on Microwave Theory and Techniques, 2021, 69, 1016-1026.	2.9	16
5	Noncontact Vital Sign Sensing Under Nonperiodic Body Movement Using a Novel Frequency-Locked-Loop Radar. IEEE Transactions on Microwave Theory and Techniques, 2021, 69, 4762-4773.	2.9	11
6	Noncontact Vital Sign Sensor Using Self-Injection-Locked (SIL) Technology and Frequency-to-Power Converter (FPC). , 2021, , .		2
7	Switch-based Self-injection-locked Radar with Data Fusion Algorithm. , 2021, , .		1
8	Highly Linear Phase-Canceling Self-Injection-Locked Ultrasonic Radar for Non-Contact Monitoring of Respiration and Heartbeat. IEEE Transactions on Biomedical Circuits and Systems, 2020, 14, 75-90.	2.7	16
9	Chest-Worn Self-Injection-Locked Oscillator Tag for Monitoring Heart Rate Variability. , 2020, , .		6
10	Human Tracking and Vital Sign Monitoring with a Switched Phased-Array Self-Injection-Locked Radar. , 2020, , .		3
11	Review of Self-Injection-Locked Radar Systems for Noncontact Detection of Vital Signs. IEEE Journal of Electromagnetics, RF and Microwaves in Medicine and Biology, 2020, 4, 294-307.	2.3	37
12	Finger Gesture Sensing and Recognition Using a Wi-Fi-based Passive Radar. , 2019, , .		4
13	Stepped-Frequency Continuous-Wave Radar With Self-Injection-Locking Technology for Monitoring Multiple Human Vital Signs. IEEE Transactions on Microwave Theory and Techniques, 2019, 67, 5396-5405.	2.9	51
14	Designing a Metasurface-based Tag Antenna for Wearable Vital Sign Sensors. , 2019, , .		12
15	Single Conversion Stepped-Frequency Continuous-Wave Radar Using Self-Injection-Locking Technology. , 2019, , .		7
16	Enhancement of Vital-Sign Sensor Signal-to-Noise Ratio Using Wireless Frequency-Locked Loop. , 2019, ,		4
17	Monitoring Displacement by a Quadrature Self-Injection-Locked Radar With Measurement- and Differential-Based Offset Calibration Methods. IEEE Sensors Journal, 2019, 19, 1905-1916.	2.4	24
18	An Injection- and Frequency-Locked Loop for Reducing Phase Noise of Wideband Oscillators. IEEE Transactions on Microwave Theory and Techniques. 2018, 66, 1374-1383.	2.9	18

4

#	Article	IF	CITATIONS
19	Noncontact Pulse Transit Time Measurement Using a Single-Frequency Continuous-Wave Radar. , 2018, ,		19
20	Transmitarray Design With Enhanced Aperture Efficiency Using Small Frequency Selective Surface Cells and Discrete Jones Matrix Analysis. IEEE Transactions on Antennas and Propagation, 2018, 66, 3983-3994.	3.1	28
21	Wearable Vital Sign Sensor Using a Single-Input Multiple-Output Self-Injection-Locked Oscillator Tag. , 2018, , .		10
22	A Review on Recent Progress of Portable Short-Range Noncontact Microwave Radar Systems. IEEE Transactions on Microwave Theory and Techniques, 2017, 65, 1692-1706.	2.9	265
23	Single Self-Injection-Locked Radar With Two Antennas for Monitoring Vital Signs With Large Body Movement Cancellation. IEEE Transactions on Microwave Theory and Techniques, 2017, 65, 5324-5333.	2.9	40
24	Displacement monitoring system based on a quadrature self-injection-locked radar technology. , 2017, , .		6
25	A single radar-based vital sign monitoring system with resistance to large body motion. , 2017, , .		8
26	Detection of vital signs for multiple subjects by using self-injection-locked radar and mutually injection-locked beam scanning array. , 2017, , .		18
27	A hybrid computer vision and Wi-Fi Doppler radar system for capturing the 3-D hand gesture trajectory with a smartphone. , 2017, , .		2
28	Wrist Pulse Rate Monitor Using Self-Injection-Locked Radar Technology. Biosensors, 2016, 6, 54.	2.3	19
29	Reducing electrochemical exfoliated graphene defects by changing the insert voltage and electrolyte composition. , 2016, , .		1
30	A low-noise CMOS frequency synthesizer with an ultra-short settling time. , 2016, , .		4
31	Electrophoretic deposition of graphene growth in a nonconductive substrate. , 2016, , .		0
32	A Self- and Mutually Injection-Locked Radar System for Monitoring Vital Signs in Real Time With Random Body Movement Cancellation. IEEE Transactions on Microwave Theory and Techniques, 2016, 64, 4812-4822.	2.9	31
33	Same side dual SIL-radar system for real-time vital sign monitoring with random body movement cancellation. , 2016, , .		4
34	Analytical modeling of vertical interconnect in single-ended applications. , 2015, , .		0
35	Vital-sign detection based on a passive WiFi radar. , 2015, , .		4

Chest-worn health monitor based on a bistatic self-injection-locked radar. , 2015, , .

#	Article	IF	CITATIONS
37	Spatially-resolved near-field diagnosis of differential signaling performance for wireless device RFI/EMC applications. , 2015, , .		3
38	Gesture Sensing Using Retransmitted Wireless Communication Signals Based on Doppler Radar Technology. IEEE Transactions on Microwave Theory and Techniques, 2015, 63, 4592-4602.	2.9	37
39	Human gesture sensor using ambient wireless signals based on passive radar technology. , 2015, , .		8
40	Chest-Worn Health Monitor Based on a Bistatic Self-Injection-Locked Radar. IEEE Transactions on Biomedical Engineering, 2015, 62, 2931-2940.	2.5	29
41	Fast prototypeâ€based design approach to highly miniaturized LTCC BPFS for WLAN/WIMAX dualâ€mode applications. Microwave and Optical Technology Letters, 2014, 56, 8-11.	0.9	1
42	Synthesizing a Multiband LTCC Bandpass Filter With Specified Transmission- and Reflection-Zero Frequencies. IEEE Transactions on Microwave Theory and Techniques, 2014, 62, 3351-3361.	2.9	23
43	Low Power FSK Receiver Using an Oscillator-Based Injection-Locked Frequency Divider. IEEE Microwave and Wireless Components Letters, 2014, 24, 114-116.	2.0	8
44	Low-Noise and High-Linearity Wideband CMOS Receiver Front-End Stacked With Glass Integrated Passive Devices. IEEE Transactions on Microwave Theory and Techniques, 2014, 62, 1229-1238.	2.9	8
45	Two CMOS Dual-Feedback Common-Gate Low-Noise Amplifiers With Wideband Input and Noise Matching. IEEE Transactions on Microwave Theory and Techniques, 2013, 61, 3690-3699.	2.9	41
46	Quasiâ€lumped bandpass filter with sharp transition edge and wide stopband rejection. Electronics Letters, 2013, 49, 479-480.	0.5	12
47	Capacitiveâ€coupled resonatorâ€based bandpass filter with controllable multiple transmission zeros at stopband. Microwave and Optical Technology Letters, 2013, 55, 1563-1565.	0.9	4
48	Design of Compact Bandpass Filter with Controllable Multiple Transmission Zeros using The Secondâ€Order Inductiveâ€Coupled Resonator. Microwave and Optical Technology Letters, 2013, 55, 2155-2157.	0.9	2
49	Phase- and Self-Injection-Locked Radar for Detecting Vital Signs with Efficient Elimination of DC Offsets and Null Points. IEEE Transactions on Microwave Theory and Techniques, 2013, 61, 685-695.	2.9	42
50	Wideband and scalable equivalent-circuit model for differential through silicon vias with measurement verification. , 2013, , .		6
51	Estimating the Reduction of Radiated Emissions From Microstrip Components Using Network Analyzer With a Bulk Current Injection Probe. IEEE Microwave and Wireless Components Letters, 2013, 23, 108-110.	2.0	6
52	Ultralow Phase Noise and Wideband CMOS VCO Using Symmetrical Body-Bias PMOS Varactors. IEEE Microwave and Wireless Components Letters, 2013, 23, 90-92.	2.0	13
53	Detection of Concealed Individuals Based on Their Vital Signs by Using a See-Through-Wall Imaging System With a Self-Injection-Locked Radar. IEEE Transactions on Microwave Theory and Techniques, 2013, 61, 696-704.	2.9	97
54	Enhancement of Frequency Synthesizer Operating Range Using a Novel Frequency-Offset Technique for LTE-A and CR Applications. IEEE Transactions on Microwave Theory and Techniques, 2013, 61, 1215-1223.	2.9	17

#	Article	IF	CITATIONS
55	Comparative modelling of differential throughâ€silicon vias up to 40ÂGHz. Electronics Letters, 2013, 49, 1483-1484.	0.5	7
56	Concurrent Vital Sign and Position Sensing of Multiple Individuals Using Self-Injection-Locked Tags and Injection-Locked I/Q Receivers With Arctangent Demodulation. IEEE Transactions on Microwave Theory and Techniques, 2013, 61, 4689-4699.	2.9	34
57	Self-injection-locked radar: An advance in continuous-wave technology for emerging radar systems. , 2013, , .		15
58	Comparative modeling study of single-ended through-silicon via between the G-S and G-S-G configuration. , 2013, , .		3
59	Design of compact BPF with controllable multiple transmission zeros for WIMAX applications. , 2013, , \cdot		1
60	Prediction of radiated emissions from microstrip components for RF/microwave circuits using measurement of common-mode current. Journal of Electromagnetic Waves and Applications, 2013, 27, 2355-2365.	1.0	1
61	ESTIMATING THE REDUCTION OF RADIATED EMISSIONS FROM TFT-LCD PANEL USING NETWORK ANALYZER WITH A BULK CURRENT INJECTION PROBE. Progress in Electromagnetics Research, 2013, 140, 181-197.	1.6	1
62	ESTIMATING RADIATED EMISSION REDUCTION FROM PRINTED CIRCUIT BOARD USING VECTOR NETWORK ANALYZER WITH A BULK CURRENT INJECTION PROBE. Progress in Electromagnetics Research, 2013, 135, 1-16.	1.6	2
63	COMPARATIVE MODELING OF SINGLE-ENDED THROUGH-SILICON VIAS IN GS AND GSG CONFIGURATIONS UP TO V-BAND FREQUENCIES. Progress in Electromagnetics Research, 2013, 143, 559-574.	1.6	7
64	Vital-sign detection Doppler radar based on phase locked self- injection oscillator. , 2012, , .		2
65	Ultralow Power Injection-Locked GFSK Receiver for Short-Range Wireless Systems. IEEE Transactions on Circuits and Systems II: Express Briefs, 2012, 59, 706-710.	2.2	5
66	Prediction of common-mode radiated emission from PCB using vector network analyzer with a bulk injection current probe. Journal of Electromagnetic Waves and Applications, 2012, 26, 2121-2129.	1.0	4
67	Optimum Design of Transformer-Type Marchand Balun Using Scalable Integrated Passive Device Technology. IEEE Transactions on Components, Packaging and Manufacturing Technology, 2012, 2, 1370-1377.	1.4	22
68	Integrated Transformer-Coupled Balun Bandpass Filters With an Optimal Common-Mode Rejection Ratio. IEEE Transactions on Components, Packaging and Manufacturing Technology, 2012, 2, 53-62.	1.4	16
69	Scalable modeling and wideband measurement techniques for a signal TSV surrounded by multiple ground TSVs for RF/high-speed applications. , 2012, , .		13
70	Design of a Direct Conversion Transmitter to Resist Combined Effects of Power Amplifier Distortion and Local Oscillator Pulling. IEEE Transactions on Microwave Theory and Techniques, 2012, 60, 2000-2009.	2.9	8
71	Effects of 3D via and die attach on power integrity of a packaged IC. , 2012, , .		0
72	Design of second-order capacitive-coupled resonator-based bandpass filter with controllable multiple transmission zeros. , 2012, , .		0

#	Article	IF	CITATIONS
73	Low cost QFN package design for millimeter-wave applications. , 2012, , .		5
74	Highly flexible and miniaturized triple-band bandpass filter design using coupled stacked spiral resonators. , 2012, , .		2
75	Wideband Compact PI Equivalent Circuit for Modeling On-Chip Spiral Inductors. IEEE Microwave and Wireless Components Letters, 2012, 22, 26-28.	2.0	8
76	Scalable modeling of Through Silicon Vias up to milimeter-wave frequency. , 2012, , .		3
77	High efficiency dual-band Class-E power amplifier design. , 2012, , .		0
78	Kahn envelope elimination and restoration technique using injection-locked oscillators. , 2012, , .		3
79	Highly sensitive and low power injection-locked FSK receiver for short-range wireless applications. , 2012, , .		3
80	High-Gain and High-Efficiency EER/Polar Transmitters Using Injection-Locked Oscillators. IEEE Transactions on Microwave Theory and Techniques, 2012, 60, 4117-4128.	2.9	8
81	Novel formulation of efficiency measure for multifilar transformers in generalized multiport configurations of integrated passive devices. Microwave and Optical Technology Letters, 2012, 54, 656-661.	0.9	1
82	Highly Miniaturized Multiband Bandpass Filter Design Based on a Stacked Spiral Resonator Structure. IEEE Transactions on Microwave Theory and Techniques, 2012, 60, 1278-1286.	2.9	23
83	Compact bandpass filter using novel transformerâ€based coupled resonators on integrated passive device glass substrate. Microwave and Optical Technology Letters, 2012, 54, 257-262.	0.9	6
84	Compact bandpass filter using novel transformerâ€based coupled resonators on integrated passive device glass substrate. Microwave and Optical Technology Letters, 2012, 54, 3-7.	0.9	6
85	GHz High Frequency TSV for 2.5D IC Packaging. International Symposium on Microelectronics, 2012, 2012, 001215-001220.	0.3	1
86	Single-Antenna Doppler Radars Using Self and Mutual Injection Locking for Vital Sign Detection With Random Body Movement Cancellation. IEEE Transactions on Microwave Theory and Techniques, 2011, 59, 3577-3587.	2.9	145
87	Integrated balun bandpass filter design with an optimal common mode rejection ratio. , 2011, , .		2
88	Direct-conversion transmitter with resistance to local oscillator pulling in non-constant envelope modulation systems. , 2011, , .		3
89	Cognitive Polar Receiver Using Two Injection-Locked Oscillator Stages. IEEE Transactions on Microwave Theory and Techniques, 2011, 59, 3484-3493.	2.9	12
90	A CMOS spectrum sensor using injection locking of two voltage-controlled oscillators for cognitive radio system. , 2011, , .		0

#	Article	IF	CITATIONS
91	VERY MINIATURE DUAL-BAND AND DUAL-MODE BANDPASS FILTER DESIGNS ON AN INTEGRATED PASSIVE DEVICE CHIP. Progress in Electromagnetics Research, 2011, 119, 461-476.	1.6	25
92	Design and analysis of spiralâ€ŧype Marchand balun using physical transformer model on glass integrated passive device substrate. Microwave and Optical Technology Letters, 2011, 53, 2011-2016.	0.9	1
93	Wireless polar receiver using two injection-locked oscillator stages for green radios. , 2011, , .		Ο
94	Vertical interconnect measurement techniques based on double-sided probing system and short-open-load-reciprocal calibration. , 2011, , .		13
95	In-plane/out-of-plane mixed probe techniques to obtain the RF characteristics of SMA connectors. , 2011, , .		1
96	A novel compact dualâ€band bandpass filter using spiralâ€shaped microstrip resonators. Microwave and Optical Technology Letters, 2010, 52, 543-547.	0.9	2
97	Miniaturized bandpass filter design using LC resonators on an organic substrate. Microwave and Optical Technology Letters, 2010, 52, 547-551.	0.9	0
98	A Novel Vital-Sign Sensor Based on a Self-Injection-Locked Oscillator. IEEE Transactions on Microwave Theory and Techniques, 2010, 58, 4112-4120.	2.9	106
99	A Rigorous Analysis of a Phase-Locked Oscillator Under Injection. IEEE Transactions on Microwave Theory and Techniques, 2010, 58, 1391-1400.	2.9	33
100	Very compact transformer-coupled balun-integrated bandpass filter using integrated passive device technology on glass substrate. , 2010, , .		2
101	Analysis and Improvement of Direct-Conversion Transmitter Pulling Effects in Constant Envelope Modulation Systems. IEEE Transactions on Microwave Theory and Techniques, 2010, 58, 4137-4146.	2.9	14
102	Generalized efficiency measure for an Above-IC multifilar transformer applied to multiport integrated passive devices. , 2010, , .		1
103	Diagnosis of EMI to laptop WWAN device from TFT-LCD driver using non-contact measurement-based transfer function technique. , 2010, , .		4
104	A novel RF sensing circuit using injection locking and frequency demodulation for cognitive radio applications. , 2009, , .		19
105	Conducted susceptibility diagnosis of vehicle electronic module using correlation between mixed-mode S-parameter measurement and bulk current injection test. , 2009, , .		3
106	A rigorous analysis of local oscillator pulling in frequency and discrete-time domain. , 2009, , .		3
107	Packaging effects on the figure of merit of a CMOS cascode low-noise amplifier: Flip-chip versus wire-bond. , 2009, , .		8
108	Design and modeling of planar transformer-based silicon integrated passive devices for wireless applications. , 2009, , .		5

7

#	Article	IF	CITATIONS
109	Electromagnetic radiation and conducted susceptibility diagnosis and analysis of vehicle electronic circuit using mixed-mode S-parameter method. , 2009, , .		Ο
110	A Novel RF Sensing Circuit Using Injection Locking and Frequency Demodulation for Cognitive Radio Applications. IEEE Transactions on Microwave Theory and Techniques, 2009, 57, 3143-3152.	2.9	18
111	Design and Linearization of Class-E Power Amplifier for Nonconstant Envelope Modulation. IEEE Transactions on Microwave Theory and Techniques, 2009, 57, 957-964.	2.9	19
112	High efficiency dual-mode RF transmitter using envelope-tracking dual-band Class-E power amplifier for W-CDMA/WiMAX systems. , 2009, , .		8
113	Packaging effects on a CMOS low-noise amplifier: Flip-chip versus wirebond. , 2009, , .		7
114	Design and modeling of planar transformer-based integrated passive devices for wireless applications. , 2009, , .		6
115	Very Compact Stacked <i> LC </i> Resonator-Based Bandpass Filters With a Novel Approach to Tune the Transmission Zeros. IEEE Microwave and Wireless Components Letters, 2009, 19, 293-295.	2.0	7
116	Design and linearization of Class-E power amplifier for non-constant envelope modulation. , 2008, , .		2
117	Hybrid quadrature polar modulator-based transmitter with digital predistorter for simultaneous enhancement of adjacent channel power ratios and power added efficiency (PAE). IET Microwaves, Antennas and Propagation, 2008, 2, 801-812.	0.7	2
118	High-performance Marchand-type balun design and fabrication using an integrated passives device (IPD) technology. , 2008, , .		1
119	Design of Miniature Bandpass Filters on an Organic Laminate Substrate Using a Modified T Prototype. , 2008, , .		4
120	A novel compact LC resonator-based bandpass filter design with tunable transmission zeros. , 2008, , .		0
121	Design of dual-band bandpass filter using compact spiral-shaped microstrip resonators. , 2008, , .		0
122	Power amplifier linearization using baseband digital predistortion for WiMAX applications. , 2008, , .		1
123	High Average-Efficiency Multimode RF Transmitter Using a Hybrid Quadrature Polar Modulator. IEEE Transactions on Circuits and Systems II: Express Briefs, 2008, 55, 249-253.	2.2	20
124	Conducted susceptibility diagnosis of vehicle electronic circuit using mixed-mode S-parameter method. , 2008, , .		0
125	Design and implementation of spiral-type Marchand Balun using glass-based IPD technology. , 2008, , .		0
126	A HQPM-Based Transmitter with Baseband Predistorter for Simultaneous Enhancement of ACPR and		0

PAE., 2007, , .

TZYY-SHENG JASON HORNG

#	Article	IF	CITATIONS
127	Q-Factor Behavior Study of On-Chip Inductors Using Transmission-Line Model. , 2007, , .		1
128	Study of Q-factor behavior of microwave integrated inductors using a lossy dispersive transmission-line model. , 2007, , .		0
129	Design and Implementation of Embedded Miniature Bandpass Filters for RF-System-in-Organic-Package Applications. , 2007, , .		7
130	Design of class-E power amplifier for hybrid quadrature polar modulation transmitter. , 2007, , .		0
131	Dual Wideband Printed Monopole Antenna for WLAN/WiMAX Applications. IEEE Antennas and Wireless Propagation Letters, 2007, 6, 149-151.	2.4	229
132	Direct-conversion quadrature modulator MMIC design with a new 90/spl deg/ phase shifter including package and PCB effects for W-CDMA applications. IEEE Transactions on Microwave Theory and Techniques, 2006, 54, 2691-2698.	2.9	9
133	A Broadband Single-Stage Equivalent Circuit for Modeling LTCC Bandpass Filters. IEEE Transactions on Microwave Theory and Techniques, 2006, 54, 4412-4421.	2.9	5
134	Envelope Following-Based RF Transmitters Using Switching-Mode Power Amplifiers. IEEE Microwave and Wireless Components Letters, 2006, 16, 476-478.	2.0	9
135	A Rigorous Study of Package and PCB Effects on W-CDMA Upconverter RFICs. IEEE Transactions on Microwave Theory and Techniques, 2006, 54, 3793-3804.	2.9	12
136	A new printed G-shaped monopole antenna for dual-band WLAN applications. Microwave and Optical Technology Letters, 2005, 45, 295-297.	0.9	55
137	Printed crisscross monopole antenna with a square conductor-backed parasitic plane for dual-band WLAN applications. Microwave and Optical Technology Letters, 2005, 46, 541-543.	0.9	4
138	High-Performance Frequency-Hopping Transmitters Using Two-Point Delta–Sigma Modulation. IEEE Transactions on Microwave Theory and Techniques, 2004, 52, 2529-2535.	2.9	48
139	S -parameter formulation of quality factor for a spiral inductor in generalized two-port configuration. IEEE Transactions on Microwave Theory and Techniques, 2003, 51, 2197-2202.	2.9	21
140	A novel modified-T equivalent circuit for modeling LTCC embedded inductors with a large bandwidth. IEEE Transactions on Microwave Theory and Techniques, 2003, 51, 2327-2333.	2.9	37
141	Radiation from a microstrip amplifier. IEEE Transactions on Microwave Theory and Techniques, 2002, 50, 2005-2010.	2.9	7
142	Optical beam induced current microscopy at DC and radio frequency. Optics Communications, 2002, 211, 39-45.	1.0	7
143	Modeling of lead-frame plastic CSPs for accurate prediction of their low-pass filter effects on RFICs. IEEE Transactions on Microwave Theory and Techniques, 2001, 49, 1538-1545.	2.9	20
144	An extrinsic-inductance independent approach for direct extraction of HBT intrinsic circuit parameters. IEEE Transactions on Microwave Theory and Techniques, 2001, 49, 2300-2305.	2.9	7

#	Article	IF	CITATIONS
145	Complete methodology for electrical modeling of RFIC packages. IEEE Transactions on Advanced Packaging, 2001, 24, 542-547.	1.7	18
146	Electrical performance improvements on RFICs using bump chip carrier packages as compared to standard thin shrink small outline packages. IEEE Transactions on Advanced Packaging, 2001, 24, 548-554.	1.7	15
147	Accurate measurement of ground-ring inductance in ball grid array package. Electronics Letters, 1999, 35, 520.	0.5	4
148	Advanced measurement techniques for generation of SPICE models of RFIC packages. Electronics Letters, 1999, 35, 1945.	0.5	6
149	Electrical modelling of enhanced ball grid array packages using coupled transmission lines. Electronics Letters, 1999, 35, 1567.	0.5	3
150	Multiple arbitrary shape via-hole and air-bridge transitions in multilayered structures. IEEE Transactions on Microwave Theory and Techniques, 1996, 44, 2504-2511.	2.9	13
151	A rigorous study of microstrip crossovers and their possible improvements. IEEE Transactions on Microwave Theory and Techniques, 1994, 42, 1802-1806.	2.9	73
152	Full-wave spectral-domain analysis of compensation of microstrip discontinuities using triangular subdomain functions. IEEE Transactions on Microwave Theory and Techniques, 1992, 40, 2137-2147.	2.9	40
153	A generalized method for distinguishing between radiation and surface-wave losses in microstrip discontinuities. IEEE Transactions on Microwave Theory and Techniques, 1990, 38, 1800-1807.	2.9	42
154	Multiple arbitrary shape via-hole and air-bridge transitions in multilayered structures. , 0, , .		3
155	An efficient current expansion technique in full-wave modeling of microstrip discontinuities of arbitrary shape. , 0, , .		0
156	A unified method for characterization of microstrip and waveguide discontinuities of irregular shape. , 0, , .		0
157	The effects of path-delay mismatch on GFSK transmitters with a dual-port architecture. , 0, , .		1
158	Linear interpolation scheme for compensation of path delay difference in an envelope elimination and restoration transmitter. , 0, , .		2
159	Miniaturized dielectric chip antenna in a C-shaped configuration with an array of shorting pins. , 0, , .		1
160	A novel EER transmitter using two-point delta-sigma modulation scheme for WLAN and 3G applications. , 0, , .		7
161	A Wideband Modulated Frequency Synthesizer for Enhanced Bluetooth Applications. , 0, , .		0