

Jiagang Wu

List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/7162444/publications.pdf>

Version: 2024-02-01

398
papers

19,063
citations

15504

65
h-index

19749

117
g-index

402
all docs

402
docs citations

402
times ranked

5676
citing authors

#	ARTICLE	IF	CITATIONS
1	Potassium–Sodium Niobate Lead-Free Piezoelectric Materials: Past, Present, and Future of Phase Boundaries. <i>Chemical Reviews</i> , 2015, 115, 2559-2595.	47.7	1,271
2	Recent development in lead-free perovskite piezoelectric bulk materials. <i>Progress in Materials Science</i> , 2018, 98, 552-624.	32.8	706
3	Giant Piezoelectricity in Potassium–Sodium Niobate Lead-Free Ceramics. <i>Journal of the American Chemical Society</i> , 2014, 136, 2905-2910.	13.7	693
4	Superior Piezoelectric Properties in Potassium–Sodium Niobate Lead-Free Ceramics. <i>Advanced Materials</i> , 2016, 28, 8519-8523.	21.0	577
5	Multiferroic bismuth ferrite-based materials for multifunctional applications: Ceramic bulks, thin films and nanostructures. <i>Progress in Materials Science</i> , 2016, 84, 335-402.	32.8	478
6	The structural origin of enhanced piezoelectric performance and stability in lead free ceramics. <i>Energy and Environmental Science</i> , 2017, 10, 528-537.	30.8	386
7	Giant Piezoelectricity and High Curie Temperature in Nanostructured Alkali Niobate Lead-Free Piezoceramics through Phase Coexistence. <i>Journal of the American Chemical Society</i> , 2016, 138, 15459-15464.	13.7	310
8	Ultrahigh Performance in Lead-Free Piezoceramics Utilizing a Relaxor Slush Polar State with Multiphase Coexistence. <i>Journal of the American Chemical Society</i> , 2019, 141, 13987-13994.	13.7	296
9	Ultrahigh energy-storage potential under low electric field in bismuth sodium titanate-based perovskite ferroelectrics. <i>Journal of Materials Chemistry A</i> , 2018, 6, 9823-9832.	10.3	244
10	Emerging new phase boundary in potassium sodium-niobate based ceramics. <i>Chemical Society Reviews</i> , 2020, 49, 671-707.	38.1	229
11	Colossal permittivity in ceramics of TiO_2 Co-doped with niobium and trivalent cation. <i>Journal of Materials Chemistry A</i> , 2015, 3, 5805-5810.	10.3	203
12	Lead-free Piezoelectrics Based on Potassium–Sodium Niobate with Giant d_{33} . <i>ACS Applied Materials & Interfaces</i> , 2013, 5, 7718-7725.	8.0	199
13	Composition and poling condition-induced electrical behavior of $(\text{Ba}_{0.85}\text{Ca}_{0.15})(\text{Ti}_{1-x}\text{Zr}_x)\text{O}_3$ lead-free piezoelectric ceramics. <i>Journal of the European Ceramic Society</i> , 2012, 32, 891-898.	5.7	197
14	Practical High Piezoelectricity in Barium Titanate Ceramics Utilizing Multiphase Convergence with Broad Structural Flexibility. <i>Journal of the American Chemical Society</i> , 2018, 140, 15252-15260.	13.7	187
15	Role of room-temperature phase transition in the electrical properties of $(\text{Ba}, \text{Ca})(\text{Ti}, \text{Zr})\text{O}_3$ ceramics. <i>Scripta Materialia</i> , 2011, 65, 771-774.	5.2	170
16	Effects of K–Na ratio on the phase structure and electrical properties of $(\text{K}_x\text{Na}_{0.96-x}\text{Li}_{0.04})(\text{Nb}_{0.91}\text{Ta}_{0.05}\text{Sb}_{0.04})\text{O}_3$ lead-free ceramics. <i>Applied Physics Letters</i> , 2007, 91, 252907.	3.3	153
17	Defects and Aliovalent Doping Engineering in Electroceramics. <i>Chemical Reviews</i> , 2020, 120, 1710-1787.	47.7	151
18	Thermally stable piezoelectric properties of $(\text{K}, \text{Na})\text{NbO}_3$ -based lead-free perovskite with rhombohedral-tetragonal coexisting phase. <i>Acta Materialia</i> , 2017, 122, 344-351.	7.9	150

#	ARTICLE	IF	CITATIONS
19	Nano-domains in lead-free piezoceramics: a review. Journal of Materials Chemistry A, 2020, 8, 10026-10073.	10.3	150
20	Perovskite lead-free piezoelectric ceramics. Journal of Applied Physics, 2020, 127, .	2.5	147
21	Ferroelectric and Impedance Behavior of La ²⁺ and Ti ⁴⁺ Codoped BiFeO ₃ Thin Films. Journal of the American Ceramic Society, 2010, 93, 2795-2803.	3.8	142
22	BiFeO ₃ thin films of (1 1 1)-orientation deposited on SrRuO ₃ buffered Pt/TiO ₂ /SiO ₂ /Si(1 0 0) substrates. Acta Materialia, 2010, 58, 1688-1697.	7.9	141
23	Colossal permittivity in titanium dioxide ceramics modified by tantalum and trivalent elements. Acta Materialia, 2016, 103, 243-251.	7.9	136
24	Multifunctional BaTiO ₃ -Based Relaxor Ferroelectrics toward Excellent Energy Storage Performance and Electrostrictive Strain Benefiting from Crossover Region. ACS Applied Materials & Interfaces, 2020, 12, 23885-23895.	8.0	127
25	Effects of Ag content on the phase structure and piezoelectric properties of (K _{0.44} xNa _{0.52} Li _{0.04} Ag _x)(Nb _{0.91} Ta _{0.05} Sb _{0.04})O ₃ lead-free ceramics. Applied Physics Letters, 2007, 91, 132914.	3.3	122
26	Effects of Secondary Phases on the High-Performance Colossal Permittivity in Titanium Dioxide Ceramics. ACS Applied Materials & Interfaces, 2018, 10, 3680-3688.	8.0	120
27	Compositional dependence of phase structure and electrical properties in (K _{0.42} Na _{0.58})NbO ₃ -LiSbO ₃ lead-free ceramics. Journal of Applied Physics, 2007, 102, 114113.	2.5	114
28	Multifunctional barium titanate ceramics via chemical modification tuning phase structure. Informa [®] Materials, 2020, 2, 1163-1190.	17.3	112
29	Giant <i>d</i> ₃₃ in (K,Na)(Nb,Sb)O ₃ -(Bi,Na,K, Li)ZrO ₃ based lead-free piezoelectrics with high <i>T</i> _c . Applied Physics Letters, 2013, 103, .	3.3	109
30	Composition dependence of colossal permittivity in (Sm _{0.5} Ta _{0.5}) _x Ti _{1-x} O ₂ ceramics. Journal of Materials Chemistry C, 2015, 3, 9206-9216.	5.5	109
31	Effect of dwell time during sintering on piezoelectric properties of (Ba _{0.85} Ca _{0.15})(Ti _{0.90} Zr _{0.10})O ₃ lead-free ceramics. Journal of Alloys and Compounds, 2011, 509, L359-L361.	5.5	107
32	Ferromagnetic, ferroelectric, and fatigue behavior of (111)-oriented BiFeO ₃ /(Bi _{1/2} Na _{1/2})TiO ₃ lead-free bilayered thin films. Applied Physics Letters, 2009, 94, .	3.3	106
33	Large <i>d</i> ₃₃ in (K,Na)(Nb,Ta,Sb)O ₃ -(Bi,Na,K)ZrO ₃ lead-free ceramics. Journal of Materials Chemistry A, 2014, 2, 4122.	10.3	103
34	Ultrahigh strain in site engineering-independent Bi _{0.5} Na _{0.5} TiO ₃ -based relaxor-ferroelectrics. Acta Materialia, 2018, 147, 70-77.	7.9	102
35	High strain in (K _{0.40} Na _{0.60})(Nb _{0.955} Sb _{0.045})O ₃ Bi _{0.50} Na _{0.50} ceramics with large piezoelectricity. Journal of Materials Chemistry C, 2014, 2, 8796-8803.	3.50	97
36	Orientation dependence of ferroelectric behavior of BiFeO ₃ thin films. Journal of Applied Physics, 2009, 106, .	2.5	94

#	ARTICLE	IF	CITATIONS
37	Construction of new morphotropic phase boundary in $0.94(K_{0.4}Na_{0.6}Ba_xNb_{1-x}Zr_x)O_3 \sim 0.06LiSbO_3$ lead-free piezoelectric ceramics. <i>Journal of Materials Science</i> , 2011, 46, 6871-6876.	3.7	93
38	Enhanced energy harvesting ability of polydimethylsiloxane-BaTiO ₃ -based flexible piezoelectric nanogenerator for tactile imitation application. <i>Nano Energy</i> , 2021, 83, 105809.	16.0	92
39	Multi-scale thermal stability of niobate-based lead-free piezoceramics with large piezoelectricity. <i>Journal of Materials Chemistry C</i> , 2015, 3, 8780-8787.	5.5	91
40	New Potassium-Sodium Niobate Ceramics with a Giant d_{33} . <i>ACS Applied Materials & Interfaces</i> , 2014, 6, 6177-6180.	8.0	90
41	Simultaneous enhancement of polarization and breakdown strength in lead-free BaTiO ₃ -based ceramics. <i>Chemical Engineering Journal</i> , 2021, 409, 128231.	12.7	89
42	Composition-driven phase boundary and electrical properties in $(Ba_{0.94}Ca_{0.06})(Ti_{1-x}M_x)O_3$ (M = Sn, Hf, Tj ETQ 0 0 0 rBT /Overlo		
43	Niobium and divalent-modified titanium dioxide ceramics: Colossal permittivity and composition design. <i>Journal of the American Ceramic Society</i> , 2017, 100, 3004-3012.	3.8	88
44	Potassium-sodium niobate lead-free ceramics: modified strain as well as piezoelectricity. <i>Journal of Materials Chemistry A</i> , 2015, 3, 1868-1874.	10.3	87
45	Perovskite BiFeO ₃ -BaTiO ₃ Ferroelectrics: Engineering Properties by Domain Evolution and Thermal Depolarization Modification. <i>Advanced Electronic Materials</i> , 2020, 6, 2000079.	5.1	87
46	Effects of a phase engineering strategy on the strain properties in KNN-based ceramics. <i>Journal of Materials Chemistry C</i> , 2019, 7, 2037-2048.	5.5	86
47	Advances in Lead-Free Piezoelectric Materials. , 2018, , .		84
48	Sintering temperature-induced electrical properties of $(Ba_{0.90}Ca_{0.10})(Ti_{0.85}Zr_{0.15})O_3$ lead-free ceramics. <i>Materials Research Bulletin</i> , 2012, 47, 1281-1284.	5.2	81
49	Multiferroic behavior and impedance spectroscopy of bilayered BiFeO ₃ /CoFe ₂ O ₄ thin films. <i>Journal of Applied Physics</i> , 2009, 105, .	2.5	80
50	Piezoelectric Properties of LiSbO ₃ -Modified $(K_{0.48}Na_{0.52})NbO_3$ Lead-Free Ceramics. <i>Japanese Journal of Applied Physics</i> , 2007, 46, 7375.	1.5	79
51	Realizing High Comprehensive Energy Storage and Ultrahigh Hardness in Lead-Free Ceramics. <i>ACS Applied Materials & Interfaces</i> , 2021, 13, 28472-28483.	8.0	78
52	Effects of K content on the dielectric, piezoelectric, and ferroelectric properties of $0.95(K_xNa_{1-x})NbO_3 \sim 0.05LiSbO_3$ lead-free ceramics. <i>Journal of Applied Physics</i> , 2008, 103, .	2.5	77
53	Role of antimony in the phase structure and electrical properties of potassium-sodium niobate lead-free ceramics. <i>RSC Advances</i> , 2015, 5, 14575-14583.	3.6	77
54	Composition-Driven Phase Boundary and Piezoelectricity in Potassium-Sodium Niobate-Based Ceramics. <i>ACS Applied Materials & Interfaces</i> , 2015, 7, 20332-20341.	8.0	76

#	ARTICLE	IF	CITATIONS
55	CaTiO ₃ -modified [(K _{0.5} Na _{0.5}) _{0.94} Li _{0.06}](Nb _{0.94} Sb _{0.06})O ₃ lead-free piezoelectric ceramics with improved temperature stability. <i>Scripta Materialia</i> , 2008, 59, 750-752.	5.2	75
56	Defect dipole-induced poling characteristics and ferroelectricity of quenched bismuth ferrite-based ceramics. <i>Journal of Materials Chemistry C</i> , 2016, 4, 6140-6151.	5.5	75
57	Identification of Phase Boundaries and Electrical Properties in Ternary Potassium-Sodium Niobate-Based Ceramics. <i>ACS Applied Materials & Interfaces</i> , 2016, 8, 18943-18953.	8.0	75
58	Compositionally Graded KNN-Based Multilayer Composite with Excellent Piezoelectric Temperature Stability. <i>Advanced Materials</i> , 2022, 34, e2109175.	21.0	74
59	Achieving Both Giant d_{33} and High T_C in Potassium-Sodium Niobate Ternary System. <i>ACS Applied Materials & Interfaces</i> , 2014, 6, 750-756.	8.0	73
60	High-performance piezoelectric-energy-harvester and self-powered mechanosensing using lead-free potassium-sodium niobate flexible piezoelectric composites. <i>Journal of Materials Chemistry A</i> , 2018, 6, 16439-16449.	10.3	73
61	Leakage mechanism of cation -modified BiFeO ₃ thin film. <i>AIP Advances</i> , 2011, 1, .	1.3	70
62	High piezoelectric coefficient of Pr ₂ O ₃ -doped Ba _{0.85} Ca _{0.15} Ti _{0.90} Zr _{0.10} O ₃ ceramics. <i>Ceramics International</i> , 2012, 38, 6359-6363.	4.8	70
63	New Lead-Free (1-x)(K _{0.5} Na _{0.5})NbO ₃ -(x)(Bi _{0.5} Na _{0.5})ZrO ₃ Ceramics with High Piezoelectricity. <i>Journal of the American Ceramic Society</i> , 2014, 97, 688-690.		
64	Effects of site engineering and doped element types on piezoelectric and dielectric properties of bismuth ferrite lead-free ceramics. <i>Journal of Materials Chemistry C</i> , 2015, 3, 11326-11334.	5.5	69
65	Thermal depolarization regulation by oxides selection in lead-free BNT/oxides piezoelectric composites. <i>Acta Materialia</i> , 2018, 158, 269-277.	7.9	69
66	Shifting the phase boundary: Potassium sodium niobate derivatives. <i>MRS Bulletin</i> , 2018, 43, 607-611.	3.5	69
67	High-performance potassium sodium niobate piezoceramics for ultrasonic transducer. <i>Nano Energy</i> , 2020, 70, 104559.	16.0	68
68	Study of the relationships among the crystal structure, phase transition behavior and macroscopic properties of modified (K,Na)NbO ₃ -based lead-free piezoceramics. <i>Journal of the European Ceramic Society</i> , 2018, 38, 2335-2343.	5.7	66
69	Effects of SrRuO ₃ buffer layer thickness on multiferroic (Bi _{0.90} La _{0.10})(Fe _{0.95} Mn _{0.05})O ₃ thin films. <i>Journal of Applied Physics</i> , 2009, 106, .	2.5	65
70	Understanding the piezoelectricity of high-performance potassium sodium niobate ceramics from diffused multi-phase coexistence and domain feature. <i>Journal of Materials Chemistry A</i> , 2019, 7, 16803-16811.	10.3	65
71	Migration Kinetics of Oxygen Vacancies in Mn-Modified BiFeO ₃ Thin Films. <i>ACS Applied Materials & Interfaces</i> , 2011, 3, 2504-2511.	8.0	64
72	Potassium-sodium niobate lead-free piezoelectric ceramics: recent advances and perspectives. <i>Journal of Materials Science: Materials in Electronics</i> , 2015, 26, 9297-9308.	2.2	64

#	ARTICLE	IF	CITATIONS
73	Giant d 33 in nonstoichiometric (K,Na)NbO ₃ -based lead-free ceramics. Scripta Materialia, 2015, 94, 25-27.	5.2	64
74	Competitive mechanism of temperature-dependent electrical properties in BiFeO ₃ -BaTiO ₃ ferroelectrics controlled by domain evolution. Acta Materialia, 2021, 206, 116601.	7.9	64
75	Strong Piezoelectricity in (1-x)(K _{0.4} Na _{0.6})(Nb _{0.96} Sb _{0.04})O _{3-x} Bi _{0.5} K _{0.5} Zr _{1-y} SnyO ₃ Lead-Free Binary System: Identification and Role of Multiphase Coexistence. ACS Applied Materials & Interfaces, 2015, 7, 5927-5937.	8.0	63
76	Role of trivalent acceptors and pentavalent donors in colossal permittivity of titanium dioxide ceramics. Journal of Materials Chemistry C, 2019, 7, 4235-4243.	5.5	63
77	Broad-temperature-span and large electrocaloric effect in lead-free ceramics utilizing successive and metastable phase transitions. Journal of Materials Chemistry A, 2019, 7, 25526-25536.	10.3	63
78	Enhanced piezoelectricity in (1-x)Tj ETQq0 0 0 rgBT /Overlock 10 Tf 50 547 Td (x)Bi _{1.05} Fe _{1-y} A _y /s ceramics: site engineering and wide phase boundary region. Dalton Transactions, 2016, 45, 11277-11285.	3.3	62
79	Giant electrostrictive effect in lead-free barium titanate-based ceramics via A-site ion-pairs engineering. Journal of Materials Chemistry A, 2019, 7, 17366-17375.	10.3	61
80	Improved temperature stability of CaTiO ₃ -modified [(K _{0.5} Na _{0.5}) _{0.96} Li _{0.04}](Nb _{0.91} Sb _{0.05} Ta _{0.04})O ₃ lead-free piezoelectric ceramics. Journal of Applied Physics, 2008, 104, .	2.5	60
81	Giant electrocaloric effect in lead-free Ba _{0.94} Ca _{0.06} Ti _{1-x} Sn _x O ₃ ceramics with tunable Curie temperature. Applied Physics Letters, 2015, 107, .	3.3	60
82	Electrical behavior and oxygen vacancies in BiFeO ₃ /[(Bi _{1/2} Na _{1/2}) _{0.94} Ba _{0.06}]TiO ₃ thin film. Applied Physics Letters, 2009, 95, .	3.3	59
83	New potassium-sodium niobate lead-free piezoceramic: Giant-d ₃₃ vs. sintering temperature. Journal of Applied Physics, 2014, 115, .	2.5	59
84	Composition-induced phase transitions and enhanced electrical properties in bismuth sodium titanate ceramics. Journal of the American Ceramic Society, 2017, 100, 5601-5609.	3.8	59
85	A new method to improve the electrical properties of KNN-based ceramics: Tailoring phase fraction. Journal of the European Ceramic Society, 2018, 38, 85-94.	5.7	58
86	Microstructural Origins of High Piezoelectric Performance: A Pathway to Practical Lead-Free Materials. Advanced Functional Materials, 2019, 29, 1902911.	14.9	58
87	Large Electrocaloric Effect in (Bi _{0.5} Na _{0.5})TiO ₃ -Based Relaxor Ferroelectrics. ACS Applied Materials & Interfaces, 2020, 12, 33934-33940.	8.0	58
88	Synergistically optimizing electrocaloric effects and temperature span in KNN-based ceramics utilizing a relaxor multiphase boundary. Journal of Materials Chemistry C, 2020, 8, 4030-4039.	5.5	57
89	Nanoscale bubble domains with polar topologies in bulk ferroelectrics. Nature Communications, 2021, 12, 3632.	12.8	57
90	New (1-x)K _{0.45} Na _{0.55} Nb _{0.96} Sb _{0.04} O _{3-x} Bi _{0.5} Na _{0.5} HfO ₃ lead-free ceramics: Phase boundary and their electrical properties. Journal of Applied Physics, 2015, 118, .	2.5	55

#	ARTICLE	IF	CITATIONS
91	Dielectric, ferroelectric, and piezoelectric properties in potassium sodium niobate ceramics with rhombohedral-orthorhombic and orthorhombic-tetragonal phase boundaries. <i>Ceramics International</i> , 2014, 40, 5771-5779.	4.8	54
92	Quenched bismuth ferrite-barium titanate lead-free piezoelectric ceramics. <i>Journal of Alloys and Compounds</i> , 2016, 676, 505-512.	5.5	54
93	A polymer-metal-polymer-metal heterostructure for enhanced photocatalytic hydrogen production. <i>Journal of Materials Chemistry A</i> , 2015, 3, 109-115.	10.3	53
94	Enhanced electrocaloric effect near polymorphic phase boundary in lead-free potassium sodium niobate ceramics. <i>Applied Physics Letters</i> , 2017, 110, .	3.3	53
95	Good temperature stability of $K_{0.5}Na_{0.5}NbO_3$ based lead-free ceramics and their applications in buzzers. <i>Journal of the European Ceramic Society</i> , 2008, 28, 2963-2968.	5.7	52
96	Ferroelectric Behavior in Bismuth Ferrite Thin Films of Different Thickness. <i>ACS Applied Materials & Interfaces</i> , 2011, 3, 3261-3263.	8.0	52
97	Enhanced d_{33} value of $Bi_{0.5}Na_{0.5}TiO_3$ -($Ba_{0.85}Ca_{0.15}$)($Ti_{0.90}Zr_{0.10}$) O_3 lead-free ceramics. <i>Journal of Alloys and Compounds</i> , 2012, 521, 4-7.	5.5	52
98	(Ba, Ca)(Ti, Zr) O_3 - $BiFeO_3$ lead-free piezoelectric ceramics. <i>Current Applied Physics</i> , 2012, 12, 534-538.	2.4	52
99	Giant piezoelectric effect and high strain response in $(1-x)(K_{0.45}Na_{0.55})(Nb_{1-x}Sb_x)O_3-xBi_{0.5}Na_{0.5}Zr_{1-x}Hf_xO_3$ lead-free ceramics. <i>Journal of the European Ceramic Society</i> , 2016, 36, 1605-1612.	5.7	52
100	Large strain of lead-free bismuth ferrite ternary ceramics at elevated temperature. <i>Scripta Materialia</i> , 2018, 155, 11-15.	5.2	52
101	Superior and anti-fatigue electro-strain in $Bi_{0.5}Na_{0.5}TiO_3$ -based polycrystalline relaxor ferroelectrics. <i>Journal of Materials Chemistry A</i> , 2019, 7, 5391-5401.	10.3	52
102	A new concept to enhance piezoelectricity and temperature stability in KNN ceramics. <i>Chemical Engineering Journal</i> , 2020, 402, 126215.	12.7	52
103	Site engineering and polarization characteristics in $(Ba_{1-x}Ca_x)(Ti_{1-x}Hf_x)O_3$ lead-free ceramics. <i>Journal of Applied Physics</i> , 2016, 119, .	2.5	51
104	Enhanced energy storage properties of $\{Bi_{0.5}[(Na_{0.8}K_{0.2})_{1-Li}]_{0.5}\}_{0.96}Sr_{0.04}(Ti_{1-Ta}Nb)O_3$ lead-free ceramics. <i>Ceramics International</i> , 2017, 43, 13541-13546.	4.8	51
105	Phase Structure and Electrical Properties of $(K_{0.48}Na_{0.52})(Nb_{0.95}Ta_{0.05})O_3$ - $LiSbO_3$ Lead-Free Piezoelectric Ceramics. <i>Journal of the American Ceramic Society</i> , 2008, 91, 319-321.		50
106	Mediating the Contradiction of d_{33} and T_C in Potassium-Sodium Niobate Lead-Free Piezoceramics. <i>ACS Applied Materials & Interfaces</i> , 2013, 5, 10409-10417.	8.0	50
107	Practical high strain with superior temperature stability in lead-free piezoceramics through domain engineering. <i>Journal of Materials Chemistry A</i> , 2018, 6, 23736-23745.	10.3	50
108	Perovskite $Na_{0.5}Bi_{0.5}TiO_3$: a potential family of peculiar lead-free electrostrictors. <i>Journal of Materials Chemistry A</i> , 2019, 7, 13658-13670.	10.3	50

#	ARTICLE	IF	CITATIONS
109	A Method to Improve Electrical Properties of BiFeO ₃ Thin Films. ACS Applied Materials & Interfaces, 2012, 4, 1182-1185.	8.0	49
110	Enhanced piezoelectric properties in potassium-sodium niobate-based ternary ceramics. Materials and Design, 2016, 109, 609-614.	7.0	49
111	Phase structure and enhanced piezoelectric properties in (1-x)(K _{0.48} Na _{0.52})(Nb _{0.95} Sb _{0.05})O _{3-x} (Bi _{0.5} Na _{0.42} Li _{0.08}) _{0.9} Sr _{0.1} ZrO ₃ lead-free piezoelectric ceramics. Ceramics International, 2017, 43, 2100-2106.	4.8	49
112	Bi nonstoichiometry and composition engineering in (1- \hat{x})Bi _{1+y} FeO _{3+3y/2} \hat{x} BaTiO ₃ ceramics. RSC Advances, 2016, 6, 90831-90839.	3.6	48
113	Improved ferroelectric behavior in (110) oriented BiFeO ₃ thin films. Journal of Applied Physics, 2010, 107, 034103.	2.5	47
114	Diodelike and resistive hysteresis behavior of heterolayered BiFeO ₃ /ZnO ferroelectric thin films. Journal of Applied Physics, 2010, 108, .	2.5	46
115	Rhombohedral \hat{c} orthorhombic phase coexistence and electrical properties of Ta and BaZrO ₃ co-modified (K, Na)NbO ₃ lead-free ceramics. Current Applied Physics, 2013, 13, 1647-1650.	2.4	46
116	A giant polarization value of Zn and Mn co-modified bismuth ferrite thin films. Applied Physics Letters, 2013, 102, .	3.3	46
117	Phase structure and piezoelectric properties of (1- \hat{x})K _{0.48} Na _{0.52} Nb _{0.95} Sb _{0.05} O _{3-x} (Bi _{0.5} Na _{0.5}) _{0.9} (Li _{0.5} Ce _{0.5}) _{0.1} ZrO ₃ lead-free piezoelectric ceramics. Journal of Applied Physics, 2016, 119, .	2.5	46
118	High piezoelectricity in (K,Na)(Nb,Sb)O ₃ \hat{c} (Bi,La,Na,Li)ZrO ₃ lead-free ceramics. Journal of Materials Science, 2016, 51, 4963-4972.	3.7	46
119	Lead-free rare earth-modified BiFeO ₃ ceramics: Phase structure and electrical properties. Materials and Design, 2017, 120, 83-89.	7.0	46
120	Large electrocaloric strength and broad electrocaloric temperature span in lead-free Ba _{0.85} Ca _{0.15} Ti _{1-x} Hf _x O ₃ ceramics. RSC Advances, 2017, 7, 5813-5820.	3.6	46
121	Phase transitions and electrical behavior of lead-free (K _{0.5} Na _{0.5})NbO ₃ thin film. Journal of Applied Physics, 2009, 106, .	2.5	45
122	Superior Electrostrictive Effect in Relaxor Potassium Sodium Niobate Based Ferroelectrics. ACS Applied Materials & Interfaces, 2020, 12, 25050-25057.	8.0	45
123	(1- \hat{x}) Tj ETQq1 1 0.784314 rgBT /Overlock 10 Tf 50 192 Td (x)(K _{0.48} Na _{0.52})(Nb _{0.95} \hat{y} \hat{z}) Ta _z lead-free ceramics: composition dependence of the phase boundaries and electrical properties. Dalton Transactions, 2015, 44, 4440-4448.	3.3	44
124	Enhanced piezoelectric activity in high-temperature Bi _{1-x} Sm _x La _y FeO ₃ lead-free ceramics. Journal of Materials Chemistry C, 2015, 3, 3684-3693.	5.5	44
125	New potassium \hat{c} sodium niobate material system: a giant-d ₃₃ and high-T _C lead-free piezoelectric. Dalton Transactions, 2014, 43, 11759.	3.3	43
126	Large strain and temperature-insensitive piezoelectric effect in high-temperature piezoelectric ceramics. Journal of Materials Chemistry C, 2018, 6, 456-463.	5.5	43

#	ARTICLE	IF	CITATIONS
127	Enhancing temperature stability in potassium-sodium niobate ceramics through phase boundary and composition design. <i>Journal of the European Ceramic Society</i> , 2019, 39, 305-315.	5.7	43
128	ZnO as a buffer layer for growth of BiFeO ₃ thin films. <i>Journal of Applied Physics</i> , 2010, 108, .	2.5	42
129	Compositional dependence of phase structure and electrical properties in (K _{0.50} Na _{0.50}) _{0.97} Bi _{0.01} (Nb _{1-x} Zr _x)O ₃ lead-free ceramics. <i>Ceramics International</i> , 2013, 39, 8021-8024.	4.8	42
130	Enhanced d ₃₃ value in (1-x)[(K _{0.50} Na _{0.50}) _{0.97} Li _{0.03} Nb _{0.97} Sb _{0.03} O ₃] _x BaZrO ₃ lead-free ceramics with an orthorhombic-rhombohedral phase boundary. <i>Journal of Alloys and Compounds</i> , 2013, 581, 446-451.	5.5	41
131	Enhanced thermal stability of (NaCe)-doped CaBi ₂ Nb ₂ O ₉ by A-site vacancies-induced pseudo-tetragonal distortion. <i>Journal of the American Ceramic Society</i> , 2018, 101, 4615-4626.	3.8	41
132	A realization of excellent piezoelectricity and good thermal stability in CaBi ₂ Nb ₂ O ₉ : Pseudo phase boundary. <i>Journal of the American Ceramic Society</i> , 2019, 102, 1794-1804.	3.8	41
133	Characteristics of giant piezoelectricity around the rhombohedral-tetragonal phase boundary in (K,Na)NbO ₃ -based ceramics with different additives. <i>Journal of Materials Chemistry A</i> , 2015, 3, 15951-15961.	10.3	40
134	Mesoscale origin of dielectric relaxation with superior electrostrictive strain in bismuth ferrite-based ceramics. <i>Materials Horizons</i> , 2020, 7, 3011-3020.	12.2	39
135	Polymorphic phase transition-induced electrical behavior of BiCoO ₃ -modified (K _{0.48} Na _{0.52})NbO ₃ lead-free piezoelectric ceramics. <i>Journal of Alloys and Compounds</i> , 2011, 509, L284-L288.	5.5	38
136	Impedance spectroscopy of bilayered bismuth ferrite thin films. <i>Journal of Applied Physics</i> , 2011, 110, .	2.5	38
137	Modification of both d ₃₃ and T _C in a potassium-sodium niobate ternary system. <i>Dalton Transactions</i> , 2015, 44, 21141-21152.	3.3	38
138	Improved temperature stability and high piezoelectricity in lead-free barium titanate-based ceramics. <i>Journal of the European Ceramic Society</i> , 2018, 38, 5411-5419.	5.7	38
139	KNNS-BNZH Lead-Free 1 st Piezoelectric Composite for Ultrasonic and Photoacoustic Imaging. <i>IEEE Transactions on Ultrasonics, Ferroelectrics, and Frequency Control</i> , 2019, 66, 1395-1401.	3.0	38
140	Enhanced piezoelectricity and temperature stability in LaFeO ₃ -modified KNN-based lead-free ceramics. <i>Journal of the American Ceramic Society</i> , 2019, 102, 6126-6136.	3.8	38
141	Electrical properties of holmium doped (K,Na)(Nb,Sb)O ₃ -(Bi,Na)HfO ₃ ceramics with wide sintering and poling temperature range. <i>Journal of Alloys and Compounds</i> , 2016, 689, 759-766.	5.5	37
142	New poling method for piezoelectric ceramics. <i>Journal of Materials Chemistry C</i> , 2017, 5, 1601-1606.	5.5	37
143	Optimization of energy storage density in relaxor (K, Na, Bi)NbO ₃ ceramics. <i>Journal of Materials Science: Materials in Electronics</i> , 2017, 28, 16199-16204.	2.2	37
144	Temperature stability and electrical properties in La-doped KNN-based ceramics. <i>Journal of the American Ceramic Society</i> , 2018, 101, 4084-4094.	3.8	37

#	ARTICLE	IF	CITATIONS
145	Lead-Free (K,Na)NbO ₃ -Based Materials: Preparation Techniques and Piezoelectricity. ACS Omega, 2020, 5, 3099-3107.	3.5	37
146	Phase boundary, poling conditions, and piezoelectric activity and their relationships in (K _{0.42} Na _{0.58})(Nb _{0.96} Sb _{0.04})O ₃ -(Bi _{0.5} K _{0.5})O ₃ ceramics. RSC Advances, 2014, 4, 64835-64842.	3.4	36
147	Wide phase boundary zone, piezoelectric properties, and stability in 0.97(K _{0.4} Na _{0.6})(Nb _{1-x} Sb _x)O ₃ -0.03Bi _{0.5} Li _{0.5} ZrO ₃ lead-free ceramics. Dalton Transactions, 2014, 43, 9419.	3.3	36
148	Phase structure, piezoelectric properties, and stability of new K _{0.48} Na _{0.52} NbO ₃ -Bi _{0.5} Ag _{0.5} ZrO ₃ lead-free ceramics. Journal of Materials Science: Materials in Electronics, 2014, 25, 3219-3225.	2.2	36
149	Relationship between Poling Characteristics and Phase Boundaries of Potassium-Sodium Niobate Ceramics. ACS Applied Materials & Interfaces, 2016, 8, 9242-9246.	8.0	36
150	Electric field-induced phase transitions and composition-driven nanodomains in rhombohedral-tetragonal potassium-sodium niobate-based ceramics. Acta Materialia, 2017, 140, 79-86.	7.9	36
151	Optimized strain properties with small hysteresis in BNT-based ceramics with ergodic relaxor state. Journal of the European Ceramic Society, 2021, 41, 5147-5154.	5.7	36
152	Preparation and properties of highly (100)-oriented Pb(Zr _{0.2} Ti _{0.8})O ₃ thin film prepared by rf magnetron sputtering with a PbO _x buffer layer. Journal of Applied Physics, 2007, 101, 094107.	2.5	35
153	Microstructure, dielectric, and piezoelectric properties of (Li, Ag, Ta) modified (K _{0.5} Na _{0.5})NbO ₃ lead-free ceramics with high Curie temperature. Journal of Applied Physics, 2007, 102, .	2.5	34
154	Composition induced rhombohedral-tetragonal phase boundary in BaZrO ₃ modified (K _{0.445} Na _{0.50} Li _{0.055})NbO ₃ lead-free ceramics. Materials Letters, 2014, 120, 275-278.	2.6	33
155	Modification of strain and piezoelectricity in (K,Na)NbO ₃ -(Bi,Na)HfO ₃ lead-free ceramics with high Curie temperature. Journal of Alloys and Compounds, 2016, 684, 217-223.	5.5	33
156	Reduced dielectric loss in new colossal permittivity (Pr, Nb)TiO ₂ ceramics by suppressing adverse effects of secondary phases. Physical Chemistry Chemical Physics, 2018, 20, 21814-21821.	2.8	33
157	Full characterization for material constants of a promising KNN-based lead-free piezoelectric ceramic. Ceramics International, 2020, 46, 5641-5644.	4.8	33
158	Highly-Tunable Multifunctional BaTiO ₃ -Based Ferroelectrics via Site Selective Doping Strategy. Acta Materialia, 2021, 209, 116792.	7.9	33
159	(1-x)[0.90NN-0.10Bi(Mg _{2/3} Nb _{1/3})O ₃]-x(Bi _{0.5} Na _{0.5}) _{0.7} Sr _{0.3} TiO ₃ ceramics with core-shell structures: A pathway for simultaneously achieving high polarization and breakdown strength. Nano Energy, 2022, 101, 107577.	16.0	33
160	Rhombohedral-tetragonal phase boundary and electrical properties of new K _{0.48} Na _{0.52} Nb _{0.98} Sb _{0.02} O ₃ -Bi _{0.5} Nb _{0.5} ZrO ₃ piezoceramics. Journal Physics D: Applied Physics, 2013, 46, 495305.	2.1	32
161	Large strain and strain memory effect in bismuth ferrite lead-free ceramics. Journal of Materials Chemistry C, 2017, 5, 9528-9533.	5.5	32
162	Properties and structures of nonstoichiometric (K, Na)NbO ₃ -based lead-free ceramics. Journal of the American Ceramic Society, 2018, 101, 1632-1645.	3.8	32

#	ARTICLE	IF	CITATIONS
163	BNT-based ferroelectric ceramics: Electrical properties modification by Ta ₂ O ₅ oxide addition. Journal of the American Ceramic Society, 2020, 103, 412-422.	3.8	32
164	Large electrocaloric response with superior temperature stability in NaNbO ₃ -based relaxor ferroelectrics benefiting from the crossover region. Journal of Materials Chemistry A, 2021, 9, 2806-2814.	10.3	32
165	High Strain in (K,Na)NbO ₃ -Based Lead-Free Piezoceramics. ACS Applied Materials & Interfaces, 2014, 6, 20358-20364.	8.0	31
166	Enhanced piezoelectricity over a wide sintering temperature (400–1050 °C) range in potassium sodium niobate-based ceramics by two step sintering. Journal of Materials Chemistry A, 2015, 3, 6772-6780.	10.3	31
167	Enhanced temperature stability in the R-T phase boundary with dominating intrinsic contribution. Physical Chemistry Chemical Physics, 2018, 20, 20149-20159.	2.8	31
168	High-Performance 0-3 Type Niobate-Based Lead-Free Piezoelectric Composite Ceramics with ZnO Inclusions. ACS Applied Materials & Interfaces, 2018, 10, 30566-30573.	8.0	31
169	Piezoelectric Properties of (1-x)(Na _{0.5} K _{0.5})NbO ₃ -xAgSbO ₃ Lead-Free Ceramics. Journal of the American Ceramic Society, 2009, 92, 755-757.	2.8	30
170	Enhanced Electrical Properties of Quenched (1-x)TjETQq000rgBT/Overlock 10 Tf 50 467 Td (x)Bi _{1-x} Y _x Bi _{1-x} Y _x Lead-Free Ceramics. Journal of Physical Chemistry C, 2015, 119, 21105-21115.	3.1	30
171	Lead-Free KNbO ₃ :xZnO Composite Ceramics. ACS Applied Materials & Interfaces, 2016, 8, 30304-30311.	8.0	30
172	Progress on the doping and phase boundary design of potassium-sodium niobate lead-free ceramics. Journal of Advanced Dielectrics, 2018, 08, 1830003.	2.4	30
173	Symmetry of the Underlying Lattice in (K,Na)NbO ₃ -Based Relaxor Ferroelectrics with Large Electromechanical Response. ACS Applied Materials & Interfaces, 2021, 13, 7461-7469.	8.0	30
174	Modulating polarization rotation to stimulate the high piezocatalytic activity of (K, Na)NbO ₃ lead-free piezoelectric materials. Applied Catalysis B: Environmental, 2022, 313, 121471.	20.2	30
175	Effects of sintering temperature and poling conditions on the electrical properties of Bi _{0.50} (Na _{0.70} K _{0.20} Li _{0.10}) _{0.50} TiO ₃ piezoelectric ceramics. Journal of Alloys and Compounds, 2012, 525, 53-57.	5.5	29
176	Microstructure and electrical properties of (1-x)K _{0.5} Na _{0.5} NbO ₃ -xBi _{0.5} Na _{0.5} Zr _{0.85} Sn _{0.15} O ₃ lead-free ceramics. Journal of Alloys and Compounds, 2018, 730, 311-317.	5.5	29
177	Modifying Temperature Stability of (K,Na)NbO ₃ Ceramics through Phase Boundary. Advanced Electronic Materials, 2018, 4, 1800205.	5.1	29
178	Understanding the Nature of Temperature Stability in Potassium Sodium Niobate Based Ceramics from Structure Evolution under External Field. ACS Applied Materials & Interfaces, 2020, 12, 32925-32934.	8.0	29
179	Advances in tuning the ϵ^*d and $1/Td$ bottleneck: simultaneously realizing large ϵ^*d and high $1/Td$ in Bi _{0.5} Na _{0.5} TiO ₃ -based relaxor ferroelectrics. Journal of Materials Chemistry A, 2020, 8, 9209-9217.	10.3	29
180	Effects of rare-earth dopants on phase structure and electrical properties of lead-free bismuth sodium titanate-based ceramics. Journal of Materiomics, 2020, 6, 286-292.	5.7	29

#	ARTICLE	IF	CITATIONS
181	Multiscale Structure Engineering for High-Performance Pb-Free Piezoceramics. <i>Accounts of Materials Research</i> , 2022, 3, 461-471.	11.7	29
182	K/Na Ratio Dependence of the Electrical Properties of $[(K_{1-x}Na_x)_{0.95}Li_{0.05}](Nb_{0.95}Ta_{0.05})O_3$ Lead-Free Ceramics. <i>Journal of the American Ceramic Society</i> , 2008, 91, 2385-2387.	2.8	28
183	Microstructure and electrical properties of (Li, Ag, Ta, Sb)-modified $(K_{0.50}Na_{0.50})NbO_3$ lead-free ceramics with good temperature stability. <i>Journal Physics D: Applied Physics</i> , 2008, 41, 125405.	2.5	28
184	Valence-driven electrical behavior of manganese-modified bismuth ferrite thin films. <i>Journal of Applied Physics</i> , 2011, 109, 124118.	5.5	28
185	Rhombohedral-tetragonal phase coexistence and piezoelectric properties based on potassium-sodium niobate ternary system. <i>Journal of Alloys and Compounds</i> , 2014, 610, 86-91.	5.5	27
186	Phase structure, microstructure and ferroelectric properties of $(1-x)[(K_{0.50}Na_{0.50})_{0.94}Li_{0.06}](Nb_{0.94}Sb_{0.06})O_3-xCaTiO_3$ lead-free ceramics. <i>Journal of Alloys and Compounds</i> , 2009, 476, 782-786.	3.3	27
187	Two-step sintering of new potassium sodium niobate ceramics: a high d_{33} and wide sintering temperature range. <i>Dalton Transactions</i> , 2014, 43, 12836.	21.0	27
188	The Atomic Circus: Small Electron Beams Spotlight Advanced Materials Down to the Atomic Scale. <i>Advanced Materials</i> , 2018, 30, e1802402.	7.9	27
189	Electric field compensation effect driven strain temperature stability enhancement in potassium sodium niobate ceramics. <i>Acta Materialia</i> , 2020, 182, 1-9.	12.7	27
190	Achieving superior energy-storage efficiency by tailoring the state of polar nano-sized regions under low electric fields. <i>Chemical Engineering Journal</i> , 2022, 447, 137494.	3.3	26
191	New lead-free piezoelectric ceramics based on $(K_{0.48}Na_{0.52})(Nb_{0.95}Ta_{0.05})O_3-xBi_{0.5}(Na_{0.7}K_{0.2}Li_{0.1})_{0.5}ZrO_3$. <i>Dalton Transactions</i> , 2014, 43, 3434.	5.5	26
192	Phase transition, microstructure, and electrical properties of Ca, Zr, and Sn-modified $BaTiO_3$ lead-free ceramics. <i>Journal of Alloys and Compounds</i> , 2014, 615, 969-974.	5.5	26
193	Composition dependence of phase structure and electrical properties in lead-free $(1-x)(K_{0.42}Na_{0.585})(Nb_{1-x}Sb_x)O_3-xBi_{0.5}K_{0.5}ZrO_3$ piezoceramics. <i>Journal of Alloys and Compounds</i> , 2015, 647, 927-934.	5.5	26
194	Balanced development of piezoelectricity, Curie temperature, and temperature stability in potassium-sodium niobate lead-free ceramics. <i>Journal of Materials Chemistry C</i> , 2016, 4, 9779-9787.	2.2	26
195	Effects of oxide additives on structure and properties of bismuth ferrite-based ceramics. <i>Journal of Materials Science: Materials in Electronics</i> , 2017, 28, 11534-11542.	4.8	25
196	Effect of $Ba_{0.85}Ca_{0.15}Ti_{0.90}Zr_{0.10}O_3$ content on the microstructure and electrical properties of $Bi_{0.51}(Na_{0.82}K_{0.18})_{0.50}TiO_3$ ceramics. <i>Ceramics International</i> , 2012, 38, 4845-4851.	5.2	25
197	Giant piezoelectricity of $(K,Na)(Nb,Sb)O_3-x(Bi,Na,K,Pb)ZrO_3$ ceramics with rhombohedral-tetragonal (R-T) phase boundary. <i>Scripta Materialia</i> , 2014, 88, 41-44.	2.3	25
198	Piezoelectric properties and thermal stability of $Ca_{0.92}(Li,Ce)_{0.04}Bi_2Nb_{2-x}W_xO_9$ high-temperature ceramics. <i>Applied Physics A: Materials Science and Processing</i> , 2015, 119, 337-341.		

#	ARTICLE	IF	CITATIONS
199	Composition design and electrical properties in $(1-x)(\text{K}_{0.40}\text{Na}_{0.60})_{0.985}\text{Li}_{0.015}(\text{Nb}_{1-x}\text{Sb}_x)\text{O}_3\text{Bi}_{0.5}\text{Na}_{0.5}\text{ZrO}_3$ lead-free ceramics. <i>Journal of Applied Physics</i> , 2015, 117, .	2.5	25
200	Structure and electrical properties of $(0.965-x)\text{TjETQq}000\text{rgBT}/\text{Overlock}10\text{Tf}50707\text{Td}(x)(\text{K}_{0.48}\text{Na}_{0.52})_{\text{sub}}$ piezoelectric ceramics. <i>RSC Advances</i> , 2016, 6, 57210-57216.	3.6	25
201	Structural evolution of the $\text{R}\hat{\text{c}}\text{T}$ phase boundary in KNN -based ceramics. <i>Journal of the American Ceramic Society</i> , 2018, 101, 1191-1200.	3.8	25
202	Diffused and successive phase transitions of $(\text{K}, \text{Na})\text{NbO}_3$ -based ceramics with high strain and temperature insensitivity. <i>Journal of the American Ceramic Society</i> , 2019, 102, 2648-2657.	3.8	25
203	Rietveld Analysis and Electrical Properties of Bi_2O_3 -Doped KNN -Based Ceramics. <i>Inorganic Chemistry</i> , 2019, 58, 428-438.	4.0	25
204	Influence of different lanthanide ions on the structure and properties of potassium sodium niobate based ceramics. <i>Scripta Materialia</i> , 2020, 177, 186-191.	5.2	25
205	The Role of Adding $\text{Bi}_{0.5}\text{A}_{0.5}\text{ZrO}_3$ in Affecting Orthorhombic-Tetragonal Phase Transition Temperature and Electrical Properties in Potassium Sodium Niobate Ceramics. <i>Acta Materialia</i> , 2020, 197, 224-234.	7.9	25
206	Dielectric and piezoelectric properties of Sb^{5+} doped $(\text{NaBi})_{0.38}(\text{LiCe})_{0.05}[\text{Bi}_{0.14}\text{Bi}_2\text{Nb}_2\text{O}_9]$ ceramics. <i>Journal of Alloys and Compounds</i> , 2011, 509, 8483-8486.	5.5	24
207	Dielectric properties and impedance analysis in Aurivillius-type $(\text{Na}_{0.25}\text{K}_{0.25}\text{Bi}_{0.5})_{1-x}(\text{LiCe})_x[\text{Bi}_{1-x}\text{Ti}_x\text{O}_{15}]$ ceramics. <i>Journal of Alloys and Compounds</i> , 2012, 541, 310-316.	5.5	24
208	Lead-free piezoelectric ceramics based on $(0.97-x)(\text{K}_{0.48}\text{Na}_{0.52}\text{NbO}_3-0.03\text{Bi}_{0.5}(\text{Na}_{0.7}\text{K}_{0.2}\text{Li}_{0.1})_{0.5}\text{ZrO}_3-x\text{Bi}_{0.5}\text{Na}_{0.5}\text{TiO}_3)$ ternary system. <i>Journal of Applied Physics</i> , 2013, 114, 124107.	2.5	24
209	Novel titanium dioxide ceramics containing bismuth and antimony. <i>Journal of Materiomics</i> , 2017, 3, 112-120.	5.7	24
210	Domain-scale imaging to dispel the clouds over the thermal depolarization of $(\text{Bi}_{0.5}\text{Na}_{0.5})_{\text{sub}}\text{TiO}_3$ -based relaxor ferroelectrics. <i>Journal of the American Ceramic Society</i> , 2020, 103, 1881-1890.	3.8	24
211	Synergetic Contributions in Phase Boundary Engineering to the Piezoelectricity of Potassium Sodium Niobate Lead-Free Piezoceramics. <i>ACS Applied Materials & Interfaces</i> , 2020, 12, 39455-39461.	8.0	24
212	Large electrostrictive coefficient with high electrostrain dominated by modified ergodic state in BNT -based solid solutions. <i>Journal of the American Ceramic Society</i> , 2021, 104, 1391-1401.	3.8	24
213	Fatigue and ferroelectric behavior of La and Zn comodified BiFeO_3 thin films. <i>Journal of Applied Physics</i> , 2010, 108, .	2.5	23
214	Microstructure and electrical properties of relaxor $(1-x)[(\text{K}_{0.5}\text{Na}_{0.5})_{0.95}\text{Li}_{0.05}](\text{Nb}_{0.95}\text{Sb}_{0.05})\text{O}_3-x\text{BaTiO}_3$ piezoelectric ceramics. <i>Ceramics International</i> , 2012, 38, 2277-2282.	4.8	22
215	Orthorhombic-tetragonal phase coexistence and piezoelectric behavior in $(1-x)(\text{Ba}, \text{Ca})(\text{Ti}, \text{Sn})\text{O}_3-x(\text{Ba}, \text{Ca})(\text{Ti}, \text{Zr})\text{O}_3$ lead-free ceramics. <i>Materials Research Bulletin</i> , 2013, 48, 4411-4414.	5.2	22
216	Effect of SrZrO_3 on phase structure and electrical properties of $0.974(\text{K}_{0.5}\text{Na}_{0.5})\text{NbO}_3-0.026\text{Bi}_{0.5}\text{K}_{0.5}\text{TiO}_3$ lead-free ceramics. <i>Ceramics International</i> , 2014, 40, 2731-2735.	4.8	22

#	ARTICLE	IF	CITATIONS
217	Phase structure and electrical properties of $(K_{0.5}Na_{0.5})NbO_3 \cdot (Bi_{0.5}Na_{0.5})ZrO_3$ lead-free ceramics with a sintering aid of ZnO. <i>Ceramics International</i> , 2014, 40, 14601-14605.	4.8	22
218	Phase transition and piezoelectric properties of Nd^{3+} doped nonstoichiometric $(K,Na)NbO_3$ -based lead free ceramics. <i>Applied Physics Letters</i> , 2017, 110, .	3.3	22
219	Composition design and electrical properties in $BiFeO_3 \cdot BaTiO_3 \cdot Bi(Zn_{0.5}Ti_{0.5})O_3$ lead-free ceramics. <i>Journal of Materials Science: Materials in Electronics</i> , 2017, 28, 13076-13083.	2.2	22
220	Multiphase coexistence and enhanced electrical properties in $(1-x)y)BaTiO_3-xCaTiO_3-yBaZrO_3$ lead-free ceramics. <i>Ceramics International</i> , 2017, 43, 13516-13523.	4.8	22
221	High Tunability of Highly (100)-Oriented Lead Zirconate Titanium Thin Films. <i>Journal of the American Ceramic Society</i> , 2008, 91, 3786-3788.	3.8	21
222	High piezoelectricity in low-temperature sintering potassium-sodium niobate-based lead-free ceramics. <i>RSC Advances</i> , 2014, 4, 53490-53497.	3.6	21
223	Giant Electrostrictive Responses and Temperature Insensitive Strain in Barium Titanate-Based Ceramics. <i>Advanced Electronic Materials</i> , 2018, 4, 1800075.	5.1	21
224	Comprehensive investigation of structural and electrical properties of $(Bi, Na) CoZrO_3$ -doped KNN ceramics. <i>Journal of Alloys and Compounds</i> , 2018, 758, 14-24.	5.5	21
225	Polymorphic characteristics challenging electrical properties in lead-free piezoceramics. <i>Dalton Transactions</i> , 2019, 48, 11250-11258.	3.3	21
226	Defect-driven conductivity behavior in lead-free KNN-based ceramics. <i>Journal of Applied Physics</i> , 2020, 127, .	2.5	21
227	Resistive hysteresis in $BiFeO_3$ thin films. <i>Materials Research Bulletin</i> , 2011, 46, 2183-2186.	5.2	20
228	Investigation of a new lead-free $(0.89-x)(Bi_{0.5}Na_{0.5})TiO_3 \cdot 0.11(Bi_{0.5}K_{0.5})TiO_3 \cdot xBa_{0.85}Ca_{0.15}Ti_{0.90}Zr_{0.10}O_3$ ceramics. <i>Materials Research Bulletin</i> , 2012, 47, 3937-3940.	5.2	20
229	Microstructure and electrical properties of $(Ba_{0.98}Ca_{0.02})(Ti_{0.94}Sn_{0.06})O_3$ -modified $Bi_{0.5}Na_{0.5}TiO_3$ lead-free ceramics. <i>Ceramics International</i> , 2012, 38, 5677-5681.	4.8	20
230	Effects of $Mo_{2/3}Bi_{1/3}$ doping on the phase structure, microstructure, and piezoelectric properties of $KNNS \cdot BNZ$ ceramics. <i>Ceramics International</i> , 2015, 41, 14610-14614.	4.8	20
231	Effect of $(LiCe)$ doping in $(NaBi)_{0.48}[(Li_{0.04}Bi_{2}Nb_{1.97}W_{0.03}O_9)$ high-temperature ceramics. <i>Journal of Alloys and Compounds</i> , 2015, 625, 113-117.	5.5	20
232	Structure and domain wall dynamics in lead-free KNN-based ceramics. <i>Journal of Applied Physics</i> , 2019, 126, .	2.5	20
233	Enhanced electrical properties and temperature stability of ZnF_{2-x} -modified $(K,Na)NbO_3$ -based ceramics. <i>Journal of Applied Physics</i> , 2019, 125, 082526.	2.5	20
234	Double hysteresis loop in $(Pb_{0.90}La_{0.10})Ti_{0.975}O_3 \cdot Pb(Zr_{0.20}Ti_{0.80})O_3$ bilayer thin films. <i>Applied Physics Letters</i> , 2007, 91, .	3.3	19

#	ARTICLE	IF	CITATIONS
235	Piezoelectric and ferroelectric properties of [(K _{0.4725} Na _{0.4725})Li _{0.055}]NbO ₃ -(Ag _{0.5} Li _{0.5})TaO ₃ lead-free ceramics. <i>Physica Status Solidi - Rapid Research Letters</i> , 2007, 1, 214-216.	2.4	19
236	Resistive Hysteresis and Diodelike Behavior of BiFeO ₃ /ZnO Heterostructure. <i>Electrochemical and Solid-State Letters</i> , 2010, 13, G9.	2.2	19
237	Multiferroic behavior and electrical conduction of BiFeO ₃ thin film deposited on quartz substrate. <i>Journal of Alloys and Compounds</i> , 2010, 507, L4-L7.	5.5	19
238	New crystallographic dielectric phase boundary in K _{0.5} Na _{0.5} NbO ₃ -based lead-free ceramics. <i>Physica Status Solidi - Rapid Research Letters</i> , 2011, 5, 220-222.	2.4	19
239	Microstructure and electrical properties of (Ba _{0.98} Ca _{0.02})(Ti _{0.94} Sn _{0.06})O ₃ -x wt% ZnO lead-free piezoelectric ceramics sintered at lower temperature. <i>Journal of Materials Science: Materials in Electronics</i> , 2015, 26, 2323-2328.	2.2	19
240	High unipolar strain in samarium-doped potassium-sodium niobate lead-free ceramics. <i>RSC Advances</i> , 2015, 5, 39295-39302.	3.6	19
241	Rare earth element boosting temperature stability of (K,Na)NbO ₃ -based ceramics. <i>Journal of Alloys and Compounds</i> , 2019, 795, 401-407.	5.5	19
242	(Bi _{0.5} Na _{0.5})TiO ₃ ferroelectric ceramics: Achieving high depolarization temperature and improved piezoelectric properties. <i>Journal of the European Ceramic Society</i> , 2020, 40, 5392-5401.	5.7	19
243	Reduced degree of phase coexistence in KNN-Based ceramics by competing additives. <i>Journal of the European Ceramic Society</i> , 2020, 40, 2945-2953.	5.7	19
244	CaTiO ₃ -Modified (K _{0.50} Na _{0.50})(Nb _{0.96} Sb _{0.04})O ₃ Lead-Free Piezoelectric Ceramics. <i>Journal of the American Ceramic Society</i> , 2008, 91, 3402-3404.	3.8	18
245	Mn ⁴⁺ :BiFeO ₃ /Zn ²⁺ :BiFeO ₃ bilayered thin films of (111) orientation. <i>Applied Surface Science</i> , 2011, 257, 7226-7230.	6.1	18
246	Phase boundary design and high piezoelectric activity in (1-x)(Ba _{0.93} Ca _{0.07})TiO ₃ -xBa(Sn _{1-x} Hf) ₂ O ₇ lead-free ceramics. <i>Journal of Alloys and Compounds</i> , 2016, 666, 372-379.	5.5	18
247	Decoding the Role of Diffused Multiphase Coexistence in Potassium Sodium Niobate-Based Ceramics with Nanodomains for Enhanced Piezoelectric Devices. <i>ACS Applied Nano Materials</i> , 2020, 3, 953-961.	5.0	18
248	Potassium sodium niobate based lead-free ceramic for high-frequency ultrasound transducer applications. <i>Journal of Materiomics</i> , 2020, 6, 513-522.	5.7	18
249	Improved Ferroelectric and Fatigue Behavior of Bi _{0.95} Gd _{0.05} FeO ₃ /BiFe _{0.95} Mn _{0.05} O ₃ Bilayered Thin Films. <i>Journal of Physical Chemistry C</i> , 2010, 114, 19318-19321.		17
250	Multiferroic and fatigue behavior of silicon-based bismuth ferrite sandwiched structure. <i>Journal of Materials Chemistry</i> , 2011, 21, 7308.	6.7	17
251	Piezoelectric properties of [Li _{0.03} (K _{0.48} Na _{0.52}) _{0.97}](Nb _{0.97} Sb _{0.03})O ₃ -(Ba _{0.85} Ca _{0.15})(Ti _{0.90} Zr _{0.10})O ₃ lead-free piezoelectric ceramics. <i>Current Applied Physics</i> , 2012, 12, 752-754.	2.4	17
252	Temperature stability, phase structure and electrical behavior of Li-modified 0.99(K _{0.48} Na _{0.52})NbO ₃ -0.01BiCoO ₃ piezoelectric ceramics. <i>Ceramics International</i> , 2014, 40, 1133-1137.	4.8	17

#	ARTICLE	IF	CITATIONS
253	Dielectric and piezoelectric properties of cerium-doped (NaBi) _{0.49} [_{0.02} Bi ₂ Nb _{1.98} Ta _{0.02} O ₉ -based piezoceramics. <i>Ceramics International</i> , 2014, 40, 14159-14163.	4.8	17
254	Investigation of new lead free (1-x)KNNs-xBKZH piezo-ceramics with O-T phase boundary. <i>Journal of Materials Science: Materials in Electronics</i> , 2017, 28, 8803-8809.	2.2	17
255	Modulating the electric and magnetic properties of BiFeO ₃ ceramics. <i>Materials and Design</i> , 2017, 125, 213-221.	7.0	17
256	Tuning the Covalency of A-O Bonds to Improve the Performance of KNN-Based Ceramics with Multiphase Coexistence. <i>ACS Applied Materials & Interfaces</i> , 2020, 12, 49795-49804.	8.0	17
257	BiFeO ₃ Thin Films Deposited on LaNiO ₃ -Buffered SiO ₂ /Si Substrate. <i>Journal of the American Ceramic Society</i> , 2010, 93, 1422-1426.	3.8	16
258	Effect of New Phase Boundary on the Dielectric and Piezoelectric Properties of K _{0.5} Na _{0.5} NbO ₃ -xBaZrO ₃ -yBi _{0.5} Na _{0.5} TiO ₃ Lead-free Ceramics. <i>Integrated Ferroelectrics</i> , 2012, 139, 63-74.	0.7	16
259	Evolution of phase structure, microstructure, and electrical properties in (1-x)(K,Na)NbO ₃ -x(Bi,Na,Li,Ba)ZrO ₃ lead-free ceramics. <i>Journal of Alloys and Compounds</i> , 2015, 628, 329-334.	5.5	16
260	New potassium-sodium niobate ternary system with large piezoelectric coefficient and high Curie temperature. <i>Journal of Materials Science: Materials in Electronics</i> , 2016, 27, 9812-9820.	2.2	16
261	The piezoelectric and dielectric properties of sodium-potassium niobate ceramics with new multiphase boundary. <i>Journal of Materials Science: Materials in Electronics</i> , 2017, 28, 18090-18098.	2.2	16
262	Electrocaloric behavior and piezoelectric effect in relaxor NaNbO ₃ -based ceramics. <i>Journal of the American Ceramic Society</i> , 2019, 102, 2578-2586.	3.8	16
263	Understanding the enhanced electrocaloric effect in BaTiO ₃ -based ferroelectrics at critical state. <i>Acta Materialia</i> , 2022, 227, 117735.	7.9	16
264	New phase boundary and piezoelectric properties in (K, Na)NbO ₃ based ceramics. <i>Journal of Alloys and Compounds</i> , 2014, 585, 748-752.	5.5	15
265	0.99(K _{0.45} Na _{0.52} Li _{0.03})(Nb _{1-x} Sb _x)O ₃ -0.01BiScO ₃ lead-free ceramics with excellent piezoelectric properties and broad sintering temperature. <i>Ceramics International</i> , 2014, 40, 7589-7593.	4.8	15
266	Temperature-insensitive piezoelectricity in lead-free NaNbO ₃ -based ceramics. <i>Journal of the American Ceramic Society</i> , 2018, 101, 5596-5603.	3.8	15
267	Defect engineering electrical properties of lead-free potassium sodium niobate-based ceramics. <i>Journal of the American Ceramic Society</i> , 2020, 103, 444-453.	3.8	15
268	A new class of ion substitution to achieve high electrostrain under low electric field in BNT-based ceramics. <i>Journal of the American Ceramic Society</i> , 2021, 104, 6277-6289.	3.8	15
269	Manipulating temperature stability in KNN-based ceramics via defect design. <i>Acta Materialia</i> , 2021, 218, 117229.	7.9	15
270	Microstructure and Electrical Properties of [(K _{0.50} Na _{0.50}) _{0.95} Li _{0.05} Ag _x](Nb _{0.95} Li _{0.05}) _{1-x} Lead-Free Ceramics. <i>Journal of the American Ceramic Society</i> , 2008, 91, 2772-2775.	0.4	15

#	ARTICLE	IF	CITATIONS
271	High Curie temperature of (Li, K, Ag)-modified (K _{0.50} Na _{0.50})NbO ₃ lead-free piezoelectric ceramics. <i>Journal of Alloys and Compounds</i> , 2009, 472, L6-L8.	5.5	14
272	Phase transition and piezoelectric properties of (1-x)(K _{0.42} Na _{0.58})(Nb _{0.96} Sb _{0.04})O ₃ -x(Bi _{0.5} Na _{0.5}) _{0.90} Mg _{0.10} ZrO ₃ lead-free ceramics. <i>Journal of Materials Science: Materials in Electronics</i> , 2014, 25, 4650-4656.	2.2	14
273	Influence of K/Na ratio on phase structure and electrical properties of 0.96 (K x Na _{1-x}) NbO ₃ -0.04 (Bi _{0.5} Na _{0.5}) ZrO ₃ lead-free ceramics. <i>Journal of Electroceramics</i> , 2015, 34, 142-149.	2.0	14
274	Contribution of Bi _{0.5} Na _{0.5} ZrO ₃ on phase boundary and piezoelectricity in K _{0.48} Na _{0.52} Nb _{0.96} Sb _{0.04} O ₃ -Bi _{0.5} Na _{0.5} SnO ₃ -xBi _{0.5} Na _{0.5} ZrO ₃ ternary ceramics. <i>Journal of Alloys and Compounds</i> , 2016, 684, 397-402.	5.5	14
275	Excellent electrostrictive coefficient in bismuth sodium titanate-based ceramics via regulating degree of diffuseness and phase composition. <i>Journal of Applied Physics</i> , 2018, 124, .	2.5	14
276	Reduced dielectric loss and high piezoelectric constant in Ce and Mn co-doped BiScO ₃ -PbCeTi ₁₋₀₃ -Bi(Zn _{0.5} Ti _{0.5})O ₃ ceramics. <i>Ceramics International</i> , 2018, 44, 16483-16488.	4.8	14
277	Enhanced electrocaloric effect in compositional driven potassium sodium niobate-based relaxor ferroelectrics. <i>Journal of Materials Research</i> , 2021, 36, 1142-1152.	2.6	14
278	One simple approach, two remarkable enhancements: Manipulating defect dipoles and local stress of (K, Na)NbO ₃ -based ceramics. <i>Acta Materialia</i> , 2021, 221, 117351.	7.9	14
279	Low-temperature dielectric relaxation associated with NbO ₆ octahedron distortion in antimony modified potassium sodium niobate ceramics. <i>Journal of Materials Science and Technology</i> , 2022, 115, 189-198.	10.7	14
280	Microstructure and electrical properties of (1-x)(K _{0.5} Na _{0.5})NbO ₃ -xBiFeO ₃ piezoelectric ceramics. <i>Physica Status Solidi (A) Applications and Materials Science</i> , 2008, 205, 1211-1214.	1.8	13
281	Multiferroic behaviour and orientation dependence of lead-free (1) Tj ETQq1 1 0.784314 rgBT /Overlock 10 Tf 50 347 Td (x) films. <i>Journal Physics D: Applied Physics</i> , 2009, 42, 195405.	2.8	13
282	Enhanced d ₃₃ value in HfO ₂ -modified (Ba _{0.98} Ca _{0.02})(Ti _{0.94} Sn _{0.06})O ₃ ceramics. <i>Journal of Alloys and Compounds</i> , 2013, 576, 299-301.	5.5	13
283	Modulation of electrostriction and strain response in bismuth sodium titanate-based ceramics. <i>Journal of the American Ceramic Society</i> , 2018, 101, 3005-3014.	3.8	13
284	Composition-driven broad phase boundary for optimizing properties and stability in lead-free barium titanate ceramics. <i>Journal of the American Ceramic Society</i> , 2019, 102, 3477-3487.	3.8	13
285	Relaxor behavior of potassium sodium niobate ceramics by domain evolution. <i>Journal of the European Ceramic Society</i> , 2021, 41, 335-343.	5.7	13
286	Defect-induced superior piezoelectric response in perovskite KNbO ₃ . <i>Journal of the European Ceramic Society</i> , 2021, 41, 2506-2513.	5.7	13
287	Decoding Thermal Depolarization Temperature in Bismuth Ferrite-Barium Titanate Relaxor Ferroelectrics with Large Strain Response. <i>ACS Applied Materials & Interfaces</i> , 2021, 13, 37422-37432.	8.0	13
288	Tailoring depolarization temperature by phase transition causing properties evolution in Bi _{0.5} (Na _{1-K}) Tj ETQq0 0 0 rgBT /Overlock 10 Tf	16.7	13

#	ARTICLE	IF	CITATIONS
289	Large electrocaloric effect under electric field behavior in potassium sodium niobate ceramics with incompletely overlapped phase boundaries. <i>Journal of Materials Chemistry A</i> , 2022, 10, 5262-5272.	10.3	13
290	Coupling effects of the A-site ions on high-performance potassium sodium niobate ceramics. <i>Journal of Materials Science and Technology</i> , 2022, 130, 198-207.	10.7	13
291	Orientation dependence of dielectric and ferroelectric properties of $\text{Pb}(\text{Zr}_{0.8}\text{Ti}_{0.2})\text{O}_3 \cdot \text{Pb}(\text{Zr}_{0.2}\text{Ti}_{0.8})\text{O}_3$ multilayered thin films. <i>Applied Physics Letters</i> , 2007, 91, .	3.3	12
292	Phase structure and electrical properties of $0.965(\text{K}_{0.45}\text{Na}_{0.55})_{0.95}\text{Ag}_{0.05}(\text{Nb}_{1-x}\text{Sb}_x)\text{Tj ETQq0 0 0 rgBT /Overlock 10 Tf 50 627 Td Electronics}$, 2015, 26, 7309-7315.	2.2	12
293	Poling temperature-insensitive piezoelectric constant of high-performance potassium sodium niobate piezoceramics. <i>Journal of the American Ceramic Society</i> , 2020, 103, 4402-4410.	3.8	12
294	Multiple property enhancement in bismuth ferrite-based ferroelectrics by balancing nanodomain and relaxor state. <i>Journal of the American Ceramic Society</i> , 2022, 105, 1241-1252.	3.8	12
295	Electrical properties and temperature stability of a new kind of lead-free piezoelectric ceramics. <i>Journal Physics D: Applied Physics</i> , 2008, 41, 245401.	2.8	11
296	Multiferroic and Fatigue Behavior of $(\text{Bi}_{\text{sub } 0.90}\text{La}_{\text{sub } 0.10})\text{FeO}_{\text{sub } 3}/\text{CoFe}_{\text{sub } 2}\text{O}_{\text{sub } 4}/(\text{Bi}_{\text{sub } \text{Tj ETQq0 0 0 rgBT /Overlock 10 Tf 50 627 Td G61}}$.	2.2	11
297	$\text{BiFeO}_3/\text{Zn}_{1-x}\text{Mn}_x\text{O}$ bilayered thin films. <i>Applied Surface Science</i> , 2011, 258, 1390-1394.	6.1	11
298	Combined effects of bilayer structure and ion substitutions on bismuth ferrite thin films. <i>Journal of Applied Physics</i> , 2011, 109, .	2.5	11
299	Effect of La and Co-doping on microstructure and electrical properties of BiFeO_3 thin films. <i>Science Bulletin</i> , 2014, 59, 5205-5211.	1.7	11
300	Phase structure, electrical properties, and stability of $0.96(\text{K}_{0.48}\text{Na}_{0.52})_{1-x}\text{Li}_x\text{NbO}_3 \cdot 0.04\text{Bi}_{0.5}\text{Na}_{0.5}\text{ZrO}_3$ lead-free piezoceramics. <i>Current Applied Physics</i> , 2014, 14, 809-813.	2.4	11
301	Lead-free $(\text{K}, \text{Na})\text{NbO}_3 \cdot \text{Bi}_{0.5}\text{K}_{0.5}\text{ZrO}_3 \cdot \text{BaZrO}_3$ ternary system: Microstructure and electrical properties. <i>Journal of Alloys and Compounds</i> , 2015, 619, 560-563.	5.5	11
302	Microstructure, electrical properties and temperature stability in $\text{Bi}_{\text{sub } 0.5}\text{Na}_{\text{sub } 0.5}\text{Zr}_{\text{sub } 0.95}\text{Ce}_{\text{sub } 0.05}\text{O}_{\text{sub } 3}$ modified $\text{R} \cdot \text{T}$ phase boundary of potassium-sodium niobium lead-free ceramics. <i>RSC Advances</i> , 2016, 6, 6983-6989.	3.6	11
303	Enhanced electrical properties and good thermal stability in $\text{K}_{0.48}\text{Na}_{0.52}\text{NbO}_3 \cdot \text{LiNbO}_3 \cdot \text{BiAlO}_3$ lead-free piezoceramics. <i>Journal of Materials Science: Materials in Electronics</i> , 2017, 28, 8500-8509.	2.2	11
304	New Role of Relaxor Multiphase Coexistence in Potassium Sodium Niobate Ceramics: Reduced Electric Field Dependence of Strain Temperature Stability. <i>ACS Applied Materials & Interfaces</i> , 2020, 12, 49822-49829.	8.0	11
305	Enhanced strain and electrostrictive properties in lead-free BNT-based ceramics via rare earth doping. <i>Journal of Materiomics</i> , 2022, 8, 401-407.	5.7	11
306	Electrocaloric refrigeration capacity in BNT-based ferroelectrics benefiting from low depolarization temperature and high breakdown electric field. <i>Journal of Materials Chemistry A</i> , 2021, 9, 12772-12781.	10.3	11

#	ARTICLE	IF	CITATIONS
307	Decoding the relationship between the electrocaloric strength and phase structure in perovskite ferroelectrics towards high performance. <i>Journal of Materials Chemistry C</i> , 2021, 9, 2063-2072.	5.5	11
308	Excellent fatigue resistance in Sb nonstoichiometric KNN-based ceramics by engineering relaxor multiphase state. <i>Journal of the European Ceramic Society</i> , 2022, 42, 4888-4897.	5.7	11
309	Effect of $(\text{Bi,Gd})\text{FeO}_3$ Layer Thickness on the Microstructure and Electrical Properties of BiFeO_3 Thin Films. <i>Journal of the American Ceramic Society</i> , 2011, 94, 4291-4298.	3.8	10
310	Orientation dependence of resistive hysteresis in bismuth ferrite thin films. <i>Journal of Alloys and Compounds</i> , 2013, 569, 126-129.	5.5	10
311	Charge defects-induced electrical properties in bismuth ferrite bilayered thin films. <i>Materials Research Bulletin</i> , 2013, 48, 2973-2977.	5.2	10
312	Temperature dependent properties and poling effect of $\text{K}_4\text{CuNb}_8\text{O}_{23}$ modified $(\text{Na}_{0.5}\text{K}_{0.5})\text{NbO}_3$ lead free piezoceramics. <i>Journal of Applied Physics</i> , 2015, 117, 124103.	2.5	10
313	Effect of B-site dopants Nb, Ta and W on microstructure and electrical properties of $\text{Ca}_{0.85}(\text{Li}, \text{Tj})\text{ETQq1}$ 1.0784314 rgBT /Overlock Electronics, 2016, 27, 913-920.	2.2	10
314	Structure and property of lead-free $(\text{K,Na})\text{NbO}_3 \cdot (\text{Bi}_{1/2}\text{Na}_{1/2})\text{ZrO}_3 \cdot \text{CaTiO}_3$ piezoelectric ceramics. <i>Journal of Materials Science: Materials in Electronics</i> , 2019, 30, 1663-1669.	2.2	10
315	Temperature-independent large strain with small hysteresis in Sb-modified BNT-based lead-free ceramics. <i>Journal of the American Ceramic Society</i> , 2022, 105, 2116-2127.	3.8	10
316	Potassium Sodium Niobate-Based Lead-Free High-Frequency Ultrasonic Transducers for Multifunctional Acoustic Tweezers. <i>ACS Applied Materials & Interfaces</i> , 2022, 14, 30979-30990.	8.0	10
317	Multiferroic Behavior of Sn-Modified BiFeO_3 Thin Films. <i>Electrochemical and Solid-State Letters</i> , 2010, 13, G83.	2.2	9
318	Effect of bilayer structure and a SrRuO_3 buffer layer on ferroelectric properties of BiFeO_3 thin films. <i>Applied Physics A: Materials Science and Processing</i> , 2012, 109, 57-61.	2.3	9
319	Low temperature sintering of $\text{Ba}_{0.91}\text{Ca}_{0.09}\text{Ti}_{0.916}\text{Sn}_{0.084}\text{O}_3$ lead-free piezoelectric ceramics with the additives of ZnO and MnO_2 . <i>Journal of Electroceramics</i> , 2014, 32, 175-179.	2.0	9
320	Microstructure and piezoelectric properties of lead-free $0.95(\text{Na}_{0.5}\text{K}_{0.5})\text{NbO}_3 \cdot 0.05(\text{Bi}_{0.5}\text{K}_{0.5})\text{Zr}_{1-x}\text{Ti}_x\text{O}_3$ ceramics. <i>Journal of Materials Science: Materials in Electronics</i> , 2014, 25, 1938-1941.	2.2	9
321	Tailored electrical properties in ternary $\text{BiScO}_3\text{-PbTiO}_3$ ceramics by composition modification. <i>Ceramics International</i> , 2018, 44, 8057-8063.	4.8	9
322	Preparation and Characterization. , 2018, , 41-108.		9
323	Defect dynamics mediated unusual field-cycling behavior in bismuth ferrite-based ceramics. <i>Scripta Materialia</i> , 2020, 187, 418-423.	5.2	9
324	Feasible Way to Achieve Multifunctional $(\text{K, Na})\text{NbO}_3$ -Based Ceramics: Controlling Long-Range Ferroelectric Ordering. <i>ACS Applied Materials & Interfaces</i> , 2021, 13, 60227-60240.	8.0	9

#	ARTICLE	IF	CITATIONS
325	Effect of Zn Concentration on Multiferroic and Fatigue Behavior of $\text{Bi}_{0.90}\text{La}_{0.10}\text{Fe}_{1-x}\text{Zn}_x\text{O}_3$ Thin Films. <i>Electrochemical and Solid-State Letters</i> , 2010, 13, G105.	2.2	8
326	Piezoelectric properties of $(\text{K}_{0.474}\text{Na}_{0.474}\text{Li}_{0.052})(\text{Nb}_{0.948}\text{Sb}_{0.052})\text{O}_3\text{-Co}_2\text{O}_3$ lead-free ceramics. <i>Journal of the Ceramic Society of Japan</i> , 2011, 119, 654-657.	1.1	8
327	PHASE STRUCTURE, PIEZOELECTRIC AND MULTIFERRIOIC BEHAVIOR OF $(\text{K}_{0.48}\text{Na}_{0.52})\text{NbO}_3\text{-Co}_2\text{O}_3$ PIEZOELECTRIC CERAMICS. <i>Functional Materials Letters</i> , 2011, 04, 225-229.	1.2	8
328	Microstructure and electrical properties of $(\text{Bi}_{0.50-x}\text{Na}_{0.50})_{0.94}\text{Ba}_{0.06}\text{TiO}_3$ ceramics with bismuth nonstoichiometry. <i>Physica Status Solidi (A) Applications and Materials Science</i> , 2012, 209, 1213-1218.	1.8	8
329	$\text{Ba}_{0.85}\text{Ca}_{0.15}\text{Ti}_{0.90}\text{Zr}_{0.10}\text{O}_3$ Lead-free Ceramics with a Sintering Aid of MnO. <i>Integrated Ferroelectrics</i> , 2013, 141, 89-98.	0.7	8
330	Phase structure and electrical properties of barium-modified potassium-sodium niobate-based lead-free ceramics. <i>Journal of Alloys and Compounds</i> , 2015, 651, 302-307.	5.5	8
331	Crystal Structure, Piezoelectric and Dielectric Properties of $(\text{Li}, \text{Ce})^{4+}$, Nb^{5+} and Mn^{2+} Co-doped $\text{CaBi}_4\text{Ti}_4\text{O}_{15}$ High-Temperature Ceramics. <i>Journal of Electronic Materials</i> , 2016, 45, 3597-3602.	2.2	8
332	Composition dependence of electrical properties in $(\text{K}_x\text{Na}_{1-x})\text{NbO}_3$ lead-free ceramics. <i>Journal of Materials Science: Materials in Electronics</i> , 2017, 28, 4828-4838.	2.2	8
333	Novel rhombohedral and tetragonal phase boundary with high T _C in alkali niobate ceramics. <i>Journal of Materials Science: Materials in Electronics</i> , 2017, 28, 12851-12857.	2.2	8
334	Enhanced piezoelectric properties in $0.96(\text{K}_{0.48}\text{Na}_{0.52})(\text{Nb}_{1-x}\text{Ta}_x)\text{O}_3\text{-}0.04(\text{Bi}_{0.5}\text{Ag}_{0.5})\text{ZrO}_3$ lead-free ceramics. <i>Journal of Materials Science: Materials in Electronics</i> , 2020, 31, 9525-9534.	2.2	8
335	Polyporous PVDF/ TiO_2 photocatalytic composites for photocatalyst fixation, recycle, and repair. <i>Journal of the American Ceramic Society</i> , 2021, 104, 6290-6298.	3.8	8
336	Constructing Relaxor/Ferroelectric Pseudocomposite To Reveal the Domain Role in Electrostrain of Bismuth Ferrite-Barium Titanate Based Ceramics. <i>ACS Applied Materials & Interfaces</i> , 2022, 14, 18713-18722.	8.0	8
337	Tuning the electrocaloric effect by tailoring phase fraction in BaTiO_3 -based ferroelectrics. <i>Journal of the European Ceramic Society</i> , 2022, 42, 5172-5178.	5.7	8
338	Electric-Field-Insensitive Temperature Stability of Strain in KNN Multilayer Composite Ceramics. <i>ACS Applied Materials & Interfaces</i> , 2022, 14, 26949-26957.	8.0	8
339	Multiferroic behavior of $\text{BiFeO}_3\text{-}R\text{TiO}_3$ (Mg, Sr, Ca, Ba, and Pb) thin films. <i>Journal of Applied Physics</i> , 2010, 108, 026101.	2.5	7
340	Effect of oxygen content during sputtering on the electrical properties of bismuth ferrite thin films. <i>Physica Status Solidi - Rapid Research Letters</i> , 2011, 5, 190-192.	2.4	7
341	Effect of $(\text{Bi}, \text{La})(\text{Fe}, \text{Zn})\text{O}_3$ thickness on the microstructure and multiferroic properties of BiFeO_3 thin films. <i>Journal of Applied Physics</i> , 2012, 112, 094109.	2.5	7
342	Photocatalytic O_2 production using WO_3 nanoparticles prepared by annealing ethylenediamine tungstate/ C_xN_y gel. <i>RSC Advances</i> , 2015, 5, 99398-99404.	3.6	7

#	ARTICLE	IF	CITATIONS
343	Sintering behavior, phase structure and electric properties of KNNTS-BKNZ ceramics with excessive alkali metals. <i>Journal of Materials Science: Materials in Electronics</i> , 2018, 29, 5337-5348.	2.2	7
344	An Alternative Way To Enhance Piezoelectricity and Temperature Stability in Lead-Free Sodium Niobate Piezoceramics. <i>Inorganic Chemistry</i> , 2018, 57, 10383-10389.	4.0	7
345	Insights into the Correlation between Tetragonal Phase and Temperature Stability of Potassium Sodium Niobate Based Ceramics from Domain Behaviors. <i>Advanced Electronic Materials</i> , 2022, 8, 2100257.	5.1	7
346	Bilayered BiFe _{0.95} Mn _{0.05} O ₃ /Bi _{0.90} La _{0.10} FeO ₃ Thin Films with Low Ferroelectric Coercivity and Large Remanent Polarization. <i>Journal of the American Ceramic Society</i> , 2010, 93, 2113-2116.	3.8	6
347	Microstructures and Piezoelectric properties of CuO-doped (Ba _{0.98} Ca _{0.02})(Ti _{0.94} Sn _{0.06})O ₃ ceramics. <i>Journal of Electroceramics</i> , 2014, 33, 117-120.	2.0	6
348	Ba _{0.95} Ca _{0.05} Ti _{0.92} Sn _{0.08} Zr _x O ₃ lead-free ceramics: microstructure and piezoelectricity. <i>Journal of Materials Science: Materials in Electronics</i> , 2015, 26, 4119-4123.	2.2	6
349	Structure-property in KNNS-BNT-BNH ternary system with rhombohedral-tetragonal phase boundary. <i>Ceramics International</i> , 2016, 42, 16049-16054.	4.8	6
350	Phase structure, electrical properties, and component stability in (1-x)(K _{0.40} Na _{0.60} Nb _{0.96} Sb _{0.04} O ₃)(Bi _{0.92} Nd _{0.08}) _{0.5} Na _{0.5} ZrO ₃ lead-free ceramics. <i>Journal of Materials Science: Materials in Electronics</i> , 2018, 29, 17209-17216.	2.2	6
351	A Bright New World of Ferroelectrics: Magic of Spontaneous Polarization. <i>ACS Applied Materials & Interfaces</i> , 2020, 12, 52231-52233.	8.0	6
352	Ultra-slim electrostrains with superior temperature-stability in lead-free sodium niobate-based ferroelectric perovskite. <i>Journal of Materiomics</i> , 2022, 8, 1230-1238.	5.7	6
353	A KNN composite-based piezoelectric helix for ultrasonic transcutaneous energy harvesting. <i>Applied Physics Letters</i> , 2022, 120, .	3.3	6
354	Highly (100)-oriented (Pb _{1-x} La _x)Ti _{1-x} /4O ₃ /Pb(Zr _{0.20} Ti _{0.80})O ₃ /(Pb _{1-x} La _x)Ti _{1-x} /4O ₃ multilayered thin films by RF magnetron sputtering. <i>Physica Status Solidi (A) Applications and Materials Science</i> , 2007, 204, 2362-2368.	1.8	5
355	Thickness-Dependent Magnetic Properties of Bismuth Ferrite Thin Films. <i>Electrochemical and Solid-State Letters</i> , 2011, 14, G57.	2.2	5
356	An enhanced mechanical quality factor and a low dielectric loss in lithium sodium niobate lead-free ceramics. <i>Ceramics International</i> , 2012, 38, 4023-4027.	4.8	5
357	Effect of Sintering Parameters on Microstructure and Electrical Properties of (Ba _{0.98} Ca _{0.02})(Ti _{0.94} Sn _{0.06})O ₃ Lead-Free Piezo-Ceramics. <i>Ferroelectrics</i> , 2015, 489, 129-134.	0.6	5
358	Microstructure and Electrical Properties of (1-x)(K _{0.46} Na _{0.54})NbO ₃ -(x)(Bi _{0.5} Na _{0.5})(Zr _{0.85} Sn _{0.15})O ₃ Piezoelectric Ceramics. <i>Ferroelectrics</i> , 2015, 489, 135-140.	2.2	5
359	Effect of Hf and Li on the structure and electrical properties of Bi _{0.5} Na _{0.5} TiO ₃ lead-free ceramics. <i>Journal of Materials Science: Materials in Electronics</i> , 2017, 28, 16948-16954.	2.2	5
360	Bi _{0.5} Na _{0.5} TiO ₃ -Based Piezoelectric Materials. , 2018, , 191-245.		5

#	ARTICLE	IF	CITATIONS
361	Origin of large piezoelectricity in BF-BT based multiphase ferroelectrics. <i>Ceramics International</i> , 2022, 48, 23808-23813.	4.8	5
362	Effect of the PbOx thickness on the microstructure and electrical properties of PLT thin films prepared by RF magnetron sputtering. <i>Surface and Coatings Technology</i> , 2008, 202, 2080-2084.	4.8	4
363	Effect of residual stress on the ferroelectric property of (Pb _{0.90} La _{0.10})Ti _{0.975} O ₃ thin films. <i>Journal of Applied Physics</i> , 2009, 105, 056107.	2.5	4
364	Compositionally graded bismuth ferrite thin films. <i>Journal of Alloys and Compounds</i> , 2011, 509, L319-L323.	5.5	4
365	Thin film bilayers of multiferroic bismuth ferrite on Pt/Si substrate. <i>Physica Status Solidi - Rapid Research Letters</i> , 2011, 5, 83-85.	2.4	4
366	Multiferroic and fatigue behavior of Bi _{0.95} Mn _{0.05} O ₃ /Bi _{0.90} La _{0.10} Fe _{0.85} Zn _{0.15} bilayered thin films. <i>IEEE Transactions on Ultrasonics, Ferroelectrics, and Frequency Control</i> , 2012, 59, 14-20.	3.0	4
367	Bismuth ferrite composite thin films. <i>Applied Physics A: Materials Science and Processing</i> , 2013, 111, 1017-1020.	2.3	4
368	Bismuth Ferrite-Based Piezoelectric Materials. , 2018, , 301-378.		4
369	Potassium sodium niobate ceramics with broad phase transition range: Temperature-insensitive strain. <i>Ceramics International</i> , 2019, 45, 24827-24834.	4.8	4
370	Orientation control and ferroelectric properties of (Pb _{0.90} La _{0.10})Ti _{0.975} O ₃ thin films prepared by rf magnetron sputtering with a LaNiO ₃ buffer layer. <i>Physica Status Solidi (A) Applications and Materials Science</i> , 2007, 204, 3526-3532.	1.8	3
371	Periodicity and orientation dependence of electrical properties of [(Pb _{0.90} La _{0.10})Ti _{0.975} O ₃ /PbTiO ₃] _n (n=1~6) multilayer thin films. <i>Applied Surface Science</i> , 2009, 255, 8305-8308.	6.1	3
372	Multiferroic, Optical, and Fatigue Behavior of BiFeO ₃ Thin Films with a Sintering Aid of CuO. <i>Electrochemical and Solid-State Letters</i> , 2010, 13, G68.	2.2	3
373	Investigation of phase structure, microstructure, and electrical properties of LaAlO ₃ -modified alkali niobate lead-free perovskite. <i>Journal of Materials Science: Materials in Electronics</i> , 2017, 28, 17761-17771.	2.2	3
374	Low leakage current resistive memory based on Bi _{1.10} (Fe _{0.95} Mn _{0.05})O ₃ films. <i>Semiconductor Science and Technology</i> , 2018, 33, 095002.	2.0	3
375	BaTiO ₃ -Based Piezoelectric Materials. , 2018, , 247-299.		3
376	Second-order transition like characteristic contributes to strain temperature stability in (K, Na)NbO ₃ based materials. <i>Journal of the American Ceramic Society</i> , 2020, 103, 2509-2519.	3.8	3
377	Growth and properties of (Pb _{0.90} La _{0.10})TiO ₃ thick films prepared by RF magnetron sputtering with a PbO buffer layer. <i>Journal of Crystal Growth</i> , 2007, 300, 398-402.	1.5	2
378	Preparation and Piezoelectric Properties of (Na _{0.52-x} K _{0.48})Nb _{0.95-x} Ta _{0.05} O _{3-x} LiSbO ₃ Ceramics. <i>Ferroelectrics</i> , 2009, 385, 6108-6113.	0.6	2

#	ARTICLE	IF	CITATIONS
379	Piezoelectric properties of new ternary Bi _{1/2} (Na, Li) _{1/2} TiO ₃ (Bi _{1/2} K _{1/2})TiO ₃ Ba _{0.85} Ca _{0.15} Ti _{0.90} Zr _{0.10} O ₃ ceramics. Applied Physics A: Materials Science and Processing, 2012, 109, 273-277.	2.3	2
380	Piezoelectric Properties of (1-x)(K _{0.52} Na _{0.48}) _{1-x} Li _x NbO ₃ (Bi _{0.5} Na _{0.5}) _{0.9} Ca _{0.1} TiO ₃ with Higher Curie Temperature. Integrated Ferroelectrics, 2013, 141, 82-88.	0.7	2
381	High-performance potassium sodium niobate-based lead-free materials without antimony. Journal of Materials Science: Materials in Electronics, 2018, 29, 14487-14494.	2.2	2
382	Application of Lead-Free Piezoelectric Materials. , 2018, , 463-522.		2
383	An exploration for new strategy: Achieving both excellent temperature stability and good electrostrain in BiFeO ₃ BaTiO ₃ -based relaxor ferroelectrics by domain engineering. Materials Today Physics, 2022, 27, 100747.	6.0	2
384	Switching-induced charge injection inducing fatigue in lead zirconate titanium thin films. Ceramics International, 2012, 38, 2583-2587.	4.8	1
385	Phase Structure and Piezoelectric Properties of (0.977-x)(K _{0.5} Na _{0.5})NbO ₃ -0.023Bi _{0.5} (Na _{0.9} K _{0.1}) _{0.1} PiO ₃ Piezoelectric Ceramics. Ferroelectrics, 2015, 489, 141-146.		
386	Dielectric and Ferroelectric Behaviors of (100)-Oriented 0.9Pb(Sc _{0.5} Ta _{0.5})O ₃ -0.1PbTiO ₃ Thin Films. Ferroelectrics, 2015, 478, 157-164.	0.6	1
387	Composition dependence of phase structure and electrical properties of (1-x)yBi _{1-x} Nd _x FeO _{3-y} BiScO ₃ ceramics. Science China Technological Sciences, 2016, 59, 1029-1035.	4.0	1
388	High-performance KNN-based ceramics: inter-granular coupling effect. Journal of Materials Science: Materials in Electronics, 2020, 31, 1065-1071.	2.2	1
389	Bi _{0.5} (Na _{1-x-y} K _x Li _y) _{0.5} TiO ₃ Lead-free Piezoelectric Ceramics and Their Applications for Buzzers and Filters. , 2006, , .		
390	THE CRYSTALLINE AND DOMAIN PROPERTIES OF PLT THIN FILMS FABRICATED BY RF SPUTTERING. Integrated Ferroelectrics, 2006, 79, 219-226.	0.7	0
391	Bismuth ferrite bilayered thin films of different constituent layer thicknesses. Journal of Alloys and Compounds, 2011, 509, 7742-7748.	5.5	0
392	Optical Properties of 0.95BiFeO ₃ -RTiO ₃ (R = Mg, Pb, Ba, Ca and Sr) Thin Films. Integrated Ferroelectrics, 2012, 139, 1-6.	0.7	0
393	Rhombohedral-Orthorhombic Phase Transition Induced Enhancement on the Electrical Behavior of (K _{0.5} Na _{0.5})NbO ₃ -BiScO ₃ -BiCoO ₃ Lead-free Piezoelectric Ceramics. Materials Research Society Symposia Proceedings, 2012, 1397, 90.	0.1	0
394	Microstructure and electrical properties of 0.94Bi _{0.51} (Na _{1-x} K _x) _{0.5} TiO ₃ -0.06(Ba _{0.98} Ca _{0.02}) _{0.1} TiO ₃ thin films. Journal of Materials Science: Materials in Electronics, 2018, 29, 14487-14494.	2.0	0
395	Recent Development of Lead-Free Piezoelectrics. , 2018, , 397-461.		0
396	Alkali Niobate-Based Piezoelectric Materials. , 2018, , 109-189.		0

#	ARTICLE	IF	CITATIONS
397	and Nanotechnology, 2019, 19, 231-234.	0.9	0
398	Enhanced electrocaloric effect in compositional driven potassium sodium niobate-based relaxor ferroelectrics. Journal of Materials Research, 2021, 36, 1-11.	2.6	0