

# Wiesław Olek

## List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/7205588/publications.pdf>

Version: 2024-02-01

34  
papers

595  
citations

516710

16  
h-index

610901

24  
g-index

34  
all docs

34  
docs citations

34  
times ranked

516  
citing authors

#	ARTICLE	IF	CITATIONS
1	Sorption and diffusion properties of untreated and thermally modified beech wood dust. <i>Wood Science and Technology</i> , 2022, 56, 7-23.	3.2	6
2	Estimation of Thermal Properties of Straw-Based Insulating Panels. <i>Materials</i> , 2022, 15, 1073.	2.9	8
3	Application of the Response Surface Methodology for Designing Oscillation Drying of Beech Timber. <i>Forests</i> , 2020, 11, 541.	2.1	1
4	Effects of heat treatment on thermal properties of European beech wood. <i>European Journal of Wood and Wood Products</i> , 2020, 78, 425-431.	2.9	24
5	Thermal properties of fractions of corn stover. <i>Construction and Building Materials</i> , 2019, 210, 709-712.	7.2	25
6	Water sorption and diffusion properties of beech wood dust. <i>Powder Technology</i> , 2019, 346, 109-115.	4.2	5
7	Dimensional stability and hygroscopic properties of PEG treated irregularly degraded waterlogged Scots pine wood. <i>Journal of Cultural Heritage</i> , 2018, 31, 133-140.	3.3	17
8	Dimensional stability and hygroscopic properties of waterlogged archaeological wood treated with alkoxysilanes. <i>International Biodeterioration and Biodegradation</i> , 2018, 133, 34-41.	3.9	23
9	Sorption isotherms of waterlogged subfossil Scots pine wood impregnated with a lactitol and trehalose mixture. <i>Holzforschung</i> , 2017, 71, 813-819.	1.9	15
10	Effects of Cyclic Changes in Relative Humidity on the Sorption Hysteresis of Thermally Modified Spruce Wood. <i>BioResources</i> , 2016, 11, .	1.0	25
11	Non-Fickian moisture diffusion in thermally modified beech wood analyzed by the inverse method. <i>International Journal of Thermal Sciences</i> , 2016, 109, 291-298.	4.9	21
12	Thermal properties of wood-based panels: thermal conductivity identification with inverse modeling. <i>European Journal of Wood and Wood Products</i> , 2016, 74, 577-584.	2.9	18
13	Changes in strength of Scots pine wood ( <i>Pinus silvestris</i> L.) decayed by brown rot ( <i>Coniophora</i> ) Tj ETQq1 1 0.784314 rgBT /Overlock 42	7.2	42
14	Thermal properties of wood-based panels: specific heat determination. <i>Wood Science and Technology</i> , 2016, 50, 537-545.	3.2	26
15	Hygroscopic properties of PEG treated archaeological wood from the rampart of the 10th century stronghold as exposed in the Archaeological Reserve Genius loci in Poznań, (Poland). <i>Journal of Cultural Heritage</i> , 2016, 18, 299-305.	3.3	13
16	Integration of experimental and computational methods for identifying geometric, thermal and diffusive properties of biomaterials. <i>International Agrophysics</i> , 2016, 30, 253-260.	1.7	2
17	Computer-aided identification of the water diffusion coefficient for maize kernels dried in a thin layer. <i>International Agrophysics</i> , 2016, 30, 323-329.	1.7	0
18	Effects of cell wall ultrastructure on the transverse shrinkage anisotropy of Scots pine wood. <i>Holzforschung</i> , 2015, 69, 501-507.	1.9	11

#	ARTICLE	IF	CITATIONS
19	Effects of thermal modification on wood ultrastructure analyzed with crystallographic texture. <i>Holzforschung</i> , 2014, 68, 721-726.	1.9	22
20	Effects of White and Brown Rot Decay on Changes of Wood Ultrastructure. <i>BioResources</i> , 2014, 9, .	1.0	4
21	Sorption isotherms of thermally modified wood. <i>Holzforschung</i> , 2013, 67, 183-191.	1.9	76
22	INFLUENCE OF CYCLIC SORPTION ON WOOD ULTRASTRUCTURE. <i>BioResources</i> , 2012, 7, .	1.0	8
23	Application of the crystalline volume fraction for characterizing the ultrastructural organization of wood. <i>Cellulose</i> , 2011, 18, 223-235.	4.9	18
24	Implementation of a relaxation equilibrium term in the convective boundary condition for a better representation of the transient bound water diffusion in wood. <i>Wood Science and Technology</i> , 2011, 45, 677-691.	3.2	21
25	Preferred crystallographic orientation in mature and juvenile wood. <i>Zeitschrift Fur Kristallographie - Crystalline Materials</i> , 2007, 222, 199-203.	0.8	1
26	Effects of the method of identification of the diffusion coefficient on accuracy of modeling bound water transfer in wood. <i>Transport in Porous Media</i> , 2007, 66, 135-144.	2.6	29
27	Texture function application for wood ultrastructure description. Part 1: theory. <i>Wood Science and Technology</i> , 2006, 40, 159-171.	3.2	7
28	Texture function application for wood ultrastructure description. Part 2: Application. <i>Wood Science and Technology</i> , 2006, 40, 336-349.	3.2	11
29	Inverse analysis of the transient bound water diffusion in wood. <i>Holzforschung</i> , 2005, 59, 38-45.	1.9	59
30	Inverse Finite Element Analysis of Technological Processes of Heat and Mass Transport in Agricultural and Forest Products. <i>Drying Technology</i> , 2005, 23, 1737-1750.	3.1	13
31	Effects of Thermal Conductivity Data on Accuracy of Modeling Heat Transfer in Wood. <i>Holzforschung</i> , 2003, 57, 317-325.	1.9	22
32	Large moisture evaporation rates from sapwood and heartwood samples of Douglas fir ( <i>Pseudotsuga</i> ) Tj ETQq0 0 0,rgBT /Overlock 10 T	2.9	2
33	IDENTIFICATION OF MATHEMATICAL MODEL COEFFICIENTS IN THE ANALYSIS OF THE HEAT AND MASS TRANSPORT IN WOOD. <i>Drying Technology</i> , 2000, 18, 1697-1708.	3.1	16
34	Prediction of temperature changes in glued laminated beams. <i>European Journal of Wood and Wood Products</i> , 1995, 53, 249-252.	2.9	4