## **Zhenxing Yue**

## List of Publications by Year in Descending Order

Source: https://exaly.com/author-pdf/7226858/zhenxing-yue-publications-by-year.pdf

Version: 2024-04-19

This document has been generated based on the publications and citations recorded by exaly.com. For the latest version of this publication list, visit the link given above.

The third column is the impact factor (IF) of the journal, and the fourth column is the number of citations of the article.

85	<b>1,202</b> citations	19	<b>29</b>
papers		h-index	g-index
88	1,401 ext. citations	3.2	4.31
ext. papers		avg, IF	L-index

#	Paper	IF	Citations
85	Structure, defects, and microwave dielectric properties of Al-doped and Al/Nd co-doped Ba4Nd9.33Ti18O54 ceramics. <i>Journal of Advanced Ceramics</i> , <b>2022</b> , 11, 629-640	10.7	2
84	Microwave and terahertz properties of porous Ba4(Sm,Nd,Bi)28/3Ti18O54 ceramics obtained by sacrificial template method. <i>Journal of the American Ceramic Society</i> , <b>2021</b> , 104, 5679-5688	3.8	3
83	Ultrahigh energy storage density and charge-discharge performance in novel sodium bismuth titanate-based ceramics. <i>Journal of the American Ceramic Society</i> , <b>2021</b> , 104, 936-947	3.8	9
82	Physical properties and structure characteristics of titanium-modified antimony-selenium phase change thin film. <i>Applied Physics Letters</i> , <b>2021</b> , 118, 081903	3.4	4
81	Phonon characteristics and intrinsic properties of single phase ZnWO4 ceramic. <i>Journal of Materials Science: Materials in Electronics</i> , <b>2020</b> , 31, 6192-6198	2.1	2
80	Improved chargedischarge cycling durability of PVDF dielectrics with MgO nanofillers. <i>Applied Physics Letters</i> , <b>2020</b> , 116, 172902	3.4	1
79	Enhancement of dielectric properties and energy storage performance in 3Y-TZP ceramics with BaTiO3 additives. <i>International Journal of Applied Ceramic Technology</i> , <b>2020</b> , 17, 1362-1370	2	4
78	Crystal structure, dielectric properties, and lattice vibrational characteristics of LiNiPO4 ceramics sintered at different temperatures. <i>Journal of the American Ceramic Society</i> , <b>2020</b> , 103, 2528-2539	3.8	20
77	Internal relations between crystal structures and dielectric properties of (1-x)BaWO4-xTiO2 composite ceramics. <i>Journal of Materials Science: Materials in Electronics</i> , <b>2020</b> , 31, 19961-19973	2.1	O
76	Investigation of significant magnetic transformation for hydrogenated ZnFe2O4 nanoparticles. <i>Journal of Materials Science</i> , <b>2020</b> , 55, 1464-1474	4.3	3
75	Influences of sintering atmosphere on the magnetic and electrical properties of barium hexaferrites. <i>AIP Advances</i> , <b>2019</b> , 9, 085129	1.5	4
74	Microwave dielectric properties and thermally stimulated depolarization of Al-doped Ba4(Sm,Nd)9.33Ti18O54 ceramics. <i>Journal of the American Ceramic Society</i> , <b>2019</b> , 102, 5494-5502	3.8	14
73	A First-Principles Study on the Multiferroic Property of Two-Dimensional BaTiO[[001] Ultrathin Film with Surface Ba Vacancy. <i>Nanomaterials</i> , <b>2019</b> , 9,	5.4	5
72	High-Q and temperature-stable microwave dielectrics in layer cofired Zn1.01Nb2O6/TiO2/Zn1.01Nb2O6 ceramic architectures. <i>Journal of the American Ceramic Society</i> , <b>2019</b> , 102, 342-350	3.8	15
71	MgTiO3/TiO2/MgTiO3: An ultrahigh-Q and temperature-stable microwave dielectric ceramic through cofired trilayer architecture. <i>Ceramics International</i> , <b>2018</b> , 44, 21000-21003	5.1	18
70	Improvement in microwave dielectric properties of Sr2TiO4 ceramics through post-annealing treatment. <i>Journal of Electroceramics</i> , <b>2018</b> , 41, 67-72	1.5	6
69	Phase transition and piezoelectricity of BaZrO3-modified (K,Na)NbO3 lead-free piezoelectric thin films. <i>Journal of the American Ceramic Society</i> , <b>2018</b> , 102, 2770	3.8	2

68	Epitaxially grown BaM hexaferrite films having uniaxial axis in the film plane for self-biased devices. <i>Scientific Reports</i> , <b>2017</b> , 7, 44193	4.9	12
67	Microwave dielectric properties and thermally stimulated relaxations of Ba0.6Sr0.4La4Ti4O15TiO2 composite ceramics by flowing oxygen sintering. <i>Journal of Materials Science: Materials in Electronics</i> , <b>2017</b> , 28, 3400-3406	2.1	2
66	Novel Low-Firing Forsterite-Based Microwave Dielectric for LTCC Applications. <i>Journal of the American Ceramic Society</i> , <b>2016</b> , 99, 1122-1124	3.8	34
65	Orientation Growth and Magnetic Properties of BaM Hexaferrite Films Deposited by Direct Current Magnetron Sputtering. <i>Journal of the American Ceramic Society</i> , <b>2016</b> , 99, 860-865	3.8	7
64	Thermally stable polymerDeramic composites for microwave antenna applications. <i>Journal of Advanced Ceramics</i> , <b>2016</b> , 5, 269-276	10.7	12
63	Dielectric response and thermally stimulated depolarization current analysis of BaNd1.76Bi0.24Ti5O14 high-temperature microwave capacitors. <i>Journal of Materials Science</i> , <b>2015</b> , 50, 1141-1149	4.3	10
62	Microwave Dielectric Properties and Thermally Stimulated Depolarization Currents of (1៤)MgTiO3⊌Ca0.8Sr0.2TiO3 Ceramics. <i>Journal of the American Ceramic Society</i> , <b>2015</b> , 98, 1548-1554	3.8	40
61	Structure, Microwave Dielectric Properties and Thermally Stimulated Depolarization Currents of (1賦)Ba0.6Sr0.4La4Ti4O15図Ba5Nb4O15 Solid Solutions. <i>Journal of the American Ceramic Society</i> , <b>2015</b> , 98, 1245-1252	3.8	11
60	Microwave Dielectric Properties and Thermally Stimulated Depolarization Currents of (1☑)Ba(Mg1/3Nb2/3)O3☑BaSnO3 Solid Solutions. <i>Journal of the American Ceramic Society</i> , <b>2015</b> , 98, 3942-3947	3.8	12
59	Highly (100)-Oriented Bi(Ni1/2Hf1/2)O3-PbTiO3 Relaxor-Ferroelectric Films for Integrated Piezoelectric Energy Harvesting and Storage System. <i>Journal of the American Ceramic Society</i> , <b>2015</b> , 98, 2968-2971	3.8	30
58	Tunable High-Frequency Properties of Co <b>N</b> i Ferromagnetic Nanowires Through Composition Modulation. <i>IEEE Transactions on Magnetics</i> , <b>2015</b> , 51, 1-6	2	1
57	Structure-Property Relationships of Ba[Ti1 $\mathbb{R}$ (Ho0.5Nb0.5)x]O3 (x = 0.05 $\mathbb{D}$ .90) Perovskite Ceramics. <i>Ferroelectrics</i> , <b>2014</b> , 459, 112-118	0.6	
56	Microwave Dielectric Properties and Thermally Stimulated Depolarization Currents of MgF2-Doped Diopside Ceramics. <i>Journal of the American Ceramic Society</i> , <b>2014</b> , 97, 3537-3543	3.8	27
55	High-frequency ferromagnetic resonance of Co nanowire arrays. <i>Physica Status Solidi (A)</i> Applications and Materials Science, <b>2014</b> , 211, 1828-1833	1.6	8
54	Polarization Response and Thermally Stimulated Depolarization Current of BaTiO3-based Y5V Ceramic Multilayer Capacitors. <i>Journal of the American Ceramic Society</i> , <b>2014</b> , 97, 2921-2927	3.8	19
53	Microwave Dielectric Properties and Thermally Stimulated Depolarization Currents Study of (1☑)Ba0.6Sr0.4La4Ti4O15☑TiO2 Ceramics. <i>Journal of the American Ceramic Society</i> , <b>2014</b> , 97, 3170-3176	3.8	17
52	HighEnergy-Storage Density Capacitors of Bi(Ni1/2Ti1/2)O3PbTiO3 Thin Films with Good Temperature Stability. <i>Journal of the American Ceramic Society</i> , <b>2013</b> , 96, 2061-2064	3.8	48
51	Controlled synthesis of anatase TiO2 nanotube and nanowire arrays via AAO template-based hydrolysis. <i>Journal of Materials Chemistry A</i> , <b>2013</b> , 1, 2552	13	39

50	Epitaxial Spinel Cobalt Ferrite Films Prepared by Two-Step Spin-Coating Method. <i>Ferroelectrics</i> , <b>2013</b> , 455, 62-68	0.6	2
49	Characterization of Domains Reorientation in Multilayer Piezoelectric Ceramic Actuators by Polarized Raman Spectroscopy. <i>Journal of the American Ceramic Society</i> , <b>2012</b> , 95, 2766-2768	3.8	1
48	Field-induced domain switching in BaTiO3-based multilayer ceramic capacitors observed by polarized Raman spectroscopy. <i>Applied Physics A: Materials Science and Processing</i> , <b>2012</b> , 109, 331-335	2.6	O
47	Structural Transitions and Microwave Dielectric Properties of (Ba, Sr)2 LnSbO6 (Ln = La, Pr, Nd, Sm, Gd, Dy) Double Perovskites. <i>Ferroelectrics</i> , <b>2012</b> , 435, 119-128	0.6	5
46	Microwave dielectric properties and low temperature sintering of Ba3Ti4½(Mg1/3Nb2/3)xNb4O21 ceramics with BaCu(B2O5) addition. <i>Journal of Materials Science: Materials in Electronics</i> , <b>2012</b> , 23, 1449	- <del>1</del> 454	3
45	Structures and Microwave Dielectric Properties of Ba[Ti1½(Co0.5W0.5)x]O3 (x1±10.4010.90) Perovskite Ceramics. <i>Journal of the American Ceramic Society</i> , <b>2012</b> , 95, 1645-1650	3.8	10
44	Structural Transitions and Microwave Dielectric Properties of Ba2@xSr2xSmSbO6 Double Perovskites. <i>Journal of the American Ceramic Society</i> , <b>2012</b> , 95, 1665-1670	3.8	10
43	Microwave Dielectric Properties of Ba2Ca1\(\mathbb{R}\)SrxWO6Double Perovskites. <i>Journal of the American Ceramic Society</i> , <b>2011</b> , 94, 2933-2938	3.8	18
42	Solgel synthesis, densification, and electrical properties of CuOB2O3 doped Ba6Bx R8+2x Ti18O54 (R = Nd) microwave dielectric ceramics. <i>Journal of Materials Science</i> , <b>2011</b> , 46, 1932-1936	4.3	4
41	Influence of CuO and B2O3 on sintering and dielectric properties of tungsten bronze type microwave ceramics: a case study in Ba4Nd9.3Ti18O54. <i>Journal of Materials Science: Materials in Electronics</i> , <b>2011</b> , 22, 106-110	2.1	10
40	Energy-storage performance and electrocaloric effect in (100)-oriented Pb0.97La0.02(Zr0.95Ti0.05)O3 antiferroelectric thick films. <i>Journal of Applied Physics</i> , <b>2011</b> , 110, 064109	9 <sup>2.5</sup>	77
39	Structural and Dielectric Characteristics in (1日)Ba(Ni1/2W1/2)O3日BaTiO3 Perovskite Solid Solutions. <i>Journal of the American Ceramic Society</i> , <b>2010</b> , 93, 516-521	3.8	9
38	Microwave Dielectric Properties of Ba3(VO4)2Mg2SiO4 Composite Ceramics. <i>Journal of the American Ceramic Society</i> , <b>2010</b> , 93, 359-361	3.8	38
37	Electric Field-Dependent Properties of BaTiO3-Based Multilayer Ceramic Capacitors. <i>Ferroelectrics</i> , <b>2010</b> , 401, 56-60	0.6	12
36	Preparation and Microwave Dielectric Properties of TiO2-Doped YAG Ceramics. <i>Ferroelectrics</i> , <b>2010</b> , 407, 69-74	0.6	8
35	Microwave Dielectric Properties of Ba(Zn1/3Nb2/3)O3-BaWO4 Composite Ceramics. <i>Ferroelectrics</i> , <b>2009</b> , 388, 88-92	0.6	1
34	Phase Characterization and Dielectric Properties of Zn2SiO4 Ceramics Derived from a Sol-Gel Process. <i>Ferroelectrics</i> , <b>2009</b> , 387, 184-188	0.6	5
33	Effects of ZnONV2O5 substitution on the microstructure and microwave dielectric properties of ZnNb2O6 ceramics. <i>Journal of Electroceramics</i> , <b>2008</b> , 21, 116-119	1.5	6

## (2004-2008)

32	Low-temperature sintering and microwave dielectric properties of ZnTiO3-based LTCC materials. Journal of Electroceramics, <b>2008</b> , 21, 141-144	1.5	11	
31	Magnetic and dielectric properties of a double-percolating Ni0.3Zn0.7Fe1.95O4-Ni-polymer composite. <i>Journal of Electroceramics</i> , <b>2008</b> , 21, 385-389	1.5	4	
30	Interfacial investigation of the Co-fired NiCuZn Ferrite/PMN composite prepared by tape casting. <i>Journal of Electroceramics</i> , <b>2008</b> , 21, 536-540	1.5	1	
29	Characterizations of fatigue and crack growth of ferroelectrics under cyclic electric field. <i>Journal of Electroceramics</i> , <b>2008</b> , 21, 581-584	1.5	5	
28	Investigation of ferroelectric phase transition for modified barium titanate in multilayer ceramic capacitors by in situ Raman scattering and dielectric measurement. <i>Applied Physics A: Materials Science and Processing</i> , <b>2008</b> , 91, 119-125	2.6	22	
27	Evaluation of Residual Stress in a Multilayer Ceramic Capacitor and its Effect on Dielectric Behaviors Under Applied dc Bias Field. <i>Journal of the American Ceramic Society</i> , <b>2008</b> , 91, 887-892	3.8	11	
26	Processing and Piezoelectric Properties of (Na0.5K0.5)0.96Li0.04(Ta0.1Nb0.9)1⊠CuxO3∃x/2 Lead-Free Ceramics. <i>Journal of the American Ceramic Society</i> , <b>2008</b> , 91, 914-917	3.8	22	
25	Low-Temperature Sintering and Microwave Dielectric Properties of Ba5Nb4O15 <b>B</b> aWO4 Composite Ceramics for LTCC Applications. <i>Journal of the American Ceramic Society</i> , <b>2008</b> , 91, 3275-327	79 <sup>3.8</sup>	28	
24	Low-Temperature Sintering and Microwave Dielectric Properties of Ba3(VO4)2 <b>B</b> aWO4 Ceramic Composites. <i>Journal of the American Ceramic Society</i> , <b>2008</b> , 91, 3738-3741	3.8	29	
23	Microstructure and Microwave Dielectric Properties of TiO2-Doped Zn2SiO4 Ceramics Synthesized Through the Sol <b>©</b> el Process. <i>Journal of the American Ceramic Society</i> , <b>2008</b> , 91, 3981-3985	3.8	60	
22	Structure and Microwave Dielectric Properties of Hexagonal Ba[Ti1🏿(Ni1/2W1/2)x]O3 Ceramics. <i>Journal of the American Ceramic Society</i> , <b>2007</b> , 90, 2461-2466	3.8	19	
21	Effects of Silver Doping on the Soltel-Derived Ba4(Nd0.7Sm0.3)9.33Ti18O54 Microwave Dielectric Ceramics. <i>Journal of the American Ceramic Society</i> , <b>2007</b> , 90, 3131-3137	3.8	13	
20	Effect of electromagnetic environment on the dielectric resonance in the ferroelectric-ferromagnetic composite. <i>Applied Physics Letters</i> , <b>2006</b> , 89, 112907	3.4	15	
19	Effects of Zinc Substitution on Crystal Structure and Microwave Dielectric Properties of CaLa4Ti5O17 Ceramics. <i>Journal of the American Ceramic Society</i> , <b>2006</b> , 89, 3421-3425	3.8	37	
18	Preparation and Spontaneous Polarization Magnetization of a New Ceramic Ferroelectric Herromagnetic Composite. <i>Journal of the American Ceramic Society</i> , <b>2005</b> , 87, 1848-1852	3.8	46	
17	Low temperature sintered ZnNb2O6 microwave dielectric ceramics doped with ZnO-V2O5 additions. <i>Journal of Materials Science</i> , <b>2005</b> , 40, 6581-6583	4.3	14	
16	Magnetic properties of composite Y-type hexagonal ferrites in a direct current magnetic field. Journal of Applied Physics, <b>2005</b> , 98, 063901	2.5	9	
15	Low-Temperature Sintering and Electromagnetic Properties of Copper-Modified Z-type Hexaferrite. <i>Journal of the American Ceramic Society</i> , <b>2004</b> , 85, 1180-1184	3.8	10	

14	Preparation and microwave dielectric properties of Ba4(Sm1⊠ Nd x )9.3Ti18O54 ceramics via a citrate sol-gel process. <i>Journal of Materials Science</i> , <b>2004</b> , 39, 1087-1089	4.3	3
13	Low temperature sintered ZnNb2O6 microwave dielectric ceramics doped with CuO-Bi2O3-V2O5 additions. <i>Journal of Materials Science Letters</i> , <b>2003</b> , 22, 595-597		8
12	Low-temperature sintered Ni-Zn manganite NTC ceramics prepared by a gel auto-combustion method. <i>Journal of Materials Science Letters</i> , <b>2002</b> , 21, 375-377		8
11	Low-fired microwave dielectrics in ZnO-TiO2 ceramics doped with CuO and B2O3. <i>Journal of Materials Science: Materials in Electronics</i> , <b>2002</b> , 13, 415-418	2.1	19
10	Microstructure and Physical Characteristics of Novel Z-Type Hexaferrite with Cu Modification <b>2002</b> , 9, 73-79		7
9	Dielectric behavior of Co2Z hexagonal ferrites with multiple modifications. <i>Journal of Applied Physics</i> , <b>2002</b> , 91, 5230-5233	2.5	12
8	Microstructure and magnetic characteristics of low-temperature-fired modified Z-type hexaferrite with Bi/sub 2/O/sub 3/ additive. <i>IEEE Transactions on Magnetics</i> , <b>2002</b> , 38, 1797-1802	2	28
7	Low-temperature sintered Mg-Zn-Cu ferrite prepared by auto-combustion of nitrate-citrate gel. <i>Journal of Materials Science Letters</i> , <b>2001</b> , 20, 1327-1329		43
6	Low-Temperature Sintering, Densification, and Properties of Z-type Hexaferrite with Bi2O3 Additives. <i>Journal of the American Ceramic Society</i> , <b>2001</b> , 84, 2889-2894	3.8	32
5	Crystallization and dielectric properties of cordierite gel-derived glasses containing B2O3 and P2O5. <i>Ferroelectrics</i> , <b>2001</b> , 262, 31-36	0.6	5
4	Dielectric behavior and DC resistivity of Ba3Co2(1日)Cu2XFe24O41 (Co2Z)Hexaferrite. <i>Ferroelectrics</i> , <b>2001</b> , 264, 157-162	0.6	2
3	Low dielectric constant borophosphosilicate glass-ceramics: Synthesis and properties. <i>Ferroelectrics</i> , <b>2001</b> , 262, 239-244	0.6	
2	Low-temperature sinterable cordierite glass-ceramics for high-frequency multilayer chip inductors. Journal of Materials Science Letters, <b>2000</b> , 19, 213-215		18
1	Microstructure and Microwave Dielectric Properties of (1 -x)ZnNb2O6-xZnTa2O6 Ceramics. <i>Ceramic Transactions</i> ,109-115	0.1	