

Kerstin LÃ¤nge

List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/7235513/publications.pdf>

Version: 2024-02-01

48
papers

2,577
citations

393982

19
h-index

253896

43
g-index

48
all docs

48
docs citations

48
times ranked

3531
citing authors

#	ARTICLE	IF	CITATIONS
1	Biophotonic sensors with integrated Si ₃ N ₄ -organic hybrid (SiNOH) lasers for point-of-care diagnostics. <i>Light: Science and Applications</i> , 2021, 10, 64.	7.7	27
2	Microfluidic Impedance Biosensor Chips Using Sensing Layers Based on DNA-Based Self-Assembled Monolayers for Label-Free Detection of Proteins. <i>Biosensors</i> , 2021, 11, 80.	2.3	16
3	Microfluidic integration for electrochemical biosensor applications. <i>Current Opinion in Electrochemistry</i> , 2021, 29, 100755.	2.5	34
4	Rapid Prototyping of Moulds for PDMS-based Microfluidic Chips. <i>Current Directions in Biomedical Engineering</i> , 2021, 7, 255-259.	0.2	1
5	Microfluidic impedance biosensor chip with DNA-based self-assembled monolayers for label-free detection of cardiac biomarker troponin I. , 2020, 60, .		0
6	Bulk and Surface Acoustic Wave Sensor Arrays for Multi-Analyte Detection: A Review. <i>Sensors</i> , 2019, 19, 5382.	2.1	72
7	Laser-induced hierarchical carbon patterns on polyimide substrates for flexible urea sensors. <i>Npj Flexible Electronics</i> , 2019, 3, .	5.1	87
8	Flexible Carbon-based Urea Sensor by Laser Induced Carbonisation of Polyimide. , 2018, , .		1
9	Long-term capability of polymer-coated surface transverse wave sensors for distinguishing vapors of similar hydrocarbons. <i>Sensors and Actuators B: Chemical</i> , 2018, 274, 560-564.	4.0	4
10	Polymer Structures on Surface Acoustic Wave Biosensors. <i>Procedia Technology</i> , 2017, 27, 35-36.	1.1	9
11	Surface Modification Procedure for Biosensor Chips Made of Chemically Sensitive Polymers. <i>Procedia Technology</i> , 2017, 27, 165-166.	1.1	0
12	Long-Term Stability of Polymer-Coated Surface Transverse Wave Sensors for the Detection of Organic Solvent Vapors. <i>Sensors</i> , 2017, 17, 2529.	2.1	16
13	Tacky cyclic olefin copolymer: a biocompatible bonding technique for the fabrication of microfluidic channels in COC. <i>Lab on A Chip</i> , 2016, 16, 1561-1564.	3.1	30
14	Localized protein immobilization on microstructured polymeric surfaces for diagnostic applications. <i>Microfluidics and Nanofluidics</i> , 2016, 20, 1.	1.0	3
15	Polysiloxane layers created by sol-gel and photochemistry: ideal surfaces for rapid, low-cost and high-strength bonding of epoxy components to polydimethylsiloxane. <i>Lab on A Chip</i> , 2015, 15, 1772-1782.	3.1	9
16	Surface Acoustic Wave (SAW) Resonators for Monitoring Conditioning Film Formation. <i>Sensors</i> , 2015, 15, 11873-11888.	2.1	22
17	Acoustic Biosensors Coated With Phosphorylcholine Groups for Label-Free Detection of Human C-Reactive Protein in Serum. <i>IEEE Sensors Journal</i> , 2015, 15, 4388-4392.	2.4	13
18	Rapid bonding of polydimethylsiloxane (PDMS) to various stereolithographically (STL) structurable epoxy resins using photochemically cross-linked intermediary siloxane layers. , 2014, , .		0

#	ARTICLE	IF	CITATIONS
19	Surface Acoustic Wave (SAW) Biosensor for Rapid and Label-Free Detection of Penicillin G in Milk. <i>Food Analytical Methods</i> , 2014, 7, 430-437.	1.3	25
20	Rapid bonding of polydimethylsiloxane to stereolithographically manufactured epoxy components using a photogenerated intermediary layer. <i>Lab on A Chip</i> , 2013, 13, 2268.	3.1	15
21	Surface Acoustic Wave (SAW) Biosensors: Coupling of Sensing Layers and Measurement. <i>Methods in Molecular Biology</i> , 2013, 949, 491-505.	0.4	16
22	Influence of Surface Preparation Parameters on the Signal Response of an Acoustic Biosensor for the Detection of a Breast Cancer Marker. <i>IEEE Sensors Journal</i> , 2012, 12, 1647-1648.	2.4	1
23	Revisiting lab-on-a-chip technology for drug discovery. <i>Nature Reviews Drug Discovery</i> , 2012, 11, 620-632.	21.5	422
24	Surface modification of an acoustic biosensor allowing the detection of low concentrations of cancer markers. <i>Analytical Biochemistry</i> , 2012, 420, 188-190.	1.1	16
25	Deposition of ultrathin parylene C films in the range of 18nm to 142nm: Controlling the layer thickness and assessing the closeness of the deposited films. <i>Thin Solid Films</i> , 2012, 520, 4884-4888.	0.8	17
26	Let there be chipâ€™s towards rapid prototyping of microfluidic devices: one-step manufacturing processes. <i>Analytical Methods</i> , 2011, 3, 2681.	1.3	298
27	Biosensors for Diagnostic Applications. <i>Advances in Biochemical Engineering/Biotechnology</i> , 2011, 133, 115-148.	0.6	31
28	Design and integration of a generic disposable array-compatible sensor housing into an integrated disposable indirect microfluidic flow injection analysis system. <i>Biomedical Microdevices</i> , 2011, 13, 909-922.	1.4	18
29	Biosensors with label-free detection designed for diagnostic applications. <i>Analytical and Bioanalytical Chemistry</i> , 2010, 398, 2403-2412.	1.9	118
30	Biosensor packaging â€™s adaptation of the surface modification procedure. <i>Procedia Engineering</i> , 2010, 5, 363-366.	1.2	1
31	Synthesis and application of photo curable perfluoropolyethers as new material for microfluidics. <i>Procedia Engineering</i> , 2010, 5, 866-869.	1.2	3
32	Label-free detection of breast cancer marker HER-2/neu with an acoustic biosensor. <i>Procedia Engineering</i> , 2010, 5, 914-917.	1.2	21
33	Biosensors coated with sulfated polysaccharides for the detection of hepatocyte growth factor/scatter factor in cell culture medium. <i>Biosensors and Bioelectronics</i> , 2010, 26, 1706-1709.	5.3	13
34	Influence of Preparative Carboxylation Steps on the Analyte Response of an Acoustic Biosensor. <i>IEEE Sensors Journal</i> , 2009, 9, 2033-2034.	2.4	9
35	Influence of intermediate hydrogel layer and amount of binding sites on the signal response of surface acoustic wave biosensors. <i>Sensors and Actuators B: Chemical</i> , 2009, 142, 39-43.	4.0	10
36	An indirect microfluidic flow injection analysis (FIA) system allowing diffusion free pumping of liquids by using tetradecane as intermediary liquid. <i>Lab on A Chip</i> , 2009, 9, 354-356.	3.1	188

#	ARTICLE	IF	CITATIONS
37	Surface acoustic wave biosensors: a review. <i>Analytical and Bioanalytical Chemistry</i> , 2008, 391, 1509-1519.	1.9	677
38	Influence of intermediate aminodextran layers on the signal response of surface acoustic wave biosensors. <i>Analytical Biochemistry</i> , 2008, 377, 170-175.	1.1	14
39	Chemical modification of parylene C coatings for SAW biosensors. <i>Sensors and Actuators B: Chemical</i> , 2007, 125, 441-446.	4.0	53
40	Polymer coating behavior of Rayleigh-SAW resonators with gold electrode structure for gas sensor applications. <i>IEEE Transactions on Ultrasonics, Ferroelectrics, and Frequency Control</i> , 2007, 54, 157-166.	1.7	13
41	Integration of a surface acoustic wave biosensor in a microfluidic polymer chip. <i>Biosensors and Bioelectronics</i> , 2006, 22, 227-232.	5.3	73
42	Investigation of initial pellicle formation on modified titanium dioxide (TiO ₂) surfaces by reflectometric interference spectroscopy (RIfS) in a model system. <i>Dental Materials</i> , 2004, 20, 814-822.	1.6	30
43	Improvement of Surface Acoustic Wave Gas and Biosensor Response Characteristics Using a Capacitive Coupling Technique. <i>Analytical Chemistry</i> , 2004, 76, 3837-3840.	3.2	33
44	On-Line Monitoring of Polymer Deposition for Tailoring the Waveguide Characteristics of Love-Wave Biosensors. <i>Langmuir</i> , 2004, 20, 2315-2319.	1.6	21
45	A Surface Acoustic Wave Biosensor Concept with Low Flow Cell Volumes for Label-Free Detection. <i>Analytical Chemistry</i> , 2003, 75, 5561-5566.	3.2	75
46	Characterization of antibodies against benzo[a]pyrene with thermodynamic and kinetic constants. <i>Talanta</i> , 2002, 56, 1153-1161.	2.9	16
47	Flow injection immunotitration: extended working range for inhibition type immunodetection. <i>Analytica Chimica Acta</i> , 1999, 399, 275-286.	2.6	5
48	Surface acoustic wave biosensors for biomolecular interaction analysis. , 0, , .		1