

Yorinobu Takigawa

List of Publications by Citations

Source: <https://exaly.com/author-pdf/7334645/yorinobu-takigawa-publications-by-citations.pdf>
Version: 2024-04-10

This document has been generated based on the publications and citations recorded by exaly.com. For the latest version of this publication list, visit the link given above.
The third column is the impact factor (IF) of the journal, and the fourth column is the number of citations of the article.

172 papers	2,795 citations	24 h-index	48 g-index
176 ext. papers	3,047 ext. citations	2.2 avg, IF	4.87 L-index

#	Paper	IF	Citations
172	Surface grafting of artificial joints with a biocompatible polymer for preventing periprosthetic osteolysis. <i>Nature Materials</i> , 2004 , 3, 829-36	27	467
171	Dislocation creep behavior in Mg ₂ Al ₃ alloys. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2005 , 407, 53-61	5.3	222
170	Effects of Ca and Sr addition on mechanical properties of a cast AZ91 magnesium alloy at room and elevated temperature. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2005 , 403, 276-280	5.3	195
169	Influence of friction stir welding parameters on grain size and formability in 5083 aluminum alloy. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2007 , 456, 344-349	5.3	163
168	Demonstration of an inverse Hall-Petch relationship in electrodeposited nanocrystalline Ni ₂ W alloys through tensile testing. <i>Scripta Materialia</i> , 2006 , 55, 143-146	5.6	117
167	Evaluation of elastic modulus of Li ₂ S ₂ P ₂ S ₅ glassy solid electrolyte by ultrasonic sound velocity measurement and compression test. <i>Journal of the Ceramic Society of Japan</i> , 2013 , 121, 946-949	1	100
166	Effect of Mg content on the minimum grain size of Al ₃ Mg alloys obtained by friction stir processing. <i>Scripta Materialia</i> , 2011 , 64, 355-358	5.6	73
165	Mechanical properties of Mg ₂ Al ₃ Ca alloy processed by hot extrusion. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2007 , 454-455, 384-388	5.3	68
164	Effect of interstitial carbon on the mechanical properties of electrodeposited bulk nanocrystalline Ni. <i>Acta Materialia</i> , 2013 , 61, 3360-3369	8.4	64
163	Effect of orientation on tensile ductility of electrodeposited bulk nanocrystalline Ni ₂ W alloys. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2013 , 578, 318-322	5.3	39
162	Effects of Zn addition and aging treatment on tensile properties of Sn ₃ Ag ₂ Cu alloys. <i>Journal of Alloys and Compounds</i> , 2012 , 527, 226-232	5.7	35
161	Fabrication of bulk nanocrystalline Fe ₂ Ni alloys with high strength and high ductility by an electrodeposition. <i>Materials Letters</i> , 2014 , 116, 71-74	3.3	34
160	Superplastic forging with dynamic recrystallization of Mg ₂ Al ₃ alloys cast by thixo-molding. <i>Scripta Materialia</i> , 2007 , 56, 237-240	5.6	33
159	Enhancement in mechanical properties of bulk nanocrystalline Fe ₂ Ni alloys electrodeposited using propionic acid. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2014 , 607, 505-510	5.3	32
158	Electrodeposition with intermittent addition of trimethylamine borane to produce ductile bulk nanocrystalline Ni ₂ B alloys. <i>Surface and Coatings Technology</i> , 2018 , 337, 411-417	4.4	29
157	Critical Assessments of Tensile Ductility in Superplastic TZP and TiO ₂ -doped TZP. <i>Materials Transactions, JIM</i> , 1998 , 39, 1108-1114		29
156	High-Strengthening of Mg–5.5 mass%Y–4.3 mass%Zn Cast Alloy by Friction Stir Processing. <i>Materials Transactions</i> , 2005 , 46, 3081-3084	1.3	28

155	Enhanced tensile ductility in bulk nanocrystalline nickel electrodeposited by sulfamate bath. <i>Materials Letters</i> , 2011 , 65, 2351-2353	3.3	26
154	High Cycle Fatigue Property and Micro Crack Propagation Behavior in Extruded AZ31 Magnesium Alloys. <i>Materials Transactions</i> , 2006 , 47, 989-994	1.3	26
153	Fabrication of bulk nanocrystalline Al electrodeposited from a dimethylsulfone bath. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2012 , 550, 363-366	5.3	25
152	Effect of additives on tensile properties of bulk nanocrystalline NiW alloys electrodeposited from a sulfamate bath. <i>Materials Letters</i> , 2013 , 99, 65-67	3.3	25
151	Effect of Initial Grain Size on Dynamically Recrystallized Grain Size in AZ31 Magnesium Alloy. <i>Materials Transactions</i> , 2008 , 49, 1979-1982	1.3	25
150	Elastic Constants of AlLi from First Principles. <i>Materials Transactions</i> , 2005 , 46, 1117-1121	1.3	25
149	Strategy for Electrodeposition of Highly Ductile Bulk Nanocrystalline Metals with a Face-Centered Cubic Structure. <i>Materials Transactions</i> , 2014 , 55, 1859-1866	1.3	24
148	Relationship between deformation behavior and microstructural evolution of friction stir processed Zn22wt.% Al alloy. <i>Scripta Materialia</i> , 2007 , 56, 477-480	5.6	24
147	Threshold stress for superplasticity in solid solution magnesium alloys. <i>Philosophical Magazine</i> , 2012 , 92, 787-803	1.6	23
146	Low cycle fatigue behavior of Zn22mass%Al alloy exhibiting high-strain-rate superplasticity at room temperature. <i>Scripta Materialia</i> , 2005 , 52, 231-236	5.6	22
145	Grain boundary bonding state and fracture energy in small amount of oxide-doped fine-grained Al ₂ O ₃ . <i>Journal of Materials Science</i> , 1999 , 34, 1991-1997	4.3	22
144	Accommodation mechanisms for grain boundary sliding as inferred from texture evolution during superplastic deformation. <i>Philosophical Magazine</i> , 2013 , 93, 2913-2931	1.6	21
143	Significance of Si impurities on exceptional room-temperature superplasticity in a high-purity Zn-22%Al alloy. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2015 , 645, 47-56	5.3	20
142	Isotropic superplastic flow in textured magnesium alloy. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2012 , 558, 656-662	5.3	20
141	Grain boundary relaxation in fine-grained magnesium solid solutions. <i>Philosophical Magazine</i> , 2011 , 91, 4158-4171	1.6	20
140	Application of Electroforming Process to Bulk Amorphous Ni-W Alloy. <i>Materials Transactions</i> , 2011 , 52, 37-40	1.3	19
139	Cavitation during grain-boundary-sliding deformation in an AZ61 magnesium alloy. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2008 , 497, 139-146	5.3	19
138	Ni-W Amorphous/Nanocrystalline Duplex Composite Produced by Electrodeposition. <i>Materials Transactions</i> , 2007 , 48, 996-1000	1.3	19

137	Effect of Pre-Introduced Shear Bands Direction on Deformation Behavior in Zr55Al10Ni5Cu30 Bulk Metallic Glass. <i>Materials Transactions</i> , 2009 , 50, 2355-2358	1.3	18
136	Nanoscale amorphous Band-like Structure induced by friction stir processing in Zr55Cu30Al10Ni5 bulk metallic glass. <i>Materials Letters</i> , 2007 , 61, 3771-3773	3.3	18
135	Improvement in tensile ductility of electrodeposited bulk nanocrystalline NiW by sulfamate bath using propionic acid. <i>Microelectronic Engineering</i> , 2012 , 91, 98-101	2.5	15
134	Influence of Gloss Agent Types on Tensile Properties of Bulk Nanocrystalline Ni Electrodeposited from Sulfamate Bath. <i>Hyomen Gijutsu/Journal of the Surface Finishing Society of Japan</i> , 2011 , 62, 686	0.1	15
133	Effect of Small Addition of Zinc on Creep Behavior of Tin. <i>Materials Transactions</i> , 2010 , 51, 1747-1752	1.3	15
132	Novel Electroforming Process for Bulk Nanocrystalline Ni-W Alloys with Minimizing W-Concentration Gradient and Fluctuation. <i>Materials Transactions</i> , 2007 , 48, 1483-1491	1.3	15
131	Influence of Bath Composition on Tensile Ductility in Electrodeposited Bulk Nanocrystalline Nickel. <i>Materials Transactions</i> , 2011 , 52, 142-146	1.3	14
130	Effect of low-temperature annealing on tensile behavior of electrodeposited bulk nanocrystalline NiW alloys. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2018 , 709, 241-246	5.3	14
129	Reduction in sulfur content of electrodeposited bulk nanocrystalline FeNi alloys using manganese chloride. <i>Materials Letters</i> , 2016 , 175, 86-88	3.3	13
128	Effect of Chemical Bonding State on High-temperature Plastic Flow Behavior in Fine-grained, Polycrystalline Cation-doped Al ₂ O ₃ . <i>Materials Transactions</i> , 2002 , 43, 1566-1572	1.3	13
127	Contribution of interstitial solute strengthening in aluminum. <i>Philosophical Magazine Letters</i> , 2014 , 94, 63-71	1	11
126	Pre-electrodeposition process for improving tensile ductility of Al electrodeposited from a dimethylsulfone bath. <i>Materials Letters</i> , 2013 , 109, 229-232	3.3	11
125	Effect of Addition of Small Amount of Zinc on Microstructural Evolution and Thermal Shock Behavior in Low-Ag Sn—Ag—Cu Solder Joints during Thermal Cycling. <i>Materials Transactions</i> , 2013 , 54, 796-805	1.3	11
124	High Cycle Fatigue Property of Extruded Non-Combustible Mg Alloy AMCa602. <i>Materials Transactions</i> , 2008 , 49, 1148-1156	1.3	11
123	Clarification of the Necessary Value of Surface Roughness for Developing Luster on an AZ31 Magnesium Alloy Surface with or without Acid Aqueous Solution Treatment. <i>Materials Transactions</i> , 2008 , 49, 909-912	1.3	11
122	First-Principles Studies on Grain Boundary Energies of [110] Tilt Grain Boundaries in Aluminum. <i>Materials Science Forum</i> , 2007 , 561-565, 1837-1840	0.4	11
121	Optimization of Die Material and Its Surface Coating for Press Forming Magnesium Alloy. <i>Materials Transactions</i> , 2006 , 47, 954-958	1.3	11
120	Effect of Dopant on Phase Stability of Zirconia in Hot Water. <i>Key Engineering Materials</i> , 2006 , 309-311, 1231-1234	0.4	10

119	Formability of Friction Stir Welded and Arc Welded 5083 Aluminum Alloy Sheets. <i>Key Engineering Materials</i> , 2007 , 340-341, 1473-1478	0.4	10
118	Environmentally Friendly Composite Film of Anodizing and Electrodeposition Coating Having a High Corrosion Resistance on Magnesium Alloy AZ91D. <i>Materials Transactions</i> , 2007 , 48, 3118-3125	1.3	10
117	Effect of Titania Doping on Phase Stability of Zirconia Bioceramics in Hot Water. <i>Materials Transactions</i> , 2007 , 48, 332-336	1.3	10
116	Optimization of Environmentally Friendly Anodic Oxide Film for Magnesium Alloys. <i>Materials Transactions</i> , 2006 , 47, 1013-1019	1.3	10
115	Triple-layered, thick glassy grain boundaries in porous cordierite ceramics. <i>Acta Materialia</i> , 2002 , 50, 597-604	8.4	10
114	Thermal embrittlement and microstructure change in electrodeposited Ni. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2019 , 745, 168-175	5.3	9
113	Al-8Mg alloy with high strength and high ductility by addition of a grain boundary strengthening element. <i>Materials Letters</i> , 2019 , 245, 218-221	3.3	9
112	Relationship between grain boundary relaxation strengthening and orientation in electrodeposited bulk nanocrystalline Ni alloys. <i>Materials Letters</i> , 2017 , 205, 211-214	3.3	9
111	Tensile Properties of Bulk Nanocrystalline Ni and Ni-W Fabricated by Sulfamate Bath. <i>Materials Science Forum</i> , 2010 , 654-656, 1114-1117	0.4	9
110	Investigation on Dynamic Friction Properties of Extruded AZ31 Magnesium Alloy Using by Ring Upsetting Method. <i>Materials Transactions</i> , 2010 , 51, 1249-1254	1.3	9
109	Effect of Melt Flow Rate of Polyethylene on Bioactivity and Mechanical Properties of Polyethylene /Titania Composites. <i>Key Engineering Materials</i> , 2003 , 254-256, 569-572	0.4	9
108	Low-cycle fatigue properties of ultrafine-grained zinc22 wt.% aluminum alloy during room-temperature superplastic flow. <i>Scripta Materialia</i> , 2008 , 59, 215-218	5.6	8
107	Optimization of Rolling Conditions in Mg–Al–Ca Alloy Containing Insoluble Second Phase Particles. <i>Materials Transactions</i> , 2008 , 49, 1262-1269	1.3	8
106	Effects of Size and Volume Fraction of Precipitated Crystalline Phase Induced by Friction Stir Processing on Hardness in Zr–Al–Ni–Cu Bulk Metallic Glass. <i>Materials Transactions</i> , 2007 , 48, 2409-2413	1.3	8
105	Microstructural Change by Friction Stir Processing in Zr-Al-Cu-Ni Bulk Metallic Glass. <i>Materials Transactions</i> , 2007 , 48, 1580-1583	1.3	8
104	Microstructural Evolution of Friction Stir Processed Cast Mg-5.9 mass%Y-2.6 mass%Zn Alloy in High Temperature Deformation. <i>Materials Transactions</i> , 2007 , 48, 618-621	1.3	8
103	Two cores in one grain in the microstructure of silicon nitride prepared with aligned whisker seeds. <i>Journal of the European Ceramic Society</i> , 2003 , 23, 555-560	6	8
102	High-Temperature Plastic Flow in Pre-Annealed Zr-Al-Ni-Cu Bulk Metallic Glass in a Supercooled Liquid Region. <i>Materials Transactions</i> , 2005 , 46, 199-202	1.3	8

101	First-principles study of transformation strains and phase stabilities in α and β -Ti-Nb-X alloys. <i>Journal of Alloys and Compounds</i> , 2017 , 716, 37-45	5.7	7
100	Calculation of alloying effect on formation enthalpy of TiCu intermetallics from first-principles calculations for designing TiCu-system metallic glasses. <i>Philosophical Magazine Letters</i> , 2016 , 96, 27-34	1	7
99	Mechanical Behavior of Electrodeposited Bulk Nanocrystalline Fe-Ni Alloys. <i>Materials Research</i> , 2015 , 18, 95-100	1.5	7
98	Optimization of the Mg-Al-Zn-Ca-Bi alloy composition based on the parameter A^* in the constitutive equation for the climb-controlled dislocation creep including the stacking fault energy. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2012 , 551, 19-24	5.3	7
97	Effect of Small Amount of Insoluble Dopant on Tetragonal to Monoclinic Phase Transformation in Tetragonal Zirconia Polycrystal. <i>Materials Transactions</i> , 2009 , 50, 1091-1095	1.3	7
96	Deformation Mechanism of Nanocrystalline Al-Fe Alloys by Analysis from Ab-Initio Calculations. <i>Materials Science Forum</i> , 2006 , 503-504, 209-214	0.4	7
95	Fabrication of the Bulk Amorphous Ni-W Alloy by an Electroforming Process. <i>Materials Science Forum</i> , 2007 , 561-565, 1375-1378	0.4	7
94	Fabrication of Homogeneous Bulk Nanocrystalline Ni-W Alloys by an Electroforming Process. <i>Advanced Materials Research</i> , 2007 , 26-28, 691-694	0.5	7
93	Effect of Microstructural Change on High-Temperature Deformation in Pre-Annealed Zr ₆₅ Al ₁₀ Ni ₁₀ Cu ₁₅ Bulk Metallic Glass. <i>Materials Transactions</i> , 2005 , 46, 2864-2869	1.3	7
92	Experimental Investigation of Cavitation Behavior in AZ61 Magnesium Alloy. <i>Materials Transactions</i> , 2005 , 46, 626-630	1.3	7
91	Effects of Solute Fe, Zn and Mg on Recrystallization in Aluminum. <i>Materials Transactions</i> , 2016 , 57, 329-334	3.4	7
90	Effect of Alloying Element X on Transformation Strains and Phase Stabilities between α' and β ; Ti-Nb-X (X = Al, Sn, Zr, Ta) Ternary Alloys from First-Principles Calculations. <i>Materials Transactions</i> , 2016 , 57, 263-268	1.3	7
89	Reduction of impurity contents in aluminum plates electrodeposited from a dimethylsulfone-aluminum chloride bath. <i>Journal of Alloys and Compounds</i> , 2019 , 783, 919-926	5.7	7
88	Microstructural heterogeneity in the electrodeposited Ni: insights from growth modes. <i>Scientific Reports</i> , 2020 , 10, 5548	4.9	6
87	Prediction and fabrication of Ti-Zr-Ta ternary metallic glasses based on effective atomic radius in Ti solid solution from first-principles calculations. <i>Journal of Non-Crystalline Solids</i> , 2014 , 400, 67-71	3.9	6
86	Fabrication of Electrodeposited Permalloys with High Strength and High Ductility. <i>Materials Transactions</i> , 2018 , 59, 598-601	1.3	6
85	Suppression of the thermal embrittlement induced by sulfur segregation to grain boundary in Ni-based electrodeposits. <i>Materialia</i> , 2019 , 6, 100312	3.2	5
84	Development of Surface Treatment in Industrial Scale for Components with Metallic Luster on AZ31 Sheets. <i>Materials Science Forum</i> , 2009 , 610-613, 999-1002	0.4	5

83	Effect of surface roughness on specular gloss in AZ31 magnesium alloy. <i>Keikinzoku/Journal of Japan Institute of Light Metals</i> , 2010 , 60, 259-263	0.3	5
82	Effect of temperature on the cavity nucleation rate for fine-grained Zn22 wt.% Al alloy. <i>Scripta Materialia</i> , 2008 , 58, 643-646	5.6	5
81	Suppression of Macroscopic Defects through the Control of Friction between Workpiece and Dies in a Forged Magnesium Alloy Part with Ribs. <i>Materials Transactions</i> , 2008 , 49, 898-902	1.3	5
80	Effect of Mn on fracture toughness in Mg8Al1wt.%Zn alloy. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2008 , 479, 117-124	5.3	5
79	Effect of Cation Dopant on Phase Stability of Zirconia Bioceramics in Hot Water. <i>Advances in Science and Technology</i> , 2006 , 49, 97-102	0.1	5
78	Application of High-Strain-Rate Superplastic Zn-Al Alloy to Seismic Dampers and its Optimised Shape Design. <i>Materials Science Forum</i> , 2007 , 551-552, 583-590	0.4	5
77	Addition of an Aminic Antioxidant to a Hindered Ester-Based Heat Resisting Oil to Improve Lubrication for Press Forming of Magnesium Alloy Sheets. <i>Materials Transactions</i> , 2006 , 47, 1782-1787	1.3	5
76	Tribological Properties of Hybrid Process DLC Coating against Magnesium Alloy. <i>Materials Transactions</i> , 2006 , 47, 1008-1012	1.3	5
75	Tensile creep behavior in lutetia-doped silicon nitride ceramics. <i>Journal of Materials Research</i> , 2005 , 20, 2213-2217	2.5	5
74	Mechanical properties and microstructures after abnormal grain growth in electrodeposited NiW alloys. <i>Materialia</i> , 2019 , 8, 100481	3.2	4
73	High Tensile Ductility in Electrodeposited Bulk Nanocrystalline NiW Alloys. <i>Advanced Materials Research</i> , 2014 , 922, 497-502	0.5	4
72	Direct observation of radial distribution change during tensile deformation of metallic glass by high energy X-ray diffraction method. <i>Journal of Alloys and Compounds</i> , 2009 , 483, 589-592	5.7	4
71	Acid aqueous solution treatment method in AZ31 magnesium alloy. <i>Keikinzoku/Journal of Japan Institute of Light Metals</i> , 2010 , 60, 117-123	0.3	4
70	Atomistic Studies of Deformation Mechanism of Nanocrystalline Al-Ti and Al-Fe Alloys from First-Principles. <i>Materials Science Forum</i> , 2007 , 561-565, 977-980	0.4	4
69	Superplastic Joining of TZP Enhanced by Titania-Doping in the Insert Material. <i>Materials Science Forum</i> , 2007 , 551-552, 513-517	0.4	4
68	New and Conventional Simulated Body Fluids. <i>Ceramic Engineering and Science Proceedings</i> , 2011 , 31, 571-576	0.1	4
67	Fabrication of Defect-Free FeMn Alloys by Using Electrodeposition. <i>Materials Transactions</i> , 2018 , 59, 935-938	1.3	4
66	Fabrication of Ti-Alloy Powder/Solid Composite with Uniaxial Anisotropy by Introducing Unidirectional Honeycomb Structure via Electron Beam Powder Bed Fusion. <i>Crystals</i> , 2021 , 11, 1074	2.3	4

65	Direct observation of strain-stored grains in electrodeposited nanocrystalline Ni-W alloys by low-angle annular dark field diffraction contrast imaging. <i>Scripta Materialia</i> , 2019 , 166, 29-33	5.6	3
64	Effect of Tool Materials on Dynamic Friction Characteristics and Microstructural Evolution at Elevated Temperature in Extruded AZ31 Magnesium Alloy. <i>Materials Transactions</i> , 2010 , 51, 477-481	1.3	3
63	Dynamic Recrystallization during Hot Extrusion in AZ31 and AZ80 Alloys. <i>Advanced Materials Research</i> , 2007 , 26-28, 449-452	0.5	3
62	First-Principles Calculations of Grain Boundary-Surface for Various Grain Boundaries with Different Energies in Aluminum. <i>Materials Science Forum</i> , 2007 , 551-552, 331-336	0.4	3
61	Revealing the intrinsic ductility of electrodeposited nanocrystalline metals. <i>Materials Letters</i> , 2019 , 235, 224-227	3.3	3
60	An Electrodeposition Process for Producing Ductile Bulk Nanocrystalline NiBe Alloys in a Wide Current Density Range. <i>Materials Transactions</i> , 2018 , 59, 1354-1358	1.3	3
59	Artificial neural network assisted by first-principles calculations for predicting transformation temperatures in shape memory alloys. <i>International Journal of Modern Physics B</i> , 2019 , 33, 1950055	1.1	2
58	Ductile electrodeposited Al from a dimethylsulfone bath with trace amounts of tin chloride. <i>Materials Letters</i> , 2019 , 244, 192-194	3.3	2
57	The evaluation parameters for glass-forming ability in TiCu system metallic glasses. <i>Materials Letters</i> , 2015 , 139, 73-76	3.3	2
56	Effect of Solute Elements on Grain Refinement during Friction Stir Processing in High-Purity Aluminum. <i>Materials Science Forum</i> , 2016 , 838-839, 116-121	0.4	2
55	Texture Change during Superplastic Deformation in Fine-Grained Magnesium Alloys. <i>Materials Science Forum</i> , 2016 , 838-839, 59-65	0.4	2
54	Dislocation Creep in Al-22.2, 53.6 and 101 at.ppm Fe Solid Solution Alloys. <i>Advanced Materials Research</i> , 2014 , 922, 749-754	0.5	2
53	Development of Highly Efficient Saving Processes of Rare Earth in R-T-B Permanent Magnet. <i>Physics Procedia</i> , 2014 , 54, 168-173		2
52	Relationship between Specular Reflectance in Visible Light Range and Surface Roughness in AZ31 Magnesium Alloy Subjected to Acidic Aqueous Solution Treatment. <i>Nippon Kinzoku Gakkaishi/Journal of the Japan Institute of Metals</i> , 2010 , 74, 788-793	0.4	2
51	Softening by Coarsening of Ni-Al B2 Phase Particles in Fe-Cr-Ni-Al-Zr Alloy. <i>Materials Transactions</i> , 2008 , 49, 489-493	1.3	2
50	Dynamic Recrystallization during Hot Extrusion in Mg-3Al-0.1Y Alloy. <i>Advanced Materials Research</i> , 2007 , 26-28, 433-436	0.5	2
49	Fabrication of Homogeneous Bulk Nanocrystalline Ni-W Alloys by an Electroforming Process. <i>Advanced Materials Research</i> , 691-694	0.5	2
48	Effect of a small amount of Fe-addition on intergranular fracture of Al7.3 mass%Mg alloys. <i>Keikinzoku/Journal of Japan Institute of Light Metals</i> , 2019 , 69, 457-464	0.3	2

47	Improvement of High Temperature Strength by Addition of Vanadium Content of NiCrMo Steel for Brake Discs. <i>ISIJ International</i> , 2017 , 57, 550-557	1.7	1
46	Effect of Small Addition of Si on Superplastic Elongation at Room Temperature in Zn-Al Eutectoid Superplastic Alloy. <i>Advanced Materials Research</i> , 2014 , 922, 328-331	0.5	1
45	Relationship between Strength and Grain Size of Friction Stir Processed and Annealed High Purity Aluminum. <i>Advanced Materials Research</i> , 2014 , 922, 372-375	0.5	1
44	Development of New High-Strength and Heat-Resistant Mg-Zn-Y-X (X=Zr and Ag) Casting Alloys. <i>Materials Science Forum</i> , 2014 , 783-786, 384-389	0.4	1
43	Dynamic Friction Properties and Microstructural Evolution in AZ31 Magnesium Alloy at Elevated Temperature during Ring Compression Test. <i>Materials Transactions</i> , 2011 , 52, 1575-1580	1.3	1
42	LOW CYCLE FATIGUE BEHAVIOR OF Zn-22Al ALLOY IN SUPERPLASTIC REGION AND NON-SUPERPLASTIC REGION. <i>International Journal of Modern Physics B</i> , 2008 , 22, 5477-5482	1.1	1
41	Effect of Manganese Addition on Strength and Fracture Toughness in Mg-6Al-1Zn Alloy. <i>Key Engineering Materials</i> , 2006 , 306-308, 857-862	0.4	1
40	Effect of Second Phase Particles on Phase Stability of Zirconia in Hot Water. <i>Advanced Materials Research</i> , 2007 , 26-28, 781-784	0.5	1
39	Effect of Crystallization on High-Temperature Plastic Flow and Ductility in Pre-Annealed Zr-Al-Ni-Cu Bulk Metallic Glass. <i>Materials Science Forum</i> , 2007 , 558-559, 1449-1452	0.4	1
38	Superplastic Properties and Microstructure of Friction Stir Welded Joints of Zn-22wt.%Al Alloy. <i>Key Engineering Materials</i> , 2007 , 340-341, 1417-1424	0.4	1
37	Mechanical Properties of Twin Roll Cast AZ91 Magnesium Alloy at Room Temperature. <i>Advanced Materials Research</i> , 2007 , 26-28, 145-148	0.5	1
36	Microstructure and Mechanical Properties in Friction Stir Processed Zr-Al-Ni-Cu Bulk Metallic Glass. <i>Materials Science Forum</i> , 2007 , 561-565, 1345-1348	0.4	1
35	High Corrosion and Weather Resistant Anionic Resin Coating for 2014 T6 Aluminum Alloys Which Maintains Mirror Luster. <i>Materials Transactions</i> , 2006 , 47, 2786-2790	1.3	1
34	Reducing sulfur to improve thermal embrittlement in electrodeposited nickel using citric acid. <i>Results in Surfaces and Interfaces</i> , 2020 , 1, 100001	0	1
33	High-Hardening Processing by Equal-Channel Angular Extrusion in Fe-13.5Cr-1.3Mo-0.4C Stainless Steel. <i>Zairyo/Journal of the Society of Materials Science, Japan</i> , 2008 , 57, 105-111	0.1	1
32	Increasing the W Content in Electrodeposited Bulk Nanocrystalline Ni-W Alloys with High Ductility. <i>Hyomen Gijutsu/Journal of the Surface Finishing Society of Japan</i> , 2019 , 70, 50-52	0.1	1
31	Electrodeposition for Bulk Nanocrystalline Ni Alloys and Their Mechanical Properties. <i>Hyomen Gijutsu/Journal of the Surface Finishing Society of Japan</i> , 2019 , 70, 103-108	0.1	1
30	Alloying Effects of Transition Metals on Beta Phase Stability of Ti Alloys from First-Principles Calculations 2016 , 1919-1923		1

29	MIG welding of Mg8%Al1%Zn2%Ca alloys. <i>Keikinzoku/Journal of Japan Institute of Light Metals</i> , 2016 , 66, 252-257	0.3	1
28	Connecting Grain Boundary Stability With Tensile Behavior in Electrodeposited Bulk Nanocrystalline Ni Alloys. <i>Materia Japan</i> , 2018 , 57, 479-486	0.1	1
27	Influence of Filler Rod Composition on the Strength of Tungsten Inert Gas Welded Magnesium Alloy Joint. <i>Advanced Materials Research</i> , 2014 , 922, 663-666	0.5	0
26	New dislocation dissociation accompanied by anti-phase shuffling in the β martensite phase of a Ti alloy. <i>Acta Materialia</i> , 2022 , 227, 117705	8.4	0
25	Fabrication of Bulk Nanocrystalline Ni-W with Plastic Deformability Electrodeposited from a Sulfamate Bath 2013 , 3291-3296		
24	Influence of Impurities on Mechanical Properties of Electrodeposited Bulk Nanocrystalline Al. <i>Advanced Materials Research</i> , 2014 , 922, 574-579	0.5	
23	Design and Fabrication of New Ti-Based Ternary Metallic Glasses Based on Effective Atomic Radius in the Ti Solid Solution Calculated by Ab Initio Calculation. <i>Advanced Materials Research</i> , 2014 , 922, 671-675	0.5	
22	Preparatory Electrodeposition Process for High Purity Bulk Aluminum. <i>Advanced Materials Research</i> , 2014 , 922, 237-241	0.5	
21	Effect of Grain Boundary Segregated Dopant on Phase Stability in Tetragonal Zirconia Polycrystal. <i>Materials Science Forum</i> , 2010 , 654-656, 2208-2211	0.4	
20	Effect of Ca and Sr Content on Elevated Temperatures Mechanical Properties of a Cast AZ91 Magnesium Alloy. <i>Advanced Materials Research</i> , 2007 , 26-28, 141-144	0.5	
19	Industrial Application in 2014 T6 Aluminum Alloys Having High Corrosion and Weather Resistant by Anionic Resin Coating with Mirror Luster. <i>Materials Science Forum</i> , 2007 , 561-565, 127-130	0.4	
18	Stacking Fault Energy of Cu-Ga Alloys from First Principles. <i>Materials Science Forum</i> , 2007 , 561-565, 1915-1918	0.4	
17	Effect of Co-Doping Cation on Phase Stability of Zirconia Bioceramics in Hot Water. <i>Advanced Materials Research</i> , 2007 , 26-28, 773-776	0.5	
16	Effect of Small Amount of Dopant on Phase Stability of Zirconia Bioceramics. <i>Materials Science Forum</i> , 2007 , 561-565, 1561-1564	0.4	
15	Prediction System for Solid Solubility Limits of Ag-, Cu-, Al-, and Mg-Based Alloys Using Artificial Neural Networks and First-Principles Calculations. <i>Materials Transactions</i> , 2020 , 61, 2083-2090	1.3	
14	Preparation of Ultra-High Molecular Weight Polyethylene/Titanium Oxide Composites for Bone Repairing Materials. <i>Zairyo/Journal of the Society of Materials Science, Japan</i> , 2003 , 52, 581-586	0.1	
13	?????????????????????. <i>Hosokawa Powder Technology Foundation ANNUAL REPORT</i> , 2005 , 13, 132-132		0
12	Optimizing on Hardening Behavior in Rapidly Solidified Processed Fe-13.5Cr-1.3Mo-0.4C Stainless Steel. <i>Zairyo/Journal of the Society of Materials Science, Japan</i> , 2008 , 57, 704-711	0.1	

- | | | |
|----|--|-----|
| 11 | Construction of Constitutive Equation for Elevated Temperature Deformation in FeCrSi Fiber-Reinforced Al Alloy Composites. <i>Zairyo/Journal of the Society of Materials Science, Japan</i> , 2018 , 67, 1000-1005 | 0.1 |
| 10 | Effects of Zr-addition on intergranular fracture of Al ₇₀ Mg and Al ₇₀ Mg ₂₀ Cu alloys. <i>Keikinzoku/Journal of Japan Institute of Light Metals</i> , 2019 , 69, 235-241 | 0.3 |
| 9 | Change in Microstructure and Mechanical Properties by Friction Stir Processing in Zr-Cu-Al-Ni Bulk Metallic Glass. <i>Zairyo/Journal of the Society of Materials Science, Japan</i> , 2009 , 58, 215-218 | 0.1 |
| 8 | OS19-1-3 Influence of Gloss Agents on Mechanical properties of Electrodeposited Bulk Nanocrystalline Ni. <i>The Abstracts of ATEM International Conference on Advanced Technology in Experimental Mechanics Asian Conference on Experimental Mechanics</i> , 2011 , 2011.10, _OS19-1-3- | 0 |
| 7 | OS19-1-4 Fabrication of Bulk Nanocrystalline Ni-W with Plastic Deformability by Electrodeposition. <i>The Abstracts of ATEM International Conference on Advanced Technology in Experimental Mechanics Asian Conference on Experimental Mechanics</i> , 2011 , 2011.10, _OS19-1-4- | 0 |
| 6 | OS19-4-4 Mechanical loss at elevated temperatures associated with grain boundary relaxation in fine-grained magnesium solid solutions. <i>The Abstracts of ATEM International Conference on Advanced Technology in Experimental Mechanics Asian Conference on Experimental Mechanics</i> , 2011 , 2011.10, _OS19-4-4- | 0 |
| 5 | Determination of Dynamic Friction Coefficients of Aluminum Alloys at Elevated Temperatures by Using Ring-Compression Tests. <i>Zairyo/Journal of the Society of Materials Science, Japan</i> , 2011 , 60, 838-843 | 0.1 |
| 4 | OS18-1-2 Effect of trace silicon on high temperature ductility in Al-8Mg and Al-8Mg-0.2Zr alloys. <i>The Abstracts of ATEM International Conference on Advanced Technology in Experimental Mechanics Asian Conference on Experimental Mechanics</i> , 2011 , 2011.10, _OS18-1-2- | 0 |
| 3 | Fabrication of bulk nanocrystalline Ni-W with plastic deformability electrodeposited from a sulfamate bath 2013 , 3291-3296 | |
| 2 | Development of Electrodeposition Process Based on Chloride Electrolytes for Bulk Pure Fe with Plastic Deformability. <i>Materials Transactions</i> , 2019 , 60, 130-135 | 1.3 |
| 1 | Fabrication of High Strength and High Ductility Alloys by Electrodeposition. <i>Hyomen Gijutsu/Journal of the Surface Finishing Society of Japan</i> , 2021 , 72, 605-609 | 0.1 |