

# Javier G Gomez

## List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/738736/publications.pdf>

Version: 2024-02-01

34  
papers

2,900  
citations

394421

19  
h-index

395702

33  
g-index

34  
all docs

34  
docs citations

34  
times ranked

1423  
citing authors

#	ARTICLE	IF	CITATIONS
1	The cohesive zone model: advantages, limitations and challenges. <i>Engineering Fracture Mechanics</i> , 2002, 69, 137-163.	4.3	896
2	A fracture criterion for sharp V-notched samples. <i>International Journal of Fracture</i> , 2003, 123, 163-175.	2.2	176
3	Local strain energy to assess the static failure of U-notches in plates under mixed mode loading. <i>International Journal of Fracture</i> , 2007, 145, 29-45.	2.2	176
4	Some advantages derived from the use of the strain energy density over a control volume in fatigue strength assessments of welded joints. <i>International Journal of Fatigue</i> , 2008, 30, 1345-1357.	5.7	174
5	Fracture assessment of U-notches under mixed mode loading: two procedures based on the $\hat{\sigma}$ -equivalent local mode I <sup>TM</sup> concept. <i>International Journal of Fracture</i> , 2007, 148, 415-433.	2.2	147
6	Cracking in PMMA containing U-shaped notches. <i>Fatigue and Fracture of Engineering Materials and Structures</i> , 2000, 23, 795-803.	3.4	142
7	Brittle failures from U- and V-notches in mode I and mixed, I + II, mode: a synthesis based on the strain energy density averaged on finite-size volumes. <i>Fatigue and Fracture of Engineering Materials and Structures</i> , 2009, 32, 671-684.	3.4	133
8	A fracture criterion for blunted V-notched samples. <i>International Journal of Fracture</i> , 2004, 127, 239-264.	2.2	121
9	Failure criteria for linear elastic materials with U-notches. <i>International Journal of Fracture</i> , 2006, 141, 99-113.	2.2	121
10	Fracture of V-notched specimens under mixed mode (I + II) loading in brittle materials. <i>International Journal of Fracture</i> , 2009, 159, 121-135.	2.2	121
11	Fracture of components with V-shaped notches. <i>Engineering Fracture Mechanics</i> , 2003, 70, 1913-1927.	4.3	107
12	Generalizations and specializations of cohesive crack models. <i>Engineering Fracture Mechanics</i> , 2003, 70, 1759-1776.	4.3	106
13	Fracture of U-notched specimens under mixed mode: Experimental results and numerical predictions. <i>Engineering Fracture Mechanics</i> , 2009, 76, 236-249.	4.3	97
14	A generalised notch stress intensity factor for U-notched components loaded under mixed mode. <i>Engineering Fracture Mechanics</i> , 2008, 75, 4819-4833.	4.3	89
15	The cohesive crack concept: application to PMMA at $\hat{\sigma} \sim 60^\circ\text{C}$ . <i>Engineering Fracture Mechanics</i> , 2005, 72, 1268-1285.	4.3	88
16	Fracture loads for ceramic samples with rounded notches. <i>Engineering Fracture Mechanics</i> , 2006, 73, 880-894.	4.3	50
17	Nanoindentation measurements of the mechanical properties of zirconium matrix and hydrides in unirradiated pre-hydrided nuclear fuel cladding. <i>Journal of Nuclear Materials</i> , 2014, 452, 69-76.	2.7	39
18	Revisiting the method to obtain the mechanical properties of hydrided fuel cladding in the hoop direction. <i>Journal of Nuclear Materials</i> , 2012, 429, 276-283.	2.7	29

#	ARTICLE	IF	CITATIONS
19	Determination of the hoop fracture properties of unirradiated hydrogen-charged nuclear fuel cladding from ring compression tests. Journal of Nuclear Materials, 2013, 436, 123-129.	2.7	20
20	Fracture of notched samples in epoxy resin: Experiments and cohesive model. Engineering Fracture Mechanics, 2015, 149, 402-411.	4.3	19
21	Study of the hoop fracture behaviour of nuclear fuel cladding from ring compression tests by means of non-linear optimization techniques. Journal of Nuclear Materials, 2017, 489, 150-157.	2.7	8
22	Obtention of the constitutive equation of hydride blisters in fuel cladding from nanoindentation tests. Journal of Nuclear Materials, 2017, 487, 220-228.	2.7	7
23	Application of the equivalent material concept to the study of the ductile failure due to U-notches. International Journal of Pressure Vessels and Piping, 2019, 172, 65-69.	2.6	7
24	Cohesive modelling of the fracture of a neutron irradiated pressure vessel steel. Nuclear Engineering and Design, 2003, 219, 111-125.	1.7	4
25	A new procedure to calculate the constitutive equation of nuclear fuel cladding from ring compression tests. Progress in Nuclear Energy, 2017, 97, 245-251.	2.9	4
26	Application of the equivalent material concept to fracture of U-notched solids under small scale yielding. Procedia Structural Integrity, 2018, 13, 267-272.	0.8	4
27	On the use of the combined FMC-ASED criterion for fracture prediction of notched specimens with nonlinear behavior. Procedia Structural Integrity, 2020, 28, 84-92.	0.8	4
28	Equivalent local mode I concept applied to fracture of graphite round V-notches under static multiaxial loading. Theoretical and Applied Fracture Mechanics, 2017, 90, 213-217.	4.7	3
29	New iterative method to obtain the softening curve in concrete.. Procedia Structural Integrity, 2016, 2, 2841-2848.	0.8	2
30	Use of iterative algorithms to calculate the softening curve in concrete. Boletín De La Sociedad Española De Cerámica Y Vidrio, 2019, 58, 64-68.	1.9	2
31	An extension of the Equivalent Material Concept applied to fracture of U-notched solids. Procedia Structural Integrity, 2020, 28, 752-763.	0.8	2
32	Effect of Zirconium Hydrides on the mechanical behavior of cladding. Kerntechnik, 2018, 83, 502-506.	0.2	1
33	Efecto de los hidruros en el comportamiento mecánico de vainas de zircaloy de combustible nuclear en dirección anular. Revista De Metalurgia, 2009, 45, 287-294.	0.5	1
34	Experimental Validation of a Non-Linear Buckling Method on a Rear Engine Mount Support Structure. , 2014, , .		0