## John A Van Leeuwen

List of Publications by Year in descending order

Source: https://exaly.com/author-pdf/7743593/publications.pdf

Version: 2024-02-01

66 papers 1,824 citations

236833 25 h-index 289141 40 g-index

67 all docs

67
docs citations

times ranked

67

1984 citing authors

#	Article	IF	CITATIONS
1	Introduction to Urban Stormwater: A Global Perspective. Applied Environmental Science and Engineering for A Sustainable Future, 2019, , 1-28.	0.2	O
2	Coagulation of dissolved organic matter in surface water by novel titanium (III) chloride: Mechanistic surface chemical and spectroscopic characterisation. Separation and Purification Technology, 2019, 213, 213-223.	3.9	52
3	Developing community based models of Corporate Social Responsibility. The Extractive Industries and Society, 2018, 5, 131-143.	0.7	17
4	Impact of zinc on biologically mediated monochloramine decay in waters from a field based pilot scale drinking water distribution system. Chemical Engineering Journal, 2018, 339, 240-248.	6.6	10
5	Modelling of THM formation potential and DOM removal based on drinking water catchment characteristics. Science of the Total Environment, 2018, 635, 761-768.	3.9	10
6	Evaluation and comparison the performance of titanium and zirconium(IV) tetrachloride in textile wastewater treatment. Data in Brief, 2018, 18, 920-927.	0.5	8
7	Study of the impacts of process changes of a pulp and paper mill on aerated stabilization basin (ASB) performance. Chemosphere, 2018, 211, 767-774.	4.2	8
8	Field based pilot-scale drinking water distribution system: Simulation of long hydraulic retention times and microbiological mediated monochloramine decay. MethodsX, 2018, 5, 684-696.	0.7	2
9	Chloramine demand estimation using surrogate chemical and microbiological parameters. Journal of Environmental Sciences, 2017, 57, 1-7.	3.2	11
10	Influence of coagulation mechanisms and floc formation on filterability. Journal of Environmental Sciences, 2017, 57, 338-345.	3.2	34
11	Seasonal variation in the nature of DOM in a river and drinking water reservoir of a closed catchment. Environmental Pollution, 2017, 220, 788-796.	3.7	24
12	Developing a chloramine decay index to understand nitrification: A case study of two chloraminated drinking water distribution systems. Journal of Environmental Sciences, 2017, 57, 170-179.	3.2	16
13	Potential use of zirconium (IV) chloride as coagulant to treat semi-aerobic leachate treatment. International Journal of Environment and Waste Management, 2016, 18, 205.	0.2	5
14	Impact of prechlorination on organophosphorus pesticides during drinking water treatment: Removal and transformation to toxic oxon byproducts. Water Research, 2016, 105, 1-10.	<b>5.</b> 3	43
15	Characterization of dissolved organic matter for prediction of trihalomethane formation potential in surface and sub-surface waters. Journal of Hazardous Materials, 2016, 308, 430-439.	6.5	28
16	Treatability of organic matter derived from surface and subsurface waters of drinking water catchments. Chemosphere, 2016, 144, 1193-1200.	4.2	6
17	Roles of coagulant species and mechanisms on floc characteristics and filterability. Chemosphere, 2016, 150, 211-218.	4.2	28
18	Impact of extracted algogenic organic matter on coagulation performance. Water Science and Technology: Water Supply, 2015, 15, 617-624.	1.0	2

#	Article	IF	CITATIONS
19	UV and UV/H2O2 treatment of diazinon and its influence on disinfection byproduct formation following chlorination. Chemical Engineering Journal, 2015, 274, 39-49.	6.6	34
20	The effect of vegetation and soil texture on the nature of organics in runoff from a catchment supplying water for domestic consumption. Science of the Total Environment, 2015, 529, 72-81.	3.9	13
21	Comparison of the coagulation performance of tetravalent titanium and zirconium salts with alum. Chemical Engineering Journal, 2014, 254, 635-646.	6.6	62
22	Changes in the nature of dissolved organics during pulp and paper mill wastewater treatment: a multivariate statistical study combining data from three analytical techniques. Environmental Science and Pollution Research, 2014, 21, 4265-4275.	2.7	1
23	Removal of As(III) and As(V) by ferric salts coagulation – Implications of particle size and zeta potential of precipitates. Separation and Purification Technology, 2014, 135, 64-71.	3.9	57
24	Changes in the quality of river water before, during and after a major flood event associated with a La NiA±a cycle and treatment for drinking purposes. Journal of Environmental Sciences, 2014, 26, 1985-1993.	3.2	24
25	Modification of jar testing protocol combined with mEnCo model predicted dose to predict dissolved organic matter removal for surface water. Water Science and Technology: Water Supply, 2014, 14, 358-366.	1.0	3
26	Characterizing DOM and removal by enhanced coagulation: A survey with typical Chinese source waters. Separation and Purification Technology, 2013, 110, 188-195.	3.9	49
27	Removal of organic contaminants from river and reservoir waters by three different aluminum-based metal salts: Coagulation adsorption and kinetics studies. Chemical Engineering Journal, 2013, 225, 394-405.	6.6	93
28	Colour formation from pre and post-coagulation treatment of Pinus radiata sulfite pulp mill wastewater using nutrient limited aerated stabilisation basins. Separation and Purification Technology, 2013, 114, 1-10.	3.9	15
29	Variation in character and treatability of organics in river water: An assessment by HPAC and alum coagulation. Separation and Purification Technology, 2013, 120, 162-171.	3.9	14
30	Characterization and predicting DOM treatability by enhanced coagulation. Water Science and Technology: Water Supply, 2013, 13, 147-157.	1.0	6
31	The impact of optimised coagulation on membrane fouling for coagulation/ultrafiltration process. Desalination and Water Treatment, 2013, 51, 2718-2725.	1.0	16
32	Synchronous X-ray and Radio Mode Switches: A Rapid Global Transformation of the Pulsar Magnetosphere. Science, 2013, 339, 436-439.	6.0	116
33	Chemometric approaches to data assessment for a long-term case study of MIEX pretreatment performance. Desalination and Water Treatment, 2013, 51, 3639-3649.	1.0	3
34	Prediction of DOM removal of low specific UV absorbance surface waters using HPSEC combined with peak fitting. Journal of Environmental Sciences, 2012, 24, 1174-1180.	3.2	24
35	Assessment of coagulated and non-coagulated ASB performance used to treat Pinus radiata sulfite pulp and paper mill effluent by resin fractionation and HPSEC techniques. Chemical Engineering Journal, 2012, 213, 109-117.	6.6	11
36	Using reverse phase high performance liquid chromatography as an alternative to resin fractionation to assess the hydrophobicity of natural organic matter. Water Science and Technology, 2012, 66, 2402-2409.	1,2	1

#	Article	IF	Citations
37	Assessment of a new combined fractionation technique for characterization of the natural organic matter in the coagulation process. Desalination and Water Treatment, 2012, 48, 252-260.	1.0	3
38	Changes in character of organics in the receiving environment of effluent from a sulphite pulp mill. Environmental Science and Pollution Research, 2012, 19, 2151-2158.	2.7	6
39	Characterization of organic matter in alum treated drinking water using high performance liquid chromatography and resin fractionation. Chemical Engineering Journal, 2012, 192, 186-191.	6.6	20
40	pH modeling for maximum dissolved organic matter removal by enhanced coagulation. Journal of Environmental Sciences, 2012, 24, 276-283.	3.2	34
41	Investigation of the adsorption characteristics of natural organic matter from typical Chinese surface waters onto alumina using quartz crystal microbalance with dissipation. Journal of Hazardous Materials, 2012, 215-216, 115-121.	6.5	9
42	Changes in the organic character of post-coagulated Pinus radiata sulfite pulp mill wastewater under aerated stabilization basin treatment—A laboratory scale study. Chemical Engineering Journal, 2011, 175, 160-168.	6.6	15
43	Coagulation assessment and optimisation with a photometric dispersion analyser and organic characterisation for natural organic matter removal performance. Chemical Engineering Journal, 2011, 168, 629-634.	6.6	24
44	Orthophosphate removal from domestic wastewater using limestone and granular activated carbon. Desalination, 2011, 271, 265-272.	4.0	82
45	Water quality with storage in permeable pavement basecourse. Water Management, 2011, 164, 361-372.	0.4	30
46	The effects of nutrient limitation (nitrogen and phosphorus) on BOD removal from post-coagulated Pinus radiata sulfite pulp and paper mill wastewater in a baffled aerated stabilisation basin–laboratory pilot scale study. Water Science and Technology, 2011, 63, 491-501.	1.2	5
47	Changes in water quality following gypsum application to catchment soils of the Mount Lofty Ranges, South Australia. Organic Geochemistry, 2010, 41, 116-123.	0.9	9
48	Development and implementation of the software mEnCoÂ $ \odot$ to predict coagulant doses for DOC removal at full-scale WTPs in South Australia. Journal of Water Supply: Research and Technology - AQUA, 2009, 58, 291-298.	0.6	13
49	Depletion of E. coli in permeable pavement mineral aggregate storage and reuse systems. Water Science and Technology, 2009, 60, 3091-3099.	1.2	12
50	Natural organic matter (NOM) removal in a typical North-China water plant by enhanced coagulation: Targets and techniques. Separation and Purification Technology, 2009, 68, 320-327.	3.9	58
51	Optimised coagulation using aluminium sulfate for the removal of dissolved organic carbon. Desalination, 2009, 245, 120-134.	4.0	105
52	The future of water in Australia: The potential effects of climate change and ozone depletion on Australian water quality, quantity and treatability. The Environmentalist, 2008, 28, 158-165.	0.7	30
53	Assessing Natural Organic Matter Treatability Using High Performance Size Exclusion Chromatography. Environmental Science & Eamp; Technology, 2008, 42, 6683-6689.	4.6	158
54	The impact of alum coagulation on the character, biodegradability and disinfection by-product formation potential of reservoir natural organic matter (NOM) fractions. Water Science and Technology, 2008, 58, 1173-1179.	1.2	48

#	Article	IF	CITATIONS
55	Modeling the treatment of drinking water to maximize dissolved organic matter removal and minimize disinfection by-product formation. Desalination, 2005, 176, 81-89.	4.0	56
56	Using Gypsum to Reduce Phosphorus in Runoff from Subcatchments in South Australia. Journal of Environmental Quality, 2005, 34, 2118-2128.	1.0	29
57	Modeling DOC Removal Enhanced Coagulation. Journal - American Water Works Association, 2004, 96, 79-89.	0.2	57
58	Application of pyrolysis–gas chromatography/mass spectrometry for characterisation of dissolved organic matter before and after alum treatment. Journal of Analytical and Applied Pyrolysis, 2003, 67, 247-262.	2.6	16
59	Effect of alum treatment on the trihalomethane formation and bacterial regrowth potential of natural and synthetic waters. Water Research, 2002, 36, 4884-4892.	5.3	29
60	Pyrolysis characterisation of plant, humus and soil extracts from Australian catchments. Journal of Analytical and Applied Pyrolysis, 2002, 65, 269-285.	2.6	26
61	Tracing terrestrial compounds leaching from two reservoir catchments as input to dissolved organic matter. Marine and Freshwater Research, 2001, 52, 223.	0.7	17
62	A bioprocessing mode for simultaneous fungal biomass protein production and wastewater treatment using an external air-lift bioreactor. Journal of Chemical Technology and Biotechnology, 2001, 76, 1041-1048.	1.6	23
63	Harming local species or preventing the transfer of exotics? Possible negative and positive effects of using zinc anodes for corrosion protection of ballast water tanks. Water Research, 2000, 34, 1937-1940.	5.3	19
64	The impact of the character of natural organic matter in conventional treatment with alum. Water Science and Technology, 1999, 40, 97.	1.2	44
65	Investigation of cyanobacteria blooms in paper mill wastewaters and assessment of zinc as a control agent. International Journal of Environmental Science and Technology, 0, , 1.	1.8	1
66	Application of model fitting technique to enhance bacterial regrowth potential (BRP) measurement for drinking water supply monitoring. Journal of Water Supply: Research and Technology - AQUA, 0, , .	0.6	0