

Ruiyuan Tian

List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/7794669/publications.pdf>

Version: 2024-02-01

29
papers

1,374
citations

516215

16
h-index

476904

29
g-index

30
all docs

30
docs citations

30
times ranked

1954
citing authors

#	ARTICLE	IF	CITATIONS
1	Recent Advances in Aqueous Batteries with Nonmetal Cations as Charge Carriers. <i>Advanced Energy and Sustainability Research</i> , 2022, 3, .	2.8	5
2	Cyclic production of biocompatible few-layer graphene ink with in-line shear-mixing for inkjet-printed electrodes and Li-ion energy storage. <i>Npj 2D Materials and Applications</i> , 2022, 6, .	3.9	15
3	Quantifying the Effect of Separator Thickness on Rate Performance in Lithium-Ion Batteries. <i>Journal of the Electrochemical Society</i> , 2022, 169, 030503.	1.3	17
4	Liquid phase exfoliation of nonlayered non-van der Waals iron trifluoride (FeF ₃) into 2D-platelets for high-capacity lithium storing cathodes. <i>FlatChem</i> , 2022, 33, 100360.	2.8	15
5	Liquid Exfoliated SnP ₃ Nanosheets for Very High Areal Capacity Lithium-Ion Batteries. <i>Advanced Energy Materials</i> , 2021, 11, 2002364.	10.2	40
6	2D nanosheets from foolâ€™s gold by LPE: High performance lithium-ion battery anodes made from stone. <i>FlatChem</i> , 2021, 30, 100295.	2.8	6
7	Developing models to fit capacityâ€‘rate data in battery systems. <i>Current Opinion in Electrochemistry</i> , 2020, 21, 1-6.	2.5	10
8	Quantifying the Dependence of Battery Rate Performance on Electrode Thickness. <i>ACS Applied Energy Materials</i> , 2020, 3, 10154-10163.	2.5	16
9	Quantifying the Effect of Electronic Conductivity on the Rate Performance of Nanocomposite Battery Electrodes. <i>ACS Applied Energy Materials</i> , 2020, 3, 2966-2974.	2.5	75
10	Production of Quasi-2D Platelets of Nonlayered Iron Pyrite (FeS ₂) by Liquid-Phase Exfoliation for High Performance Battery Electrodes. <i>ACS Nano</i> , 2020, 14, 13418-13432.	7.3	45
11	Using chronoamperometry to rapidly measure and quantitatively analyse rate-performance in battery electrodes. <i>Journal of Power Sources</i> , 2020, 468, 228220.	4.0	16
12	Effect of the Gate Volume on the Performance of Printed Nanosheet Network-Based Transistors. <i>ACS Applied Electronic Materials</i> , 2020, 2, 2164-2170.	2.0	6
13	The Rate Performance of Two-Dimensional Material-Based Battery Electrodes May Not Be as Good as Commonly Believed. <i>ACS Nano</i> , 2020, 14, 3129-3140.	7.3	58
14	Liquid phase exfoliation of GeS nanosheets in ambient conditions for lithium ion battery applications. <i>2D Materials</i> , 2020, 7, 035015.	2.0	25
15	High Charge and Discharge Rate Limitations in Ordered Macroporous Li-ion Battery Materials. <i>Journal of the Electrochemical Society</i> , 2020, 167, 140532.	1.3	3
16	Quantifying the Tradeâ€‘off between Absolute Capacity and Rate Performance in Battery Electrodes. <i>Advanced Energy Materials</i> , 2019, 9, 1901359.	10.2	43
17	High areal capacity battery electrodes enabled by segregated nanotube networks. <i>Nature Energy</i> , 2019, 4, 560-567.	19.8	281
18	Quantifying the factors limiting rateâ€‘performance in battery electrodes. <i>Nature Communications</i> , 2019, 10, 1933.	5.8	185

#	ARTICLE	IF	CITATIONS
19	Solvent exfoliation stabilizes TiS_2 nanosheets against oxidation, facilitating lithium storage applications. <i>Nanoscale</i> , 2019, 11, 6206-6216.	2.8	44
20	Liquid phase exfoliation of MoO_3 nanosheets for lithium ion battery applications. <i>Nanoscale Advances</i> , 2019, 1, 1560-1570.	2.2	35
21	Enhanced capacity and lower mean charge voltage of Li-rich cathodes for lithium ion batteries resulting from low-temperature electrochemical activation. <i>RSC Advances</i> , 2017, 7, 7116-7121.	1.7	25
22	High-Temperature Treatment of Li-Rich Cathode Materials with Ammonia: Improved Capacity and Mean Voltage Stability during Cycling. <i>Advanced Energy Materials</i> , 2017, 7, 1700708.	10.2	139
23	Drastically Enhanced High-Rate Performance of Carbon-Coated LiFePO_4 Nanorods Using a Green Chemical Vapor Deposition (CVD) Method for Lithium Ion Battery: A Selective Carbon Coating Process. <i>ACS Applied Materials & Interfaces</i> , 2015, 7, 11377-11386.	4.0	65
24	On the drastically improved performance of Fe-doped LiMn_2O_4 nanoparticles prepared by a facile solution-gelation route. <i>Electrochimica Acta</i> , 2015, 180, 138-146.	2.6	58
25	Synthesis and characterization of oriented linked LiFePO_4 nanoparticles with fast electron and ion transport for high-power lithium-ion batteries. <i>Nano Research</i> , 2015, 8, 3803-3814.	5.8	25
26	Very high power and superior rate capability LiFePO_4 nanorods hydrothermally synthesized using tetraglycol as surfactant. <i>RSC Advances</i> , 2015, 5, 1859-1866.	1.7	16
27	Formation, structure and electrochemical performance of nano-sized $\text{Li}_2\text{FeSiO}_4/\text{C}$ synthesized with the co-incorporation of citric acid and glucose followed by a two-step annealing. <i>RSC Advances</i> , 2014, 4, 64702-64710.	1.7	4
28	Structure, Optical, and Catalytic Properties of Novel Hexagonal Metastable h-MoO_3 Nano- and Microrods Synthesized with Modified Liquid-Phase Processes. <i>Chemistry of Materials</i> , 2010, 22, 6202-6208.	3.2	99
29	In-situ electrochemical synthesis of high-performance S/VO_x composite for aqueous zinc ion battery. <i>Journal Physics D: Applied Physics</i> , 0, , .	1.3	2