Vladimir E Ovcharenko

List of Publications by Year in descending order

Source: https://exaly.com/author-pdf/8031470/publications.pdf Version: 2024-02-01



| # | Article | IF | CITATIONS |
|----|--|------|-----------|
| 1 | Microstructure and mechanical properties of Ni3Al fabricated by thermal explosion and hot extrusion. Intermetallics, 2009, 17, 572-577. | 3.9 | 75 |
| 2 | Microstructure and mechanical properties of Ni3Al and Ni3Al–1B alloys fabricated by SHS/HE. Intermetallics, 2011, 19, 137-142. | 3.9 | 52 |
| 3 | Influence of Features of Interphase Boundaries on Mechanical Properties and Fracture Pattern in Metal–Ceramic Composites. Journal of Materials Science and Technology, 2013, 29, 1025-1034. | 10.7 | 40 |
| 4 | A mathematical model of high-temperature synthesis of nickel aluminide Ni3Al by thermal shock of a powder mixture of pure elements. Combustion, Explosion and Shock Waves, 1996, 32, 299-305. | 0.8 | 28 |
| 5 | Development of a formalism of movable cellular automaton method for numerical modeling of fracture of heterogeneous elastic-plastic materials. Frattura Ed Integrita Strutturale, 2013, 7, 26-59. | 0.9 | 28 |
| 6 | Microstructure and kinetics study on tantalum carbide coating produced on gray cast iron in situ. Surface and Coatings Technology, 2016, 286, 347-353. | 4.8 | 27 |
| 7 | Fabrication, microstructure and abrasive wear characteristics of an in situ tantalum carbide ceramic gradient composite. Ceramics International, 2015, 41, 12950-12957. | 4.8 | 24 |
| 8 | Influence of phase interface properties on mechanical characteristics of metal ceramic composites. Physical Mesomechanics, 2014, 17, 282-291. | 1.9 | 22 |
| 9 | Modifying structure and properties of nickel alloys by nanostructured composite powders. Thermophysics and Aeromechanics, 2015, 22, 127-132. | 0.5 | 17 |
| 10 | Microstructural and Mechanical Properties of In Situ WC-Fe/Fe Composites. Journal of Materials Engineering and Performance, 2015, 24, 4561-4568. | 2.5 | 17 |
| 11 | Effect of the microstructure of SHS powders of titanium carbide–nichrome on the properties of detonation coatings. Journal of Surface Investigation, 2016, 10, 1040-1047. | 0.5 | 12 |
| 12 | Effect of nanostructured composite powders on the structure and strength properties of the high-temperature inconel 718 alloy. Physics of Metals and Metallography, 2015, 116, 1279-1284. | 1.0 | 11 |
| 13 | A mathematical model of high-temperature synthesis of the intermetallic compound Ni3Al during ignition. Combustion, Explosion and Shock Waves, 1996, 32, 158-164. | 0.8 | 10 |
| 14 | Surface Modification of TiC–NiCrAl Hard Alloy by Pulsed Electron Beam. IEEE Transactions on Plasma Science, 2009, 37, 1998-2001. | 1.3 | 10 |
| 15 | Plasma Sprayed Metal-Ceramic Coatings and Modification of Their Structure with Pulsed Electron Beam Irradiation. Journal of Thermal Spray Technology, 2011, 20, 927-938. | 3.1 | 10 |
| 16 | Improving Durability of Cermets for Metal Cutting by Generation of Subsurface Multilevel Structures. Applied Mechanics and Materials, 0, 379, 131-138. | 0.2 | 10 |
| 17 | Reaction of carbon filaments coated with titanium carbide and molten aluminum. Metal Science and Heat Treatment, 1980, 22, 809-812. | 0.6 | 9 |
| 18 | Influence of surface nanostructure on the life of cermet in metal cutting. Steel in Translation, 2013, 43, 348-350. | 0.3 | 8 |

| # | Article | IF | CITATIONS |
|----|---|--------------------|--------------|
| 19 | Determination of thermokinetic parameters from the inverse problem of an electrothermal explosion. Combustion, Explosion and Shock Waves, 1992, 28, 258-262. | 0.8 | 7 |
| 20 | Effect of an inert filler on the ignition conditions of a powder mixture of nickel and aluminum. Combustion, Explosion and Shock Waves, 1998, 34, 26-28. | 0.8 | 7 |
| 21 | Effect of aluminum content on thermograms of synthesis of intermetallide Ni3Al by thermal shock. Combustion, Explosion and Shock Waves, 1998, 34, 636-638. | 0.8 | 7 |
| 22 | Thermokinetic characteristics of the final stage of the thermal shock of the 3Ni + Al + TiC powder mixture. Combustion, Explosion and Shock Waves, 2005, 41, 64-70. | 0.8 | 7 |
| 23 | Formation of a multigrain structure and its influence on the strength and plasticity of the Ni3Al intermetallic compound. Physics of the Solid State, 2015, 57, 1293-1299. | 0.6 | 7 |
| 24 | Formation of the granular structure in the intermetallic compound Ni3Al in high-temperature synthesis under compression. Combustion, Explosion and Shock Waves, 2006, 42, 302-308. | 0.8 | 6 |
| 25 | Title is missing!. Combustion, Explosion and Shock Waves, 2002, 38, 430-434. | 0.8 | 5 |
| 26 | Self-Propagating High-Temperature Synthesis of a Ni3Al Intermetallic Compound under Compression. Combustion, Explosion and Shock Waves, 2002, 38, 670-674. | 0.8 | 5 |
| 27 | High-temperature synthesis of intermetallide Ni3Al by thermal shock of a powder mixture of pure elements with inert filler. Combustion, Explosion and Shock Waves, 1999, 35, 407-409. | 0.8 | 4 |
| 28 | Effect of the heating stage on ignition conditions of a nickel-aluminum powder mixture. Combustion, Explosion and Shock Waves, 2000, 36, 571-574. | 0.8 | 4 |
| 29 | Modification of the structure and properties of heat-resistant alloys with the help of nanopowders of refractory compounds. , 2012, , . | | 4 |
| 30 | The influence of high-energy impacts on the microstructure of synthesized metal ceramics. Technical Physics Letters, 2012, 38, 1000-1003. | 0.7 | 4 |
| 31 | Evolution of the structure of plasma metal-ceramic coating under pulsed electron-beam treatment. Inorganic Materials: Applied Research, 2012, 3, 210-215. | 0.5 | 4 |
| 32 | The Structure and Properties of Hard Metals Irradiated by High-Energy Electron Beam. Advanced Materials Research, 2013, 872, 214-218. | 0.3 | 4 |
| 33 | Influence of Structural Phase State of the Surface Layer on Wear Resistance of Cutting Edge of Metal-Ceramic Insert when Metalcutting. Applied Mechanics and Materials, 0, 682, 530-536. | 0.2 | 4 |
| 34 | Effect of TiN nanoparticles on the grain size, wear resistance, and strength of the intermetallic compound Ni3Al. Inorganic Materials, 2016, 52, 729-734. | 0.8 | 4 |
| 35 | Effect of the surface structure of carbon fibers on their strength in the application of a carbide coating in a metal melt. Soviet Powder Metallurgy and Metal Ceramics (English Translation of) Tj ETQq1 1 0.784 | 431 ⊕.n gBT | /Oværlock 10 |
| 36 | Effect of chromium on structure, strength, and plasticity of high-temperature intermetallide Ni3Al. Russian Physics Journal, 1993, 36, 534-539. | 0.4 | 3 |

VLADIMIR E OVCHARENKO

| # | Article | IF | CITATIONS |
|----|--|-----|-----------|
| 37 | High-temperature synthesis of the Ni3Al intermetallic compound under pressure. Russian Journal of Non-Ferrous Metals, 2007, 48, 297-302. | 0.6 | 3 |
| 38 | Study on TaC Reinforced Iron Matrix Surface Gradient Composites Produced <i>In Situ</i> . Materials Science Forum, 0, 848, 38-42. | 0.3 | 3 |
| 39 | Wear resistance of the surface layers of hard alloys with a multilevel structural phase state. Journal of Surface Investigation, 2016, 10, 718-722. | 0.5 | 3 |
| 40 | Reinforcement of nickel with carbide-coated carbon fibers. Soviet Powder Metallurgy and Metal Ceramics (English Translation of Poroshkovaya Metallurgiya), 1979, 18, 713-715. | 0.1 | 2 |
| 41 | Microstructure and Scratch Resistance of TaC Dense Ceramic Layer on an Iron Matrix. Journal of Materials Engineering and Performance, 2016, 25, 2375-2383. | 2.5 | 2 |
| 42 | Modification of a hard alloy cermet structure upon pulsed electron-ion-plasma irradiation. Inorganic Materials: Applied Research, 2016, 7, 786-790. | 0.5 | 2 |
| 43 | Diffusion parameters in liquid phase sintering of the al-cu system. Science of Sintering, 2002, 34, 203-213. | 1.4 | 2 |
| 44 | Nature of the temperature dependence of plasticity in the polycrystalline intermetallic compound Ni3Al. Russian Physics Journal, 1994, 37, 1079-1086. | 0.4 | 1 |
| 45 | Calculation of the temperature field in the surface layer of a cermet with electron-pulsed irradiation. Metal Science and Heat Treatment, 2008, 50, 238-241. | 0.6 | 1 |
| 46 | Influence of the structural-phase state on the strength and plasticity of the pressure-synthesized intermetallic compound Ni3Al. Steel in Translation, 2010, 40, 878-880. | 0.3 | 1 |
| 47 | Bulk Nanostructured Ni ₃ Al Intermetallic and Ni ₃ Al-Base Alloy. Applied Mechanics and Materials, 0, 682, 210-215. | 0.2 | 1 |
| 48 | Bulk nanostructuring intermetallic composite material. , 2014, , . | | 1 |
| 49 | Structural State Scale-Dependent Physical Characteristics and Endurance of Cermet Composite for Cutting Metal. Applied Mechanics and Materials, 0, 682, 405-409. | 0.2 | 1 |
| 50 | Formation of a multimodal grain structure and its influence on the strength and the ductility of the intermetallic compound Ni3Al. Russian Metallurgy (Metally), 2014, 2014, 299-302. | 0.5 | 1 |
| 51 | Nanostructuring and Physical Properties of Metal-Ceramic Composites With a Different Content the Ceramic Components. IOP Conference Series: Materials Science and Engineering, 2016, 125, 012008. | 0.6 | 1 |
| 52 | Modification of subsurface structure in TiC-(Ni-Cr) cermet composite under pulsed electron-beam irradiation of samples in plasmas of light and heavy inert gases. AIP Conference Proceedings, 2016, , . | 0.4 | 1 |
| 53 | A General Process for <i>In Situ</i> Formation of Iron-Matrix Composites Reinforced by Carbide Ceramic. Materials Science Forum, 0, 852, 461-466. | 0.3 | 1 |
| 54 | Computer-aided study of key factors determining high mechanical properties of nanostructured surface layers in metal-ceramic composites. AIP Conference Proceedings, 2017, , . | 0.4 | 1 |

| # | Article | IF | CITATIONS |
|----|--|-----|-----------|
| 55 | Frictional forces and resistance to the beginning of plastic deformation in Cu-Al solid solutions. Soviet Physics Journal (English Translation of Izvestiia Vysshykh Uchebnykh Zavedenii, Fizika), 1969, 12, 620-627. | 0.0 | 0 |
| 56 | Region of the propagation of a flame in a fluidized bed of solid material. Combustion, Explosion and Shock Waves, 1979, 15, 98-100. | 0.8 | 0 |
| 57 | Activated graphitization of carbon fibers in a composite material with a nickel matrix. Soviet Powder Metallurgy and Metal Ceramics (English Translation of Poroshkovaya Metallurgiya), 1980, 19, 260-264. | 0.1 | 0 |
| 58 | Composition and fine structure of an intermetallic prepared by the SHS method. Powder Metallurgy and Metal Ceramics, 1993, 32, 501-504. | 0.8 | 0 |
| 59 | Mathematical simulation and structural macrokinetics of the high-temperature synthesis of intermetallic compounds. Journal of Engineering Physics and Thermophysics, 1993, 65, 991-993. | 0.6 | 0 |
| 60 | Influence of boron on the low-temperature plasticity and fracture mechanism in the high-temperature synthesis of the intermetallic Ni3Al. Russian Physics Journal, 1993, 36, 1135-1140. | 0.4 | 0 |
| 61 | Influence of deviation from stoichiometry on the plasticity and mechanism of fracture of the boron-alloyed intermetallic compound Ni3Al obtained by self-propagating high-temperature synthesis. Russian Physics Journal, 1994, 37, 394-399. | 0.4 | 0 |
| 62 | Distinctive features of the phase composition and structure of the intermetallic compound Ni3Al obtained by self-propagating high-temperature synthesis under pressure. Russian Physics Journal, 1995, 38, 1069-1073. | 0.4 | 0 |
| 63 | High-temperature synthesis of a tungsten-free cermet. Combustion, Explosion and Shock Waves, 1999, 35, 518-522. | 0.8 | 0 |
| 64 | Mathematical Model of Compact Changes in Volume during Liquid-Phase Sintering. I. Journal of Materials Synthesis and Processing, 2001, 9, 25-30. | 0.3 | 0 |
| 65 | Effect of electron pulse irradiation on the microstructure of the surface layer of a cermet. Metal Science and Heat Treatment, 2008, 50, 359-363. | 0.6 | 0 |
| 66 | Structural state scale-dependent physical characteristics and endurance of cermet composite for cutting metal. , 2014, , . | | 0 |
| 67 | Effect of xenon on the structural phase state of the surface layer of cemented carbide under pulsed electron-beam irradiation. AlP Conference Proceedings, 2015, , . | 0.4 | 0 |
| 68 | Grain structure and strength of a plastically deformed Ni3Al intermetallic compound. Doklady Physics, 2015, 60, 440-441. | 0.7 | 0 |
| 69 | Modification of Structure and Strength Properties of Permanent Joints Under Laser Beam Welding with Application of Nanopowder Modifiers. IOP Conference Series: Materials Science and Engineering, 2016, 142, 012092. | 0.6 | 0 |
| 70 | Nanostructured Hardening of Hard Alloys Surface Layers Through Electron Irradiation in Heavy Inert Gas Plasma Conditions. IOP Conference Series: Materials Science and Engineering, 2016, 142, 012093. | 0.6 | 0 |
| 71 | Metal ceramic alloy structure and surface layer modification during electron-ion-plasma irradiation of its surface. AIP Conference Proceedings, 2016, , . | 0.4 | 0 |
| 72 | Comparative analysis of different models of interphase boundaries in metal-ceramic composites. AIP Conference Proceedings, 2016, , . | 0.4 | 0 |

| # | Article | IF | CITATIONS |
|----|--|-----|-----------|
| 73 | Nanophase modification of the superficial layer of cast iron during the interaction of the melt with a carbide-forming metal. AIP Conference Proceedings, 2016, , . | 0.4 | 0 |
| 74 | Effects of Inert Nanoparticles of High-Melting-Point Compositions on Grain Structure and Strength of Ni3Al Intermetallic Compounds. IOP Conference Series: Materials Science and Engineering, 2016, 142, 012083. | 0.6 | 0 |
| 75 | General Process for <i>In Situ</i> Formation of Iron-Matrix Surface Composites Reinforced by Carbide Ceramic. Materials Science Forum, 0, 852, 467-471. | 0.3 | 0 |
| 76 | Grain Size and Strength of the Ni ₃ Al Intermetallic Compound Synthesized under Pressure. Solid State Phenomena, 0, 313, 41-49. | 0.3 | 0 |
| 77 | Investigation of Structural Factors that Increase the Mechanical Properties of Surface Layers Modified by Pulsed Electro-Beam Irradiation. Metal Working and Material Science, 2019, 21, 93-107. | 0.3 | 0 |