

Jun Zhao

List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/8267906/publications.pdf>

Version: 2024-02-01

31
papers

1,290
citations

331259

21
h-index

476904

29
g-index

32
all docs

32
docs citations

32
times ranked

795
citing authors

| # | ARTICLE | IF | CITATIONS |
|----|---|-----|-----------|
| 1 | An investigation on the tribological properties of multilayer graphene and MoS ₂ nanosheets as additives used in hydraulic applications. Tribology International, 2016, 97, 14-20. | 3.0 | 193 |
| 2 | Friction-induced nano-structural evolution of graphene as a lubrication additive. Applied Surface Science, 2018, 434, 21-27. | 3.1 | 175 |
| 3 | Nanolubricant additives: A review. Friction, 2021, 9, 891-917. | 3.4 | 124 |
| 4 | Optimization of groove texture profile to improve hydrodynamic lubrication performance: Theory and experiments. Friction, 2020, 8, 83-94. | 3.4 | 65 |
| 5 | Influence of the micromorphology of reduced graphene oxide sheets on lubrication properties as a lubrication additive. Tribology International, 2018, 119, 614-621. | 3.0 | 60 |
| 6 | Highly Exfoliated Reduced Graphite Oxide Powders as Efficient Lubricant Oil Additives. Advanced Materials Interfaces, 2016, 3, 1600700. | 1.9 | 59 |
| 7 | Synthesis of thermally reduced graphite oxide in sulfuric acid and its application as an efficient lubrication additive. Tribology International, 2017, 116, 303-309. | 3.0 | 58 |
| 8 | Real-Time and Online Lubricating Oil Condition Monitoring Enabled by Triboelectric Nanogenerator. ACS Nano, 2021, 15, 11869-11879. | 7.3 | 56 |
| 9 | In Situ Green Synthesis of the New Sandwichlike Nanostructure of Mn ₃ O ₄ /Graphene as Lubricant Additives. ACS Applied Materials & Interfaces, 2019, 11, 36931-36938. | 4.0 | 55 |
| 10 | Numerical optimization of the groove texture bottom profile for thrust bearings. Tribology International, 2017, 109, 69-77. | 3.0 | 47 |
| 11 | Mild thermal reduction of graphene oxide as a lubrication additive for friction and wear reduction. RSC Advances, 2017, 7, 1766-1770. | 1.7 | 41 |
| 12 | An investigation on the tribological behaviors of steel/copper and steel/steel friction pairs via lubrication with a graphene additive. Friction, 2021, 9, 228-238. | 3.4 | 33 |
| 13 | A novel route to the synthesis of an Fe ₃ O ₄ /h-BN 2D nanocomposite as a lubricant additive. RSC Advances, 2019, 9, 6583-6588. | 1.7 | 31 |
| 14 | Ultrastable Lubricating Properties of Robust Self-Repairing Tribofilms Enabled by in Situ-Assembled Polydopamine Nanoparticles. Langmuir, 2020, 36, 852-861. | 1.6 | 31 |
| 15 | Operando Formation of Van der Waals Heterostructures for Achieving Macroscale Superlubricity on Engineering Rough and Worn Surfaces. Advanced Functional Materials, 2022, 32, . | 7.8 | 31 |
| 16 | Superhigh-exfoliation graphene with a unique two-dimensional (2D) microstructure for lubrication application. Applied Surface Science, 2020, 513, 145608. | 3.1 | 30 |
| 17 | Two-dimensional (2D) graphene nanosheets as advanced lubricant additives: A critical review and prospect. Materials Today Communications, 2021, 29, 102755. | 0.9 | 28 |
| 18 | In situ synthesis of Mn ₃ O ₄ /graphene nanocomposite and its application as a lubrication additive at high temperatures. Applied Surface Science, 2021, 546, 149019. | 3.1 | 27 |

| # | ARTICLE | IF | CITATIONS |
|----|---|-----|-----------|
| 19 | Influence of a carbon-based tribofilm induced by the friction temperature on the tribological properties of impregnated graphite sliding against a cemented carbide. <i>Friction</i> , 2021, 9, 686-696. | 3.4 | 26 |
| 20 | Improvement of the lubrication properties of grease with Mn ₃ O ₄ /graphene (Mn ₃ O ₄ #G) nanocomposite additive. <i>Friction</i> , 2021, 9, 1361-1377. | 3.4 | 23 |
| 21 | Efficient one-pot synthesis of mussel-inspired Cu-doped polydopamine nanoparticles with enhanced lubrication under heavy loads. <i>Chemical Engineering Journal</i> , 2021, 426, 131287. | 6.6 | 23 |
| 22 | Influence of annealing on the tribological properties of Zr-based bulk metallic glass. <i>Journal of Non-Crystalline Solids</i> , 2018, 481, 94-97. | 1.5 | 19 |
| 23 | High-quality ultra-flat reduced graphene oxide nanosheets with super-robust lubrication performances. <i>Chemical Engineering Journal</i> , 2022, 438, 135620. | 6.6 | 19 |
| 24 | Medium ion energy synthesis of hard elastic fullerene-like hydrogenated carbon film with ultra-low friction and wear in humid air. <i>Materials Letters</i> , 2015, 143, 188-190. | 1.3 | 9 |
| 25 | Coupling effect of boundary tribofilm and hydrodynamic film. <i>Cell Reports Physical Science</i> , 2022, 3, 100778. | 2.8 | 6 |
| 26 | The Tribological Performance of Metal-/Resin-Impregnated Graphite under Harsh Condition. <i>Lubricants</i> , 2022, 10, 2. | 1.2 | 6 |
| 27 | Using Green, Economical, Efficient Two-Dimensional (2D) Talc Nanosheets as Lubricant Additives under Harsh Conditions. <i>Nanomaterials</i> , 2022, 12, 1666. | 1.9 | 6 |
| 28 | Synthesis of novel CuO@Graphene nanocomposites for lubrication application via a convenient and economical method. <i>Wear</i> , 2022, 498-499, 204323. | 1.5 | 5 |
| 29 | The tribological behaviors between fullerene-like hydrogenated carbon films produced on Si substrates, steel and Si ₃ N ₄ balls. <i>Tribology International</i> , 2017, 115, 518-524. | 3.0 | 4 |
| 30 | Dry gas seal performance analysis using a hydrodynamic and hydrostatic pressure decoupling method: Part 1. <i>Sealing Technology</i> , 2020, 2020, 4-9. | 0.2 | 0 |
| 31 | Dry gas seal performance analysis using a hydrodynamic and hydrostatic pressure decoupling method: Part 2. <i>Sealing Technology</i> , 2020, 2020, 4-9. | 0.2 | 0 |