David Blaauw

List of Publications by Year in Descending Order

Source: https://exaly.com/author-pdf/834865/david-blaauw-publications-by-year.pdf

Version: 2024-04-10

This document has been generated based on the publications and citations recorded by exaly.com. For the latest version of this publication list, visit the link given above.

The third column is the impact factor (IF) of the journal, and the fourth column is the number of citations of the article.

3,180 29 125 53 h-index g-index citations papers 4,090 139 4.3 5.45 L-index avg, IF ext. citations ext. papers

#	Paper	IF	Citations
125	A Delta Sigma-Modulated Sample and Average Common-Mode Feedback Technique for Capacitively Coupled Amplifiers in a 192-nW Acoustic Analog Front-End. <i>IEEE Journal of Solid-State Circuits</i> , 2022 , 1-1	5.5	1
124	A Light-Tolerant Wireless Neural Recording IC for Motor Prediction With Near-Infrared-Based Power and Data Telemetry. <i>IEEE Journal of Solid-State Circuits</i> , 2022 , 1-1	5.5	2
123	Versa: A 36-Core Systolic Multiprocessor With Dynamically Reconfigurable Interconnect and Memory. <i>IEEE Journal of Solid-State Circuits</i> , 2022 , 1-1	5.5	1
122	A 43 nW, 32 kHz, \pm 4.2 ppm Piecewise Linear Temperature-Compensated Crystal Oscillator With EModulated Load Capacitance. <i>IEEE Journal of Solid-State Circuits</i> , 2022 , 1-1	5.5	
121	Ultra-Low Power 32kHz Crystal Oscillators: Fundamentals and Design Techniques. <i>IEEE Open Journal of the Solid-State Circuits Society</i> , 2021 , 1, 79-93		1
120	RRAM-DNN: An RRAM and Model-Compression Empowered All-Weights-On-Chip DNN Accelerator. <i>IEEE Journal of Solid-State Circuits</i> , 2021 , 56, 1105-1115	5.5	4
119	Bridging the"Last Millimeter" Gap of Brain-Machine Interfaces via Near-Infrared Wireless Power Transfer and Data Communications. <i>ACS Photonics</i> , 2021 , 8, 1430-1438	6.3	6
118	An Ultra-Low-Power Image Signal Processor for Hierarchical Image Recognition With Deep Neural Networks. <i>IEEE Journal of Solid-State Circuits</i> , 2021 , 56, 1071-1081	5.5	2
117	Physical Layer Secret Key Generation Using Joint Interference and Phase Shift Keying Modulation. <i>IEEE Transactions on Microwave Theory and Techniques</i> , 2021 , 69, 2673-2685	4.1	3
116	A Light Tolerant Neural Recording IC for Near-Infrared-Powered Free Floating Motes. 2021 , 2021,		3
115	Millimeter-sized smart sensors reveal that a solar refuge protects tree snail Partula hyalina from extirpation. <i>Communications Biology</i> , 2021 , 4, 744	6.7	O
114	A 2.46M Reads/s Seed-Extension Accelerator for Next-Generation Sequencing Using a String-Independent PE Array. <i>IEEE Journal of Solid-State Circuits</i> , 2021 , 56, 824-833	5.5	
113	A 510-pW 32-kHz Crystal Oscillator With High Energy-to-Noise-Ratio Pulse Injection. <i>IEEE Journal of Solid-State Circuits</i> , 2021 , 1-1	5.5	1
112	An Analog-Assisted Digital LDO With Single Subthreshold Output pMOS Achieving 1.44-fs FOM. <i>IEEE Solid-State Circuits Letters</i> , 2021 , 4, 154-157	2	O
111	Reference Oversampling PLL Achieving 256-dB FoM and 28-dBc Reference Spur. <i>IEEE Journal of Solid-State Circuits</i> , 2021 , 56, 2993-3007	5.5	5
110	A High-Throughput Pruning-Based Pair-Hidden-Markov-Model Hardware Accelerator for Next-Generation DNA Sequencing. <i>IEEE Solid-State Circuits Letters</i> , 2021 , 4, 31-35	2	
109	A 40-nm Ultra-Low Leakage Voltage-Stacked SRAM for Intelligent IoT Sensors. <i>IEEE Solid-State Circuits Letters</i> , 2021 , 4, 14-17	2	4

(2019-2020)

108	A 7.3 M Output Non-Zeros/J, 11.7 M Output Non-Zeros/GB Reconfigurable Sparse Matrix Matrix Multiplication Accelerator. <i>IEEE Journal of Solid-State Circuits</i> , 2020 , 55, 933-944	5.5	7	
107	A 0.190.17mm Wireless Neural Recording IC for Motor Prediction with Near-Infrared-Based Power and Data Telemetry <i>Digest of Technical Papers - IEEE International Solid-State Circuits Conference</i> , 2020 , 2020, 416-418	4	9	
106	Transmuter 2020 ,		4	
105	Millimeter-Scale Node-to-Node Radio Using a Carrier Frequency-Interlocking IF Receiver for a Fully Integrated 4 \$times\$ 4 \$times\$ 4 mm3 Wireless Sensor Node. <i>IEEE Journal of Solid-State Circuits</i> , 2020 , 55, 1128-1138	5.5	6	
104	Sample and Average Common-Mode Feedback in a 101 nW Acoustic Amplifier 2020 ,		2	
103	A low-power band of neuronal spiking activity dominated by local single units improves the performance of brain-machine interfaces. <i>Nature Biomedical Engineering</i> , 2020 , 4, 973-983	19	23	
102	A 0.3-V to 1.8B.3-V Leakage-Biased Synchronous Level Converter for ULP SoCs. <i>IEEE Solid-State Circuits Letters</i> , 2020 , 3, 130-133	2	4	
101	Dual-Junction GaAs Photovoltaics for Low Irradiance Wireless Power Transfer in Submillimeter-Scale Sensor Nodes. <i>IEEE Journal of Photovoltaics</i> , 2020 , 10, 1721-1726	3.7	3	
100	A 67-fsrms Jitter, 🛮 30 dBc/Hz In-Band Phase Noise, 🗷 56-dB FoM Reference Oversampling Digital PLL With Proportional Path Timing Control. <i>IEEE Solid-State Circuits Letters</i> , 2020 , 3, 430-433	2	5	
99	AA-ResNet: Energy Efficient All-Analog ResNet Accelerator 2020 ,		1	
98	Introduction to the Special Issue on the 2020 IEEE International Solid-State Circuits Conference (ISSCC). <i>IEEE Journal of Solid-State Circuits</i> , 2020 , 55, 3127-3130	5.5		
97	A 28-nm Compute SRAM With Bit-Serial Logic/Arithmetic Operations for Programmable In-Memory Vector Computing. <i>IEEE Journal of Solid-State Circuits</i> , 2020 , 55, 76-86	5.5	33	
96	A Self-Tuning IoT Processor Using Leakage-Ratio Measurement for Energy-Optimal Operation. <i>IEEE Journal of Solid-State Circuits</i> , 2020 , 55, 87-97	5.5	16	
95	A Microelectronic Sensor Device Powered by a Small Implantable Biofuel Cell. <i>ChemPhysChem</i> , 2020 , 21, 120-128	3.2	29	
94	2019,		4	
93	Energy-Efficient Motion-Triggered IoT CMOS Image Sensor With Capacitor Array-Assisted Charge-Injection SAR ADC. <i>IEEE Journal of Solid-State Circuits</i> , 2019 , 54, 2921-2931	5.5	14	
92	5.2 Energy-Efficient Low-Noise CMOS Image Sensor with Capacitor Array-Assisted Charge-Injection SAR ADC for Motion-Triggered Low-Power IoT Applications 2019 ,		17	
91	2019,		8	

90	High-Efficiency Photovoltaic Modules on a Chip for Millimeter-Scale Energy Harvesting. <i>Progress in Photovoltaics: Research and Applications</i> , 2019 , 27, 540-546	6.8	10
89	The Internet of Tiny Things: Recent Advances of Millimeter-Scale Computing. <i>IEEE Design and Test</i> , 2019 , 36, 65-72	1.4	7
88	A 1920 \$times\$ 1080 25-Frames/s 2.4-TOPS/W Low-Power 6-D Vision Processor for Unified Optical Flow and Stereo Depth With Semi-Global Matching. <i>IEEE Journal of Solid-State Circuits</i> , 2019 , 54, 1048-7	1058	14
87	Low Complexity, Hardware-Efficient Neighbor-Guided SGM Optical Flow for Low-Power Mobile Vision Applications. <i>IEEE Transactions on Circuits and Systems for Video Technology</i> , 2019 , 29, 2191-2204	1 ^{6.4}	5
86	IoT2 Ithe Internet of Tiny Things: Realizing mm-Scale Sensors through 3D Die Stacking 2019,		5
85	An Acoustic Signal Processing Chip With 142-nW Voice Activity Detection Using Mixer-Based Sequential Frequency Scanning and Neural Network Classification. <i>IEEE Journal of Solid-State Circuits</i> , 2019 , 54, 3005-3016	5.5	19
84	An Efficient Piezoelectric Energy Harvesting Interface Circuit Using a Sense-and-Set Rectifier. <i>IEEE Journal of Solid-State Circuits</i> , 2019 , 54, 3348-3361	5.5	12
83	A Reference Oversampling Digital Phase-Locked Loop with -240 dB FOM and -80 dBc Reference Spur 2019 ,		5
82	A 42 nJ/Conversion On-Demand State-of-Charge Indicator for Miniature IoT Li-Ion Batteries. <i>IEEE Journal of Solid-State Circuits</i> , 2019 , 54, 524-537	5.5	3
81	. IEEE Journal of Solid-State Circuits, 2019 , 54, 231-239	5.5	22
80	. IEEE Journal of Solid-State Circuits, 2018, 53, 1006-1015	5.5	36
79	OuterSPACE: An Outer Product Based Sparse Matrix Multiplication Accelerator 2018,		56
78	. IEEE Journal of Solid-State Circuits, 2018 , 53, 995-1005	5.5	50
77	. IEEE Journal of Solid-State Circuits, 2018 , 53, 261-274	5.5	32
76	GenAx: A Genome Sequencing Accelerator 2018,		24
75	A Noise-Efficient Neural Recording Amplifier Using Discrete-Time Parametric Amplification. <i>IEEE Solid-State Circuits Letters</i> , 2018 , 1, 203-206	2	5
74	A Subthreshold Voltage Reference With Scalable Output Voltage for Low-Power IoT Systems. <i>IEEE Journal of Solid-State Circuits</i> , 2017 , 52, 1443-1449	5.5	94
73	A 23-mW Face Recognition Processor with Mostly-Read 5T Memory in 40-nm CMOS. <i>IEEE Journal of Solid-State Circuits</i> , 2017 , 52, 1628-1642	5.5	21

72	2017,		58	
71	Subcutaneous Photovoltaic Infrared Energy Harvesting for Bio-Implantable Devices. <i>IEEE Transactions on Electron Devices</i> , 2017 , 64, 2432-2437	2.9	46	
70	Circuit and System Designs of Ultra-Low Power Sensor Nodes With Illustration in a Miniaturized GNSS Logger for Position Tracking: Part IAnalog Circuit Techniques. <i>IEEE Transactions on Circuits and Systems I: Regular Papers</i> , 2017 , 64, 2237-2249	3.9	15	
69	A 42nJ/conversion on-demand state-of-charge indicator for miniature IoT Li-ion batteries 2017 ,		1	
68	Infrared Energy Harvesting in Millimeter-Scale GaAs Photovoltaics. <i>IEEE Transactions on Electron Devices</i> , 2017 , 64, 4554-4560	2.9	5	
67	A Fully Integrated Counter Flow Energy Reservoir for Peak Power Delivery in Small Form-Factor Sensor Systems. <i>IEEE Journal of Solid-State Circuits</i> , 2017 , 52, 3155-3167	5.5		
66	A 1.7nW PLL-assisted current injected 32KHz crystal oscillator for IoT 2017 ,		9	
65	Small-area Si Photovoltaics for Low-Flux Infrared Energy Harvesting. <i>IEEE Transactions on Electron Devices</i> , 2017 , 64, 15-20	2.9	14	
64	Hardware Designs for Security in Ultra-Low-Power IoT Systems: An Overview and Survey. <i>IEEE Micro</i> , 2017 , 37, 72-89	1.8	33	
63	A 0.3V VDDmin 4+2T SRAM for searching and in-memory computing using 55nm DDC technology 2017 ,		14	
62	Subthreshold voltage reference with nwell/psub diode leakage compensation for low-power high-temperature systems 2017 ,		6	
61	A 1.02nW PMOS-only, trim-free current reference with 282ppm/fC from 40fC to 120fC and 1.6% within-wafer inaccuracy 2017 ,		7	
60	Battery Voltage Supervisors for Miniature IoT Systems. <i>IEEE Journal of Solid-State Circuits</i> , 2016 , 51, 27	′43 5. 375	5613	
59	MBus: A System Integration Bus for the Modular Microscale Computing Class. <i>IEEE Micro</i> , 2016 , 36, 60-	70 1.8	7	
58	Millimeter-scale computing platform for next generation of Internet of Things 2016,		4	
57	Energy Harvesting for GaAs Photovoltaics Under Low-Flux Indoor Lighting Conditions. <i>IEEE Transactions on Electron Devices</i> , 2016 , 63, 2820-2825	2.9	39	
56	A 5.58 nW Crystal Oscillator Using Pulsed Driver for Real-Time Clocks. <i>IEEE Journal of Solid-State Circuits</i> , 2016 , 51, 509-522	5.5	17	
55	A Low Ripple Switched-Capacitor Voltage Regulator Using Flying Capacitance Dithering. <i>IEEE Journal of Solid-State Circuits</i> , 2016 , 51, 919-929	5.5	19	

54	A Constant Energy-Per-Cycle Ring Oscillator Over a Wide Frequency Range for Wireless Sensor Nodes. <i>IEEE Journal of Solid-State Circuits</i> , 2016 , 51, 697-711	5.5	30
53	Approximate SRAMs With Dynamic Energy-Quality Management. <i>IEEE Transactions on Very Large Scale Integration (VLSI) Systems</i> , 2016 , 24, 2128-2141	2.6	27
52	Low complexity optical flow using neighbor-guided semi-global matching 2016 ,		7
51	A Dual-Stage, Ultra-Low-Power Acoustic Event Detection System 2016 ,		7
50	A >78%-Efficient Light Harvester over 100-to-100klux with Reconfigurable PV-Cell Network and MPPT Circuit. <i>Digest of Technical Papers - IEEE International Solid-State Circuits Conference</i> , 2016 , 2016, 370-371	4	25
49	Using Low Cost Erasure and Error Correction Schemes to Improve Reliability of Commodity DRAM Systems. <i>IEEE Transactions on Computers</i> , 2016 , 65, 3766-3779	2.5	7
48	A Resonant Current-Mode Wireless Power Receiver and Battery Charger With B2 dBm Sensitivity for Implantable Systems. <i>IEEE Journal of Solid-State Circuits</i> , 2016 , 51, 2880-2892	5.5	30
47	AlGaAs Photovoltaics for Indoor Energy Harvesting in mm-Scale Wireless Sensor Nodes. <i>IEEE Transactions on Electron Devices</i> , 2015 , 62, 2170-2175	2.9	56
46	System-On-Mud: Ultra-Low Power Oceanic Sensing Platform Powered by Small-Scale Benthic Microbial Fuel Cells. <i>IEEE Transactions on Circuits and Systems I: Regular Papers</i> , 2015 , 1-10	3.9	15
45	A 5.8 nW CMOS Wake-Up Timer for Ultra-Low-Power Wireless Applications. <i>IEEE Journal of Solid-State Circuits</i> , 2015 , 50, 1754-1763	5.5	32
44	SRAM for Error-Tolerant Applications With Dynamic Energy-Quality Management in 28 nm CMOS. <i>IEEE Journal of Solid-State Circuits</i> , 2015 , 50, 1310-1323	5.5	46
43	MBus: An Ultra-Low Power Interconnect Bus for Next Generation Nanopower Systems 2015 , 2015, 629	-641	7
42	FOCUS: Key building blocks and integration strategy of a miniaturized wireless sensor node 2015 ,		1
41	An Ultra-Low Power Fully Integrated Energy Harvester Based on Self-Oscillating Switched-Capacitor Voltage Doubler. <i>IEEE Journal of Solid-State Circuits</i> , 2014 , 49, 2800-2811	5.5	100
40	A 346 µm 2 VCO-Based, Reference-Free, Self-Timed Sensor Interface for Cubic-Millimeter Sensor Nodes in 28 nm CMOS. <i>IEEE Journal of Solid-State Circuits</i> , 2014 , 49, 2462-2473	5.5	21
39	Dual-slope capacitance to digital converter integrated in an implantable pressure sensing system 2014 ,		8
38	A 23pW, 780ppm/EC resistor-less current reference using subthreshold MOSFETs 2014 ,		16
37	Low-Power High-Throughput LDPC Decoder Using Non-Refresh Embedded DRAM. <i>IEEE Journal of Solid-State Circuits</i> , 2014 , 49, 783-794	5.5	50

(2011-2013)

36	A Modular 1 mm\$^{3}\$ Die-Stacked Sensing Platform With Low Power I\$^{2}\$C Inter-Die Communication and Multi-Modal Energy Harvesting. <i>IEEE Journal of Solid-State Circuits</i> , 2013 , 48, 229-	·24 3 ·5	127
35	Low-Power Circuit Analysis and Design Based on Heterojunction Tunneling Transistors (HETTs). <i>IEEE Transactions on Very Large Scale Integration (VLSI) Systems</i> , 2013 , 21, 1632-1643	2.6	39
34	Achieving Ultralow Standby Power With an Efficient SCCMOS Bias Generator. <i>IEEE Transactions on Circuits and Systems II: Express Briefs</i> , 2013 , 60, 842-846	3.5	2
33	A Statistical Framework for Post-Fabrication Oxide Breakdown Reliability Prediction and Management. <i>IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems</i> , 2013 , 32, 630-643	2.5	2
32	Circuit and System Design Guidelines for Ultra-low Power Sensor Nodes. <i>IPSJ Transactions on System LSI Design Methodology</i> , 2013 , 6, 17-26	0.2	5
31	Swizzle-Switch Networks for Many-Core Systems. <i>IEEE Journal on Emerging and Selected Topics in Circuits and Systems</i> , 2012 , 2, 278-294	5.2	50
30	Circuits for ultra-low power millimeter-scale sensor nodes 2012 ,		1
29	Design Methodology for Voltage-Overscaled Ultra-Low-Power Systems. <i>IEEE Transactions on Circuits and Systems II: Express Briefs</i> , 2012 , 59, 952-956	3.5	18
28	. IEEE Journal of Solid-State Circuits, 2012 , 47, 2534-2545	5.5	199
27	A 5.58nW 32.768kHz DLL-assisted XO for real-time clocks in wireless sensing applications 2012 ,		15
26	2012,		5
25	Demo: Ultra-constrained sensor platform interfacing 2012,		1
24	SLC: Split-control Level Converter for dense and stable wide-range voltage conversion 2012,		24
23	A 1.6-mm2 38-mW 1.5-Gb/s LDPC decoder enabled by refresh-free embedded DRAM 2012 ,		7
22	CAS-FEST 2010: Mitigating Variability in Near-Threshold Computing. IEEE Journal on Emerging and		a
	Selected Topics in Circuits and Systems, 2011 , 1, 42-49	5.2	31
21		5.2	12
	Selected Topics in Circuits and Systems, 2011 , 1, 42-49 Robust Clock Network Design Methodology for Ultra-Low Voltage Operations. <i>IEEE Journal on</i>		

18	A 1.85fW/bit ultra low leakage 10T SRAM with speed compensation scheme 2011,		15
17	A 128kb high density portless SRAM using hierarchical bitlines and thyristor sense amplifiers 2011 ,		2
16	Energy-optimized high performance FFT processor 2011 ,		6
15	Synchronization of ultra-low power wireless sensor nodes 2011,		2
14	Variation-aware static and dynamic writability analysis for voltage-scaled bit-interleaved 8-T SRAMs 2011 ,		11
13	Millimeter-scale nearly perpetual sensor system with stacked battery and solar cells 2010,		115
12	Yield-Driven Near-Threshold SRAM Design. <i>IEEE Transactions on Very Large Scale Integration (VLSI)</i> Systems, 2010 , 18, 1590-1598	2.6	58
11	Victim Alignment in Crosstalk-Aware Timing Analysis. <i>IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems</i> , 2010 , 29, 261-274	2.5	3
10	Near-Threshold Computing: Reclaiming Moore@Law Through Energy Efficient Integrated Circuits. <i>Proceedings of the IEEE</i> , 2010 , 98, 253-266	14.3	490
9	A highly resilient routing algorithm for fault-tolerant NoCs 2009,		111
8	A Low-Voltage Processor for Sensing Applications With Picowatt Standby Mode. <i>IEEE Journal of Solid-State Circuits</i> , 2009 , 44, 1145-1155	5.5	112
7	True Random Number Generator With a Metastability-Based Quality Control. <i>IEEE Journal of Solid-State Circuits</i> , 2008 , 43, 78-85	5.5	119
6	A Variation-Tolerant Sub-200 mV 6-T Subthreshold SRAM. <i>IEEE Journal of Solid-State Circuits</i> , 2008 , 43, 2338-2348	5.5	91
5	STEEL: A technique for stress-enhanced standard cell library design 2008,		4
4	Self-Timed Regenerators for High-Speed and Low-Power On-Chip Global Interconnect. <i>IEEE Transactions on Very Large Scale Integration (VLSI) Systems</i> , 2008 , 16, 673-677	2.6	3
3	A statistical approach for full-chip gate-oxide reliability analysis 2008,		16
2	Standby power reduction techniques for ultra-low power processors 2008,		2
1	Robust ultra-low voltage ROM design 2008 ,		11