

# Igor Krupa

## List of Publications by Year in Descending Order

**Source:** <https://exaly.com/author-pdf/8645255/igor-krupa-publications-by-year.pdf>

**Version:** 2024-04-25

This document has been generated based on the publications and citations recorded by exaly.com. For the latest version of this publication list, visit the link given above.

The third column is the impact factor (IF) of the journal, and the fourth column is the number of citations of the article.

75  
papers

1,897  
citations

27  
h-index

40  
g-index

78  
ext. papers

2,216  
ext. citations

5  
avg. IF

4.93  
L-index

#	Paper	IF	Citations
75	Phase change materials for thermal energy storage applications in greenhouses: A review. <i>Sustainable Energy Technologies and Assessments</i> , <b>2022</b> , 52, 102241	4.7	0
74	Impact of ionic liquids on the processing and photo-actuation behavior of SBR composites containing graphene nanoplatelets. <i>Sensors and Actuators B: Chemical</i> , <b>2021</b> , 329, 129195	8.5	5
73	Facile preparation of N-S co-doped graphene quantum dots (GQDs) from graphite waste for efficient humidity sensing. <i>Sensors and Actuators B: Chemical</i> , <b>2021</b> , 328, 129058	8.5	12
72	Some Theoretical Aspects of Tertiary Treatment of Water/Oil Emulsions by Adsorption and Coalescence Mechanisms: A Review. <i>Water (Switzerland)</i> , <b>2021</b> , 13, 652	3	2
71	Materials and Technologies for the Tertiary Treatment of Produced Water Contaminated by Oil Impurities through Nonfibrous Deep-Bed Media: A Review. <i>Water (Switzerland)</i> , <b>2020</b> , 12, 3419	3	3
70	Alginate-Halloysite Nanocomposite Aerogel: Preparation, Structure, and Oil/Water Separation Applications. <i>Biomolecules</i> , <b>2020</b> , 10,	5.9	7
69	Controllably coated graphene oxide particles with enhanced compatibility with poly(ethylene-co-propylene) thermoplastic elastomer for excellent photo-mechanical actuation capability. <i>Reactive and Functional Polymers</i> , <b>2020</b> , 148, 104487	4.6	6
68	Preparation and Characterization of New Electrically Conductive Composites Based on Expanded Graphite with Potential Use as Remote Environmental Detectors. <i>Processes</i> , <b>2020</b> , 8, 1176	2.9	
67	Separation of Water/Oil Emulsions by an Electrospun Copolyamide Mat Covered with a 2D TiCT MXene. <i>Materials</i> , <b>2020</b> , 13,	3.5	4
66	Thermally Conductive Polyethylene/Expanded Graphite Composites as Heat Transfer Surface: Mechanical, Thermo-Physical and Surface Behavior. <i>Polymers</i> , <b>2020</b> , 12,	4.5	9
65	Electrochemical Investigation of Interfacial Properties of TiCT MXene Modified by Aryldiazonium Betaine Derivatives. <i>Frontiers in Chemistry</i> , <b>2020</b> , 8, 553	5	8
64	Polyzwitterionic Hydrogels in Engines Based on the Antipolyelectrolyte Effect and Driven by the Salinity Gradient. <i>Environmental Science &amp; Technology</i> , <b>2019</b> , 53, 9260-9268	10.3	9
63	Recycled Polyethylene/Paraffin Wax/Expanded Graphite Based Heat Absorbers for Thermal Energy Storage: An Artificial Aging Study. <i>Molecules</i> , <b>2019</b> , 24,	4.8	6
62	Modification of Polyethylene by RF Plasma in Different/Mixture Gases. <i>Coatings</i> , <b>2019</b> , 9, 145	2.9	17
61	Smart Non-Woven Fiber Mats with Light-Induced Sensing Capability. <i>Nanomaterials</i> , <b>2019</b> , 10,	5.4	2
60	Electrically Conductive, Transparent Polymeric Nanocomposites Modified by 2D TiCT (MXene). <i>Polymers</i> , <b>2019</b> , 11,	4.5	16
59	Preparation of Progressive Antibacterial LDPE Surface via Active Biomolecule Deposition Approach. <i>Polymers</i> , <b>2019</b> , 11,	4.5	7

58	Piezoresistive Sensors Based on Electrospun Mats Modified by 2D TiCT MXene. <i>Sensors</i> , <b>2019</b> , 19,	3.8	23
57	Novel Enzyme-Free Multifunctional Bentonite/Polypyrrole/Silver Nanocomposite Sensor for Hydrogen Peroxide Detection over a Wide pH Range. <i>Sensors</i> , <b>2019</b> , 19,	3.8	6
56	Electrically Conductive Electrospun Polymeric Mats for Sensing Dispersed Vegetable Oil Impurities in Wastewater. <i>Processes</i> , <b>2019</b> , 7, 906	2.9	3
55	Electrospun Copolyamide Mats Modified by Functionalized Multiwall Carbon Nanotubes. <i>Polymer Composites</i> , <b>2019</b> , 40, E1451-E1460	3	2
54	Bentonite-decorated calix [4] arene: A new, promising hybrid material for heavy-metal removal. <i>Applied Clay Science</i> , <b>2018</b> , 161, 15-22	5.2	21
53	Effect of corona treatment on adhesion enhancement of LLDPE. <i>Surface and Coatings Technology</i> , <b>2018</b> , 335, 118-125	4.4	29
52	Superhydrophobic Polyester/Cotton Fabrics Modified by Barrier Discharge Plasma and Organosilanes. <i>Polymer-Plastics Technology and Engineering</i> , <b>2018</b> , 57, 440-448		9
51	Piezoresponse, Mechanical, and Electrical Characteristics of Synthetic Spider Silk Nanofibers. <i>Nanomaterials</i> , <b>2018</b> , 8,	5.4	7
50	Foamy phase change materials based on linear low-density polyethylene and paraffin wax blends. <i>Emergent Materials</i> , <b>2018</b> , 1, 47-54	3.5	15
49	Anti-corrosive and oil sensitive coatings based on epoxy/polyaniline/magnetite-clay composites through diazonium interfacial chemistry. <i>Scientific Reports</i> , <b>2018</b> , 8, 13369	4.9	27
48	Emerging clay-aryl-gold nanohybrids for efficient electrocatalytic proton reduction. <i>Energy Conversion and Management</i> , <b>2018</b> , 168, 170-177	10.6	14
47	Photoimmobilization of zwitterionic polymers on surfaces to reduce cell adhesion. <i>Journal of Colloid and Interface Science</i> , <b>2017</b> , 500, 294-303	9.3	9
46	Natural aging of shape stabilized phase change materials based on paraffin wax. <i>Polymer Testing</i> , <b>2017</b> , 63, 567-572	4.5	8
45	2D Ti3C2Tx (MXene)-reinforced polyvinyl alcohol (PVA) nanofibers with enhanced mechanical and electrical properties. <i>PLoS ONE</i> , <b>2017</b> , 12, e0183705	3.7	62
44	Overview: Clay Preparation, Properties, Modification <b>2017</b> , 1-28		11
43	The preparation, properties and applications of electrospun co-polyamide 6,12 membranes modified by cellulose nanocrystals. <i>Materials and Design</i> , <b>2017</b> , 132, 314-323	8.1	28
42	FLEXIBLE OIL SENSORS BASED ON MULTIWALLED CARBON NANOTUBE-BILLED ISOPRENE ELASTOMER COMPOSITES. <i>Rubber Chemistry and Technology</i> , <b>2016</b> , 89, 306-315	1.7	9
41	Thermal characterization of phase change materials based on linear low-density polyethylene, paraffin wax and expanded graphite. <i>Renewable Energy</i> , <b>2016</b> , 88, 372-382	8.1	90

40	Heat transfer performance of paraffin wax based phase change materials applicable in building industry. <i>Applied Thermal Engineering</i> , <b>2016</b> , 107, 1313-1323	5.8	38
39	A polysulfobetaine hydrogel for immobilization of a glucose-binding protein. <i>RSC Advances</i> , <b>2016</b> , 6, 83896-83900	3.7	30
38	The stabilizing effect of expanded graphite on the artificial aging of shape stabilized phase change materials. <i>Polymer Testing</i> , <b>2015</b> , 46, 65-71	4.5	17
37	Positive influence of expanded graphite on the physical behavior of phase change materials based on linear low-density polyethylene and paraffin wax. <i>Thermochimica Acta</i> , <b>2015</b> , 614, 218-225	2.9	28
36	Graphene and graphitic derivative filled polymer composites as potential sensors. <i>Physical Chemistry Chemical Physics</i> , <b>2015</b> , 17, 3954-81	3.6	88
35	A new experimental device and inverse method to characterize thermal properties of composite phase change materials. <i>Composite Structures</i> , <b>2015</b> , 133, 1149-1159	5.3	7
34	Calorimetric and dynamic mechanical behavior of phase change materials based on paraffin wax supported by expanded graphite. <i>Thermochimica Acta</i> , <b>2015</b> , 617, 111-119	2.9	30
33	Unconventional experimental technologies available for phase change materials (PCM) characterization. Part 1. Thermophysical properties. <i>Renewable and Sustainable Energy Reviews</i> , <b>2015</b> , 43, 1399-1414	16.2	65
32	Thermal properties of phase-change materials based on high-density polyethylene filled with micro-encapsulated paraffin wax for thermal energy storage. <i>Energy and Buildings</i> , <b>2015</b> , 88, 144-152	7	60
31	Thermal properties of smart microencapsulated paraffin/plaster composites for the thermal regulation of buildings. <i>Energy and Buildings</i> , <b>2015</b> , 88, 183-192	7	41
30	Effect of expanded graphite on the phase change materials of high density polyethylene/wax blends. <i>Thermochimica Acta</i> , <b>2015</b> , 600, 35-44	2.9	53
29	Unconventional experimental technologies used for phase change materials (PCM) characterization: part 2 [morphological and structural characterization, physico-chemical stability and mechanical properties. <i>Renewable and Sustainable Energy Reviews</i> , <b>2015</b> , 43, 1415-1426	16.2	22
28	Effect of waste wax and chain structure on the mechanical and physical properties of polyethylene. <i>Arabian Journal of Chemistry</i> , <b>2015</b> , 8, 388-399	5.9	33
27	Thermal and mechanical characterization of injection moulded high density polyethylene/paraffin wax blends as phase change materials. <i>Renewable Energy</i> , <b>2014</b> , 68, 140-145	8.1	31
26	Viscoelastic and photo-actuation studies of composites based on polystyrene-grafted carbon nanotubes and styrene-b-isoprene-b-styrene block copolymer. <i>Polymer</i> , <b>2014</b> , 55, 211-218	3.9	34
25	Electrically conductive composites based on an elastomeric matrix filled with expanded graphite as a potential oil sensing material. <i>Smart Materials and Structures</i> , <b>2014</b> , 23, 125020	3.4	15
24	Designing dual phase sensing materials from polyaniline filled styrene-b-isoprene-b-styrene composites. <i>Materials Chemistry and Physics</i> , <b>2014</b> , 147, 1029-1036	4.4	30
23	Phase change materials based on high-density polyethylene filled with microencapsulated paraffin wax. <i>Energy Conversion and Management</i> , <b>2014</b> , 87, 400-409	10.6	68

22	Influence of surface modification of carbon nanotubes on interactions with polystyrene-b-polyisoprene-b-polystyrene matrix and its photo-actuation properties. <i>Polymers for Advanced Technologies</i> , <b>2014</b> , 25, 1293-1300	3.2	13
21	Thermal characterization of polymer matrix composites containing microencapsulated paraffin in solid or liquid state. <i>Energy Conversion and Management</i> , <b>2014</b> , 78, 796-804	10.6	28
20	Thermal conductivity and latent heat thermal energy storage properties of LDPE/wax as a shape-stabilized composite phase change material. <i>Energy Conversion and Management</i> , <b>2014</b> , 77, 586-596	10.6	77
19	The mechanical and adhesive properties of electrically and thermally conductive polymeric composites based on high density polyethylene filled with nickel powder. <i>Materials &amp; Design</i> , <b>2013</b> , 51, 620-628		64
18	Elastomeric photo-actuators and their investigation by confocal laser scanning microscopy. <i>Smart Materials and Structures</i> , <b>2013</b> , 22, 104001	3.4	12
17	Effect of filler size on thermophysical and electrical behavior of nanocomposites based on expanded graphite nanoparticles filled in low-density polyethylene matrix. <i>Polymer Composites</i> , <b>2013</b> , 34, 149-155	3	37
16	Nanocomposite photoactuators based on an ethylene vinyl acetate copolymer filled with carbon nanotubes. <i>Sensors and Actuators B: Chemical</i> , <b>2013</b> , 186, 701-710	8.5	26
15	Photo-actuating materials based on elastomers and modified carbon nanotubes. <i>Journal of Nanophotonics</i> , <b>2012</b> , 6, 063522	1.1	27
14	Electrical and Mechanical Properties of Ethylene Vinyl Acetate Based Composites. <i>Materials Science Forum</i> , <b>2012</b> , 714, 193-199	0.4	6
13	Glucose diffusivity and porosity in silica hydrogel based on organofunctional silanes. <i>European Polymer Journal</i> , <b>2011</b> , 47, 1477-1484	5.2	7
12	Zwitterionic hydrogels crosslinked with novel zwitterionic crosslinkers: Synthesis and characterization. <i>Polymer</i> , <b>2011</b> , 52, 3011-3020	3.9	44
11	Mechanical properties of silica hydrogels prepared and aged at physiological conditions: testing in the compression mode. <i>Journal of Sol-Gel Science and Technology</i> , <b>2010</b> , 53, 107-114	2.3	30
10	Silica hydrogel formation and aging monitored by pyrene-based fluorescence probes. <i>Journal of Sol-Gel Science and Technology</i> , <b>2010</b> , 55, 143-150	2.3	4
9	A comparative study on the electrical and mechanical behaviour of multi-walled carbon nanotube composites prepared by diluting a masterbatch with various types of polypropylenes. <i>Journal of Applied Polymer Science</i> , <b>2009</b> , 113, 2536-2551	2.9	129
8	Study of adhesion and surface properties of low-density poly(ethylene) pre-treated by cold discharge plasma. <i>Polymers for Advanced Technologies</i> , <b>2007</b> , 18, 97-105	3.2	26
7	Conductive polymer-coated textiles: The role of fabric treatment by pyrrole-functionalized triethoxysilane. <i>Synthetic Metals</i> , <b>2007</b> , 157, 914-923	3.6	36
6	Mechanical and electrical properties of composites based on thermoplastic matrices and conductive cellulose fibers. <i>Journal of Applied Polymer Science</i> , <b>2006</b> , 101, 133-142	2.9	25
5	Electro-conductive resins filled with graphite for casting applications. <i>European Polymer Journal</i> , <b>2004</b> , 40, 1417-1422	5.2	46

4	Analysis of correlation between percolation concentration and elongation at break in filled electroconductive epoxy-based adhesives. <i>European Polymer Journal</i> , <b>2003</b> , 39, 585-592	5.2	62
3	PE/wax blends: interesting observations. <i>Macromolecular Symposia</i> , <b>2002</b> , 178, 109-116	0.8	9
2	Thermal lag and its practical consequence in the dynamic mechanical analysis of polymers. <i>Polymer Testing</i> , <b>2000</b> , 19, 755-771	4.5	26
1	An updated review on boron removal from water through adsorption processes. <i>Emergent Materials</i> , 1	3.5	8