

# Liu Ting

## List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/8765961/publications.pdf>

Version: 2024-02-01

16  
papers

2,115  
citations

566801

15  
h-index

940134

16  
g-index

16  
all docs

16  
docs citations

16  
times ranked

2366  
citing authors

| #  | ARTICLE  | IF  | CITATIONS |
|----|--|-----|-----------|
| 1  | Single-atom-layer traps in a solid electrolyte for lithium batteries. Nature Communications, 2020, 11, 1828.   | 5.8 | 35        |
| 2  | Atomically Intimate Contact between Solid Electrolytes and Electrodes for Li Batteries. Matter, 2019, 1, 1001-1016.  | 5.0 | 52        |
| 3  | Nanoarchitected Co <sub>3</sub> O <sub>4</sub> /reduced graphene oxide as anode material for lithium-ion batteries with enhanced cycling stability. Ionics, 2019, 25, 5779-5786.   | 1.2 | 19        |
| 4  | High Capacity and Superior Cyclic Performances of All-Solid-State Lithium Batteries Enabled by a Glass-Ceramics Solo. ACS Applied Materials & Interfaces, 2018, 10, 10029-10035.   | 4.0 | 37        |
| 5  | Enhanced electrochemical performance of bulk type oxide ceramic lithium batteries enabled by interface modification. Journal of Materials Chemistry A, 2018, 6, 4649-4657.   | 5.2 | 98        |
| 6  | High-performance all-solid-state lithium-sulfur batteries with sulfur/carbon nano-hybrids in a composite cathode. Journal of Materials Chemistry A, 2018, 6, 23345-23356.  | 5.2 | 48        |
| 7  | High-Conductivity Argyrodite Li <sub>6</sub> PS <sub>5</sub> Cl Solid Electrolytes Prepared via Optimized Sintering Processes for All-Solid-State Lithium-Sulfur Batteries. ACS Applied Materials & Interfaces, 2018, 10, 42279-42285.   | 4.0 | 170       |
| 8  | Lithium-Salt-Rich PEO/Li <sub>0.3</sub> La <sub>0.557</sub> TiO <sub>3</sub> Interpenetrating Composite Electrolyte with Three-Dimensional Ceramic Nano-Backbone for All-Solid-State Lithium-Ion Batteries. ACS Applied Materials & Interfaces, 2018, 10, 24791-24798.   | 4.0 | 230       |
| 9  | Addressing the Interface Issues in All-Solid-State Bulk-Type Lithium Ion Battery via an All-Composite Approach. ACS Applied Materials & Interfaces, 2017, 9, 9654-9661.  | 4.0 | 139       |
| 10 | Ultrathin N-doped carbon-coated TiO <sub>2</sub> coaxial nanofibers as anodes for lithium ion batteries. Journal of the American Ceramic Society, 2017, 100, 2939-2947.  | 1.9 | 14        |
| 11 | Synergistic Coupling between Li <sub>6.75</sub> La <sub>3</sub> Zr <sub>1.75</sub> Ta <sub>0.25</sub> O <sub>12</sub> and Poly(vinylidene fluoride) Induces High Ionic Conductivity, Mechanical Strength, and Thermal Stability of Solid Composite Electrolytes. Journal of the American Chemical Society, 2017, 139, 13779-13785. | 6.6 | 698       |
| 12 | Garnet-type oxide electrolyte with novel porous-dense bilayer configuration for rechargeable all-solid-state lithium batteries. Ionics, 2017, 23, 2521-2527.   | 1.2 | 50        |
| 13 | High Capacity, Superior Cyclic Performances in All-Solid-State Lithium-Ion Batteries Based on 78Li <sub>2</sub> S-22P <sub>2</sub> S <sub>5</sub> Glass-Ceramic Electrolytes Prepared via Simple Heat Treatment. ACS Applied Materials & Interfaces, 2017, 9, 28542-28548.   | 4.0 | 49        |
| 14 | Chemical compatibility between garnet-like solid state electrolyte Li <sub>6.75</sub> La <sub>3</sub> Zr <sub>1.75</sub> Ta <sub>0.25</sub> O <sub>12</sub> and major commercial lithium battery cathode materials. Journal of Materiomics, 2016, 2, 256-264.  | 2.8 | 96        |
| 15 | Achieving high capacity in bulk-type solid-state lithium ion battery based on Li <sub>6.75</sub> La <sub>3</sub> Zr <sub>1.75</sub> Ta <sub>0.25</sub> O <sub>12</sub> electrolyte: Interfacial resistance. Journal of Power Sources, 2016, 324, 349-357.  | 4.0 | 154       |
| 16 | Oxide Electrolytes for Lithium Batteries. Journal of the American Ceramic Society, 2015, 98, 3603-3623.  | 1.9 | 226       |