

# Oldrich Sevecek

## List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/8828678/publications.pdf>

Version: 2024-02-01

52  
papers

396  
citations

759055

12  
h-index

839398

18  
g-index

53  
all docs

53  
docs citations

53  
times ranked

320  
citing authors

#	ARTICLE	IF	CITATIONS
1	Resolving measurement of large (~ÅGDa) chemical/biomolecule complexes with multimode nanomechanical resonators. <i>Sensors and Actuators B: Chemical</i> , 2022, 353, 131062.	4.0	13
2	Achievable accuracy of resonating nanomechanical systems for mass sensing of larger analytes in GDa range. <i>International Journal of Mechanical Sciences</i> , 2022, 224, 107353.	3.6	8
3	Experimentally Verified Analytical Models of Piezoelectric Cantilevers in Different Design Configurations. <i>Sensors</i> , 2021, 21, 6759.	2.1	4
4	Design of damage tolerant and crack-free layered ceramics with textured microstructure. <i>Journal of the European Ceramic Society</i> , 2020, 40, 427-435.	2.8	23
5	Crack kinking out of interface of two orthotropic materials under combined thermal/mechanical loading. <i>Theoretical and Applied Fracture Mechanics</i> , 2020, 105, 102397.	2.1	3
6	Energy Harvesting Technologies for Structural Health Monitoring of Airplane Components – A Review. <i>Sensors</i> , 2020, 20, 6685.	2.1	45
7	Modeling of electromechanical response and fracture resistance of multilayer piezoelectric energy harvester with residual stresses. <i>Journal of Intelligent Material Systems and Structures</i> , 2020, 31, 2261-2287.	1.4	5
8	Crack Protective Layered Architecture of Lead-Free Piezoelectric Energy Harvester in Bistable Configuration. <i>Sensors</i> , 2020, 20, 5808.	2.1	4
9	Mass Spectrometry of Heavy Analytes and Large Biological Aggregates by Monitoring Changes in the Quality Factor of Nanomechanical Resonators in Air. <i>ACS Sensors</i> , 2020, 5, 2128-2135.	4.0	16
10	Piezoelectric PVDF Elements and Systems for Mechanical Engineering Applications. , 2020, , .		2
11	Modelling of cracking of the ceramic foam specimen with a central notch under the tensile load. <i>Theoretical and Applied Fracture Mechanics</i> , 2019, 100, 242-250.	2.1	7
12	Influence of the cell geometry on the tensile strength of open-cell ceramic foams. <i>Procedia Structural Integrity</i> , 2019, 23, 553-558.	0.3	2
13	Elastic properties of multi-layered ceramic systems for SOCs. <i>International Journal of Applied Ceramic Technology</i> , 2018, 15, 370-379.	1.1	7
14	Electro-mechanical analysis of a multilayer piezoelectric cantilever energy harvester upon harmonic vibrations. <i>MATEC Web of Conferences</i> , 2018, 210, 02053.	0.1	0
15	Optimization of Design Parameters of Fracture Resistant Piezoelectric Vibration Energy Harvester. <i>Key Engineering Materials</i> , 2018, 774, 416-422.	0.4	3
16	Preparation and characterization of novel environmentally friendly Al <sub>2</sub> O <sub>3</sub> /SiO <sub>2</sub> /CaO ceramic foams. <i>Ceramics International</i> , 2018, 44, 19063-19069.	2.3	1
17	Computational Analysis of Crack-Like Defects Influence on the Open Cell Ceramic Foam Tensile Strength. <i>Key Engineering Materials</i> , 2018, 774, 271-276.	0.4	3
18	What is the tensile strength of a ceramic to be used in numerical models for predicting crack initiation?. <i>International Journal of Fracture</i> , 2018, 212, 89-103.	1.1	16

#	ARTICLE	IF	CITATIONS
19	Crack bridging modelling in Bioglass Å® based scaffolds reinforced by poly-vinyl alcohol/microfibrillated cellulose composite coating. <i>Mechanics of Materials</i> , 2017, 110, 16-28.	1.7	5
20	Assessment of crack-related problems in layered ceramics using the finite fracture mechanics and coupled stress-energy criterion. <i>Procedia Structural Integrity</i> , 2016, 2, 2014-2021.	0.3	10
21	Modelling of edge crack formation and propagation in ceramic laminates using the stress- energy coupled criterion. <i>Engineering Fracture Mechanics</i> , 2016, 167, 45-55.	2.0	8
22	Investigation of the bonding strength and bonding mechanisms of SOFCs interconnector- electrode interfaces. <i>Materials Letters</i> , 2016, 162, 250-253.	1.3	16
23	Understanding the edge crack phenomenon in ceramic laminates. <i>Frattura Ed Integrita Strutturale</i> , 2016, , .	0.5	0
24	Application of the coupled stress-energy criterion to predict the fracture behaviour of layered ceramics designed with internal compressive stresses. <i>European Journal of Mechanics, A/Solids</i> , 2015, 54, 94-104.	2.1	24
25	Edge cracking due to a compressive residual stress in ceramic laminates. <i>Comptes Rendus - Mecanique</i> , 2015, 343, 192-198.	2.1	9
26	Design of alumina-zirconia composites with spatially tailored strength and toughness. <i>Journal of the European Ceramic Society</i> , 2015, 35, 631-640.	2.8	24
27	Influence of the T-stress on the Crack Bifurcation Phenomenon in Ceramic Laminates. , 2014, 3, 1062-1067.		3
28	Effect of aging on the onset of cracks due to redistribution of residual stresses in functionally graded environmental barrier coatings of mullite/ZrO <sub>2</sub> . <i>Composites Part B: Engineering</i> , 2014, 61, 199-205.	5.9	14
29	The influence of the first non-singular stress terms on crack initiation direction in an orthotropic bi-material plate. <i>Theoretical and Applied Fracture Mechanics</i> , 2014, 71, 67-75.	2.1	9
30	Prediction of the crack bifurcation in layered ceramics with high residual stresses. <i>Engineering Fracture Mechanics</i> , 2013, 108, 120-138.	2.0	18
31	An energetic criterion for a micro-crack of finite length initiated in orthotropic bi-material notches. <i>Engineering Fracture Mechanics</i> , 2013, 110, 396-409.	2.0	9
32	Crack growth in ceramic laminates with strong interfaces and large compressive residual stresses. <i>Theoretical and Applied Fracture Mechanics</i> , 2012, 61, 40-50.	2.1	14
33	Effect of higher order asymptotic terms on the competition between crack penetration and debond at a bimaterial interface between aligned orthotropic materials. <i>Engineering Fracture Mechanics</i> , 2012, 80, 28-51.	2.0	7
34	Analysis of multiple cracks in thin coating on orthotropic substrate under mechanical and residual stresses. <i>Engineering Fracture Mechanics</i> , 2010, 77, 229-248.	2.0	15
35	Modeling of Cracks Crossing an Interface between Dissimilar Elastic Anisotropic Materials. <i>Materials Science Forum</i> , 2008, 567-568, 17-22.	0.3	0
36	The Analysis of the Stress and Displacement Field near the Surface Crack Tip Terminating Perpendicular to the Interface between Two Orthotropic Materials. <i>Materials Science Forum</i> , 2008, 567-568, 137-140.	0.3	0

#	ARTICLE	IF	CITATIONS
37	Calculation of K-factor and T-stress for cracks in anisotropic bimerials. Engineering Fracture Mechanics, 2008, 75, 3707-3726.	2.0	30
38	Solution Methods for General Stress Concentrators in Anisotropic Heterogeneous Media. Key Engineering Materials, 2007, 348-349, 677-680.	0.4	0
39	Dislocation tri-material solution in the analysis of bridged crack in anisotropic bimerial half-space. International Journal of Fracture, 2007, 147, 199-217.	1.1	3
40	Analysis of Edge Bridged Crack in Bimerial Anisotropic Half-Space. Key Engineering Materials, 2006, 324-325, 1143-1148.	0.4	2
41	Calculation of K-Factor and T-Stress for Crack at Anisotropic Bimerials. , 2006, , 879-880.		6
42	Crack Propagation from Bi-Material Notches – Matched Asymptotic Procedure. Key Engineering Materials, 0, 488-489, 416-419.	0.4	1
43	Modelling of Crack Bifurcation in Laminar Ceramics with Large Compressive Stress. Key Engineering Materials, 0, 488-489, 130-133.	0.4	0
44	On the Direction of a Crack Initiated from an Orthotropic Bi-Material Notch Composed of Materials with Non-Uniform Fracture Mechanics Properties. Key Engineering Materials, 0, 525-526, 545-548.	0.4	0
45	An Effect of the First Non-Singular Term of the Williams Asymptotic Expansion to the Stability of the Bi-Material Orthotropic Notch. Key Engineering Materials, 0, 592-593, 745-748.	0.4	0
46	Crack Deflection from the Interface between Two Orthotropic Materials-Effect of Higher Order Terms in Asymptotic Analysis. Key Engineering Materials, 0, 577-578, 157-160.	0.4	0
47	Criterion for Crack Kinking out of the Interface of Two Orthotropic Layers Subjected to Thermal and Mechanical Loading. Key Engineering Materials, 0, 592-593, 169-172.	0.4	0
48	Computational Modeling of Porous Ceramics with Bioactive Layer. Key Engineering Materials, 0, 592-593, 378-381.	0.4	0
49	Validity of the Finite Fracture Mechanics Based Asymptotic Analysis for Predictions of Crack Deflection in Thin Layers of Ceramic Laminates. Key Engineering Materials, 0, 627, 237-240.	0.4	1
50	Influence of the Ceramic Foam Structure Irregularity on the Tensile Response. Solid State Phenomena, 0, 258, 161-164.	0.3	2
51	Prediction of the Ceramic Foam Structure Failure Using a Detailed Finite Element Model. Key Engineering Materials, 0, 827, 222-227.	0.4	0
52	Analysis of piezoelectric skin on vibrating structure for energy harvesting and structural health monitoring applications. European Physical Journal: Special Topics, 0, , 1.	1.2	1