Sheikh Ali Akbar

List of Publications by Year in descending order

Source: https://exaly.com/author-pdf/8888658/publications.pdf

Version: 2024-02-01

57758 36028 9,859 156 44 97 citations h-index g-index papers 159 159 159 9591 docs citations times ranked citing authors all docs

| # | Article | IF | CITATIONS |
|----|--|-----|-----------|
| 1 | Supramolecularly assembled isonicotinamide/reduced graphene oxide nanocomposite for room-temperature NO2 gas sensor. Environmental Technology and Innovation, 2022, 25, 102066. | 6.1 | 12 |
| 2 | Nano-Heterostructure Metal Oxide Gas Sensors: Opportunities and Challenges. , 2022, , 297-301. | | O |
| 3 | Selectivity mechanisms in resistive-type metal oxide heterostructural gas sensors. Sensors and Actuators B: Chemical, 2022, 355, 131242. | 7.8 | 35 |
| 4 | Zinc Oxideâ€Based Acetone Gas Sensors for Breath Analysis: A Review. Chemistry - an Asian Journal, 2021, 16, 1519-1538. | 3.3 | 55 |
| 5 | New Materials for Extreme Environment Solid-State Electrochemical Sensors. ECS Meeting Abstracts, 2021, MA2021-01, 1512-1512. | 0.0 | 1 |
| 6 | CdO–ZnO nanorices for enhanced and selective formaldehyde gas sensing applications. Environmental Research, 2021, 200, 111377. | 7.5 | 42 |
| 7 | Enhanced NO2 gas sensor device based on supramolecularly assembled polyaniline/silver oxide/graphene oxide composites. Ceramics International, 2021, 47, 25696-25707. | 4.8 | 31 |
| 8 | Nano-Heterostructure Metal Oxide Gas Sensors: Opportunities and Challenges. , 2020, , . | | 0 |
| 9 | Comparison of electrical measurements of nanostructured gas sensors using wire bonding vs. probe station. Measurement: Journal of the International Measurement Confederation, 2020, 153, 107451. | 5.0 | 3 |
| 10 | Visible-light activated room temperature NO2 sensing of SnS2 nanosheets based chemiresistive sensors. Sensors and Actuators B: Chemical, 2020, 305, 127455. | 7.8 | 109 |
| 11 | A new open-access online database for resistive-type gas sensor properties and performance. Sensors and Actuators B: Chemical, 2020, 321, 128591. | 7.8 | 9 |
| 12 | Editors' Choiceâ€"Critical Reviewâ€"A Critical Review of Solid State Gas Sensors. Journal of the Electrochemical Society, 2020, 167, 037570. | 2.9 | 112 |
| 13 | Heterostructural Nano-Scale Conductometric Sensing Devices to Improve Selective Gas Detection. ECS Meeting Abstracts, 2020, MA2020-01, 2036-2036. | 0.0 | 1 |
| 14 | Effect of Heterojunction Interface (SnO2ZnO) on Gas Sensing Properties of Core-Shell Nanostructures. ECS Meeting Abstracts, 2020, MA2020-01, 2052-2052. | 0.0 | 1 |
| 15 | Rate-Limiting Steps Elucidated By Electrochemical Impedance Spectroscopy of a Yttria-Stabilized Zirconia 2-in-1 Temperature and Oxygen Gas Sensor Measured at Extreme Temperatures. ECS Meeting Abstracts, 2020, MA2020-01, 2159-2159. | 0.0 | O |
| 16 | Role of Oxygen Vacancies in Nanostructured Metal-Oxide Gas Sensors: A Review. Sensors and Actuators B: Chemical, 2019, 301, 126845. | 7.8 | 416 |
| 17 | Conduction mechanisms in one dimensional core-shell nanostructures for gas sensing: A review. Sensors and Actuators B: Chemical, 2019, 295, 127-143. | 7.8 | 150 |
| 18 | Editorial: Nano-Hetero-Structures for Chemical Sensing: Opportunities and Challenges. Frontiers in Materials, 2019, 6, . | 2.4 | 1 |

| # | Article | IF | Citations |
|----|---|------|-----------|
| 19 | Synergistic effects in gas sensing semiconducting oxide nano-heterostructures: A review. Sensors and Actuators B: Chemical, 2019, 286, 624-640. | 7.8 | 410 |
| 20 | Modulation of osteoblast behavior on nanopatterned yttria-stabilized zirconia surfaces. Journal of the Mechanical Behavior of Biomedical Materials, 2017, 68, 26-31. | 3.1 | 8 |
| 21 | Spontaneous Rippling and Subsequent Polymer Molding on Yttria-Stabilized Zirconia (110) Surfaces. ACS Nano, 2017, 11, 2257-2265. | 14.6 | 2 |
| 22 | Synthesis of Hierarchical SnO2 Nanowire–TiO2 Nanorod Brushes Anchored to Commercially Available FTO-coated Glass Substrates. Nano-Micro Letters, 2017, 9, 33. | 27.0 | 12 |
| 23 | Measuring optical properties of individual SnO2 nanowires via valence electron energy-loss spectroscopy. Journal of Materials Research, 2017, 32, 2479-2486. | 2.6 | 5 |
| 24 | Step faceting and the self-assembly of nanoislands on miscut YSZ(001) surfaces. Applied Surface Science, 2017, 407, 192-196. | 6.1 | 0 |
| 25 | Conduction mechanisms in SnO2 single-nanowire gas sensors: An impedance spectroscopy study. Sensors and Actuators B: Chemical, 2017, 241, 99-108. | 7.8 | 63 |
| 26 | STEM-Cathodoluminescence of SnO2 nanowires and powders. Sensors and Actuators B: Chemical, 2017, 240, 193-203. | 7.8 | 22 |
| 27 | In-situ fabricated gas sensors based on one dimensional core-shell TiO2-Al2O3 nanostructures. Sensors and Actuators B: Chemical, 2017, 238, 972-984. | 7.8 | 64 |
| 28 | Surface Patterning of Functional Ceramics: A Materials Design. Frontiers in Materials, 2017, 3, . | 2.4 | 0 |
| 29 | Enhanced in vitro angiogenic behaviour of human umbilical vein endothelial cells on thermally oxidized TiO2 nanofibrous surfaces. Scientific Reports, 2016, 6, 21828. | 3.3 | 30 |
| 30 | Review of zirconia-based bioceramic: Surface modification and cellular response. Ceramics International, 2016, 42, 12543-12555. | 4.8 | 129 |
| 31 | Osteoblast and stem cell response to nanoscale topographies: a review. Science and Technology of Advanced Materials, 2016, 17, 698-714. | 6.1 | 17 |
| 32 | Detection of Formaldehyde in Mixed VOCs Gases Using Sensor Array With Neural Networks. IEEE Sensors Journal, 2016, 16, 6081-6086. | 4.7 | 35 |
| 33 | Human fetal osteoblast cell response to self-assembled nanostructures on YSZ-(110) single crystal substrates. Materials and Design, 2016, 94, 274-279. | 7.0 | 8 |
| 34 | Reduced graphene oxide (rGO) decorated TiO2 microspheres for selective room-temperature gas sensors. Sensors and Actuators B: Chemical, 2016, 230, 330-336. | 7.8 | 161 |
| 35 | Correlative STEM-Cathodoluminescence and Low-Loss EELS of Semiconducting Oxide Nano-Heterostructures for Resistive Gas-Sensing Applications. Microscopy and Microanalysis, 2015, 21, 1255-1256. | 0.4 | 1 |
| 36 | Growth and characterization of the oxide scales and core/shell nanowires on Ti-6Al-4V particles during thermal oxidation. Ceramics International, 2015, 41, 4401-4409. | 4.8 | 20 |

| # | Article | IF | CITATIONS |
|----|--|--------------|-----------|
| 37 | Tailoring ZnO nanostructures by spray pyrolysis and thermal annealing. Ceramics International, 2015, 41, 5205-5211. | 4.8 | 32 |
| 38 | Gas sensing properties of zinc stannate (Zn2SnO4) nanowires prepared by carbon assisted thermal evaporation process. Journal of Alloys and Compounds, 2015, 618, 455-462. | 5 . 5 | 75 |
| 39 | Proliferation and stemness preservation of human adipose-derived stem cells by surface-modified in situ TiO2 nanofibrous surfaces. International Journal of Nanomedicine, 2014, 9, 5389. | 6.7 | 13 |
| 40 | Enhanced Ethanol Gas Sensing Properties of SnO2-Core/ZnO-Shell Nanostructures. Sensors, 2014, 14, 14586-14600. | 3.8 | 73 |
| 41 | A Selective Ultrahigh Responding High Temperature Ethanol Sensor Using TiO2 Nanoparticles. Sensors, 2014, 14, 13613-13627. | 3.8 | 36 |
| 42 | High-Temperature Ceramic Electrochemical Sensors. , 2014, , 973-981. | | 1 |
| 43 | Catalyst free single-step fabrication of SnO2/ZnO core–shell nanostructures. Ceramics International, 2014, 40, 7601-7605. | 4.8 | 12 |
| 44 | Potentiometric carbon dioxide sensor based on thin Li3PO4 electrolyte and Li2CO3 sensing electrode. lonics, 2014, 20, 563-569. | 2.4 | 20 |
| 45 | In vitro chondrocyte interactions with TiO2 nanofibers grown on Ti–6Al–4V substrate by oxidation. Ceramics International, 2014, 40, 8301-8304. | 4.8 | 11 |
| 46 | Osteogenic potential of in situ TiO 2 nanowire surfaces formed by thermal oxidation of titanium alloy substrate. Applied Surface Science, 2014, 320, 161-170. | 6.1 | 23 |
| 47 | Nanoscale metal oxide-based heterojunctions for gas sensing: A review. Sensors and Actuators B: Chemical, 2014, 204, 250-272. | 7.8 | 1,465 |
| 48 | Co-synthesis of ZnO/SnO2 mixed nanowires via a single-step carbothermal reduction method. Ceramics International, 2014, 40, 5039-5042. | 4.8 | 14 |
| 49 | Synthesis of bioactive titania nanofibrous structures via oxidation. Materials Research Innovations, 2014, 18, S6-220-S6-223. | 2.3 | 1 |
| 50 | <i>A Special Issue on</i> Energy and Environment: Role of Advanced Materials. Journal of Nanoengineering and Nanomanufacturing, 2014, 4, 77-79. | 0.3 | 0 |
| 51 | Enhanced room temperature sensing of Co3O4-intercalated reduced graphene oxide based gas sensors. Sensors and Actuators B: Chemical, 2013, 188, 902-908. | 7.8 | 186 |
| 52 | Epitaxial pore-free gadolinia-doped ceria thin films on yttria-stabilized zirconia by RF magnetron sputtering. Ceramics International, 2013, 39, 9749-9752. | 4.8 | 7 |
| 53 | Thermally grown TiO2 nanowires to improve cell growth and proliferation on titanium based materials. Ceramics International, 2013, 39, 5949-5954. | 4.8 | 32 |
| 54 | Stress enhanced TiO 2 nanowire growth on Ti–6Al–4V particles by thermal oxidation. Ceramics International, 2013, 39, 6517-6526. | 4.8 | 18 |

| # | Article | IF | CITATIONS |
|----|--|-----|-----------|
| 55 | Self Assembly of Nanoislands on YSZ-(001) Surface: A Mechanistic Approach Toward a Robust Process. Nano Letters, 2013, 13, 2116-2121. | 9.1 | 15 |
| 56 | Interface reaction and its effect on the performance of a CO2 gas sensor based on Li0.35La0.55TiO3 electrolyte and Li2CO3 sensing electrode. Sensors and Actuators B: Chemical, 2013, 182, 95-103. | 7.8 | 18 |
| 57 | Advances in fabrication of TiO2 nanofiber/nanowire arrays toward the cellular response in biomedical implantations: a review. Journal of Materials Science, 2013, 48, 8337-8353. | 3.7 | 41 |
| 58 | (Sensor Division Outstanding Achievement Award Presentation) Ceramic Gas Sensors to Oxide Nanostructures: Opportunities and Challenges. ECS Transactions, 2013, 50, 119-128. | 0.5 | 0 |
| 59 | Growth of coaxial nanowires by thermal oxidation of Ti64 alloy. Materials Technology, 2013, 28, 280-285. | 3.0 | 9 |
| 60 | CO Sensor Based on Au–TiO ₂ Nanowires Prepared by Conventional Heat-Treatment. Sensor Letters, 2013, 11, 2287-2290. | 0.4 | 2 |
| 61 | Hierarchical structured TiO2 nano-tubes for formaldehyde sensing. Ceramics International, 2012, 38, 6341-6347. | 4.8 | 57 |
| 62 | Ceramic nanopatterned surfaces to explore the effects of nanotopography on cell attachment. Materials Science and Engineering C, 2012, 32, 2469-2475. | 7.3 | 16 |
| 63 | Gas Sensors Based on One Dimensional Nanostructured Metal-Oxides: A Review. Sensors, 2012, 12, 7207-7258. | 3.8 | 488 |
| 64 | Review of titania nanotubes: Fabrication and cellular response. Ceramics International, 2012, 38, 4421-4435. | 4.8 | 215 |
| 65 | Comparison of gas sensor performance of SnO2 nano-structures on microhotplate platforms. Sensors and Actuators B: Chemical, 2012, 165, 13-18. | 7.8 | 69 |
| 66 | Nano-structured Oxides: A Materials Approach. , 2011, , . | | 1 |
| 67 | A selective room temperature formaldehyde gas sensor using TiO2 nanotube arrays. Sensors and Actuators B: Chemical, 2011, 156, 505-509. | 7.8 | 202 |
| 68 | Nano-structured Oxides: Platforms for Chemical Sensing and Beyond., 2011,,. | | 0 |
| 69 | Self Assembly of Nanoislands in Oxide Ceramics. Science of Advanced Materials, 2011, 3, 821-844. | 0.7 | 1 |
| 70 | Synthesis of Nano-Structured Metal-Oxides and Deposition via Ink-Jet Printing on Microhotplate Substrates. Science of Advanced Materials, 2011, 3, 845-852. | 0.7 | 1 |
| 71 | A Special Section on Nanostructured Ceramic Oxides: Challenges and Opportunities. Science of Advanced Materials, 2011, 3, 735-738. | 0.7 | 0 |
| 72 | Growth of 1-D TiO ₂ Nanowires on Ti and Ti Alloys by Oxidation. Journal of Nanomaterials, 2010, 2010, 1-7. | 2.7 | 21 |

| # | Article | IF | CITATIONS |
|----|---|------|-----------|
| 73 | ONE-DIMENSIONAL OXIDE NANOSTRUCTURES PRODUCED BY GAS PHASE REACTION. Functional Materials Letters, 2009, 02, 87-94. | 1.2 | 13 |
| 74 | High temperature potentiometric carbon dioxide sensor with minimal interference to humidity. Sensors and Actuators B: Chemical, 2009, 142, 337-341. | 7.8 | 28 |
| 75 | Highly sensitive and ultra-fast responding gas sensors using self-assembled hierarchical SnO2 spheres. Sensors and Actuators B: Chemical, 2009, 136, 138-143. | 7.8 | 136 |
| 76 | Gas-phase driven nano-machined TiO2 ceramics. Journal of Electroceramics, 2008, 21, 103-109. | 2.0 | 3 |
| 77 | Selfâ€Assembly of Pseudoperiodic Arrays of Nanoislands on YSZâ€(001). Advanced Materials, 2008, 20, 1699-1705. | 21.0 | 23 |
| 78 | Development of Agile Titania Sensors Via High-Temperature Reductive Etching Process (HiTREP©): I. Structural Reorganization. International Journal of Applied Ceramic Technology, 2008, 5, 480-489. | 2.1 | 5 |
| 79 | Reactive conversion of polycrystalline SnO ₂ into single-crystal nanofiber arrays at low oxygen partial pressure. Journal of Materials Research, 2008, 23, 2639-2644. | 2.6 | 8 |
| 80 | Sensing Behavior of TiO ₂ Thin Film Prepared by r.f. Reactive Sputtering. Sensor Letters, 2008, 6, 1049-1053. | 0.4 | 3 |
| 81 | High temperature sensor array for simultaneous determination of O2, CO, and CO2 with kernel ridge regression data analysis. Sensors and Actuators B: Chemical, 2007, 123, 950-963. | 7.8 | 19 |
| 82 | Aluminum-doped TiO2 nano-powders for gas sensors. Sensors and Actuators B: Chemical, 2007, 124, 111-117. | 7.8 | 122 |
| 83 | High temperature zirconia oxygen sensor with sealed metal/metal oxide internal reference. Sensors and Actuators B: Chemical, 2007, 124, 192-201. | 7.8 | 53 |
| 84 | Kinetic mechanism of TiO2 nanocarving via reaction with hydrogen gas. Journal of Materials Research, 2006, 21, 1822-1829. | 2.6 | 15 |
| 85 | Mixed Ionic and Electronic Conduction in Li[sub 3]PO[sub 4] Electrolyte for a CO[sub 2] Gas Sensor. Journal of the Electrochemical Society, 2006, 153, H4. | 2.9 | 24 |
| 86 | Novel Structural Modulation in Ceramic Sensors Via Redox Processing in Gas Buffers. International Journal of Applied Ceramic Technology, 2006, 3, 177-192. | 2.1 | 6 |
| 87 | High-Temperature Ceramic Gas Sensors: A Review. International Journal of Applied Ceramic Technology, 2006, 3, 302-311. | 2.1 | 164 |
| 88 | Dependence of potentiometric oxygen sensing characteristics on the nature of electrodes. Sensors and Actuators B: Chemical, 2006, 113, 162-168. | 7.8 | 30 |
| 89 | Synthesis and electrical properties of dense Bi2Al4O9. Journal of Solid State Electrochemistry, 2006, 10, 488-498. | 2.5 | 13 |
| 90 | Nano-Structured Ceramics by Gas-Phase Reaction. ECS Transactions, 2006, 3, 107-113. | 0.5 | 2 |

| # | Article | IF | Citations |
|-----|--|-----|-----------|
| 91 | Ceramic materials and nanostructures for chemical sensing. , 2005, , . | | 3 |
| 92 | TiO2–SnO2 nanostructures and their H2 sensing behavior. Sensors and Actuators B: Chemical, 2005, 108, 29-33. | 7.8 | 105 |
| 93 | Temperature-controlled CO, CO2 and NOx sensing in a diesel engine exhaust stream. Sensors and Actuators B: Chemical, 2005, 107, 839-848. | 7.8 | 32 |
| 94 | Comment on "Potentiometric solid state CO2 sensor and the role of electronic conductivity of the electrolyteâ€-by H. NÃ♠. Sensors and Actuators B: Chemical, 2005, 105, 124-126. | 7.8 | 1 |
| 95 | Nanocarving of titania (TiO2): a novel approach for fabricating chemical sensing platform. Ceramics International, 2004, 30, 1121-1126. | 4.8 | 37 |
| 96 | An Additive Micromolding Approach for the Development of Micromachined Ceramic Substrates for RF Applications. Journal of Microelectromechanical Systems, 2004, 13, 514-525. | 2.5 | 10 |
| 97 | Ceramic-based chemical sensors, probes and field-tests in automobile engines. Journal of Materials Science, 2003, 38, 4239-4245. | 3.7 | 44 |
| 98 | Oxygen sensors: Materials, methods, designs and applications. Journal of Materials Science, 2003, 38, 4271-4282. | 3.7 | 424 |
| 99 | Ceramics for chemical sensing. Journal of Materials Science, 2003, 38, 4611-4637. | 3.7 | 207 |
| 100 | Ceramic electrolytes and electrochemical sensors. Journal of Materials Science, 2003, 38, 4639-4660. | 3.7 | 92 |
| 101 | Guest editorial: Chemical and bio-ceramics. Journal of Materials Science, 2003, 38, 4609-4610. | 3.7 | 0 |
| 102 | Guest editorial: Chemical sensors for pollution monitoring and control. Journal of Materials Science, 2003, 38, 4237-4237. | 3.7 | 4 |
| 103 | ZnO sol–gel derived porous film for CO gas sensing. Sensors and Actuators B: Chemical, 2003, 96, 717-722. | 7.8 | 125 |
| 104 | Structural and thermal analyses on phase evolution of sol–gel (Ba,Sr)TiO3 thin films. Surface and Coatings Technology, 2003, 167, 203-206. | 4.8 | 27 |
| 105 | The origin of oxygen dependence in a potentiometric CO2 sensor with Li-ion conducting electrolytes. Sensors and Actuators B: Chemical, 2003, 88, 53-59. | 7.8 | 24 |
| 106 | Detection of CO in a reducing, hydrous environment using CuBr as electrolyte. Sensors and Actuators B: Chemical, 2003, 92, 351-355. | 7.8 | 15 |
| 107 | Selective detection of ethanol vapor using xTiO2–(1 â^' x)WO3 based sensor. Sensors and Actuators B: Chemical, 2003, 94, 99-102. | 7.8 | 25 |
| 108 | Hillock Formation of SnO2Thin Films Prepared by Metal-Organic Chemical Vapor Deposition. Japanese Journal of Applied Physics, 2003, 42, 7071-7072. | 1.5 | 1 |

| # | Article | IF | CITATIONS |
|-----|--|------------|---|
| 109 | <title>Nondestructive evaluation of bonding characteristics of TiO<formula><inf><roman>2</roman></inf></formula>Ogas sensor</title> ., 2002, 4703, 31. | kformula > | ✓onf><roma< li=""> </roma<> |
| 110 | Pyrolysis of Negative Photoresists to Fabricate Carbon Structures for Microelectromechanical Systems and Electrochemical Applications. Journal of the Electrochemical Society, 2002, 149, E78. | 2.9 | 138 |
| 111 | Selective gas detection with catalytic filter. Materials Chemistry and Physics, 2002, 75, 56-60. | 4.0 | 45 |
| 112 | Microporous zeolite modified yttria stabilized zirconia (YSZ) sensors for nitric oxide (NO) determination in harsh environments. Sensors and Actuators B: Chemical, 2002, 82, 142-149. | 7.8 | 75 |
| 113 | A phosphate-based proton conducting solid electrolyte hydrocarbon gas sensor. Sensors and Actuators B: Chemical, 2002, 87, 480-486. | 7.8 | 20 |
| 114 | Effects of NiO addition in WO3-based gas sensors prepared by thick film process. Solid State Ionics, 2002, 152-153, 827-832. | 2.7 | 36 |
| 115 | Composite n–p semiconducting titanium oxides as gas sensors. Sensors and Actuators B: Chemical, 2001, 79, 17-27. | 7.8 | 206 |
| 116 | Potentiometric CO2 gas sensor with lithium phosphorous oxynitride electrolyte. Sensors and Actuators B: Chemical, 2001, 80, 234-242. | 7.8 | 60 |
| 117 | Titanium dioxide based high temperature carbon monoxide selective sensor. Sensors and Actuators B: Chemical, 2001, 72, 239-248. | 7.8 | 194 |
| 118 | A Rugged Oxygen Gas Sensor with Solid Reference for High Temperature Applications. Journal of the Electrochemical Society, 2001, 148, G91. | 2.9 | 30 |
| 119 | A new method for fabrication of stable and reproducible yttria-based thermistors. Sensors and Actuators A: Physical, 2000, 87, 60-66. | 4.1 | 19 |
| 120 | A Research Driven Multidisciplinary Curriculum In Sensor Materials. , 2000, , 5.52.1. | | 2 |
| 121 | An In-house-Built Thermally Stimulated Current Measurement Setup: Strontium Titanate as a Test System. Japanese Journal of Applied Physics, 2000, 39, 4830-4834. | 1.5 | 8 |
| 122 | High-Temperature Electrical Behaviors of Li2ZrO3 Thick Films. Japanese Journal of Applied Physics, 2000, 39, L474-L475. | 1.5 | 0 |
| 123 | Niobium pentoxide as a lean-range oxygen sensor. Sensors and Actuators B: Chemical, 1999, 56, 121-128. | 7.8 | 22 |
| 124 | Electrode attachment, aging and thermal-cycling characteristics of yttria-based thermistors. Materials Letters, 1999, 40, 213-221. | 2.6 | 8 |
| 125 | Interaction of Carbon Monoxide with Anatase Surfaces at High Temperatures:Â Optimization of a Carbon Monoxide Sensor. Journal of Physical Chemistry B, 1999, 103, 4412-4422. | 2.6 | 136 |
| 126 | Title is missing!. , 1998, 2, 21-31. | | 30 |

| # | Article | IF | CITATIONS |
|-----|---|-----|-----------|
| 127 | Evaluation of bond integrity of TiO2-Y2O3 sensor using thermal wave imaging technique. Materials Letters, 1998, 34, 76-80. | 2.6 | 1 |
| 128 | Sensing Mechanism of a Carbon Monoxide Sensor Based on Anatase Titania. Journal of the Electrochemical Society, 1997, 144, 1750-1753. | 2.9 | 69 |
| 129 | Sintering and Dielectric Properties of Hydrothermally Synthesized Cubic and TetragonalBaTiO3Powders. Japanese Journal of Applied Physics, 1997, 36, 214-221. | 1.5 | 45 |
| 130 | Characterization of Submicron Particles of Tetragonal BaTiO3. Chemistry of Materials, 1996, 8, 226-234. | 6.7 | 229 |
| 131 | The AC Electrical Behavior of Hydrothermally Synthesized Barium Titanate Ceramics. Japanese Journal of Applied Physics, 1996, 35, 6145-6152. | 1.5 | 11 |
| 132 | Electrical properties of high-temperature oxides, borides, carbides, and nitrides. Journal of Materials Science, 1995, 30, 1627-1641. | 3.7 | 110 |
| 133 | Electrical Resistivity of Titanium Diboride and Zirconium Diboride. Journal of the American Ceramic Society, 1995, 78, 1380-1382. | 3.8 | 89 |
| 134 | Determination of atomistic parameters and transport properties combining theory and experiments of demixing in (Co,Mg)O. Journal Physics D: Applied Physics, 1995, 28, 120-128. | 2.8 | 8 |
| 135 | The ac electrical behavior of polycrystalline yttria. Journal of Applied Physics, 1995, 78, 1757-1762. | 2.5 | 34 |
| 136 | Bismuth oxide-based solid electrolytes for fuel cells. Journal of Materials Science, 1994, 29, 4135-4151. | 3.7 | 234 |
| 137 | High-Temperature Immittance Response in Anatase-Based Sensor Materials. Journal of the American Ceramic Society, 1994, 77, 3145-3152. | 3.8 | 30 |
| 138 | Characterization of TiO2-Based Sensor Materials Using Immittafice Spectroscopy. Journal of the American Ceramic Society, 1994, 77, 481-486. | 3.8 | 44 |
| 139 | A generalized view of the correlation factor in solidâ€state diffusion. Journal of Applied Physics, 1994, 75, 2851-2856. | 2.5 | 6 |
| 140 | Hydrothermal Synthesis and Dielectric Properties of Tetragonal BaTiO3. Chemistry of Materials, 1994, 6, 1542-1548. | 6.7 | 197 |
| 141 | Ceramic Sensors for Carbon Monoxide and Hydrogen. Electrochemical Society Interface, 1994, 3, 31-34. | 0.4 | 5 |
| 142 | Mixed conduction in \hat{l}^2 -alumina type materials: a critical review. Journal of Materials Processing Technology, 1993, 38, 15-27. | 6.3 | 1 |
| 143 | Demixing of (Ni,Co)O under an Oxygen Potential Gradient(II). Journal of the Electrochemical Society, 1992, 139, L77-L78. | 2.9 | 5 |
| 144 | Solidâ€State Gas Sensors: A Review. Journal of the Electrochemical Society, 1992, 139, 3690-3704. | 2.9 | 366 |

| # | Article | IF | CITATIONS |
|-----|---|-----|-----------|
| 145 | The path probability method: An atomistic technique of diffusion. Journal of Materials Science, 1992, 27, 3125-3132. | 3.7 | 6 |
| 146 | Carbon Monoxide and Hydrogen Detection by Anatase Modification of Titanium Dioxide. Journal of the American Ceramic Society, 1992, 75, 2964-2968. | 3.8 | 199 |
| 147 | Demixing of (Ni, Co)O Under an Oxygen Potential Gradient Using a YSZâ€Based Galvanic Cell. Journal of the Electrochemical Society, 1991, 138, 3673-3677. | 2.9 | 23 |
| 148 | Infrared reflectance spectra of doped BaTi4O9. Journal of Solid State Chemistry, 1991, 95, 275-282. | 2.9 | 15 |
| 149 | Microwave Dielectric Properties of Doped BaTi4O9. Journal of the American Ceramic Society, 1991, 74, 1894-1898. | 3.8 | 59 |
| 150 | Demixing: A source of material deterioration. Journal of Physics and Chemistry of Solids, 1989, 50, 729-733. | 4.0 | 3 |
| 151 | Time Evolution of Demixing in Oxides under an Oxygen Potential Gradient. Journal of the American Ceramic Society, 1988, 71, 513-521. | 3.8 | 26 |
| 152 | Demixing of Oxides under a Temperature Gradient. Journal of the American Ceramic Society, 1987, 70, 246-253. | 3.8 | 16 |
| 153 | Performance of a Ceramic CO Sensor in the Automotive Exhaust System. , 0, , . | | 4 |
| 154 | Surface Properties and Cell Response of Bioactive Thermally Grown TiO ₂ Nanofibers. Applied Mechanics and Materials, 0, 575, 219-222. | 0.2 | 0 |
| 155 | Evaluation of Surface Properties and <i>In Vitro</i> Characterization of Surface Modified <i>In Situ</i> TiO ₂ Nanofibers. Key Engineering Materials, 0, 656-657, 63-67. | 0.4 | 0 |
| 156 | Ceramic Sensors for the Glass Industry. Ceramic Engineering and Science Proceedings, 0, , 91-100. | 0.1 | 2 |