
## Andrzej Rybak

List of Publications by Year in descending order

Source: https://exaly.com/author-pdf/8913871/publications.pdf Version: 2024-02-01



ANDDZEL RVRAK

#	Article	IF	CITATIONS
1	Thermally Conductive Shape Memory Polymer Composites Filled with Boron Nitride for Heat Management in Electrical Insulation. Polymers, 2021, 13, 2191.	2.0	18
2	Functional Polymer Composite with Core-Shell Ceramic Filler: II. Rheology, Thermal, Mechanical, and Dielectric Properties. Polymers, 2021, 13, 2161.	2.0	15
3	Montmorillonite–triclosan hybrid as effective antibacterial additive with enhanced thermal stability for protection of plastic electrical components. Polymer Bulletin, 2020, 77, 17-31.	1.7	7
4	Monitoring of air voids at plastic-metal interfaces by terahertz radiation. Infrared Physics and Technology, 2020, 104, 103119.	1.3	5
5	Synthesis and characterization of silane based binder for the amorphous metal ribbon. Thin Solid Films, 2020, 716, 138433.	0.8	1
6	Modelling of Effective Thermal Conductivity of Composites Filled with Core-Shell Fillers. Materials, 2020, 13, 5480.	1.3	7
7	Spectroscopic and rheological investigation of candidates for the double-layered binder for amorphous metal ribbon. Journal of Molecular Structure, 2020, 1207, 127763.	1.8	Ο
8	Processing Influence on Thermal Conductivity of Polymer Nanocomposites. , 2019, , 463-487.		9
9	Highly structured graphene polyethylene nanocomposites. AIP Conference Proceedings, 2019, , .	0.3	9
10	Aluminosilicateâ€epoxy resin composite as novel material for electrical insulation with enhanced mechanical properties and improved thermal conductivity. Polymer Composites, 2019, 40, 3182-3188.	2.3	26
11	Transient dynamics of a nonlinear magneto-optical rotation. Physical Review A, 2018, 97, .	1.0	10
12	Investigation of the influence of pretreatment parameters on the surface characteristics of amorphous metal for use in power industry. Journal of Molecular Structure, 2018, 1160, 360-367.	1.8	6
13	Graphene nanoplateletâ€silica hybrid epoxy composites as electrical insulation with enhanced thermal conductivity. Polymer Composites, 2018, 39, E1682.	2.3	47
14	Epoxy composites with ceramic core–shell fillers for thermal management in electrical devices. Polymers for Advanced Technologies, 2017, 28, 1676-1682.	1.6	26
15	Investigation into Limitation of Arc Erosion in LV Switches Through Application of Hybrid Switching. IEEE Transactions on Plasma Science, 2017, 45, 446-453.	0.6	9
16	Two-Step Procedure of Fly Ash Modification as an Alternative Method for Creation of Functional Composite. Journal of Polymers and the Environment, 2017, 25, 1342-1347.	2.4	25
17	Enhanced thermal conductivity of graphene nanoplatelets epoxy composites. Materials Science-Poland, 2017, 35, 382-389.	0.4	46
18	Gas Barrier, Thermal, Mechanical and Rheological Properties of Highly Aligned Graphene-LDPE Nanocomposites. Polymers, 2017, 9, 294.	2.0	54

Andrzej Rybak

#	Article	IF	CITATIONS
19	An Investigation into the Influence of Filler Silanization Conditions on Mechanical and Thermal Parameters of Epoxy Resin-Fly Ash Composites. Journal of Polymers and the Environment, 2016, 24, 298-308.	2.4	29
20	Influence of magnetic field-aided filler orientation on structure and transport properties of ferrite filled composites. Journal of Magnetism and Magnetic Materials, 2016, 419, 345-353.	1.0	15
21	Terahertz Detection of Wavelength-Size Metal Particles in Pressboard Samples. IEEE Transactions on Terahertz Science and Technology, 2016, 6, 99-107.	2.0	13
22	Polymer matrix influence on stability of wood polymer composites. Polymers for Advanced Technologies, 2015, 26, 1076-1082.	1.6	25
23	Enhanced thermal conductivity of epoxy–matrix composites with hybrid fillers. Polymers for Advanced Technologies, 2015, 26, 26-31.	1.6	57
24	Metal migration at conductor / XLPE interface subjected to partial discharges at different electrical stresses. IEEE Transactions on Dielectrics and Electrical Insulation, 2015, 22, 456-462.	1.8	4
25	Magnetic-aligned, magnetite-filled epoxy composites with enhanced thermal conductivity. Journal of Materials Science, 2015, 50, 2510-2516.	1.7	35
26	Functional composites with core–shell fillers: I. Particle synthesis and thermal conductivity measurements. Journal of Materials Science, 2015, 50, 7779-7789.	1.7	29
27	Analysis of interfacial metal Migration into dielectric materials subjected to high voltage stress. , 2014, , .		0
28	Correlation between nanostructural, optical, and photoelectrical properties of P3 <scp>HT</scp> : <scp>S</scp> i <scp>NW</scp> nanocomposites for solar ell application. Physica Status Solidi (A) Applications and Materials Science, 2014, 211, 670-676.	0.8	5
29	Modification of epoxy–anhydride thermosets with a hyperbranched poly(ester amide). II. Thermal, dynamic mechanical, and dielectric properties and thermal reworkability. Journal of Applied Polymer Science, 2013, 128, 4001-4013.	1.3	17
30	Migration effects at conductor / XLPE interface subjected to partial discharges at different electrical stresses. , 2013, , .		0
31	Interaction of conductor with polymeric materials (XLPE/EPR) at partial discharges. IEEE Transactions on Dielectrics and Electrical Insulation, 2012, 19, 2119-2127.	1.8	25
32	Silicon Nanowire/P3HT Hybrid Solar Cells: Effect of the Electron Localization at Wire Nanodiameters. Energy Procedia, 2012, 31, 136-143.	1.8	17
33	Comparison of PWM and SIN aging of insulating material subjected to surface discharges. , 2012, , .		5
34	Hybrid films based on silicon nanowires dispersed in a semiconducting polymer for thin film solar cells: Opportunities and new challenges. Synthetic Metals, 2012, 161, 2623-2627.	2.1	4
35	Modification of epoxy–anhydride thermosets using a hyperbranched poly(esterâ€amide): I. Kinetic study. Polymer International, 2012, 61, 1710-1725.	1.6	37
36	The influence of different conductors on insulating materials degradation by partial discharges. , 2011, , .		5

Andrzej Rybak

#	Article	IF	CITATIONS
37	Photogeneration of free charge carriers in tenuously packed <i>ï€</i> conjugated polymer chains. Polymers for Advanced Technologies, 2011, 22, 2075-2083.	1.6	6
38	Conductive polymer composites based on metallic nanofiller as smart materials for current limiting devices. Composites Science and Technology, 2010, 70, 410-416.	3.8	114
39	Hybrid polymer/TiO2 films by in situ hydrolysis condensation of titanium alkoxide precursors for photovoltaic transparent windows. Physica Status Solidi (A) Applications and Materials Science, 2010, 207, 1627-1630.	0.8	2
40	Synthesis of polystyrene coated SiC nanowires as fillers in a polyurethane matrix for electromechanical conversion. Nanotechnology, 2010, 21, 145610.	1.3	21
41	Electrical and thermomechanical properties of segregated nanocomposites based on PVC and multiwalled carbon nanotubes. Journal of Non-Crystalline Solids, 2010, 356, 635-641.	1.5	51
42	Photogeneration and photovoltaic effect in poly(N-vinylcarbazole):TiO2 bulk-heterojunction elaborated by hydrolysis–condensation reactions of TiO2 precursors. Synthetic Metals, 2009, 159, 508-512.	2.1	13
43	Influence of molecular order on charge carrier photogeneration in perylene derivative layer. Thin Solid Films, 2008, 516, 4201-4207.	0.8	12
44	Charge carrier transport in layers of discotic liquid crystals as studied by transient photocurrents. Synthetic Metals, 2006, 156, 302-309.	2.1	22
45	Photogeneration and photovoltaic effect in blends of derivatives of hexabenzocoronene and perylene. Synthetic Metals, 2005, 155, 150-156.	2.1	31
46	Photogeneration and transport in thin films of p- and n-type discotic liquid crystals. Synthetic Metals, 2003, 137, 905-906.	2.1	23