

Wangfeng Bai

List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/9054092/publications.pdf>

Version: 2024-02-01

47
papers

2,137
citations

201575

27
h-index

233338

45
g-index

47
all docs

47
docs citations

47
times ranked

1206
citing authors

#	ARTICLE	IF	CITATIONS
1	Realizing high-performance capacitive energy storage in lead-free relaxor ferroelectrics via synergistic effect design. <i>Journal of the European Ceramic Society</i> , 2022, 42, 129-139.	2.8	39
2	Simultaneously achieving high energy-storage efficiency and density in Bi-modified SrTiO ₃ -based relaxor ferroelectrics by ion selective engineering. <i>Composites Part B: Engineering</i> , 2022, 230, 109493.	5.9	52
3	High energy storage performance in tungsten bronze-based relaxor ceramic via doping with CuO. <i>Scripta Materialia</i> , 2022, 211, 114514.	2.6	16
4	Superior energy storage performance in (Bi _{0.5} Na _{0.5})TiO ₃ -based lead-free relaxor ferroelectrics for dielectric capacitor application via multiscale optimization design. <i>Journal of Materials Chemistry A</i> , 2022, 10, 9535-9546.	5.2	70
5	Excellent energy storage performance of paraelectric Ba _{0.4} Sr _{0.6} TiO ₃ based ceramics through induction of polar nano-regions. <i>Ceramics International</i> , 2022, 48, 19864-19873.	2.3	9
6	Synergy of a Stabilized Antiferroelectric Phase and Domain Engineering Boosting the Energy Storage Performance of NaNbO ₃ -Based Relaxor Antiferroelectric Ceramics. <i>ACS Applied Materials & Interfaces</i> , 2022, 14, 17662-17673.	4.0	48
7	Promoting Energy Storage Performance of Sr _{0.7} Ba _{0.3} Nb ₂ O ₆ Tetragonal Tungsten Bronze Ceramic by a Two-Step Sintering Technique. <i>ACS Applied Electronic Materials</i> , 2022, 4, 452-460.	2.0	15
8	Simultaneously achieving high energy storage performance and remarkable thermal stability in Bi _{0.5} K _{0.5} TiO ₃ -based ceramics. <i>Materials Today Energy</i> , 2022, 28, 101078.	2.5	11
9	Remarkable capacitive performance in novel tungsten bronze ceramics. <i>Dalton Transactions</i> , 2021, 50, 124-130.	1.6	30
10	Significantly tailored energy-storage performances in Bi _{0.5} Na _{0.5} TiO ₃ -based relaxor ferroelectric ceramics by introducing bismuth layer-structured relaxor BaBi ₂ Nb ₂ O ₉ for capacitor application. <i>Journal of Materials Chemistry C</i> , 2021, 9, 5234-5243.	2.7	50
11	Simultaneously Realizing Superior Energy Storage Properties and Outstanding Charge-Discharge Performances in Tungsten Bronze-Based Ceramic for Capacitor Applications. <i>Inorganic Chemistry</i> , 2021, 60, 6559-6568.	1.9	46
12	Relaxor ferroelectric (Bi _{0.5} Na _{0.5})TiO ₃ -based ceramic with remarkable comprehensive energy storage performance under low electric field for capacitor applications. <i>Journal of Materials Science: Materials in Electronics</i> , 2021, 32, 21164-21177.	1.1	9
13	(Bi _{0.5} Na _{0.5})TiO ₃ -based relaxor ferroelectrics with simultaneous high energy storage properties and remarkable charge-discharge performances under low working electric fields for dielectric capacitor applications. <i>Ceramics International</i> , 2021, 47, 25800-25809.	2.3	25
14	Pb/Bi-free Tungsten Bronze-Based Relaxor Ferroelectric Ceramics with Remarkable Energy Storage Performance. <i>ACS Applied Energy Materials</i> , 2021, 4, 9066-9076.	2.5	13
15	High capacitive performance at moderate operating field in (Bi _{0.5} Na _{0.5})TiO ₃ -based dielectric ceramics via synergistic effect of site engineering strategy. <i>Chemical Engineering Journal</i> , 2021, 426, 130811.	6.6	45
16	Tailoring electromechanical performance in BiScO ₃ -modified Bi _{0.5} Na _{0.5} TiO ₃ -based lead-free piezoceramics. <i>Journal of Materials Science: Materials in Electronics</i> , 2020, 31, 1491-1501.	1.1	6
17	Giant Field-Induced Strain with Low Hysteresis and Boosted Energy Storage Performance under Low Electric Field in (Bi _{0.5} Na _{0.5})TiO ₃ -Based Grain Orientation-Controlled Ceramics. <i>Advanced Electronic Materials</i> , 2020, 6, 2000332.	2.6	59
18	Enhanced energy storage performance in bismuth layer-structured BaBi ₂ Me ₂ O ₉ (Me = Nb and Ta) relaxor ferroelectric ceramics. <i>Ceramics International</i> , 2020, 46, 15907-15914.	2.3	23

#	ARTICLE	IF	CITATIONS
19	Tailoring high energy density with superior stability under low electric field in novel (Bi _{0.5} Na _{0.5})TiO ₃ -based relaxor ferroelectric ceramics. Journal of the European Ceramic Society, 2020, 40, 4475-4486.	2.8	123
20	Integrating chemical engineering and crystallographic texturing design strategy for the realization of practically viable lead-free sodium bismuth titanate-based incipient piezoceramics. Dalton Transactions, 2020, 49, 8661-8671.	1.6	10
21	Influences of rare earth site engineering on piezoelectric and electromechanical response of (Ba _{0.85} Ca _{0.15})(Zr _{0.1} Ti _{0.9})O ₃ lead-free ceramics. Journal of Materials Science: Materials in Electronics, 2020, 31, 6560-6573.	1.1	9
22	Simultaneously achieving high energy storage density and efficiency under low electric field in BiFeO ₃ -based lead-free relaxor ferroelectric ceramics. Journal of the European Ceramic Society, 2020, 40, 5450-5457.	2.8	103
23	Achieving high-energy storage performance in 0.67Bi ₁ Sm ₁ FeO ₃ -0.33BaTiO ₃ lead-free relaxor ferroelectric ceramics. Ceramics International, 2020, 46, 11549-11555.	2.3	83
24	Multifunctional bismuth sodium titanate-based ferroelectric ceramics with bright red emission and large strain response. Materials Chemistry and Physics, 2020, 244, 122706.	2.0	0
25	Tailoring frequency-insensitive large field-induced strain and energy storage properties in (Ba _{0.85} Ca _{0.15})(Zr _{0.1} Ti _{0.9})O ₃ -modified (Bi _{0.5} Na _{0.5})TiO ₃ lead-free ceramics. Dalton Transactions, 2019, 48, 10160-10173.	1.6	59
26	BaTiO ₃ nanowires-induced phase transition and thermally stable strain in (Bi _{0.5} Na _{0.5})TiO ₃ piezoelectric ceramics. Ceramics International, 2019, 45, 18623-18631.	2.3	9
27	Large electrostrictive effect in lead-free (Bi _{0.5} Na _{0.5})TiO ₃ -based composite piezoceramics. Ceramics International, 2018, 44, 8628-8634.	2.3	28
28	Promoting Charge Separation in g-C ₃ N ₄ /Graphene/MoS ₂ Photocatalysts by Two-Dimensional Nanojunction for Enhanced Photocatalytic H ₂ Production. ACS Applied Energy Materials, 2018, 1, 1400-1407.	2.5	171
29	Enhanced thermal stability, hardening of piezoelectric property, and mediated electromechanical response in (Bi _{0.5} Na _{0.5})TiO ₃ -based piezoceramics via composite approach. Ceramics International, 2018, 44, 17022-17032.	2.3	15
30	Electromechanical response and piezoelectric properties in (Ba _{0.85} Ca _{0.15})(Zr _{0.1} Ti _{0.9})O ₃ piezoceramics using nano-sized AlN modification. Ceramics International, 2018, 44, 16040-16050.	2.3	15
31	NaNbO ₃ templates-induced phase evolution and enhancement of electromechanical properties in grain oriented lead-free BNT-based piezoelectric materials. Journal of the European Ceramic Society, 2017, 37, 2591-2604.	2.8	84
32	Lead-free BNT-based composite materials: enhanced depolarization temperature and electromechanical behavior. Dalton Transactions, 2017, 46, 15340-15353.	1.6	38
33	Microstructure and Piezoelectric Properties of Lead-Free (K _{0.5} Na _{0.5})NbO ₃ -LiNbO ₃ -SrTiO ₃ Ceramics. Ferroelectrics, 2016, 490, 78-84.	0.3	1
34	Composition- and temperature-driven phase transition characteristics and associated electromechanical properties in Bi _{0.5} Na _{0.5} TiO ₃ -based lead-free ceramics. Dalton Transactions, 2016, 45, 8573-8586.	1.6	84
35	Phase evolution and correlation between tolerance factor and electromechanical properties in BNT-based ternary perovskite compounds with calculated end-member Bi(Me _{0.5} Ti _{0.5})O ₃ (Me = Zn, Mg, Ni, Co). Dalton Transactions, 2016, 45, 14141-14153.	1.6	47
36	Electromechanical properties and structure evolution in BiAlO ₃ -modified Bi _{0.5} Na _{0.5} TiO ₃ BaTiO ₃ lead-free piezoceramics. Journal of Alloys and Compounds, 2016, 667, 6-17.	2.8	45

#	ARTICLE	IF	CITATIONS
37	Effect of Different Templates on Electrical Properties of Textured KNN-Based Ceramics. <i>Ferroelectrics</i> , 2016, 490, 85-93.	0.3	6
38	Temperature-insensitive large strain response with a low hysteresis behavior in BNT-based ceramics. <i>Ceramics International</i> , 2016, 42, 7669-7680.	2.3	97
39	Structure and electromechanical properties in Bi _{0.5} Na _{0.5} TiO ₃ -based lead-free piezoceramics with calculated end-member Bi(Ni _{0.5} Ti _{0.5})O ₃ . <i>Journal of the European Ceramic Society</i> , 2015, 35, 3457-3466.	2.8	35
40	Effect of CaZrO ₃ on phase structure and electrical properties of KNN-based lead-free ceramics. <i>RSC Advances</i> , 2015, 5, 19647-19651.	1.7	32
41	Structure evolution and large strain response in BNT-BT lead-free piezoceramics modified with Bi(Ni _{0.5} Ti _{0.5})O ₃ . <i>Journal of Alloys and Compounds</i> , 2015, 649, 772-781.	2.8	90
42	Microwave dielectric properties of low temperature sintered ZnWO ₄ -TiO ₂ composite ceramics. <i>Ceramics International</i> , 2015, 41, S435-S440.	2.3	21
43	Effect of different templates on structure evolution and large strain response under a low electric field in $\text{Bi}(\text{Ni}_{0.5}\text{Ti}_{0.5})\text{O}_3$-textured lead-free BNT-based piezoelectric ceramics. <i>Journal of the European Ceramic Society</i> , 2015, 35, 2489-2499.	2.8	79
44	Phase Diagrams and Electromechanical Strains in Lead-Free BNT-Based Ternary Perovskite Compounds. <i>Journal of the American Ceramic Society</i> , 2014, 97, 3510-3518.	1.9	61
45	The Composition and Temperature-Dependent Structure Evolution and Large Strain Response in $(\text{Bi}_{0.5}\text{Na}_{0.5}\text{TiO}_3)_{1-x}(\text{Bi}_{0.5}\text{Ni}_{0.5}\text{TiO}_3)_x$ Lead-Free Piezoceramics. <i>Journal of the American Ceramic Society</i> , 2013, 96, 246-252.	1.1	99
46	Phase transitions, relaxor behavior, and large strain response in LiNbO ₃ -modified Bi _{0.5} (Na _{0.80} K _{0.20}) _{0.5} TiO ₃ lead-free piezoceramics. <i>Journal of Applied Physics</i> , 2013, 114, .	1.1	99
47	High Capacitive Performance Achieved in NaNbO ₃ -Based Ceramics via Grain Refinement and Relaxation Enhancement. <i>Energy Technology</i> , 0, , 2100777.	1.8	6