

Shengping Ruan

List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/920670/publications.pdf>

Version: 2024-02-01

227
papers

7,183
citations

44069

48
h-index

88630

70
g-index

229
all docs

229
docs citations

229
times ranked

7324
citing authors

#	ARTICLE	IF	CITATIONS
1	Passivation agent with dipole moment for surface modification towards efficient and stable perovskite solar cells. <i>Journal of Energy Chemistry</i> , 2022, 64, 55-61.	12.9	17
2	Mesoporous Ti _{0.5} Cr _{0.5} N for trace H ₂ S detection with excellent long-term stability. <i>Journal of Hazardous Materials</i> , 2022, 423, 127193.	12.4	9
3	G-C ₃ N ₄ /In ₂ O ₃ composite for effective formaldehyde detection. <i>Sensors and Actuators B: Chemical</i> , 2022, 358, 131414.	7.8	23
4	Using Ligand Engineering to Produce Efficient and Stable Pb-Sn Perovskite Solar Cells with Antioxidative 2D Capping Layers. <i>ACS Applied Materials & Interfaces</i> , 2022, 14, 14729-14738.	8.0	8
5	Synthesis and gas sensing properties of γ -Fe ₂ O ₃ derived from Fe/Ga bimetallic organic framework. <i>Journal of Alloys and Compounds</i> , 2022, 921, 166193.	5.5	9
6	Enhanced gas sensing properties for formaldehyde based on ZnO/Zn ₂ SnO ₄ composites from one-step hydrothermal synthesis. <i>Journal of Alloys and Compounds</i> , 2021, 850, 156606.	5.5	45
7	Mesoporous titanium niobium nitrides supported Pt nanoparticles for highly selective and sensitive formaldehyde sensing. <i>Journal of Materials Chemistry A</i> , 2021, 9, 19840-19846.	10.3	14
8	Molecular Doping Inhibits Charge Trapping in Low-Temperature-Processed ZnO toward Flexible Organic Solar Cells. <i>ACS Applied Materials & Interfaces</i> , 2021, 13, 14423-14432.	8.0	13
9	Construction of p-n heterojunctions by modifying MOF-derived γ -Fe ₂ O ₃ with partially covered cobalt tungstate for high-performance ethyl acetate detection. <i>Sensors and Actuators B: Chemical</i> , 2021, 344, 130129.	7.8	20
10	Synthesis of Au-decorated SnO ₂ crystallites with exposed (221) facets and their enhanced acetylene sensing properties. <i>Sensors and Actuators B: Chemical</i> , 2020, 307, 127629.	7.8	44
11	Engineering Co ³⁺ cations in Co ₃ O ₄ multishelled microspheres by Mn doping: The roles of Co ³⁺ and oxygen species for sensitive xylene detection. <i>Sensors and Actuators B: Chemical</i> , 2020, 308, 127651.	7.8	31
12	The effects of Zr-doping on improving the sensitivity and selectivity of a one-dimensional γ -MoO ₃ -based xylene gas sensor. <i>Inorganic Chemistry Frontiers</i> , 2020, 7, 1704-1712.	6.0	29
13	Novel ultraviolet photodetector with ultrahigh photosensitivity employing SILAR-deposited ZnS film on MgZnO. <i>Journal of Alloys and Compounds</i> , 2020, 832, 155022.	5.5	22
14	Metal-organic framework-derived ZnO/ZnCo ₂ O ₄ microspheres modified by catalytic PdO nanoparticles for sub-ppm-level formaldehyde detection. <i>Sensors and Actuators B: Chemical</i> , 2020, 315, 128118.	7.8	50
15	UV detector based on an FTO/TiO ₂ /MoO ₃ heterojunction with a potential well trapping electrons in the dark. <i>Nanotechnology</i> , 2019, 30, 465501.	2.6	15
16	Metal-organic framework-derived Co ₃ O ₄ /CoFe ₂ O ₄ double-shelled nanocubes for selective detection of sub-ppm-level formaldehyde. <i>Sensors and Actuators B: Chemical</i> , 2019, 298, 126887.	7.8	62
17	Synthesis of CuO-CdS composite nanowires and their ultrasensitive ethanol sensing properties. <i>Inorganic Chemistry Frontiers</i> , 2019, 6, 238-247.	6.0	27
18	Highly efficient polymer solar cells based on low-temperature processed ZnO: application of a bifunctional Au@CNTs nanocomposite. <i>Journal of Materials Chemistry C</i> , 2019, 7, 2676-2685.	5.5	9

#	ARTICLE	IF	CITATIONS
19	Oxygen vacancies dominated CuO@ZnFe ₂ O ₄ yolk-shell microspheres for robust and selective detection of xylene. <i>Sensors and Actuators B: Chemical</i> , 2019, 295, 117-126.	7.8	47
20	Metal-organic framework derived core-shell PrFeO ₃ -functionalized γ -Fe ₂ O ₃ nano-octahedrons as high performance ethyl acetate sensors. <i>Sensors and Actuators B: Chemical</i> , 2019, 297, 126738.	7.8	27
21	Delicate Energy-Level Adjustment and Interfacial Defect Passivation of ZnO Electron Transport Layers in Organic Solar Cells by Constructing ZnO/In Nanojunctions. <i>Journal of Physical Chemistry C</i> , 2019, 123, 16546-16555.	3.1	16
22	Excellent Gas Sensing of CdS Nanowires Decorated with Ag Nanoparticles. <i>Journal of Nanoscience and Nanotechnology</i> , 2019, 19, 7083-7088.	0.9	4
23	Synthesis of sea urchin-like microsphere of CdS and its gas sensing properties. <i>Materials Science and Engineering B: Solid-State Materials for Advanced Technology</i> , 2019, 243, 206-213.	3.5	14
24	Hierarchical Co ₃ O ₄ @NiMoO ₄ core-shell nanowires for chemiresistive sensing of xylene vapor. <i>Mikrochimica Acta</i> , 2019, 186, 222.	5.0	26
25	Enhanced Electronic Quality of Perovskite via a Novel C ₆₀ -o-Quinodimethane Bisadducts toward Efficient and Stable Perovskite Solar Cells. <i>ACS Sustainable Chemistry and Engineering</i> , 2019, 7, 8579-8586.	6.7	12
26	Built-in electric field promotes photoexcitation separation and depletion of most carriers in TiO ₂ :C UV detectors. <i>Nanotechnology</i> , 2019, 30, 295502.	2.6	13
27	Fe ₂ O ₃ nanoparticles-decorated MoO ₃ nanobelts for enhanced chemiresistive gas sensing. <i>Journal of Alloys and Compounds</i> , 2019, 782, 672-678.	5.5	60
28	Modulated charge transport characteristics in solution-processed UV photodetector by incorporating localized built-in electric field. <i>Journal of Alloys and Compounds</i> , 2019, 774, 887-895.	5.5	5
29	Facilitated extrinsic majority carrier depletion and photogenerated exciton dissociation in an annealing-free ZnO:C photodetector. <i>Nanoscale</i> , 2018, 10, 6459-6466.	5.6	12
30	Coordination Polymer-Derived Multishelled Mixed Ni-Co Oxide Microspheres for Robust and Selective Detection of Xylene. <i>ACS Applied Materials & Interfaces</i> , 2018, 10, 15314-15321.	8.0	64
31	The significant improvement for BTX (benzene, toluene and xylene) sensing performance based on Au-decorated hierarchical ZnO porous rose-like architectures. <i>Sensors and Actuators B: Chemical</i> , 2018, 262, 86-94.	7.8	53
32	Trapped-Electron-Induced Hole Injection in Perovskite Photodetector with Controllable Gain. <i>Advanced Optical Materials</i> , 2018, 6, 1701189.	7.3	27
33	Synthesis and characterization of Cr-doped WO ₃ nanofibers for conductometric sensors with high xylene sensitivity. <i>Sensors and Actuators B: Chemical</i> , 2018, 265, 355-364.	7.8	60
34	Self-template derived ZnFe ₂ O ₄ double-shell microspheres for chemiresistive gas sensing. <i>Sensors and Actuators B: Chemical</i> , 2018, 265, 625-631.	7.8	64
35	Synthesis of hierarchical 3D porous ZnO microspheres decorated by ultra-small Au nanoparticles and its highly enhanced acetylene gas sensing ability. <i>Journal of Alloys and Compounds</i> , 2018, 731, 1029-1036.	5.5	36
36	Incorporating deep electron traps into perovskite devices: towards high efficiency solar cells and fast photodetectors. <i>Journal of Materials Chemistry A</i> , 2018, 6, 21039-21046.	10.3	8

#	ARTICLE	IF	CITATIONS
37	Using a facile processing method to facilitate charge extraction for polymer solar cells. Journal of Materials Chemistry C, 2018, 6, 11045-11051.	5.5	3
38	A PFTBT modified visible-blind ultraviolet photodetector with a narrow detecting range and high responsivity. Nanotechnology, 2018, 29, 465501.	2.6	2
39	On the high response towards TEA of gas sensors based on Ag-loaded 3D porous ZnO microspheres. Sensors and Actuators B: Chemical, 2018, 270, 492-499.	7.8	124
40	Employing Pentacene To Balance the Charge Transport in Inverted Organic Solar Cells. Journal of Physical Chemistry C, 2018, 122, 17110-17117.	3.1	6
41	Improved gas sensing properties of silver-functionalized ZnSnO ₃ hollow nanocubes. Inorganic Chemistry Frontiers, 2018, 5, 2123-2131.	6.0	56
42	Self-sacrificing templated formation of Co ₃ O ₄ /ZnCo ₂ O ₄ composite hollow nanostructures for highly sensitive detecting acetone vapor. Sensors and Actuators B: Chemical, 2018, 273, 1202-1210.	7.8	69
43	Suppressing TiO ₂ /Perovskite Interfacial Electron Trapping in Perovskite Solar Cell for Efficient Charge Extraction and Improved Device Performance. ACS Sustainable Chemistry and Engineering, 2018, 6, 11295-11302.	6.7	18
44	Polyelectrolyte interlayers with a broad processing window for high efficiency inverted organic solar cells towards mass production. Journal of Materials Chemistry A, 2018, 6, 17662-17670.	10.3	13
45	Self-Sacrificial Template-Driven LaFeO ₃ /±Fe ₂ O ₃ Porous Nano-Octahedrons for Acetone Sensing. ACS Applied Nano Materials, 2018, 1, 4671-4681.	5.0	65
46	The role of polymer dots on efficiency enhancement of organic solar cells: Improving charge transport property. Optics Communications, 2017, 395, 127-132.	2.1	6
47	An easily prepared carbon quantum dots and employment for inverted organic photovoltaic devices. Chemical Engineering Journal, 2017, 315, 621-629.	12.7	33
48	Combining plasmonic trap filling and optical backscattering for highly efficient third generation solar cells. Journal of Materials Chemistry A, 2017, 5, 3995-4002.	10.3	19
49	Improved gas sensing performance with Pd-doped WO ₃ ·H ₂ O nanomaterials for the detection of xylene. Sensors and Actuators B: Chemical, 2017, 244, 837-848.	7.8	50
50	Boosted Electron Transport and Enlarged Built-In Potential by Eliminating the Interface Barrier in Organic Solar Cells. ACS Applied Materials & Interfaces, 2017, 9, 8830-8837.	8.0	25
51	Interface passivation and electron transport improvement of polymer solar cells through embedding a polyfluorene layer. Physical Chemistry Chemical Physics, 2017, 19, 15207-15214.	2.8	8
52	Organics filled one-dimensional TiO ₂ nanowires array ultraviolet detector with enhanced photo-conductivity and dark-resistivity. Nanoscale, 2017, 9, 9095-9103.	5.6	22
53	Decreased Charge Transport Barrier and Recombination of Organic Solar Cells by Constructing Interfacial Nanojunction with Annealing-Free ZnO and Al Layers. ACS Applied Materials & Interfaces, 2017, 9, 22068-22075.	8.0	28
54	Dual Roles of the Fullerene Interlayer on Light Harvesting and Electron Transfer for Highly Efficient Polymer Solar Cells. Journal of Physical Chemistry C, 2017, 121, 8722-8730.	3.1	4

#	ARTICLE	IF	CITATIONS
55	Annealing-Free ZnO:PEI Composite Cathode Interfacial Layer for Efficient Organic Solar Cells. ACS Photonics, 2017, 4, 2952-2958.	6.6	32
56	Increasing the fill factor of inverted polymer bulk heterojunction solar cells by doping PVP modified NaYF ₄ nanoparticles. Integrated Ferroelectrics, 2017, 180, 168-174.	0.7	0
57	Orienting the Microstructure Evolution of Copper Phthalocyanine as an Anode Interlayer in Inverted Polymer Solar Cells for High Performance. ACS Applied Materials & Interfaces, 2017, 9, 32044-32053.	8.0	6
58	Enhanced Photovoltaic Performance of Tetrazine-Based Small Molecules with Conjugated Side Chains. ACS Sustainable Chemistry and Engineering, 2017, 5, 8684-8692.	6.7	10
59	Preparation of three-dimensional Ce-doped Sn ₃ O ₄ hierarchical microsphere and its application on formaldehyde gas sensor. Journal of Alloys and Compounds, 2017, 726, 1092-1100.	5.5	41
60	Synthesis of Ni-doped λ -MoO ₃ nanolamella and their improved gas sensing properties. Sensors and Actuators B: Chemical, 2017, 252, 757-763.	7.8	65
61	Enhanced ethyl acetate sensing performance of Al-doped In ₂ O ₃ microcubes. Sensors and Actuators B: Chemical, 2017, 253, 461-469.	7.8	45
62	The effect of self-depleting in UV photodetector based on simultaneously fabricated TiO ₂ /NiO pn heterojunction and Ni/Au composite electrode. Nanotechnology, 2017, 28, 365505.	2.6	20
63	One-step synthesis and gas sensing properties of hierarchical Fe doped Co ₃ O ₄ nanostructures. Journal of Alloys and Compounds, 2017, 723, 779-786.	5.5	52
64	Synthesis of SnO ₂ nano-dodecahedrons with high-energy facets and their sensing properties to SO ₂ at low temperature. Journal of Alloys and Compounds, 2017, 723, 595-601.	5.5	40
65	High sensitive and fast formaldehyde gas sensor based on Ag-doped LaFeO ₃ nanofibers. Journal of Alloys and Compounds, 2017, 695, 1122-1127.	5.5	102
66	High performance humidity sensor based on metal organic framework MIL-101(Cr) nanoparticles. Journal of Alloys and Compounds, 2017, 695, 520-525.	5.5	82
67	Improved performance of inverted polymer solar cells using Cd ₂ SSe/ZnS quantum dots. Materials Letters, 2017, 188, 244-247.	2.6	1
68	Xylene gas sensor based on Au-loaded WO ₃ ·H ₂ O nanocubes with enhanced sensing performance. Sensors and Actuators B: Chemical, 2017, 238, 364-373.	7.8	118
69	Improving the charge carrier transport of organic solar cells by incorporating a deep energy level molecule. Physical Chemistry Chemical Physics, 2017, 19, 245-250.	2.8	22
70	Research of dual-band microwave photonic filter for WLAN based on optical frequency comb. Applied Optics, 2016, 55, 5520.	2.1	6
71	An organosilane self-assembled monolayer incorporated into polymer solar cells enabling interfacial coherence to improve charge transport. Physical Chemistry Chemical Physics, 2016, 18, 16005-16012.	2.8	5
72	Enhanced electron extraction capability of polymer solar cells via modifying the cathode buffer layer with inorganic quantum dots. Physical Chemistry Chemical Physics, 2016, 18, 11435-11442.	2.8	9

#	ARTICLE	IF	CITATIONS
73	Small molecules based on tetrazine unit for efficient performance solution-processed organic solar cells. <i>Solar Energy Materials and Solar Cells</i> , 2016, 155, 30-37.	6.2	18
74	Versatile dual organic interface layer for performance enhancement of polymer solar cells. <i>Journal of Power Sources</i> , 2016, 333, 99-106.	7.8	17
75	Optimization of PDTS-DTffBT-Based Solar Cell Performance through Control of Polymer Molecular Weight. <i>Journal of Physical Chemistry C</i> , 2016, 120, 19513-19520.	3.1	8
76	Performance enhancement of organic photovoltaic devices enabled by Au nanoarrows inducing surface plasmonic resonance effect. <i>Physical Chemistry Chemical Physics</i> , 2016, 18, 24285-24289.	2.8	10
77	Synthesis and enhanced gas sensing properties of Au-nanoparticle decorated CdS nanowires. <i>RSC Advances</i> , 2016, 6, 70907-70912.	3.6	23
78	One-step synthesis and the enhanced xylene-sensing properties of Fe-doped MoO ₃ nanobelts. <i>RSC Advances</i> , 2016, 6, 106364-106369.	3.6	31
79	Mechanism of Polyfluorene Interlayer in Ultraviolet Photodetector: Barrier-Blocking Electron Transport and Light-Inducing Hole Injection. <i>Journal of Physical Chemistry C</i> , 2016, 120, 26103-26109.	3.1	7
80	Fabrication of Sm-doped porous In ₂ O ₃ nanotubes and their excellent formaldehyde-sensing properties. <i>Journal of Materials Science: Materials in Electronics</i> , 2016, 27, 9870-9876.	2.2	9
81	Employing inorganic/organic hybrid interface layer to improve electron transfer for inverted polymer solar cells. <i>Electrochimica Acta</i> , 2016, 210, 874-879.	5.2	4
82	Efficiency Improvement of Organic Solar Cells via Introducing Combined Anode Buffer Layer To Facilitate Hole Extraction. <i>Journal of Physical Chemistry C</i> , 2016, 120, 13954-13962.	3.1	16
83	Enhanced Electron Extraction Capability of Polymer Solar Cells via Employing Electrostatically Self-Assembled Molecule on Cathode Interfacial Layer. <i>ACS Applied Materials & Interfaces</i> , 2016, 8, 8224-8231.	8.0	29
84	Performance Improvement of Polymer Solar Cells by Surface-Energy-Induced Dual Plasmon Resonance. <i>ACS Applied Materials & Interfaces</i> , 2016, 8, 6183-6189.	8.0	46
85	Hydrothermal synthesis and enhanced xylene-sensing properties of pompon-like Cr-doped Co ₃ O ₄ hierarchical nanostructures. <i>RSC Advances</i> , 2016, 6, 22889-22895.	3.6	24
86	Applications for rapid formaldehyde nanoreactor with hierarchical and spherical structure. <i>Sensors and Actuators B: Chemical</i> , 2016, 227, 475-481.	7.8	8
87	Unique Gold Nanorods Embedded Active Layer Enabling Strong Plasmonic Effect To Improve the Performance of Polymer Photovoltaic Devices. <i>Journal of Physical Chemistry C</i> , 2016, 120, 6198-6205.	3.1	32
88	Enhanced toluene sensing performance of gold-functionalized WO ₃ ·H ₂ O nanosheets. <i>Sensors and Actuators B: Chemical</i> , 2016, 223, 761-767.	7.8	58
89	Three dimensions sphere formaldehyde nanosensor applications: preparation and sensing properties. <i>RSC Advances</i> , 2015, 5, 50336-50343.	3.6	14
90	Synthesis and photovoltaic properties of dithieno[3,2-b:2'â€²,3'â€²-d]silole-based conjugated copolymers. <i>Journal of Materials Chemistry A</i> , 2015, 3, 13794-13800.	10.3	18

#	ARTICLE	IF	CITATIONS
91	Humidity sensing properties of CeO ₂ @NiO nanocomposite materials. Journal of Materials Science: Materials in Electronics, 2015, 26, 3083-3089.	2.2	4
92	Visible-light photodetector with enhanced performance based on a ZnO@CdS heterostructure. Journal of Materials Chemistry C, 2015, 3, 2231-2236.	5.5	43
93	Improved color rendering index of low band gap semi-transparent polymer solar cells using one-dimensional photonic crystals. RSC Advances, 2015, 5, 54638-54644.	3.6	14
94	Single passband microwave photonic filter with high selectivity and large tunable range. Optical and Quantum Electronics, 2015, 47, 1589-1597.	3.3	4
95	Xylene sensor based on In_2MoO_7 nanobelts with fast response and low operating temperature. RSC Advances, 2015, 5, 18655-18659.	3.6	33
96	Special nanostructure control of ethanol sensing characteristics based on Au@In ₂ O ₃ sensor with good selectivity and rapid response. RSC Advances, 2015, 5, 9884-9890.	3.6	40
97	Humidity sensor based on AlPO ₄ -5 zeolite with high responsivity and its sensing mechanism. Sensors and Actuators B: Chemical, 2015, 212, 242-247.	7.8	20
98	Improving the efficiency of inverted polymer solar cells by introducing inorganic dopants. Physical Chemistry Chemical Physics, 2015, 17, 7960-7965.	2.8	20
99	Highly stabilized and rapid sensing acetone sensor based on Au nanoparticle-decorated flower-like ZnO microstructures. Journal of Alloys and Compounds, 2015, 650, 37-44.	5.5	55
100	Improved Power Conversion Efficiency of Inverted Organic Solar Cells by Incorporating Au Nanorods into Active Layer. ACS Applied Materials & Interfaces, 2015, 7, 15848-15854.	8.0	20
101	The preparation of Cr ₂ O ₃ @WO ₃ hierarchical nanostructures and their application in the detection of volatile organic compounds (VOCs). RSC Advances, 2015, 5, 61528-61534.	3.6	23
102	A new type of acetylene gas sensor based on a hollow heterostructure. RSC Advances, 2015, 5, 61521-61527.	3.6	32
103	The study of an ultrawide tunable range single passband microwave photonic notch filter. Optik, 2015, 126, 2512-2517.	2.9	1
104	Efficiency Improvement of Inverted Organic Solar Cells via Introducing a Series of Polyfluorene Dots in Electron Transport Layer. Journal of Physical Chemistry C, 2015, 119, 16462-16467.	3.1	2
105	Highly Efficient Semitransparent Polymer Solar Cells with Color Rendering Index Approaching 100 Using One-Dimensional Photonic Crystal. ACS Applied Materials & Interfaces, 2015, 7, 9920-9928.	8.0	81
106	Synergistically improved formaldehyde gas sensing properties of SnO ₂ microspheres by indium and palladium co-doping. Ceramics International, 2015, 41, 7329-7336.	4.8	55
107	Unraveling the effect of polymer dots doping in inverted low bandgap organic solar cells. Physical Chemistry Chemical Physics, 2015, 17, 16086-16091.	2.8	6
108	Humidity sensing properties of SrTiO ₃ nanospheres with high sensitivity and rapid response. RSC Advances, 2015, 5, 22879-22883.	3.6	16

#	ARTICLE	IF	CITATIONS
109	Highly Efficient Low-Bandgap Polymer Solar Cells with Solution-Processed and Annealing-Free Phosphomolybdic Acid as Hole-Transport Layers. ACS Applied Materials & Interfaces, 2015, 7, 5367-5372.	8.0	52
110	Xylene gas sensor based on Ni doped TiO ₂ bowl-like submicron particles with enhanced sensing performance. RSC Advances, 2015, 5, 28105-28110.	3.6	43
111	Xylene gas sensor based on $\text{In}_2\text{MoO}_3/\text{In}_2\text{Fe}_2\text{O}_3$ heterostructure with high response and low operating temperature. RSC Advances, 2015, 5, 39442-39448.	3.6	60
112	Enhancing the light-harvesting and charge transport properties of polymer solar cells by embedding NaLuF ₄ :Yb,Tm nanorods. RSC Advances, 2015, 5, 32891-32896.	3.6	8
113	Enhanced performance of a TiO ₂ ultraviolet detector modified with graphene oxide. RSC Advances, 2015, 5, 83795-83800.	3.6	25
114	Synthesis and highly enhanced acetylene sensing properties of Au nanoparticle-decorated hexagonal ZnO nanorings. RSC Advances, 2015, 5, 87132-87138.	3.6	20
115	The Performance Enhancement of Polymer Solar Cells by Introducing Cadmium-Free Quantum Dots. Journal of Physical Chemistry C, 2015, 119, 26747-26752.	3.1	25
116	The operation mechanism of poly(9,9-dioctylfluorenyl-2,7-diyl) dots in high efficiency polymer solar cells. Applied Physics Letters, 2015, 106, .	3.3	4
117	Optically tunable frequency-sextupling optoelectronic oscillator based on Brillouin gain-loss compensation and carrier phase-shifted double sideband modulation. Optical and Quantum Electronics, 2015, 47, 3455-3465.	3.3	4
118	Low-temperature synthesis of WO ₃ nanolamella and their sensing properties for xylene. RSC Advances, 2015, 5, 85598-85605.	3.6	15
119	Surface Plasmon Resonance Enhanced Polymer Solar Cells by Thermally Evaporating Au into Buffer Layer. ACS Applied Materials & Interfaces, 2015, 7, 18866-18871.	8.0	45
120	Preparation of Pd nanoparticle-decorated hollow SnO ₂ nanofibers and their enhanced formaldehyde sensing properties. Journal of Alloys and Compounds, 2015, 651, 690-698.	5.5	99
121	High performance ultraviolet detector based on SrTiO ₃ /TiO ₂ heterostructure fabricated by two steps in situ hydrothermal method. Journal of Alloys and Compounds, 2015, 650, 97-101.	5.5	20
122	Improved Efficiency in Dithieno[3,2-b:2',3'-d]silole-Based Polymer Solar Cells by the Insertion of ZnO Optical Spacer. Journal of Physical Chemistry C, 2015, 119, 20817-20822.	3.1	13
123	Gas Sensors Based on Metal Sulfide Zn _{1-x} Cd _x S Nanowires with Excellent Performance. ACS Applied Materials & Interfaces, 2015, 7, 20793-20800.	8.0	60
124	Hexagonal ZnO nanorings: synthesis, formation mechanism and trimethylamine sensing properties. RSC Advances, 2015, 5, 80561-80567.	3.6	38
125	Humidity sensing properties of MoO ₃ -NiO nanocomposite materials. Ceramics International, 2015, 41, 4348-4353.	4.8	26
126	Bandwidth reconfigurable microwave photonic filter based on stimulated Brillouin scattering. Optical Fiber Technology, 2015, 21, 187-192.	2.7	4

#	ARTICLE	IF	CITATIONS
127	Enhanced H ₂ S sensing characteristics of CuO-NiO core-shell microspheres sensors. <i>Sensors and Actuators B: Chemical</i> , 2015, 209, 515-523.	7.8	177
128	Electrospun nanofibers of p-type NiO/n-type ZnO heterojunction with different NiO content and its influence on trimethylamine sensing properties. <i>Sensors and Actuators B: Chemical</i> , 2015, 207, 90-96.	7.8	91
129	High performance ultraviolet detector based on TiO ₂ /ZnO heterojunction. <i>Journal of Alloys and Compounds</i> , 2015, 618, 551-554.	5.5	51
130	Ultraviolet detector based on TiO ₂ nanowire array/polymer hybrids with low dark current. <i>Journal of Alloys and Compounds</i> , 2015, 618, 233-235.	5.5	27
131	The Role of Fe ₃ O ₄ Nanocrystal Film in Bilayer-Heterojunction CuPc/C ₆₀ /Solar Cells. <i>Journal of Nanoscience and Nanotechnology</i> , 2014, 14, 3623-3626.	0.9	0
132	The role of Au nanorods in highly efficient inverted low bandgap polymer solar cells. <i>Applied Physics Letters</i> , 2014, 105, 223305.	3.3	12
133	Preparation and Ethanol Sensing Properties of In ₂ O ₃ Nanotubes. <i>Journal of Nanoscience and Nanotechnology</i> , 2014, 14, 3653-3657.	0.9	5
134	Photovoltaic Properties of ZrO ₂ /TiO ₂ /SnO ₂ Solid Solution Nanowire Arrays. <i>Journal of Nanoscience and Nanotechnology</i> , 2014, 14, 3731-3734.	0.9	5
135	Solar-Blind Photodetector Based on LaAlO ₃ with Low Dark Current. <i>Journal of Nanoscience and Nanotechnology</i> , 2014, 14, 3827-3830.	0.9	5
136	Application of Solution-Processed V ₂ O ₅ in Inverted Polymer Solar Cells Based on Fluorine-Doped Tin Oxide Substrate. <i>Journal of Nanoscience and Nanotechnology</i> , 2014, 14, 4214-4217.	0.9	10
137	Excellent gas sensing and optical properties of single-crystalline cadmium sulfide nanowires. <i>RSC Advances</i> , 2014, 4, 61691-61697.	3.6	44
138	Light harvesting enhancement toward low IPCE region of semitransparent polymer solar cells via one-dimensional photonic crystal reflectors. <i>Solar Energy Materials and Solar Cells</i> , 2014, 127, 27-32.	6.2	24
139	Design of thermo-optic tunable optical filter based on Si/Air DBR and polymer Fabry-Perot microcavity in SOI. <i>Optik</i> , 2014, 125, 2885-2890.	2.9	5
140	Hierarchical Fe ₃ O ₄ @Co ₃ O ₄ core-shell microspheres: Preparation and acetone sensing properties. <i>Sensors and Actuators B: Chemical</i> , 2014, 199, 346-353.	7.8	98
141	Effects of surface self-assembled NH ₄ ⁺ on the performance of TiO ₂ -based ultraviolet photodetectors. <i>Journal of Alloys and Compounds</i> , 2014, 601, 104-107.	5.5	17
142	Humidity sensing properties of FeCl ₃ -NH ₂ -MIL-125(Ti) composites. <i>Sensors and Actuators B: Chemical</i> , 2014, 201, 281-285.	7.8	34
143	Highly efficient and high transmittance semitransparent polymer solar cells with one-dimensional photonic crystals as distributed Bragg reflectors. <i>Organic Electronics</i> , 2014, 15, 470-477.	2.6	45
144	Semitransparent Polymer Solar Cells with 5% Power Conversion Efficiency Using Photonic Crystal Reflector. <i>ACS Applied Materials & Interfaces</i> , 2014, 6, 599-605.	8.0	66

#	ARTICLE	IF	CITATIONS
145	Efficiency enhancement of inverted organic solar cells by introducing PFDTBT quantum dots into PCDTBT:PC71BM active layer. <i>Organic Electronics</i> , 2014, 15, 2632-2638.	2.6	15
146	Fe ₃ O ₄ @NiO core-shell composites: Hydrothermal synthesis and toluene sensing properties. <i>Materials Letters</i> , 2014, 132, 167-170.	2.6	35
147	Ultrahigh responsivity UV detector based on TiO ₂ /Pt-doped TiO ₂ multilayer nanofilms. <i>Journal of Alloys and Compounds</i> , 2014, 616, 155-158.	5.5	15
148	Effects of growth substrates on the morphologies of TiO ₂ nanowire arrays and the performance of assembled UV detectors. <i>Applied Surface Science</i> , 2014, 315, 55-58.	6.1	26
149	Performance improvement of inverted polymer solar cells thermally evaporating CuI as an anode buffer layer. <i>Synthetic Metals</i> , 2014, 198, 1-5.	3.9	15
150	Influences of different interdigital spacing on the performance of UV photodetectors based on ZnO nanofibers. <i>Applied Surface Science</i> , 2014, 307, 20-23.	6.1	44
151	Preparation and Xylene Sensing Properties of Co ₃ O ₄ Nanofibers. <i>International Journal of Applied Ceramic Technology</i> , 2014, 11, 619-625.	2.1	45
152	Facile fabrication of NaTaO ₃ film and its photoelectric properties. <i>Journal of Alloys and Compounds</i> , 2014, 602, 322-325.	5.5	27
153	V-doped In ₂ O ₃ nanofibers for H ₂ S detection at low temperature. <i>Ceramics International</i> , 2014, 40, 6685-6689.	4.8	55
154	Template-free synthesis of Cu ₂ O@Co ₃ O ₄ core-shell composites and their application in gas sensing. <i>RSC Advances</i> , 2014, 4, 24211-24216.	3.6	27
155	Highly efficient ITO-free polymer solar cells based on metal resonant microcavity using WO ₃ /Au/WO ₃ as transparent electrodes. <i>Organic Electronics</i> , 2014, 15, 1545-1551.	2.6	23
156	The Short Circuit Current Improvement in P3HT:PCBM Based Polymer Solar Cell by Introducing PSBTBT as Additional Electron Donor. <i>Journal of Nanoscience and Nanotechnology</i> , 2014, 14, 3446-3449.	0.9	1
157	Simultaneous improvement in efficiency and transmittance of low bandgap semitransparent polymer solar cells with one-dimensional photonic crystals. <i>Solar Energy Materials and Solar Cells</i> , 2013, 117, 198-202.	6.2	36
158	Performance study of microwave photonic phase shifter based on vector-sum technique. <i>Optik</i> , 2013, 124, 6140-6145.	2.9	2
159	Low temperature operating In _{2-x} Ni _x O ₃ sensors with high response and good selectivity for NO ₂ gas. <i>Journal of Alloys and Compounds</i> , 2013, 581, 653-658.	5.5	23
160	A novel humidity sensor based on NH ₂ -MIL-125(Ti) metal organic framework with high responsiveness. <i>Journal of Nanoparticle Research</i> , 2013, 15, 1.	1.9	76
161	Role of solution-processed V ₂ O ₅ in P3HT:PCBM based inverted polymer solar cells. <i>Synthetic Metals</i> , 2013, 170, 7-10.	3.9	10
162	Electrospun ZnO Nanofibers Based Ultraviolet Detector with High Responsivity. <i>Journal of the American Ceramic Society</i> , 2013, 96, 3183-3187.	3.8	21

#	ARTICLE	IF	CITATIONS
163	The role of Ag nanoparticles in inverted polymer solar cells: Surface plasmon resonance and backscattering centers. Applied Physics Letters, 2013, 102, .	3.3	26
164	An organic–inorganic hybrid UV photodetector based on a TiO ₂ nanobowl array with high spectrum selectivity. RSC Advances, 2013, 3, 21413.	3.6	27
165	Ultraviolet Detector Based on $\text{SrZr}_{0.1}\text{Ti}_{0.9}\text{O}_3$ Film. IEEE Electron Device Letters, 2013, 34, 420-422.	3.9	4
166	NaTaO_3 -Based Ultraviolet Photodetector With Capacitive Efficacy. IEEE Electron Device Letters, 2013, 34, 1539-1541.	3.9	6
167	TiO ₂ ultraviolet detector based on LaAlO ₃ substrate with low dark current. Journal of Alloys and Compounds, 2013, 580, 614-617.	5.5	31
168	High response solar-blind ultraviolet photodetector based on Zr _{0.5} Ti _{0.5} O ₂ film. Applied Surface Science, 2013, 268, 312-316.	6.1	23
169	Sodium Titanate Nanorod Moisture Sensor and Its Sensing Mechanism. IEEE Electron Device Letters, 2013, 34, 1424-1426.	3.9	3
170	Analysis of plasma waves resonant detection for terahertz radiation in high mobility field effect transistor. Optik, 2013, 124, 6408-6410.	2.9	0
171	Influences of surface capping with electrostatically self-assembled PEI on the photoresponse of a TiO ₂ thin film. Chemical Communications, 2013, 49, 6328.	4.1	13
172	Multiple microwave frequencies measurement based on stimulated Brillouin scattering with improved measurement range. Optics Express, 2013, 21, 31740.	3.4	25
173	Photovoltaic ultraviolet detectors based on $\text{Zr}_{0.004}\text{Ti}_{0.096}\text{O}_{2.0}$ solid solution nanowire arrays. Applied Optics, 2013, 52, 750.	1.8	3
174	An ultrawide tunable range single passband microwave photonic filter based on stimulated Brillouin scattering. Optics Express, 2013, 21, 2718.	3.4	21
175	Performance improvement of inverted polymer solar cells by doping Au nanoparticles into TiO ₂ cathode buffer layer. Applied Physics Letters, 2013, 103, .	3.3	23
176	Performance Improvement of Low-Band-Gap Polymer Solar Cells by Optical Microcavity Effect. IEEE Electron Device Letters, 2013, 34, 87-89.	3.9	8
177	Zr _{0.05} Ti _{0.95} O ₂ -Nanowire-Based Ultraviolet Photodetector with Self-Powered Properties. Applied Physics Express, 2013, 6, 062002.	2.4	1
178	Ultraviolet photodetector with high internal gain enhanced by TiO ₂ /SrTiO ₃ heterojunction. Optics Express, 2012, 20, 5936.	3.4	36
179	Schottky barrier characteristics and internal gain mechanism of TiO ₂ UV detectors. Applied Optics, 2012, 51, 894.	1.8	16
180	Semitransparent polymer solar cells with one-dimensional (WO ₃ /LiF)/N photonic crystals. Applied Physics Letters, 2012, 101, .	3.3	37

#	ARTICLE	IF	CITATIONS
181	Open-circuit voltage enhancement of inverted polymer bulk heterojunction solar cells by doping NaYF ₄ nanoparticles/PVP composites. Journal of Materials Chemistry, 2012, 22, 22382.	6.7	32
182	A novel humidity sensor based on NaTaO ₃ nanocrystalline. Sensors and Actuators B: Chemical, 2012, 174, 485-489.	7.8	52
183	MSM Ultraviolet Detectors Based on Zr _{0.1} Ti _{0.9} O ₂ Solid Solution. Integrated Ferroelectrics, 2012, 138, 94-99.	0.7	0
184	Schottky Diode Ultraviolet Detector Based on TiO ₂ Nanowire Array. IEEE Electron Device Letters, 2012, 33, 83-85.	3.9	60
185	Preparation and NO ₂ Sensing Properties of the Ni-Doped In ₂ O ₃ Nanofibers. Integrated Ferroelectrics, 2012, 138, 71-76.	0.7	7
186	TiO ₂ Ultraviolet Detectors with Sandwich Structure. Integrated Ferroelectrics, 2012, 135, 138-143.	0.7	0
187	Modelling of Charge Carrier Mobility Effect on Organic Bulk Heterojunction Solar Cells. Integrated Ferroelectrics, 2012, 138, 38-43.	0.7	0
188	Efficient Semitransparent Inverted Polymer Solar Cells With the Anode of Tunable Incident Light Transmittance. IEEE Electron Device Letters, 2012, 33, 1027-1029.	3.9	6
189	Photoelectron Properties of Nanocrystalline TiO ₂ Films Prepared by a Powerful Hydrothermal Technique. Journal of the American Ceramic Society, 2012, 95, 1980-1984.	3.8	6
190	Highly efficient rapid ethanol sensing based on In ₂ Ni O ₃ nanofibers. Sensors and Actuators B: Chemical, 2012, 166-167, 83-88.	7.8	54
191	Semitransparent inverted polymer solar cells using MoO ₃ /Ag/V ₂ O ₅ as transparent anodes. Solar Energy Materials and Solar Cells, 2012, 97, 59-63.	6.2	40
192	Performance improvement of inverted polymer solar cells thermally evaporating nickel oxide as an anode buffer layer. Solar Energy Materials and Solar Cells, 2012, 98, 212-215.	6.2	60
193	Effects of the optical microcavity on the performance of ITO-free polymer solar cells with WO ₃ /Ag/WO ₃ transparent electrode. Solar Energy Materials and Solar Cells, 2012, 100, 226-230.	6.2	59
194	The Photocurrent Improvement of Inverted Polymer Solar Cells Using ZnPc to Extend Light Absorption Range. , 2011, , .		1
195	Zr _{0.27} Ti _{0.73} O ₂ -Based MSM Ultraviolet Detectors With Pt Electrodes. IEEE Electron Device Letters, 2011, 32, 653-655.	3.9	23
196	The Study of Transmission Characteristics of a 17x17 All Fluorinated Polyimide Arrayed Waveguide Grating Multiplexer. , 2011, , .		1
197	Tailoring Spatial Distribution of the Optical Field Intensity in Semitransparent Inverted Organic Solar Cells. Journal of Physical Chemistry C, 2011, 115, 12611-12615.	3.1	31
198	Design of a vector-sum integrated microwave photonic phase shifter in silicon-on-insulator waveguides. Applied Optics, 2011, 50, 2523.	2.1	6

#	ARTICLE	IF	CITATIONS
199	Photoelectric Properties of TiO ₂ -ZrO ₂ Thin Films Prepared by Sol-Gel Method. Journal of Nanoscience and Nanotechnology, 2011, 11, 10003-10006.	0.9	6
200	Ethanol sensing properties of LaCoFeO ₃ nanoparticles: Effects of calcination temperature, Co-doping, and carbon nanotube-treatment. Sensors and Actuators B: Chemical, 2011, 155, 232-238.	7.8	65
201	Semitransparent polymer solar cells using V ₂ O ₅ /Ag/V ₂ O ₅ as transparent anodes. Organic Electronics, 2011, 12, 1223-1226.	2.6	68
202	Semitransparent inverted polymer solar cells using MoO ₃ /Ag/WO ₃ as highly transparent anodes. Solar Energy Materials and Solar Cells, 2011, 95, 877-880.	6.2	64
203	$\text{Zr}_x\text{Ti}_{1-x}\text{O}_2$ -Based Ultraviolet Detectors Series. IEEE Electron Device Letters, 2011, 32, 934-936.	3.9	18
204	Photonic generation of ultrawideband doublet pulse based on cross-absorption modulation in an electroabsorption modulator. , 2011, , .		1
205	Study on PDLC films for variable optical attenuation in optical communication. , 2011, , .		0
206	Short-circuit current density improvement of inverted polymer solar cells using PbPc to enhance photon absorption over 600 nm. Solar Energy Materials and Solar Cells, 2010, 94, 2451-2454.	6.2	15
207	Analysis and design of tunable wideband microwave photonics phase shifter based on Fabry-Perot cavity and Bragg mirrors in silicon-on-insulator waveguide. Applied Optics, 2010, 49, 2391.	2.1	11
208	Role of tungsten oxide in inverted polymer solar cells. Applied Physics Letters, 2009, 94, .	3.3	294
209	Synthesis, characterization, and gas-sensing property for HCHO of Ag-doped In ₂ O ₃ nanocrystalline powders. Materials Chemistry and Physics, 2009, 117, 489-493.	4.0	47
210	HCHO sensing properties of Ag-doped In ₂ O ₃ nanofibers synthesized by electrospinning. Materials Letters, 2009, 63, 1750-1753.	2.6	36
211	Semitransparent inverted polymer solar cells with MoO ₃ /Ag/MoO ₃ as transparent electrode. Applied Physics Letters, 2009, 95, .	3.3	91
212	Metal-semiconductor-metal TiO ₂ ultraviolet detectors with Ni electrodes. Applied Physics Letters, 2009, 94, .	3.3	140
213	Research on MEMS acceleration sensor detection circuit based on adaptive filter. , 2009, , .		2
214	Photocatalytic degradation of C.I. Acid Orange 52 in the presence of Zn-doped TiO ₂ prepared by a stearic acid gel method. Dyes and Pigments, 2008, 77, 204-209.	3.7	74
215	Performance improvement of inverted polymer solar cells with different top electrodes by introducing a MoO ₃ buffer layer. Applied Physics Letters, 2008, 93, .	3.3	211
216	Fabrication of TiO ₂ Schottky barrier diodes by RF magnetron sputtering. , 2008, , .		2

#	ARTICLE	IF	CITATIONS
217	Affect on the UV polymerization condition of polymer liquid crystal materials for variable optical attenuator. , 2008, , .		0
218	Performance improvement of TiO ₂ •P3HT solar cells using CuPc as a sensitizer. Applied Physics Letters, 2008, 92, 073307.	3.3	67
219	TiO ₂ based metal-semiconductor-metal ultraviolet photodetectors. Applied Physics Letters, 2007, 90, 201118.	3.3	170
220	Preparation of polymer liquid crystal material for use in the variable optical attenuator. , 2005, 5623, 541.		2
221	Design and fabrication of slant-counter electrodes for optical switches. Microwave and Optical Technology Letters, 2004, 41, 273-275.	1.4	7
222	Effect of the fluorinated groups on nematic liquid crystal alignment on monomer crosslinked film. Thin Solid Films, 2004, 466, 326-330.	1.8	8
223	New method of optical variable attenuator with polymer-network liquid crystals. , 2004, , .		0
224	Transparent ITO electrode in the polymer network liquid crystal variable optical attenuator. , 2004, 5280, 397.		0
225	Surface state studies of TiO ₂ nanoparticles and photocatalytic degradation of methyl orange in aqueous TiO ₂ dispersions. Materials Chemistry and Physics, 2001, 69, 7-9.	4.0	64
226	Microwave absorptive behavior of ZnCo-substituted W-type Ba hexaferrite nanocrystalline composite material. Journal of Magnetism and Magnetic Materials, 2000, 212, 175-177.	2.3	162
227	Surface oxidation for enhancing the hydrogen evolution reaction of metal nitrides: a theoretical study on vanadium nitride. Materials Advances, 0, , .	5.4	4