

Junphil Hwang

List of Publications by Year in Descending Order

Source: <https://exaly.com/author-pdf/9419716/junphil-hwang-publications-by-year.pdf>

Version: 2024-04-23

This document has been generated based on the publications and citations recorded by exaly.com. For the latest version of this publication list, visit the link given above.

The third column is the impact factor (IF) of the journal, and the fourth column is the number of citations of the article.

20
papers

720
citations

13
h-index

20
g-index

20
ext. papers

830
ext. citations

8.2
avg, IF

3.78
L-index

#	Paper	IF	Citations
20	Enhancement of thermoelectric performance in a non-toxic CuInTe ₂ /SnTe coated grain nanocomposite. <i>Journal of Materials Chemistry A</i> , 2021 , 9, 14851-14858	13	6
19	High Thermoelectric Performance of ZnO by Coherent Phonon Scattering and Optimized Charge Transport. <i>Advanced Functional Materials</i> , 2021 , 31, 2105008	15.6	3
18	Synergetic enhancement of thermoelectric performances by localized carrier and phonon scattering in Cu ₂ Se with incorporated fullerene nanoparticles. <i>Nanoscale Advances</i> , 2021 , 3, 3107-3113	5.1	3
17	Size-Controlled Au-CuSe Core-Shell Nanoparticles and Their Thermoelectric Properties. <i>ACS Applied Materials & Interfaces</i> , 2020 , 12, 36589-36599	9.5	4
16	Gigantic Phonon-Scattering Cross Section To Enhance Thermoelectric Performance in Bulk Crystals. <i>ACS Nano</i> , 2019 , 13, 8347-8355	16.7	38
15	Improved thermoelectric properties of n-type Bi ₂ Te ₃ alloy deriving from two-phased heterostructure by the reduction of CuI with Sn. <i>Journal of Materials Science: Materials in Electronics</i> , 2019 , 30, 1282-1291	2.1	8
14	Optimization of peak and average figures of merits for In & Se co-doped SnTe alloys. <i>Inorganic Chemistry Frontiers</i> , 2018 , 5, 793-801	6.8	14
13	High power output from body heat harvesting based on flexible thermoelectric system with low thermal contact resistance. <i>Journal Physics D: Applied Physics</i> , 2018 , 51, 365501	3	27
12	Enhancement of the thermoelectric performance of bulk SnTe alloys via the synergistic effect of band structure modification and chemical bond softening. <i>Journal of Materials Chemistry A</i> , 2017 , 5, 14163-14173	13.1	148
11	Low Thermal Conductivity and High Thermoelectric Performance in In ₄ Se ₃ with Phase-Separated Indium Inclusions. <i>Journal of Electronic Materials</i> , 2017 , 46, 1444-1450	1.9	8
10	Ultralow Lattice Thermal Conductivity and Enhanced Thermoelectric Performance in SnTe:Ga Materials. <i>Chemistry of Materials</i> , 2017 , 29, 612-620	9.6	76
9	More than half reduction in price per watt of thermoelectric device without increasing the thermoelectric figure of merit of materials. <i>Applied Energy</i> , 2017 , 205, 1459-1466	10.7	14
8	Mat-like flexible thermoelectric system based on rigid inorganic bulk materials. <i>Journal Physics D: Applied Physics</i> , 2017 , 50, 494006	3	21
7	Band Degeneracy, Low Thermal Conductivity, and High Thermoelectric Figure of Merit in SnTe _{1-x} Te _x Alloys. <i>Chemistry of Materials</i> , 2016 , 28, 376-384	9.6	180
6	High Thermoelectric Performance of a Heterogeneous PbTe Nanocomposite. <i>Chemistry of Materials</i> , 2015 , 27, 944-949	9.6	90
5	New device architecture of a thermoelectric energy conversion for recovering low-quality heat. <i>Applied Physics A: Materials Science and Processing</i> , 2014 , 114, 1201-1208	2.6	13
4	Right sizes of nano- and microstructures for high-performance and rigid bulk thermoelectrics. <i>Proceedings of the National Academy of Sciences of the United States of America</i> , 2014 , 111, 10949-54	11.5	108

- 3 Study on Metalizing 2% Na-PbTe for Thermoelectric Device. *Transactions of the Society of Information Storage Systems*, **2014**, 10, 32-38
- 2 Thermoelectricity in semiconductor nanowires. *Physica Status Solidi - Rapid Research Letters*, **2013**, 7, 767-780 2.5 24
- 1 Large enhancement in the thermoelectric properties of Pb_{0.98}Na_{0.02}Te by optimizing the synthesis conditions. *Journal of Materials Chemistry A*, **2013**, 1, 11269 13 35