

# Djurado Elisabeth

## List of Publications by Year in Descending Order

**Source:** <https://exaly.com/author-pdf/9519629/djurado-elisabeth-publications-by-year.pdf>

**Version:** 2024-04-23

This document has been generated based on the publications and citations recorded by exaly.com. For the latest version of this publication list, visit the link given above.

The third column is the impact factor (IF) of the journal, and the fourth column is the number of citations of the article.

115  
papers

2,627  
citations

29  
h-index

43  
g-index

122  
ext. papers

2,886  
ext. citations

5.1  
avg, IF

5.14  
L-index

#	Paper	IF	Citations
115	Reaction Mechanisms of La <sub>2</sub> NiO <sub>4</sub> + $\delta$ Oxygen Electrodes Operated in Electrolysis and Fuel Cell Mode. <i>Journal of the Electrochemical Society</i> , <b>2022</b> , 169, 034518	3.9	1
114	One-step fabrication of single-phase hydroxyapatite coatings on Ti-alloy implants by electrostatic spray deposition: From microstructural investigation to in vitro studies. <i>Surface and Coatings Technology</i> , <b>2021</b> , 427, 127805	4.4	2
113	Design of advanced one-step hydroxyapatite coatings for biomedical applications using the electrostatic spray deposition. <i>Applied Surface Science</i> , <b>2021</b> , 541, 148462	6.7	9
112	Electrode kinetics of porous Ni-3YSZ cermet operated in fuel cell and electrolysis modes for solid oxide cell application. <i>Electrochimica Acta</i> , <b>2021</b> , 389, 138765	6.7	3
111	Coupling sol-gel with electrospray deposition: Towards nanotextured bioactive glass coatings. <i>Journal of the European Ceramic Society</i> , <b>2021</b> , 41, 7288-7300	6	2
110	Durability of nanostructured LaPrNiO <sub>4</sub> + $\delta$ electrode for solid oxide cells: Electrochemical, microstructural, and structural investigation. <i>Journal of Power Sources</i> , <b>2020</b> , 450, 227724	8.9	4
109	Electrostatic spray deposited Ca <sub>3</sub> Co <sub>4</sub> O <sub>9</sub> + $\delta$ and Ca <sub>3</sub> Co <sub>4</sub> O <sub>9</sub> + $\delta$ Ce <sub>0.9</sub> Gd <sub>0.1</sub> O <sub>1.95</sub> cathodes for SOFC. <i>Electrochimica Acta</i> , <b>2020</b> , 362, 137142	6.7	10
108	K- and Cu-doped CaTiO <sub>3</sub> -based nanostructured hollow spheres as alternative catalysts to produce fatty acid ethyl esters as potential biodiesel. <i>Applied Catalysis B: Environmental</i> , <b>2020</b> , 272, 118986	21.8	14
107	Highly efficient architected Pr <sub>6</sub> O <sub>11</sub> oxygen electrode for solid oxide fuel cell. <i>Journal of Power Sources</i> , <b>2019</b> , 419, 171-180	8.9	9
106	Cyclic voltammetry and high-frequency series resistance of La <sub>0.6</sub> Sr <sub>0.4</sub> Co <sub>0.2</sub> Fe <sub>0.8</sub> O <sub>3</sub> + $\delta$ electrode deposited on GDC: Effect of the electrode microstructure and the oxygen partial pressure. <i>Electrochimica Acta</i> , <b>2019</b> , 304, 312-322	6.7	6
105	Improving the electrochemical performance of LaPrNiO <sub>4</sub> + $\delta$ as an oxygen electrode for intermediate temperature solid oxide cells by varying the architectural design. <i>Journal of Electroanalytical Chemistry</i> , <b>2019</b> , 849, 113373	4.1	3
104	Enhanced catalytic activity of nanostructured, A-site deficient (La <sub>0.7</sub> Sr <sub>0.3</sub> ) <sub>0.95</sub> (Co <sub>0.2</sub> Fe <sub>0.8</sub> )O <sub>3</sub> + $\delta$ for SOFC cathodes. <i>Journal of Materials Chemistry A</i> , <b>2019</b> , 7, 25102-25111	13	25
103	An efficient hierarchical nanostructured Pr <sub>6</sub> O <sub>11</sub> electrode for solid oxide fuel cells. <i>Journal of Materials Chemistry A</i> , <b>2018</b> , 6, 10787-10802	13	13
102	Oxygen Reduction Reaction Electrocatalysis in Alkaline Electrolyte on Glassy-Carbon-Supported Nanostructured Pr <sub>6</sub> O <sub>11</sub> Thin-Films. <i>Catalysts</i> , <b>2018</b> , 8, 461	4	4
101	A-site order/disorder in the NdBaMn <sub>2</sub> O <sub>5</sub> + $\delta$ SOFC electrode material monitored in situ by neutron diffraction under hydrogen flow. <i>Journal of Materials Chemistry A</i> , <b>2017</b> , 5, 11078-11085	13	9
100	Synthesis and structural characterization of calcium titanate by spray pyrolysis method. <i>Materials Letters</i> , <b>2017</b> , 201, 148-151	3.3	10
99	Design of La <sub>2</sub> Pr <sub>x</sub> NiO <sub>4</sub> + $\delta$ SOFC cathodes: a compromise between electrochemical performance and thermodynamic stability. <i>Journal of Materials Chemistry A</i> , <b>2017</b> , 5, 1120-1132	13	31

98	Transmission electron microscopy characterization of protective $\text{La}_{0.7}\text{Sr}_{0.3}\text{MnO}_3$ coatings prepared by electrostatic spray deposition on ferritic alloy. <i>Functional Materials Letters</i> , <b>2017</b> , 10, 175001-2	12	1
97	Functionally graded and homogeneous composites of $\text{La}_2\text{NiO}_4$ and $\text{La}_{n+1}\text{Ni}_n\text{O}_{3n+1}$ (n = 2 and 3) solid oxide fuel cell cathodes. <i>Journal of Materials Chemistry A</i> , <b>2017</b> , 5, 22277-22287	13	11
96	State-of-the-Art $\text{La}_{0.6}\text{Sr}_{0.4}\text{Co}_{0.2}\text{Fe}_{0.8}\text{O}_{3-\delta}$ Cathode for SOFC: Microstructural and Electrochemical Properties. <i>ECS Transactions</i> , <b>2017</b> , 78, 747-758	1	7
95	Influence of sintering temperature on morphology and electrochemical performance of LSCF/GDC composite films as efficient cathode for SOFC. <i>Electrochimica Acta</i> , <b>2017</b> , 246, 1248-1258	6.7	28
94	Electrochemical properties of graded and homogeneous $\text{Ce}_{0.9}\text{Gd}_{0.1}\text{O}_2$ - $\text{La}_{0.6}\text{Sr}_{0.4}\text{Co}_{0.2}\text{Fe}_{0.8}\text{O}_{3-\delta}$ composite electrodes for intermediate-temperature solid oxide fuel cells. <i>International Journal of Hydrogen Energy</i> , <b>2016</b> , 41, 17037-17043	6.7	13
93	A Coupled Experimental/Numerical Approach for Tuning High-Performing SOFC-Cathode. <i>ECS Transactions</i> , <b>2016</b> , 72, 81-92	1	4
92	An innovative architectural design to enhance the electrochemical performance of $\text{La}_2\text{NiO}_4$ cathodes for solid oxide fuel cell applications. <i>Journal of Power Sources</i> , <b>2016</b> , 316, 17-28	8.9	34
91	Electrostatic spray deposition of $\text{Ca}_3\text{Co}_4\text{O}_9$ + $\delta$ layers to be used as cathode materials for IT-SOFC. <i>Solid State Ionics</i> , <b>2016</b> , 286, 102-110	3.3	15
90	Design of interfaces in efficient $\text{Ln}_2\text{NiO}_4$ (Ln = La, Pr) cathodes for SOFC applications. <i>Journal of Materials Chemistry A</i> , <b>2016</b> , 4, 12451-12462	13	18
89	Durability test on coral $\text{Ce}_{0.9}\text{Gd}_{0.1}\text{O}_2$ - $\text{La}_{0.6}\text{Sr}_{0.4}\text{Co}_{0.2}\text{Fe}_{0.8}\text{O}_{3-\delta}$ with $\text{La}_{0.6}\text{Sr}_{0.4}\text{Co}_{0.2}\text{Fe}_{0.8}\text{O}_{3-\delta}$ current collector working in SOFC and SOEC modes. <i>Electrochimica Acta</i> , <b>2016</b> , 201, 57-69	6.7	11
88	Rational design of hierarchically nanostructured electrodes for solid oxide fuel cells. <i>Journal of Power Sources</i> , <b>2016</b> , 333, 72-82	8.9	27
87	Mechanical behavior of $\text{Ce}_{0.9}\text{Gd}_{0.1}\text{O}_{1.95}$ - $\text{La}_{0.6}\text{Sr}_{0.4}\text{Co}_{0.2}\text{Fe}_{0.8}\text{O}_{3-\delta}$ oxygen electrode with a coral microstructure for solid oxide fuel cell and solid oxide electrolyzer cell. <i>Ceramics International</i> , <b>2016</b> , 42, 16981-16991	5.1	1
86	$\text{La}_{n+1}\text{Ni}_n\text{O}_{3n+1}$ (n = 2 and 3) phases and composites for solid oxide fuel cell cathodes: Facile synthesis and electrochemical properties. <i>Journal of Power Sources</i> , <b>2016</b> , 325, 337-345	8.9	21
85	Laccase wiring on free-standing electrospun carbon nanofibres using a mediator plug. <i>Chemical Communications</i> , <b>2015</b> , 51, 14574-7	5.8	11
84	$\text{La}_4\text{Ni}_3\text{O}_{10}$ as an efficient solid oxide fuel cell cathode: electrochemical properties versus microstructure. <i>Journal of Materials Chemistry A</i> , <b>2015</b> , 3, 23833-23843	13	18
83	Three dimensional analysis of $\text{Ce}_{0.9}\text{Gd}_{0.1}\text{O}_{1.95}$ - $\text{La}_{0.6}\text{Sr}_{0.4}\text{Co}_{0.2}\text{Fe}_{0.8}\text{O}_{3-\delta}$ oxygen electrode for solid oxide cells. <i>Journal of the European Ceramic Society</i> , <b>2015</b> , 35, 4497-4505	6	10
82	Interfaces and Durability for Different LSCF/CGO/YSZ Systems for IT-SOFC. <i>ECS Transactions</i> , <b>2015</b> , 66, 109-114	1	6
81	$\text{La}_{0.7}\text{Sr}_{0.3}\text{MnO}_3$ barrier for $\text{Cr}_2\text{O}_3$ -forming SOFC interconnect alloy coated by electrostatic spray deposition. <i>Surface and Coatings Technology</i> , <b>2014</b> , 254, 157-166	4.4	14

80	Coral Microstructure of Graded CGO/LSCF Oxygen Electrode by Electrostatic Spray Deposition for Energy (IT-SOFC, SOEC). <i>Fuel Cells</i> , <b>2014</b> , 14, 357-363	2.9	13
79	Microstructural and electrical characterizations of tungsten-doped La <sub>2</sub> Mo <sub>2</sub> O <sub>9</sub> prepared by spray pyrolysis. <i>Ionics</i> , <b>2013</b> , 19, 1761-1774	2.7	10
78	Influence of crystallinity and particle size on the electrochemical properties of spray pyrolyzed Nd <sub>2</sub> NiO <sub>4</sub> + $\beta$ powders. <i>Electrochimica Acta</i> , <b>2013</b> , 87, 330-335	6.7	15
77	Synthesis and sintering of Gd-doped CeO <sub>2</sub> nanopowders prepared by ultrasonic spray pyrolysis. <i>Journal of the European Ceramic Society</i> , <b>2013</b> , 33, 769-778	6	25
76	Efficiency of a dense thin CGO buffer layer for solid oxide fuel cell operating at intermediate temperature. <i>Solid State Ionics</i> , <b>2013</b> , 249-250, 98-104	3.3	41
75	Pre-coating of LSCM perovskite with metal catalyst for scalable high performance anodes. <i>International Journal of Hydrogen Energy</i> , <b>2013</b> , 38, 9519-9524	6.7	28
74	La <sub>0.7</sub> Sr <sub>0.3</sub> MnO <sub>3</sub> -coated SS444 alloy by dip-coating process for metallic interconnect supported Solid Oxide Fuel Cells. <i>Journal of Power Sources</i> , <b>2013</b> , 241, 159-167	8.9	20
73	Thin films of La <sub>0.7</sub> Sr <sub>0.3</sub> MnO <sub>3</sub> dip-coated on Fe/Al alloys for SOFC metallic interconnect. <i>International Journal of Hydrogen Energy</i> , <b>2013</b> , 38, 15335-15347	6.7	10
72	Interface stability of thin, dense CGO film coating on YSZ for solid oxide fuel cells. <i>Solid State Ionics</i> , <b>2013</b> , 235, 36-41	3.3	23
71	Low temperature synthesis of ultrafine non vermicular $\beta$ -alumina from aerosol decomposition of aluminum nitrates salts. <i>Journal of the European Ceramic Society</i> , <b>2013</b> , 33, 1917-1928	6	9
70	Comprehensive Review of Current Developments in IT-SOFCs. <i>Current Inorganic Chemistry</i> , <b>2013</b> , 3, 2-22		21
69	Electrochemical investigation of oxygen reduction reaction on La <sub>0.6</sub> Sr <sub>0.4</sub> Co <sub>0.2</sub> Fe <sub>0.8</sub> O <sub>3</sub> cathodes deposited by Electrostatic Spray Deposition. <i>Journal of Power Sources</i> , <b>2012</b> , 197, 80-87	8.9	39
68	Elaboration and electrical characterization of electrosprayed YSZ thin films for intermediate temperature-solid oxide fuel cells (IT-SOFC). <i>Solid State Ionics</i> , <b>2012</b> , 222-223, 1-7	3.3	13
67	Pressure-less spark plasma sintering effect on non-conventional necking process during the initial stage of sintering of copper and alumina. <i>Journal of Materials Science</i> , <b>2012</b> , 47, 5766-5773	4.3	29
66	Influence of Gadolinia-Doped Ceria Buffer Layer on the Durability of LSCF/CGO/YSZ System for IT-SOFC. <i>ECS Transactions</i> , <b>2012</b> , 45, 295-305	1	2
65	Electrical Characterization of Thin Films by an Original Micro-Electrode Calibration Method. <i>Electrochemical and Solid-State Letters</i> , <b>2012</b> , 15, F16		4
64	Elaboration of thin and dense CGO films adherent to YSZ by electrostatic spray deposition for IT-SOFC applications. <i>New Journal of Chemistry</i> , <b>2011</b> , 35, 716	3.6	10
63	Spark Plasma Sintering Kinetics of Pure $\beta$ -Alumina. <i>Journal of the American Ceramic Society</i> , <b>2011</b> , 94, 2825-2833	3.8	48

62	Reducibility of La <sub>2</sub> Mo <sub>2</sub> O <sub>9</sub> based ceramics versus porosity. <i>Solid State Ionics</i> , <b>2011</b> , 204-205, 97-103	3.3	9
61	Fluorescent organic nanocrystal confined in sol-gel matrix for bio-imaging. <i>Journal of Sol-Gel Science and Technology</i> , <b>2011</b> , 57, 253-257	2.3	8
60	Structure characterization of spark plasma sintered alumina by positron annihilation lifetime spectroscopy. <i>Physica Status Solidi (A) Applications and Materials Science</i> , <b>2011</b> , 208, 795-802	1.6	8
59	Microstructural 3D Reconstruction and Performance Evaluation of LSCF Cathodes Obtained by Electrostatic Spray Deposition. <i>Chemistry of Materials</i> , <b>2011</b> , 23, 5340-5348	9.6	55
58	Performance of (La,Sr)(Co,Fe)O <sub>3-<math>\delta</math></sub> double-layer cathode films for intermediate temperature solid oxide fuel cell. <i>Journal of Power Sources</i> , <b>2011</b> , 196, 5084-5090	8.9	39
57	Vortex pinning in bulk-processed YBaCuO with ZrO <sub>2</sub> nano-particles: Optimum pinning center size. <i>Physica C: Superconductivity and Its Applications</i> , <b>2011</b> , 471, 97-103	1.3	16
56	Comparison of Electrochemical Performances of Electro sprayed LSCF Cathode Films for IT-SOFCs for Different Morphologies and Cobalt Contents. <i>ECS Transactions</i> , <b>2011</b> , 35, 2283-2294	1	1
55	Microstructure-Electrical Properties of Original LSCF Films Deposited by ESD for IT-SOFCs. <i>ECS Transactions</i> , <b>2010</b> , 28, 93-103	1	6
54	Thermal ageing of nanostructured tetragonal zirconia ceramics: Characterization of interfaces. <i>Journal of the European Ceramic Society</i> , <b>2010</b> , 30, 227-231	6	12
53	Atomic layer deposition of tantalum oxide thin films for their use as diffusion barriers in microelectronic devices. <i>Microelectronic Engineering</i> , <b>2010</b> , 87, 373-378	2.5	32
52	Nanopowder synthesis of the SOFC cathode material Nd <sub>2</sub> NiO <sub>4</sub> + $\delta$ by ultrasonic spray pyrolysis. <i>Solid State Ionics</i> , <b>2010</b> , 181, 1015-1023	3.3	11
51	ESD and ALD Depositions of Ta <sub>2</sub> O <sub>5</sub> Thin Films Investigated as Barriers to Copper Diffusion for Advanced Metallization. <i>Journal of the Electrochemical Society</i> , <b>2009</b> , 156, H311	3.9	17
50	Electrochemical Performance of Nanostructured IT-SOFC Cathodes with Different Morphologies. <i>ECS Transactions</i> , <b>2009</b> , 25, 2473-2480	1	9
49	Electrochemical characterization of nanostructured zirconias. <i>Solid State Ionics</i> , <b>2009</b> , 180, 978-983	3.3	14
48	A Screening Design Approach for the Understanding of Spark Plasma Sintering Parameters: A Case of Translucent Polycrystalline Undoped Alumina. <i>International Journal of Applied Ceramic Technology</i> , <b>2009</b> , 7, 574-586	2	14
47	Fabrication by electrostatic spray deposition and structural investigation of ultra thin and dense zirconia films. <i>Thin Solid Films</i> , <b>2009</b> , 517, 6784-6788	2.2	1
46	The synthesis and sintering behaviour of BaZr <sub>0.9</sub> Y <sub>0.1</sub> O <sub>3-<math>\delta</math></sub> powders prepared by spray pyrolysis. <i>Journal of the European Ceramic Society</i> , <b>2009</b> , 29, 697-702	6	23
45	Influence of green state processes on the sintering behaviour and the subsequent optical properties of spark plasma sintered alumina. <i>Journal of the European Ceramic Society</i> , <b>2009</b> , 29, 3363-3370	6	41

44	Influence of electro spraying parameters on the microstructure of La <sub>0.6</sub> Sr <sub>0.4</sub> Co <sub>0.2</sub> Fo <sub>0.8</sub> O <sub>3</sub> films for SOFCs. <i>Journal of Solid State Chemistry</i> , <b>2009</b> , 182, 1742-1748	3.3	43
43	Microstructure Related Conductivity in La <sub>2</sub> Mo <sub>2</sub> O <sub>9</sub> Ceramics. <i>Journal of Physical Chemistry C</i> , <b>2008</b> , 112, 3194-3202	3.8	19
42	Nanocrystallites obtained through the pyrosol method. <i>Physica Status Solidi (A) Applications and Materials Science</i> , <b>2008</b> , 205, 1488-1493	1.6	8
41	Blocking Effect in High Purity Nanostructured Cubic Zirconia Ceramics. <i>Fuel Cells</i> , <b>2008</b> , 8, 313-321	2.9	14
40	Pt/YSZ electrochemical catalysts prepared by electrostatic spray deposition for selective catalytic reduction of NO by C <sub>3</sub> H <sub>6</sub> . <i>Solid State Ionics</i> , <b>2008</b> , 178, 1998-2008	3.3	27
39	Nanostructured LSM/YSZ composite cathodes for IT-SOFC: A comprehensive microstructural study by electrostatic spray deposition. <i>Solid State Ionics</i> , <b>2008</b> , 179, 1921-1928	3.3	32
38	Elaboration of Ta <sub>2</sub> O <sub>5</sub> Thin Films Using Electrostatic Spray Deposition for Microelectronic Applications. <i>Journal of Physical Chemistry C</i> , <b>2007</b> , 111, 5708-5714	3.8	23
37	Structural investigations of YSZ coatings prepared by DC magnetron sputtering. <i>Surface and Coatings Technology</i> , <b>2007</b> , 201, 6012-6018	4.4	45
36	Nanocrystalline Pt thin films prepared by electrostatic spray deposition for automotive exhaust gas treatment. <i>Solid State Ionics</i> , <b>2007</b> , 177, 3491-3499	3.3	24
35	Electrochemical and surface properties of nanocrystalline EMnO <sub>2</sub> in aqueous electrolyte. <i>Electrochimica Acta</i> , <b>2006</b> , 51, 3076-3085	6.7	16
34	Influence of the process parameters on the ESD synthesis of thin film YSZ electrolytes. <i>Solid State Ionics</i> , <b>2006</b> , 177, 1981-1984	3.3	19
33	ZrO <sub>2</sub> -based thin films synthesized by electrostatic spray deposition: Effect of post-deposition thermal treatments. <i>Solid State Ionics</i> , <b>2006</b> , 177, 1443-1449	3.3	10
32	Zirconia coatings deposited by electrostatic spray deposition A chemical approach. <i>Solid State Ionics</i> , <b>2006</b> , 177, 1451-1460	3.3	19
31	Zirconia coatings deposited by electrostatic spray deposition. Influence of the process parameters. <i>Surface and Coatings Technology</i> , <b>2006</b> , 200, 6815-6820	4.4	28
30	Initial Stages in Zirconia Coatings Using ESD. <i>Chemistry of Materials</i> , <b>2005</b> , 17, 902-910	9.6	30
29	Porosity Control of LSM/YSZ Cathode Coating Deposited by Electro spraying. <i>Chemistry of Materials</i> , <b>2005</b> , 17, 1220-1227	9.6	41
28	Raman investigation of the O, Pt/YSZ electrode under polarization. <i>Solid State Ionics</i> , <b>2005</b> , 176, 2599-2607	9.7	24
27	Comparative study of nanocrystalline Zr <sub>0.85</sub> Ce <sub>0.15</sub> O <sub>2</sub> powders synthesised by spray-pyrolysis and gel-combustion methods. <i>Materials Research Bulletin</i> , <b>2005</b> , 40, 2029-2038	5.1	9

26	YSZ electrolyte of anode-supported SOFCs prepared from sub micron YSZ powders. <i>Journal of Materials Science</i> , <b>2005</b> , 40, 3735-3743	4.3	17
25	Catalytic and Electrochemical Properties of Doped Lanthanum Chromites as New Anode Materials for Solid Oxide Fuel Cells. <i>Journal of the American Ceramic Society</i> , <b>2004</b> , 84, 2289-2295	3.8	43
24	Synthesis of sodium titanate composites by sol-gel method for use in gas potentiometric sensors. <i>Journal of the European Ceramic Society</i> , <b>2004</b> , 24, 2477-2483	6	64
23	Delay of tetragonal-to-monoclinic transition in water vapour due to nanostructural effect. <i>Journal of the European Ceramic Society</i> , <b>2004</b> , 24, 1181-1185	6	14
22	Morphology and sintering behaviour of yttria stabilised zirconia (8-YSZ) powders synthesised by spray pyrolysis. <i>Ceramics International</i> , <b>2004</b> , 30, 2295-2303	5.1	55
21	Dopant Segregation and Space Charge Effect in Nanostructured Tetragonal Zirconia. <i>Journal of the Electrochemical Society</i> , <b>2004</b> , 151, A1210	3.9	11
20	Study on Aging of Tetragonal Zirconia by Coupling Impedance and Raman Spectroscopies in Water Vapor Atmosphere. <i>Journal of the Electrochemical Society</i> , <b>2004</b> , 151, A774	3.9	8
19	Microstructural Investigations of Nanostructured La(Sr)MnO <sub>3</sub> -Films Deposited by Electrostatic Spray Deposition. <i>Chemistry of Materials</i> , <b>2004</b> , 16, 3733-3739	9.6	40
18	Structural characterization of La <sub>1-x</sub> MnO <sub>3</sub> by x-ray diffraction and x-ray absorption spectroscopy. <i>Physical Review B</i> , <b>2004</b> , 69,	3.3	62
17	Materials synthesis and characterization of 8YSZ nanomaterials for the fabrication of electrolyte membranes in solid oxide fuel cells. <i>Ceramics International</i> , <b>2003</b> , 29, 619-628	5.1	24
16	Structural changes of rare-earth-doped, nanostructured zirconia solid solution. <i>Solid State Ionics</i> , <b>2003</b> , 157, 335-340	3.3	45
15	Quantification of Chemical Pressure in Doped Nanostructured Zirconia Ceramics. <i>Journal of Physical Chemistry B</i> , <b>2003</b> , 107, 8321-8326	3.4	7
14	Metastable forms of the tetragonal phase in compositionally homogeneous, nanocrystalline zirconia $\gamma$ powders synthesised by gel-combustion. <i>Journal of Materials Chemistry</i> , <b>2003</b> , 13, 904-910		48
13	Dopant size effect on structural and transport properties of nanometric and single-phased TZP. <i>Solid State Ionics</i> , <b>2002</b> , 154-155, 143-150	3.3	13
12	Cold isostatic and explosive isodynamic compaction of Y-TZP nanoparticles. <i>Solid State Ionics</i> , <b>2002</b> , 154-155, 375-380	3.3	7
11	Deposition and characterization of nanocrystalline tetragonal zirconia films using electrostatic spray deposition. <i>Solid State Ionics</i> , <b>2001</b> , 138, 191-197	3.3	63
10	Physico-chemical characterization of highly pure nanocrystalline doped TZP. <i>Journal of the European Ceramic Society</i> , <b>2001</b> , 21, 1847-1850	6	3
9	Low temperature phase transformation of nanocrystalline tetragonal ZrO <sub>2</sub> by neutron and Raman scattering studies. <i>Solid State Sciences</i> , <b>2001</b> , 3, 647-654		46

8	DOMAIN SIZE DISTRIBUTION OF Y-TZP NANO-PARTICLES USING XRD AND HRTEM. <i>Image Analysis and Stereology</i> , <b>2001</b> , 20, 157	1	32
7	Crystallite Size Effect on the Tetragonal-Monoclinic Transition of Undoped Nanocrystalline Zirconia Studied by XRD and Raman Spectrometry. <i>Journal of Solid State Chemistry</i> , <b>2000</b> , 149, 399-407	3-3	198
6	Phase stability of nanostructured tetragonal zirconia polycrystals versus temperature and water vapor. <i>Solid State Ionics</i> , <b>2000</b> , 136-137, 1249-1254	3-3	16
5	High-pressure structural evolution of undoped tetragonal nanocrystalline zirconia. <i>Physical Review B</i> , <b>2000</b> , 62, 8731-8737	3-3	110
4	Synthesis of Doped and Undoped Nanopowders of Tetragonal Polycrystalline Zirconia (TPZ) by Spray-Pyrolysis. <i>Journal of Solid State Chemistry</i> , <b>1998</b> , 141, 191-198	3-3	63
3	Second phases in doped lanthanum gallate perovskites. <i>Journal of the European Ceramic Society</i> , <b>1998</b> , 18, 1397-1404	6	101
2	Low-temperature oxygen electrode reaction on bismuth ruthenium oxides/stabilized zirconia. <i>Solid State Ionics</i> , <b>1998</b> , 107, 191-201	3-3	11
1	Synthesis and structural characterization of a new system: $ZrO_2?Y_2O_3?RuO_2$ . <i>Journal of the European Ceramic Society</i> , <b>1996</b> , 16, 767-771	6	10