

# Qingming Chen

## List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/9570218/publications.pdf>

Version: 2024-02-01

73  
papers

1,055  
citations

430442

18  
h-index

500791

28  
g-index

73  
all docs

73  
docs citations

73  
times ranked

544  
citing authors

#	ARTICLE	IF	CITATIONS
1	Enhanced temperature coefficient of resistance and magnetoresistance of Co-doped La <sub>0.67</sub> Ca <sub>0.33</sub> MnO <sub>3</sub> polycrystalline ceramics. <i>Ceramics International</i> , 2022, 48, 407-414.	2.3	8
2	Effect of La-site substitution on the magnetoelectric transport properties of La <sub>0.7</sub> Ca <sub>0.3</sub> MnO <sub>3</sub> polycrystalline ceramics. <i>Ceramics International</i> , 2022, 48, 17425-17432.	2.3	3
3	An Antifatigue Liquid Metal Composite Electrode Ionic Polymer-Metal Composite Artificial Muscle with Excellent Electromechanical Properties. <i>ACS Applied Materials &amp; Interfaces</i> , 2022, 14, 14630-14639.	4.0	17
4	Effect of Fe substitution on temperature coefficient of resistance and magnetoresistance of La <sub>0.67</sub> Ca <sub>0.33</sub> MnO <sub>3</sub> polycrystalline ceramics. <i>Ceramics International</i> , 2022, 48, 8169-8176.	2.3	5
5	Structural, electrical, and magnetic transport properties of La <sub>0.72</sub> Ca <sub>0.28</sub> Mn <sub>1-x</sub> Cr <sub>x</sub> O <sub>3</sub> (0 ≤ x ≤ 0.06) ceramics. <i>Ceramics International</i> , 2022, 48, 21187-21193.	2.3	4
6	Adjusting the K-doping of La <sub>1-x</sub> K <sub>x</sub> MnO <sub>3</sub> (0.1 ≤ x ≤ 0.35) films to obtain high TCR and LFMR at room-temperature. <i>Applied Surface Science</i> , 2022, 589, 152905.	3.1	10
7	Effect of deposition time on electrical properties of La <sub>0.67</sub> Ca <sub>0.33</sub> MnO <sub>3</sub> :Ag <sub>0.2</sub> thin films by pulsed laser deposition. <i>Applied Physics A: Materials Science and Processing</i> , 2022, 128, 1.	1.1	1
8	Impact of the transition metal ion-doped on the electrical and magnetic properties of La <sub>0.67</sub> Ca <sub>0.33</sub> MnO <sub>3</sub> Ag <sub>0.15</sub> -based polycrystalline ceramics. <i>Advanced Powder Technology</i> , 2022, 33, 103714.	2.0	0
9	Effect of Gd doping on electrical transport properties of La <sub>0.8</sub> Sr <sub>0.2</sub> MnO <sub>3</sub> polycrystalline ceramics. <i>Ceramics International</i> , 2021, 47, 5944-5950.	2.3	3
10	High-performance bio-based epoxies from ferulic acid and furfuryl alcohol: synthesis and properties. <i>Green Chemistry</i> , 2021, 23, 1772-1781.	4.6	38
11	Improved room-temperature TCR and MR of La <sub>0.9-x</sub> K <sub>x</sub> Ca <sub>0.1</sub> MnO <sub>3</sub> ceramics by A-sites vacancy and disorder degree adjustment. <i>Journal of Materials Science: Materials in Electronics</i> , 2021, 32, 8848-8862.	1.1	8
12	Effect of sintering temperature on structure and electrical transport properties of La <sub>0.7</sub> Ca <sub>0.26</sub> Na <sub>0.04</sub> MnO <sub>3</sub> ceramics. <i>Ceramics International</i> , 2021, 47, 12716-12724.	2.3	7
13	Exploring the electrical transport properties of La <sub>0.67</sub> Ca <sub>0.33</sub> MnO <sub>3</sub> at different sintering temperatures. <i>Journal of Materials Science: Materials in Electronics</i> , 2021, 32, 14164-14173.	1.1	3
14	La <sub>0.7</sub> Ca <sub>0.3-x</sub> Na <sub>x</sub> MnO <sub>3</sub> polycrystalline with high magnetoresistance and temperature coefficient of resistance were prepared via the sol-gel method. <i>Journal of Materials Science: Materials in Electronics</i> , 2021, 32, 18397-18407.	1.1	1
15	La <sub>1-x</sub> Ca <sub>x</sub> MnO <sub>3</sub> :Ag <sub>0.2</sub> (0.25 ≤ x ≤ 0.31) ceramics with high temperature coefficient of resistivity under magnetic field. <i>Ceramics International</i> , 2021, 47, 19659-19667.	2.3	11
16	Enhancement of magnetoresistance and near room-temperature temperature coefficient of resistivity in polycrystalline La <sub>0.7</sub> Ca <sub>0.24</sub> Na <sub>0.06</sub> MnO <sub>3</sub> by silver doping. <i>Journal of Sol-Gel Science and Technology</i> , 2021, 99, 627-635.	1.1	4
17	Electrical properties of La <sub>0.72</sub> Ca <sub>0.28</sub> MnO <sub>3</sub> :Ag <sub>0.2</sub> thin films of different deposition time prepared by deposited pulsed laser method. <i>Journal of Materials Science: Materials in Electronics</i> , 2021, 32, 22999-23006.	1.1	0
18	Electrical transport properties of Sm-doped La <sub>0.7</sub> Ca <sub>0.3</sub> MnO <sub>3</sub> polycrystalline ceramics. <i>Ceramics International</i> , 2021, 47, 25281-25286.	2.3	5

#	ARTICLE	IF	CITATIONS
19	Colossal magnetoresistive polycrystalline La <sub>0.61</sub> Sm <sub>0.06</sub> Ca <sub>0.33</sub> MnO <sub>3</sub> with large and unperturbed temperature coefficient of resistivity under a magnetic field. <i>Ceramics International</i> , 2021, 47, 30671-30676.	2.3	3
20	Large temperature coefficient of resistance and magnetoresistance of La <sub>0.71</sub> Ca <sub>0.29</sub> Mn <sub>1-x</sub> Co <sub>x</sub> O <sub>3</sub> polycrystalline ceramics. <i>Ceramics International</i> , 2021, 47, 32097-32103.	2.3	4
21	Robust temperature coefficient of resistance of polycrystalline La <sub>0.6</sub> Ca <sub>0.4</sub> MnO <sub>3</sub> under magnetic fields at room temperature. <i>Ceramics International</i> , 2021, 47, 29631-29637.	2.3	3
22	Influence of different post-annealing temperatures on physical properties of La <sub>0.72</sub> Ca <sub>0.28</sub> MnO <sub>3</sub> :Ag <sub>0.2</sub> thin films by pulsed laser deposition technique. <i>Ceramics International</i> , 2020, 46, 6418-6423.	2.3	7
23	Utilization of metallic Ag and Ag <sup>+</sup> ions to optimize room-temperature TCR and MR of La <sub>0.7</sub> (Ca <sub>0.205</sub> Sr <sub>0.095</sub> )MnO <sub>3</sub> :Ag <sub>2</sub> O composites. <i>Journal of Materials Chemistry C</i> , 2020, 8, 17054-17064.	2.7	24
24	Effect of annealing temperature on electrical and magnetic properties of La <sub>0.7</sub> Ca <sub>0.3</sub> MnO <sub>3</sub> :Ag <sub>0.2</sub> thin films. <i>Ceramics International</i> , 2020, 46, 27951-27956.	2.3	1
25	Effect of sintering temperature on structural and electrical transport properties of La <sub>0.7</sub> Ca <sub>0.28</sub> K <sub>0.02</sub> MnO <sub>3</sub> ceramics. <i>Ceramics International</i> , 2020, 46, 25949-25955.	2.3	12
26	Effect of V doping on electrical and magnetic properties of La <sub>0.71</sub> Ca <sub>0.29</sub> MnO <sub>3</sub> polycrystalline ceramics. <i>Journal of Materials Science: Materials in Electronics</i> , 2020, 31, 10355-10365.	1.1	4
27	Effect of different post-annealing durations on electromagnetic properties of La <sub>0.67</sub> Ca <sub>0.33</sub> MnO <sub>3</sub> :Ag <sub>0.2</sub> thin films prepared by pulsed laser deposition. <i>Ceramics International</i> , 2020, 46, 20272-20276.	2.3	0
28	Effect of A-site cationic radius on ceramic La <sub>0.67</sub> Dy <sub>x</sub> Sr <sub>0.33</sub> MnO <sub>3</sub> prepared by sol-gel technique. <i>Journal of Materials Science: Materials in Electronics</i> , 2020, 31, 7623-7629.	1.1	1
29	Effect of Y doping on transport properties of La <sub>0.8</sub> Sr <sub>0.2</sub> MnO <sub>3</sub> polycrystalline ceramics. <i>Ceramics International</i> , 2020, 46, 11950-11954.	2.3	7
30	Electrical and magnetic properties of La <sub>1-x</sub> Ag <sub>x</sub> MnO <sub>3</sub> (0 ≤ x ≤ 0.5) polycrystalline ceramics by combination of first principles calculations and experimental methods. <i>Journal of Alloys and Compounds</i> , 2019, 808, 151709.	2.8	17
31	La <sub>0.67</sub> (Ca <sub>0.24</sub> Sr <sub>0.09</sub> )MnO <sub>3</sub> :xAg <sub>2</sub> O (0 ≤ x ≤ 0.25) composites with improved room-temperature TCR and MR for advanced uncooling infrared bolometers and magnetic sensors. <i>Applied Surface Science</i> , 2019, 493, 448-457.	3.1	31
32	Influence of Ag on TCR and MR of La <sub>0.7</sub> (Ca <sub>0.27</sub> Sr <sub>0.03</sub> )MnO <sub>3</sub> :Ag <sub>0.2</sub> ceramics subjected to cross magnetic fields. <i>Ceramics International</i> , 2019, 45, 20396-20404.	2.3	8
33	Electrical transport and magnetoresistive properties of Nd-doped La <sub>0.8</sub> Sr <sub>0.2</sub> MnO <sub>3</sub> ceramics. <i>Journal of Materials Science: Materials in Electronics</i> , 2019, 30, 19035-19042.	1.1	3
34	La <sub>0.7</sub> Ca <sub>0.3</sub> Sr <sub>x</sub> MnO <sub>3</sub> :Ag <sub>0.2</sub> (0.0165 ≤ x ≤ 0.1) ceramics with large and stable TCR in different magnetic field environments. <i>Ceramics International</i> , 2019, 45, 24742-24749.	2.3	9
35	Improved temperature coefficient of resistance in La <sub>1-x</sub> Ca <sub>x</sub> MnO <sub>3</sub> :Ag <sub>0.2</sub> (0.25 ≤ x ≤ 0.33) ceramics prepared by sol-gel method. <i>Journal of Alloys and Compounds</i> , 2019, 800, 64-71.	2.8	9
36	Electrical and magnetic properties of La <sub>1-x</sub> Sr <sub>x</sub> MnO <sub>3</sub> (0.1 ≤ x ≤ 0.25) ceramics prepared by sol-gel technique. <i>Ceramics International</i> , 2019, 45, 16323-16330.	2.3	35

#	ARTICLE	IF	CITATIONS
37	Structure and electromagnetic properties of La <sub>0.7</sub> Ca <sub>0.3</sub> K MnO <sub>3</sub> polycrystalline ceramics. <i>Ceramics International</i> , 2019, 45, 10558-10564.	2.3	36
38	Modulation of room-temperature TCR and MR in La <sub>1-x</sub> Sr <sub>x</sub> MnO <sub>3</sub> polycrystalline ceramics via Sr doping. <i>Journal of Sol-Gel Science and Technology</i> , 2019, 90, 221-229.	1.1	23
39	Electrical transport properties and enhanced broad-temperature-range low field magnetoresistance in LCMO ceramics by Sm <sub>2</sub> O <sub>3</sub> adding. <i>Journal of Alloys and Compounds</i> , 2019, 790, 240-247.	2.8	19
40	Influence of Ag doping on electrical and magnetic properties of La <sub>0.67</sub> Ca <sub>0.33</sub> MnO <sub>3</sub> polycrystalline ceramics. <i>Ceramics International</i> , 2019, 45, 11006-11012.	2.3	35
41	Printable Liquid@Metal@PDMS Stretchable Heater with High Stretchability and Dynamic Stability for Wearable Thermo-therapy. <i>Advanced Materials Technologies</i> , 2019, 4, 1800435.	3.0	92
42	La <sub>1-x</sub> Sr <sub>x</sub> MnO <sub>3</sub> :Ag <sub>0.2</sub> (0.1 ≤ x ≤ 0.2) ceramics with large room-temperature TCR for uncooled infrared bolometers. <i>Journal of the European Ceramic Society</i> , 2019, 39, 352-357.	2.8	58
43	Colossal photovoltages in strain-driven crystal field transition and symmetry breaking of superconducting epitaxial systems. <i>Physical Review Materials</i> , 2019, 3, .	0.9	1
44	Influence of silver addition on microstructures and transport properties of La <sub>0.67</sub> Ca <sub>0.33</sub> MnO <sub>3</sub> :Ag <sub>x</sub> composites. <i>Journal of Materials Science: Materials in Electronics</i> , 2018, 29, 6167-6173.	1.1	5
45	Effects of A-site cationic radius and cationic disorder on the electromagnetic properties of La <sub>0.7</sub> Ca <sub>0.3</sub> MnO <sub>3</sub> ceramic with added Sr, Pb, and Ba. <i>Ceramics International</i> , 2018, 44, 5378-5384.	2.3	30
46	Improved Curie temperature and temperature coefficient of resistance (TCR) in La <sub>0.7</sub> Ca <sub>0.3</sub> -Sr MnO <sub>3</sub> :Ag <sub>0.2</sub> composites. <i>Journal of Alloys and Compounds</i> , 2018, 747, 1027-1032.	2.8	33
47	Improvement of room-temperature TCR and MR in polycrystalline La <sub>0.67</sub> (Ca <sub>0.27</sub> Sr <sub>0.06</sub> )MnO <sub>3</sub> ceramics by Ag <sub>2</sub> O doping. <i>Ceramics International</i> , 2018, 44, 9865-9874.	2.3	46
48	Structure, electrical and magnetic properties of La <sub>0.67</sub> Ca <sub>0.33</sub> K <sub>x</sub> MnO <sub>3</sub> polycrystalline ceramic. <i>Journal of Materials Science: Materials in Electronics</i> , 2018, 29, 1808-1816.	1.1	13
49	Effects of silver doping on structure and electrical properties of La <sub>0.67</sub> Ca <sub>0.23</sub> K <sub>0.1</sub> MnO <sub>3</sub> polycrystalline ceramic. <i>Ceramics International</i> , 2018, 44, 3448-3453.	2.3	22
50	Effect of Ca-doping on electrical properties of La <sub>0.46</sub> Sm <sub>0.21</sub> Sr <sub>0.33-x</sub> Ca <sub>x</sub> MnO <sub>3</sub> ceramics prepared by sol-gel technique. <i>Journal of Sol-Gel Science and Technology</i> , 2018, 87, 400-407.	1.1	9
51	Preparation and properties of La <sub>0.71</sub> Ca <sub>0.29</sub> Mn <sub>1-x</sub> Cr <sub>x</sub> O <sub>3</sub> polycrystalline composites. <i>Journal of Materials Science: Materials in Electronics</i> , 2018, 29, 19070-19077.	1.1	3
52	Enhanced Bidimensionality-Driven Ultrahigh Laser-Induced Voltages in High-T <sub>c</sub> Superconducting Epitaxial Films. <i>Advanced Electronic Materials</i> , 2018, 4, 1800116.	2.6	11
53	Improvement in structure and superconductivity of YBa <sub>2</sub> Cu <sub>3</sub> O <sub>6+δ</sub> ceramics superconductors by optimizing sintering processing. <i>Journal of Rare Earths</i> , 2017, 35, 85-89.	2.5	6
54	Enhancement of temperature coefficient of resistance (TCR) and Magneto-resistance (MR) in La <sub>1-x</sub> Ca <sub>x</sub> MnO <sub>3</sub> :Ag <sub>0.2</sub> polycrystalline composites. <i>Journal of Sol-Gel Science and Technology</i> , 2017, 82, 193-200.	1.1	22

#	ARTICLE	IF	CITATIONS
55	Effect of Ca-doping on the electrical properties of La <sub>0.2</sub> Nd <sub>0.47</sub> Sr <sub>0.33</sub> MnO <sub>3</sub> ceramics prepared by sol-gel technique. Journal of Sol-Gel Science and Technology, 2017, 82, 177-183.	1.1	11
56	Effect of laser energy on the electrical transport properties of La <sub>0.67</sub> Ca <sub>0.33</sub> MnO <sub>3</sub> :Ag <sub>0.2</sub> films by pulsed laser deposition technique. Applied Physics A: Materials Science and Processing, 2017, 123, 1.	1.1	5
57	Influence of Gd-content on the electrical transport properties of La <sub>0.67-<i>x</i></sub> Gd <sub><i>x</i></sub> Sr <sub>0.33</sub> MnO <sub>3</sub> polycrystalline ceramics by sol-gel method. Journal of Materials Science: Materials in Electronics, 2017, 28, 17026-17030.	1.1	0
58	Improvement in electronic and magnetic transport of La <sub>0.67</sub> Ca <sub>0.33</sub> MnO <sub>3</sub> manganites by optimizing sintering temperature. Journal of Sol-Gel Science and Technology, 2017, 81, 177-184.	1.1	11
59	Effect of A-site cationic radius on polycrystalline ceramics La <sub><i>x</i></sub> Sm <sub>0.67-<i>x</i></sub> Sr <sub>0.33</sub> MnO <sub>3</sub> prepared by sol-gel technique. Journal of Sol-Gel Science and Technology, 2016, 80, 474-479.	1.1	11
60	Fabrication of La <sub><i>x</i></sub> Nd <sub>0.67-<i>x</i></sub> Sr <sub>0.33</sub> MnO <sub>3</sub> polycrystalline ceramics by sol-gel method. Journal of Sol-Gel Science and Technology, 2016, 80, 168-173.	1.1	16
61	Preparation of c-axis oriented YBa <sub>2</sub> Cu <sub>3</sub> O <sub>7</sub> polycrystalline ceramics by sol-gel method. Physica C: Superconductivity and Its Applications, 2015, 511, 1-3.	0.6	5
62	Effect of Ag addition on the magnetic and electrical properties of La <sub>0.67</sub> Ca <sub>0.33</sub> MnO <sub>3</sub> films. Applied Surface Science, 2015, 349, 983-987.	3.1	13
63	Search for high temperature coefficient of resistance La <sub>2/3</sub> Ca <sub>1/3</sub> MnO <sub>3</sub> polycrystalline ceramics. Applied Physics A: Materials Science and Processing, 2014, 117, 2051-2055.	1.1	13
64	Enhancement of temperature coefficient of resistivity in La <sub>0.67</sub> Ca <sub>0.33</sub> MnO <sub>3</sub> polycrystalline ceramics. Ceramics International, 2014, 40, 4963-4968.	2.3	31
65	Electrical transport properties and laser-induced voltage effect in La <sub>0.8</sub> Ca <sub>0.2</sub> MnO <sub>3</sub> epitaxial thin films. Applied Physics A: Materials Science and Processing, 2014, 114, 1085-1090.	1.1	10
66	Effect of Ca doping level on the laser-induced voltages in tilted La <sub>1-<i>x</i></sub> Ca <sub><i>x</i></sub> MnO <sub>3</sub> (0.1 ≤ <i>x</i> ≤ 0.7) thin films. Applied Physics A: Materials Science and Processing, 2014, 114, 1075-1078.	1.1	15
67	Preparation of La <sub>0.67</sub> Ca <sub>0.33</sub> MnO <sub>3</sub> :Ag <sub><i>x</i></sub> polycrystalline by sol-gel method. Journal of Sol-Gel Science and Technology, 2014, 70, 361-365.	1.1	41
68	Effects of substrate-induced-strain on the electrical properties and laser induced voltages of tilted La <sub>0.67</sub> Ca <sub>0.33</sub> MnO <sub>3</sub> thin films. Journal of Applied Physics, 2013, 114, .	1.1	11
69	Influence of synthesis methods and calcination temperature on electrical properties of La <sub>1-<i>x</i></sub> Ca <sub><i>x</i></sub> MnO <sub>3</sub> ( <i>x</i> =0.33 and 0.28) ceramics. Ceramics International, 2013, 39, 7839-7843.	2.3	37
70	Structural and electrical characterization of La <sub>0.72</sub> Ca <sub>0.28</sub> MnO <sub>3</sub> ceramic and thin films. Applied Surface Science, 2013, 264, 225-228.	3.1	9
71	Viscosity sensor using ZnO and AlN thin film bulk acoustic resonators with tilted polar <i>c</i> -axis orientations. Journal of Applied Physics, 2011, 110, .	1.1	44
72	Effect of Ag doping on structure and electrical properties of La <sub>0.7</sub> Ca <sub>0.26</sub> K <sub>0.04</sub> MnO <sub>3</sub> ceramics. Journal of Sol-Gel Science and Technology, 0, , 1.	1.1	0

#	ARTICLE	IF	CITATIONS
73	Effect of V doping on the electrical transport and magnetoresistance properties of La <sub>0.825</sub> Sr <sub>0.175</sub> MnO <sub>3</sub> ceramics. Journal of Sol-Gel Science and Technology, 0, , .	1.1	2