

Maria A Madre

List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/9576634/publications.pdf>

Version: 2024-02-01

150
papers

2,470
citations

147566

31
h-index

264894

42
g-index

150
all docs

150
docs citations

150
times ranked

691
citing authors

#	ARTICLE	IF	CITATIONS
1	Preparation of high-performance Ca ₃ Co ₄ O ₉ thermoelectric ceramics produced by a new two-step method. Journal of the European Ceramic Society, 2013, 33, 1747-1754.	2.8	73
2	Enhancement of Ca ₃ Co ₄ O ₉ thermoelectric properties by Cr for Co substitution. Ceramics International, 2013, 39, 6051-6056.	2.3	67
3	Improvement of thermoelectric properties of Ca ₃ Co ₄ O ₉ using soft chemistry synthetic methods. Journal of the European Ceramic Society, 2012, 32, 2415-2422.	2.8	66
4	Effect of Sr substitution for Ca on the Ca ₃ Co ₄ O ₉ thermoelectric properties. Journal of Alloys and Compounds, 2013, 577, 511-515.	2.8	66
5	Ag distribution in thick Bi-2212 floating zone textured rods. Journal of the European Ceramic Society, 2005, 25, 2947-2950.	2.8	60
6	Solution-based synthesis routes to thermoelectric Bi ₂ Ca ₂ Co _{1.7} O _x . Journal of the European Ceramic Society, 2011, 31, 1763-1769.	2.8	53
7	New method to improve the grain alignment and performance of thermoelectric ceramics. Materials Letters, 2012, 83, 144-147.	1.3	53
8	The influence of Pb and Ag doping on the J_c (H_c , T_c) dependence and the mechanical properties of Bi-2212 textured rods. Superconductor Science and Technology, 2009, 22, 034012.	1.8	52
9	Very Large Superconducting Currents Induced by Growth Tailoring. Crystal Growth and Design, 2015, 15, 2094-2101.	1.4	52
10	Relationship Between Growth Speed, Microstructure, Mechanical and Electrical Properties in Bi-2212/Ag Textured Composites. Journal of Superconductivity and Novel Magnetism, 2012, 25, 799-804.	0.8	49
11	Effect of synthesis methods on the Ca ₃ Co ₄ O ₉ thermoelectric ceramic performances. Journal of Solid State Chemistry, 2015, 221, 247-254.	1.4	49
12	Enhancement of mechanical and thermoelectric properties of Ca ₃ Co ₄ O ₉ by Ag addition. Journal of the European Ceramic Society, 2015, 35, 3835-3841.	2.8	48
13	Significant enhancement of the thermoelectric performance in Ca ₃ Co ₄ O ₉ thermoelectric materials through combined strontium substitution and hot-pressing process. Journal of the European Ceramic Society, 2019, 39, 1186-1192.	2.8	46
14	Efecto de la adición de Ag en Bi-2212 texturado mediante laser. Boletín De La Sociedad Española De Cerámica Y Vidrio, 2005, 44, 199-203.	0.9	46
15	Improvement of Bi ₂ Sr ₂ Co _{1.8} O _x thermoelectric properties by laser floating zone texturing. Solid State Ionics, 2009, 180, 827-830.	1.3	45
16	Improved thermoelectric properties in directionally grown Bi ₂ Sr ₂ Co _{1.8} O _y ceramics by Pb for Bi substitution. Materials Research Bulletin, 2011, 46, 2537-2542.	2.7	45
17	Enhancement of the high-temperature thermoelectric performance of Bi ₂ Ba ₂ Co ₂ O _x ceramics. Scripta Materialia, 2013, 68, 75-78.	2.6	45
18	Improvement of textured Bi _{1.6} Pb _{0.4} Sr ₂ Co _{1.8} O thermoelectric performances by metallic Ag additions. Ceramics International, 2013, 39, 1597-1602.	2.3	43

#	ARTICLE	IF	CITATIONS
19	Effect of Ag addition on the mechanical and thermoelectric performances of annealed Bi ₂ Sr ₂ Co _{1.8} O _x textured ceramics. Journal of the European Ceramic Society, 2012, 32, 3745-3751.	2.8	42
20	Fabrication and properties of textured Bi-based cobaltite thermoelectric rods by zone melting. Journal of the European Ceramic Society, 2007, 27, 3697-3700.	2.8	39
21	Enhancement of the thermoelectric properties of directionally grown Bi ₂ Ca ₂ Co ₂ O ₈ through Pb for Bi substitution. Journal of the European Ceramic Society, 2010, 30, 1815-1820.	2.8	39
22	New solution method to produce high performance thermoelectric ceramics: A case study of Bi-Sr-Co-O. Materials Letters, 2010, 64, 2566-2568.	1.3	38
23	Tailoring Ca ₃ Co ₄ O ₉ microstructure and performances using a transient liquid phase sintering additive. Journal of the European Ceramic Society, 2016, 36, 1025-1032.	2.8	38
24	Barras texturadas de (Bi _{1.6} Pb _{0.4})Sr ₂ CaCu ₂ O ₈ + \tilde{A} dopadas con Ag. Boletín De La Sociedad Española De Cerámica Y Vidrio, 2008, 47, 148-152.	0.9	38
25	Cerámicas termoeléctricas Bi ₂ Ca ₂ Co ₂ O ₈ + \tilde{A} texturadas mediante fusión zonal flotante inducida por láser. Boletín De La Sociedad Española De Cerámica Y Vidrio, 2008, 47, 225-228.	0.9	38
26	Improved Thermoelectric Properties of Bi-M-Co-O (M=ÅSr, Ca) Misfit Compounds by Laser Directional Solidification. Journal of Electronic Materials, 2010, 39, 1601-1605.	1.0	37
27	Precursor Influence on the Electrical Properties of Textured Bi-2212 Superconductors. Journal of Superconductivity and Novel Magnetism, 2011, 24, 19-25.	0.8	37
28	Growth rate effects on the thermoelectric performance of CaMnO ₃ -based ceramics. Journal of the European Ceramic Society, 2019, 39, 4184-4188.	2.8	37
29	Growth rate effect on microstructure and thermoelectric properties of melt grown Bi ₂ Ba ₂ Co ₂ O _x textured ceramics. Advances in Applied Ceramics, 2012, 111, 490-494.	0.6	36
30	Effect of Cu by Co substitution on Ca ₃ Co ₄ O ₉ thermoelectric ceramics. Journal of Materials Science: Materials in Electronics, 2013, 24, 2309-2314.	1.1	36
31	Properties variation of Bi-2212 directionally solidified induced by 0.4Pb substitution. Journal of the European Ceramic Society, 2007, 27, 3959-3962.	2.8	33
32	Improvement of superconducting properties in Na-doped BSCCO superconductor. Journal of Materials Science: Materials in Electronics, 2015, 26, 441-447.	1.1	33
33	Relationship Between Annealing Time and Magnetic Properties in Bi-2212 Textured Composites. Journal of Superconductivity and Novel Magnetism, 2013, 26, 873-878.	0.8	30
34	Use of laser technology to produce high thermoelectric performances in Bi ₂ Sr ₂ Co _{1.8} O _x . Materials & Design, 2015, 75, 143-148.	5.1	29
35	Variación de las curvas E-I en la transición normal superconductor de cerámicas texturadas Bi-2212 por adición de PB. Boletín De La Sociedad Española De Cerámica Y Vidrio, 2006, 45, 228-232.	0.9	29
36	Effect of Current Polarity on BSCCO/Ag Ceramics Textured by Electrically Assisted Laser Floating Zone. Journal of Superconductivity and Novel Magnetism, 2013, 26, 943-946.	0.8	26

#	ARTICLE	IF	CITATIONS
37	High thermoelectric performance in Bi _{2-x} Pb _x Ba ₂ Co ₂ O _y promoted by directional growth and annealing. <i>Journal of the European Ceramic Society</i> , 2016, 36, 67-74.	2.8	26
38	Effect of Ce Substitution on the Magnetoresistivity and Flux Pinning Energy of the Bi ₂ Sr ₂ Ca _{1-x} Ce _x Cu ₂ O _{8+y} Superconductors. <i>Journal of Low Temperature Physics</i> , 2014, 174, 136-147.	0.6	24
39	Effect of Na substitution on superconducting properties of Bi-2212 ceramics prepared by Sinter-Forged process. <i>Journal of the European Ceramic Society</i> , 2017, 37, 1007-1012.	2.8	24
40	Structural, Electrical, and Magnetic Properties of the Co-Substituted Bi-2212 System Textured by Laser Floating Zone Technique. <i>Journal of Superconductivity and Novel Magnetism</i> , 2014, 27, 53-59.	0.8	23
41	Effect of Yb-substitution on thermally activated flux creep in the Bi ₂ Sr ₂ Ca ₁ Cu ₂ Yb _x O _y superconductors. <i>Journal of Materials Science: Materials in Electronics</i> , 2013, 24, 2568-2575.	1.1	22
42	Physical, Mechanical and Magnetic Properties of the Yb-Substituted Bi ₂ Sr ₂ Ca ₁ Cu ₂ O _y Textured Superconductor. <i>Journal of Superconductivity and Novel Magnetism</i> , 2013, 26, 111-115.	0.8	22
43	Effect of Na doping on the Ca ₃ Co ₄ O ₉ thermoelectric performance. <i>Ceramics International</i> , 2015, 41, 10897-10903.	2.3	22
44	Role of Ag in textured-annealed Bi ₂ Ca ₂ Co _{1.7} O _x thermoelectric ceramic. <i>Acta Materialia</i> , 2016, 102, 273-283.	3.8	22
45	Effect of Ce substitution on structural and superconducting properties of Bi-2212 system. <i>Journal of Materials Science: Materials in Electronics</i> , 2013, 24, 1580-1586.	1.1	21
46	Effect of simultaneous K, and Yb substitution for Ca on the microstructural and thermoelectric characteristics of CaMnO ₃ ceramics. <i>Ceramics International</i> , 2018, 44, 12697-12701.	2.3	21
47	Improvement of Bi ₂ Sr ₂ Co ₂ O _y thermoelectric performances by Na doping. <i>Journal of Electroceramics</i> , 2018, 40, 11-15.	0.8	21
48	Effect of Pb doping on the electrical properties of textured Bi-2212 superconductors. <i>Journal of the European Ceramic Society</i> , 2014, 34, 2977-2982.	2.8	19
49	Effect of synthesis process on the densification, microstructure, and electrical properties of Ca _{0.9} Yb _{0.1} MnO ₃ ceramics. <i>International Journal of Applied Ceramic Technology</i> , 2017, 14, 1190-1196.	1.1	19
50	Effect of Ga addition on Ca-deficient Ca ₃ Co ₄ O _y thermoelectric materials. <i>Ceramics International</i> , 2014, 40, 6255-6260.	2.3	18
51	Effect of Yttrium substitution on superconductivity in Bi-2212 textured rods prepared by a LFZ technique. <i>Ceramics International</i> , 2016, 42, 3418-3423.	2.3	18
52	Effect of annealing on the thermoelectric properties of directionally grown Bi ₂ Sr ₂ Co _{1.8} O _x ceramics. <i>Ceramics International</i> , 2012, 38, 5419-5424.	2.3	17
53	Relationship Between Growth Speed and Magnetic Properties in Bi-2212/Ag Textured Composites. <i>Journal of Superconductivity and Novel Magnetism</i> , 2013, 26, 1093-1098.	0.8	17
54	Structural, superconducting and mechanical properties of molybdenum substituted Bi _{1.8} Sr ₂ Ca _{1.1} Cu _{2.1} O _y . <i>Journal of Materials Science: Materials in Electronics</i> , 2013, 24, 1158-1167.	1.1	17

#	ARTICLE	IF	CITATIONS
55	Improvement of structural and superconducting properties of Bi-2212 textured rods by substituting sodium. <i>Ceramics International</i> , 2016, 42, 8473-8477.	2.3	16
56	Sintering Effects in Na-Substituted Bi-(2212) Superconductor Prepared by a Polymer Method. <i>Journal of Superconductivity and Novel Magnetism</i> , 2015, 28, 1913-1924.	0.8	15
57	Effect of Na-doping on thermoelectric and magnetic performances of textured Bi ₂ Sr ₂ Co ₂ O _y ceramics. <i>Journal of the European Ceramic Society</i> , 2018, 38, 515-520.	2.8	15
58	Floating zone Ag doped (Bi ₁₋₆ Pb _{0.4})Sr ₂ CaCu ₂ O _{8+δ} textured rods. <i>Advances in Applied Ceramics</i> , 2009, 108, 285-289.	0.6	14
59	Improvement of thermoelectric performances of Bi ₂ Sr ₂ Co _{1.8} O _x textured materials by Pb addition using a polymer solution method. <i>Materials Letters</i> , 2012, 76, 5-7.	1.3	14
60	Development of a new thermoelectric Bi ₂ Ca ₂ Co _{1.7} O _x +Ca ₃ Co ₄ O ₉ composite. <i>Scripta Materialia</i> , 2014, 80, 1-4.	2.6	14
61	Effect of K substitution on Structural, Electrical and Magnetic Properties of Bi-2212 system. <i>Journal of Materials Science: Materials in Electronics</i> , 2014, 25, 4476-4482.	1.1	13
62	Improvement of the intergranular pinning energy in the Na-doped Bi-2212 superconductors. <i>Journal of Materials Science: Materials in Electronics</i> , 2015, 26, 2830-2837.	1.1	13
63	Improvement of thermoelectric properties in Ca ₃ Co ₄ O ₉ ceramics by Ba doping. <i>Journal of Materials Science: Materials in Electronics</i> , 2015, 26, 3466-3473.	1.1	13
64	Relationship between microstructure and superconducting properties in hot-pressed Bi-2212/Ag ceramic composites. <i>Ceramics International</i> , 2015, 41, 14924-14929.	2.3	13
65	Modification of physical and structural properties of Bi _{1.8} Pb _{0.4} Sr ₂ Ca _{2.2} Cu ₃ O _y ceramics induced by annealing. <i>Physica B: Condensed Matter</i> , 2013, 426, 85-89.	1.3	12
66	Fabrication and evolution of nanoprecursors to produce Bi(Pb)-2212/Ag textured superconducting composites. <i>Ceramics International</i> , 2015, 41, 14276-14284.	2.3	12
67	Mejora de las propiedades termoeléctricas de Bi ₂ Sr ₂ Co _{1.8} O _x por métodos de síntesis en disolución. <i>Boletín De La Sociedad Española De Cerámica Y Vidrio</i> , 2012, 51, 1-6.	0.9	12
68	Effect of metallic Ag on the properties of Bi-2212 ceramic superconductors. <i>Journal of Materials Science: Materials in Electronics</i> , 2013, 24, 3344-3351.	1.1	11
69	Effect of alkaline earth dopant on density, mechanical, and electrical properties of Cu _{0.97} AE _{0.03} CrO ₂ (AE = Mg, Ca, Sr, and Ba) delafossite oxide. <i>Journal of the Australian Ceramic Society</i> , 2019, 55, 257-263.	1.1	11
70	From nanosized precursors to high performance ceramics: The case of Bi ₂ Ca ₂ Co _{1.7} O _x . <i>Materials Letters</i> , 2017, 191, 14-16.	1.3	10
71	The Influence of Postannealing on Structural and Superconducting Properties of Bi-2212 Ceramics. <i>Journal of Superconductivity and Novel Magnetism</i> , 2013, 26, 3247-3252.	0.8	9
72	Effect of Postannealing Process on Bi ₂ Sr _{2.1} Ca _{0.9} Cu ₂ O _{8+δ} Textured Superconductors. <i>Journal of Superconductivity and Novel Magnetism</i> , 2013, 26, 985-990.	0.8	9

#	ARTICLE	IF	CITATIONS
73	Decrease of $\text{Ca}_3\text{Co}_4\text{O}_9$ thermal conductivity by Yb-doping. <i>Ceramics International</i> , 2015, 41, 12529-12534.	2.3	9
74	Textured Pb-Doped Bi-2212 Superconductors for Current Limiters. <i>Journal of Superconductivity and Novel Magnetism</i> , 2015, 28, 447-452.	0.8	9
75	Drastic enhancement of mechanical properties of $\text{Ca}_3\text{Co}_4\text{O}_9$ by B4C addition. <i>Journal of the European Ceramic Society</i> , 2021, 41, 402-408.	2.8	9
76	Thermoelectric doping effect in $\text{Ca}_3\text{Co}_{4-x}\text{Ni}_x\text{O}_9$ ceramics. <i>Boletin De La Sociedad Espanola De Ceramica Y Vidrio</i> , 2015, 54, 21-27.	0.9	8
77	Effects of K substitution on thermoelectric and magnetic properties of $\text{Bi}_2\text{Sr}_2\text{Co}_2\text{O}_y$ ceramic. <i>Journal of Materials Science: Materials in Electronics</i> , 2017, 28, 12652-12659.	1.1	8
78	Thermoelectric properties of rare earth doped $\text{Ca}_3\text{-xRE}_x\text{Co}_4\text{O}_9$ (RE = Dy, Er, Gd, and Tb; $x = 0, 0.01, 0.03$), <i>Ti ETQq 0 0 rgBT / C</i>	0.8	7
79	Decrease of electrical resistivity in $\text{Ca}_3\text{Co}_4\text{O}_9$ thermoelectric ceramics by Ti doping. <i>Journal of Materials Science: Materials in Electronics</i> , 2015, 26, 815-820.	1.1	7
80	The Effect of K Substitution on Magnetoresistivity and Activation Energy of Bi-2212 System. <i>Journal of Superconductivity and Novel Magnetism</i> , 2015, 28, 553-559.	0.8	7
81	Effect of Na substitution and Ag addition on the superconducting properties of Bi-2212 textured materials. <i>Journal of Materials Science: Materials in Electronics</i> , 2017, 28, 6278-6283.	1.1	7
82	Improving bulk $\text{Ca}_3\text{Co}_4\text{O}_9$ thermoelectric materials through Zr doping. <i>Advances in Applied Ceramics</i> , 2018, 117, 142-146.	0.6	7
83	New environmentally friendly Ba-Fe-O thermoelectric material by flexible laser floating zone processing. <i>Scripta Materialia</i> , 2018, 145, 54-57.	2.6	7
84	U-type unileg thermoelectric module: A novel structure for high-temperature application with long lifespan. <i>Energy</i> , 2022, 238, 121771.	4.5	7
85	Thermoelectric properties in $\text{Ca}_3\text{Co}_4\text{Mn}_x\text{O}_y$ ceramics. <i>Advances in Applied Ceramics</i> , 2015, 114, 303-308.	0.6	6
86	Thermoelectric properties of directionally grown $\text{Bi}_2\text{Ba}_2\text{Co}_2\text{O}_7/\text{Ag}$ composites: effect of annealing. <i>Journal of Materials Science: Materials in Electronics</i> , 2016, 27, 12964-12973.	1.1	6
87	Effect of substrate on the microstructure and thermoelectric performances of Sr-doped $\text{Ca}_3\text{Co}_4\text{O}_9$ thick films. <i>Ceramics International</i> , 2019, 45, 5431-5435.	2.3	6
88	Effect of Rubidium Substitution on the Physical and Superconducting Properties of Textured High-Tc BSCCO Samples. <i>Journal of Superconductivity and Novel Magnetism</i> , 2020, 33, 1285-1292.	0.8	6
89	Influence of Ca substitution by Mg on the $\text{Ca}_3\text{Co}_4\text{O}_9$ performances. <i>Boletin De La Sociedad Espanola De Ceramica Y Vidrio</i> , 2014, 53, 41-47.	0.9	6
90	Electrical Polarization Effect on $\text{Bi}_2\text{Ca}_2\text{Co}_1.7\text{O}_x$ thermoelectrics grown by laser floating zone. <i>Microscopy and Microanalysis</i> , 2012, 18, 93-94.	0.2	5

#	ARTICLE	IF	CITATIONS
91	The effect of environmental conditions on the mechanical and thermoelectric properties of Bi ₂ Ca ₂ Co _{1.7} O _x textured rods. <i>Ceramics International</i> , 2015, 41, 6358-6363.	2.3	5
92	Preparation of high performance Bi ₂ Sr ₂ Co _{1.8} O _x thermoelectric materials from nanosized precursors. <i>Advances in Applied Ceramics</i> , 2017, 116, 383-391.	0.6	5
93	Effect of precursors on the microstructure and electrical properties of Bi ₂ Ba ₂ Co ₂ O _x . <i>Journal of the Australian Ceramic Society</i> , 2017, 53, 583-590.	1.1	5
94	Influence of Ag on the Properties of Ca _{0.9} Yb _{0.1} MnO ₃ Sintered Ceramics. <i>Materials</i> , 2018, 11, 2503.	1.3	5
95	Effect of Na-substitution on magnetoresistance and flux pinning energy of Bi-2212 ceramics prepared via hot-forging process. <i>Journal of Materials Science: Materials in Electronics</i> , 2018, 29, 19147-19154.	1.1	5
96	Effect of Carbon Nanotube Addition on the Superconducting Properties of BSCCO Samples Textured via Laser Floating Zone Technique. <i>Journal of Superconductivity and Novel Magnetism</i> , 2019, 32, 3135-3141.	0.8	5
97	Enhancement of electrical conductivity of Ca _{2.93} Sr _{0.07} Co ₄ O ₉ thick films via hot uniaxial pressing. <i>International Journal of Applied Ceramic Technology</i> , 2020, 17, 1322-1327.	1.1	5
98	Stress corrosion cracking of Bi-2212 thin rods. <i>Journal of the European Ceramic Society</i> , 2007, 27, 3963-3966.	2.8	4
99	Effect of Fe Substitution for Cu on Microstructure and Magnetic Properties of Laser Floating Zone (LFZ) Grown Bi-2212 Rods. <i>Journal of Superconductivity and Novel Magnetism</i> , 2013, 26, 1143-1149.	0.8	4
100	Modification of thermoelectric properties in Ca ₃ Co ₄ O _y ceramics by Nd doping. <i>Journal of Materials Science: Materials in Electronics</i> , 2014, 25, 922-927.	1.1	4
101	High Thermoelectric Performances in Co-oxides Processed by a Laser Floating Zone Technique. <i>Materials Today: Proceedings</i> , 2015, 2, 654-660.	0.9	4
102	Improved thermoelectric performances in textured Bi _{1.6} Pb _{0.4} Ba ₂ Co ₂ O _y /Ag composites. <i>Ceramics International</i> , 2016, 42, 18592-18596.	2.3	4
103	Thermoelectrics. <i>Materials Today</i> , 2016, 19, 415-416.	8.3	4
104	Enhanced electrical and thermoelectric properties from textured Bi _{1.6} Pb _{0.4} Ba ₂ Co ₂ O _y /Ag composites. <i>Journal of Materials Science</i> , 2017, 52, 4833-4839.	1.7	4
105	Effect of Cesium Substitution on the Superconducting Properties of Bi-2212 Samples Prepared Via Solid-State Reaction and Laser Floating Zone Technique. <i>Journal of Superconductivity and Novel Magnetism</i> , 2019, 32, 3439-3448.	0.8	4
106	High-Temperature Stability of Hot-Pressed Sr-Doped Ca ₃ Co ₄ O ₉ . <i>Journal of Electronic Materials</i> , 2019, 48, 1965-1970.	1.0	4
107	Improvement of thermoelectric properties of Ca _{0.9} Gd _{0.1} MnO ₃ by powder engineering through K ₂ CO ₃ additions. <i>Journal of Materials Science</i> , 2019, 54, 3252-3261.	1.7	4
108	Tuning thermoelectric properties of Ca _{0.9} Gd _{0.1} MnO ₃ by laser processing. <i>Journal of Materials Science: Materials in Electronics</i> , 2020, 31, 18913-18922.	1.1	4

#	ARTICLE	IF	CITATIONS
109	Detail investigation of thermoelectric performance and magnetic properties of Cs-doped Bi ₂ Sr ₂ Co ₂ O _y ceramic materials. SN Applied Sciences, 2021, 3, 1.	1.5	4
110	Enhanced Superconducting Properties in Bi ₂ Sr ₂ Ca ₁ Cu _{1.75} Na _{0.25} O _y Ceramics Prepared by Hot-Pressing Under Different Pressures and Temperatures. Journal of Superconductivity and Novel Magnetism, 2022, 35, 1831-1838.	0.8	4
111	Composite Bi-2212/Ag Superconductors Grown by Laser Travelling Floating Zone at Low Rates. Journal of Superconductivity and Novel Magnetism, 2015, 28, 415-418.	0.8	3
112	Unileg Thermoelectric Structure for Cycling Robustness at High Temperature and Low Manufacturing Cost. Journal of Electronic Materials, 2019, 48, 2010-2017.	1.0	3
113	Effect of annealing and potassium substitution on the thermoelectric and magnetic properties of directionally grown Bi ₂ Sr ₂ Co ₂ O ceramics. Boletin De La Sociedad Espanola De Ceramica Y Vidrio, 2020, 59, 121-128.	0.9	3
114	Significant enhancement of superconducting performances of Bi-2212 fibers through combined sodium substitution and LFZ process. Journal of Materials Science: Materials in Electronics, 2021, 32, 17686-17699.	1.1	3
115	Estudio del eutÁctico Al ₂ O ₃ -ZrO ₂ (3%) Tj ETQq1 1 0.784314 rgBT /Overlock 10 Tf 50 507 Td Boletin De La Sociedad Espanola De Ceramica Y Vidrio, 2007, 46, 119-122.	0.9	3
116	Dynamic fatigue behaviour of Ag-doped Bi-2212 textured thin rods. Journal of Physics: Conference Series, 2009, 153, 012021.	0.3	2
117	Environmental Degradation Effect on the Properties of Bi-2212 Highly Textured Rods. Journal of Superconductivity and Novel Magnetism, 2013, 26, 895-900.	0.8	2
118	Structural and Superconducting Properties of Magnetically Doped Bi-2212 Textured Rods Grown by Laser Floating Zone (LFZ) Technique. Journal of Superconductivity and Novel Magnetism, 2013, 26, 1135-1141.	0.8	2
119	New promising Co-free thermoelectric ceramic based on BaFe oxide. Journal of Materials Science: Materials in Electronics, 2013, 24, 1832-1836.	1.1	2
120	Doping effect in Ca ₃ Co _{4-x} Zn _x O _y ceramics. Journal of Materials Science: Materials in Electronics, 2014, 25, 4033-4038.	1.1	2
121	Effect of Secondary Annealing Process on Critical Current Density in Highly Textured Bi-2212 Superconducting System. Jom, 2015, 67, 2079-2086.	0.9	2
122	Mechanical and thermoelectric environmental evolution properties of Bi ₂ Sr ₂ Co _{1.8} O _x ceramics textured by laser floating zone technique. Journal of Materials Science: Materials in Electronics, 2015, 26, 1461-1465.	1.1	2
123	Grain alignment and its relationship with superconductivity and thermal transport of Ni-substituted Bi-2212 textured rods fabricated at two different growth rates. Journal of Materials Science: Materials in Electronics, 2015, 26, 3090-3099.	1.1	2
124	Growth Speed and Substitution Effects on Alignment and Thermal Transport Properties of Bi-2212 Textured Superconductors. Jom, 2015, 67, 222-232.	0.9	2
125	Laser transmission welding as an assembling process for high temperature electronic packaging. , 2016, , .		2
126	Enhancement of magnetic relaxation behavior by texturing in Bi-2212 superconducting rods. Ceramics International, 2016, 42, 8325-8330.	2.3	2

#	ARTICLE	IF	CITATIONS
127	High mechanical and thermoelectric performances in hot-pressed CdO. Journal of Materials Science: Materials in Electronics, 2017, 28, 5518-5522.	1.1	2
128	Long-Term High-Temperature Stability of Directionally Grown [Bi ₂ Ba ₂ O ₄] _p [CoO ₂] Rods. Materials, 2017, 10, 146.	1.3	2
129	High thermoelectric performances of Bi _{1-x} AE _x Co _{1-x} O compounds directionally growth from the melt. Boletín De La Sociedad Española De Cerámica Y Vidrio, 2018, 57, 1-8.	0.9	2
130	Improving thermoelectric properties of Ca ₃ Co ₄ O ₉ + δ through both Na doping and K addition at optimal values. Journal of Materials Science: Materials in Electronics, 2019, 30, 8832-8837.	1.1	2
131	Drastic modification of low temperature thermoelectric properties of Na-doped Bi ₂ Sr ₂ Co ₂ O _y ceramics prepared via laser floating zone technique. Journal of Materials Science: Materials in Electronics, 2020, 31, 15558-15564.	1.1	2
132	Exploring the High-Temperature Electrical Performance of Ca ₃ δ xLa _x Co ₄ O ₉ Thermoelectric Ceramics for Moderate and Low Substitution Levels. Symmetry, 2021, 13, 782.	1.1	2
133	Tuning thermoelectric properties of Bi ₂ Ca ₂ Co ₂ O _y through K doping and laser floating zone processing. Solid State Sciences, 2021, 120, 106732.	1.5	2
134	Effect of Ag additions on the Bi _{1-x} Pb _x Co _{1-x} O thermoelectric properties. Boletín De La Sociedad Española De Cerámica Y Vidrio, 2013, 52, 93-97.	0.8	2
135	Processing effects on the thermoelectric properties of Bi _{2-x} Ca ₂ Co ₂ O _y ceramics. Boletín De La Sociedad Española De Cerámica Y Vidrio, 2014, 53, 207-212.	0.9	2
136	Influence of ceramic particles additions on the properties of Ca ₃ Co ₄ O ₉ . SN Applied Sciences, 2022, 4, 1.	1.5	2
137	A thermoelectric by any other name! . Materials Today, 2012, 15, 415.	8.3	1
138	Effect of Yb substitution in Bi-2212 ceramics prepared by laser floating zone technique. Journal of Materials Science: Materials in Electronics, 2015, 26, 5761-5766.	1.1	1
139	Thermal Conductivity and Thermoelectric Power of Yb-Substituted Bi-2212 Superconductor. Journal of Physics: Conference Series, 2016, 667, 012001.	0.3	1
140	General approach of the photothermoelectric technique for thermal characterization of solid thermoelectric materials. Journal Physics D: Applied Physics, 2017, 50, 265501.	1.3	1
141	Superconducting stacks. Materials Today, 2018, 21, 98-99.	8.3	1
142	Reduction in Processing Time in Ca ₃ Co ₄ O ₉ + δ Ceramics through Nanoprecursors Produced by an Easily Scalable and Environmentally Friendly Process. Nanomaterials, 2020, 10, 2533.	1.9	1
143	Drastic microstructural modification of Bi ₂ Ca ₂ Co ₂ O ceramics by Na doping and laser texturing. Boletín De La Sociedad Española De Cerámica Y Vidrio, 2022, 61, 634-640.	0.9	1
144	Ceramics, squared. Materials Today, 2013, 16, 151-152.	8.3	0

#	ARTICLE	IF	CITATIONS
145	Thermal Conductivity and Thermoelectric Power of Potassium and Sodium-Substituted Bi-2212 Superconductor Prepared by PEI Technique. Journal of Superconductivity and Novel Magnetism, 2015, 28, 2641-2647.	0.8	0
146	In-situ measurements of temperature distribution during transmission laser welding of poly(aryletherketone). AIP Conference Proceedings, 2016, , .	0.3	0
147	Physical, electrical and magnetic properties of Cr doped Bi ₂ Sr ₂ Ca ₁ Cu ₂ âˆ™xCr _x O _y (Bi-2212) superconductors prepared by laser floating zone technique. Journal of Materials Science: Materials in Electronics, 2017, 28, 13120-13125.	1.1	0
148	Processing of Superconducting and Thermoelectric Bulk Materials Via Laser Technologies. NATO Science for Peace and Security Series C: Environmental Security, 2020, , 297-312.	0.1	0
149	Role of Y substitution for Ca-site on magneto-resistivity properties of Bi-2212 superconductor rods prepared by LFZ. Materials Chemistry and Physics, 2022, 282, 125995.	2.0	0
150	Variation of mechanical and electrical performances of Bi ₂ Ca ₂ Co _{1.7} O _x ceramics above working conditions. Journal of Materials Science: Materials in Electronics, 0, , .	1.1	0