

# Ian J Davies

## List of Publications by Year in Descending Order

**Source:** <https://exaly.com/author-pdf/994029/ian-j-davies-publications-by-year.pdf>

**Version:** 2024-04-28

This document has been generated based on the publications and citations recorded by exaly.com. For the latest version of this publication list, visit the link given above.

The third column is the impact factor (IF) of the journal, and the fourth column is the number of citations of the article.

124  
papers

2,206  
citations

25  
h-index

42  
g-index

129  
ext. papers

2,535  
ext. citations

3.6  
avg. IF

5.53  
L-index

#	Paper	IF	Citations
124	Direct comparison between monofilament and multifilament tow testing for evaluating the tensile strength distribution of SiC fibers. <i>Journal of the European Ceramic Society</i> , <b>2022</b> , 42, 1928-1937	6	1
123	Multi-objective particle swarm optimisation of multilayer functionally graded coating systems for improved interfacial delamination resistance. <i>Materials Today Communications</i> , <b>2020</b> , 24, 101202	2.5	0
122	Mechanisms and control of edge interfacial delamination in a multilayer system containing a functionally graded interlayer. <i>Surface and Coatings Technology</i> , <b>2020</b> , 382, 125221	4.4	2
121	Finite element analysis of edge crack delamination and optimisation of functionally graded interlayer for coated stainless steel in hydrogen storage applications. <i>Surface and Coatings Technology</i> , <b>2019</b> , 372, 148-159	4.4	6
120	Methods for accurate high-temperature Sieverts-type hydrogen measurements of metal hydrides. <i>Journal of Alloys and Compounds</i> , <b>2019</b> , 787, 1225-1237	5.7	15
119	Tribological behavior of unsaturated polyester hybrid composites containing wood flour and carbon nanotubes. <i>SN Applied Sciences</i> , <b>2019</b> , 1, 1	1.8	5
118	Optimization of material formulation and processing parameters in relation to mechanical properties of bioepoxy/clay nanocomposites using Taguchi design of experiments. <i>Journal of Applied Polymer Science</i> , <b>2018</b> , 135, 45769	2.9	6
117	Hybrid Composite Using Natural Filler and Multi-Walled Carbon Nanotubes (MWCNTs). <i>Applied Composite Materials</i> , <b>2018</b> , 25, 1323-1337	2	17
116	Effect of stacking sequence on the flexural properties of carbon and glass fibre-reinforced hybrid composites. <i>Advanced Composites and Hybrid Materials</i> , <b>2018</b> , 1, 530-540	8.7	15
115	Mechanical and thermal characterization of polyester composite containing treated wood flour from Palm oil biomass. <i>Polymer Composites</i> , <b>2018</b> , 39, 1200-1211	3	10
114	A review of micro-mechanical cutting. <i>International Journal of Advanced Manufacturing Technology</i> , <b>2018</b> , 94, 789-806	3.2	38
113	Rapid mapping and analysing rock mass discontinuities with 3D terrestrial laser scanning in the underground excavation. <i>International Journal of Rock Mechanics and Minings Sciences</i> , <b>2018</b> , 110, 28-35	6	11
112	Identification of preferred combination of factors in manufacturing bioepoxy/clay nanocomposites. <i>Advanced Composite Materials</i> , <b>2018</b> , 27, 511-530	2.8	1
111	Eco-friendly polyvinyl alcohol (PVA)/bamboo charcoal (BC) nanocomposites with superior mechanical and thermal properties. <i>Advanced Composite Materials</i> , <b>2018</b> , 27, 499-509	2.8	17
110	Effect of machining parameters on the surface finish of a metal matrix composite under dry cutting conditions. <i>Proceedings of the Institution of Mechanical Engineers, Part B: Journal of Engineering Manufacture</i> , <b>2017</b> , 231, 913-923	2.4	18
109	Mechanical properties of Macadamia nutshell powder and PLA bio-composites. <i>Australian Journal of Mechanical Engineering</i> , <b>2017</b> , 15, 150-156	1	11
108	Influence of Alkali Treatment and Nanoclay Content on the Properties of Rice Husk Filled Polyester Composites. <i>Materials Science Forum</i> , <b>2017</b> , 882, 89-100	0.4	6

107	A review identifying the effectiveness of minimum quantity lubrication (MQL) during conventional machining. <i>International Journal of Advanced Manufacturing Technology</i> , <b>2017</b> , 92, 321-340	3.2	115
106	Effect of matrix voids, fibre misalignment and thickness variation on multi-objective robust optimization of carbon/glass fibre-reinforced hybrid composites under flexural loading. <i>Composites Part B: Engineering</i> , <b>2017</b> , 123, 136-147	10	25
105	Fracture toughness enhancement of silicon carbide composites with hydrophilic-modified Tyranno <sup>®</sup> SiAlON fibre addition. <i>Advances in Applied Ceramics</i> , <b>2017</b> , 116, 278-285	2.3	1
104	Contribution of machining to the fatigue behaviour of metal matrix composites (MMCs) of varying reinforcement size. <i>International Journal of Fatigue</i> , <b>2017</b> , 102, 9-17	5	20
103	Unbiased estimation of the Weibull scale parameter using linear least squares analysis. <i>Journal of the European Ceramic Society</i> , <b>2017</b> , 37, 2973-2981	6	8
102	Multi-objective robust optimization of multi-directional carbon/glass fibre-reinforced hybrid composites with manufacture related uncertainties under flexural loading. <i>Composite Structures</i> , <b>2017</b> , 182, 132-142	5.3	23
101	Effect of filler load on the curing behavior and mechanical and thermal performance of wood flour filled thermoset composites. <i>Journal of Cleaner Production</i> , <b>2017</b> , 164, 1145-1156	10.3	31
100	Confidence limits for Weibull parameters estimated using linear least squares analysis. <i>Journal of the European Ceramic Society</i> , <b>2017</b> , 37, 5057-5064	6	8
99	Review of machining metal matrix composites. <i>International Journal of Advanced Manufacturing Technology</i> , <b>2017</b> , 90, 2429-2441	3.2	64
98	Unbiased estimation of Weibull modulus using linear least squares analysis A systematic approach. <i>Journal of the European Ceramic Society</i> , <b>2017</b> , 37, 369-380	6	11
97	Multi-objective analysis for optimal and robust design of unidirectional glass/carbon fibre reinforced hybrid epoxy composites under flexural loading. <i>Composites Part B: Engineering</i> , <b>2016</b> , 84, 130-139	10	25
96	Numerical investigation of the hybridisation mechanism in fibre reinforced hybrid composites subjected to flexural load. <i>Composites Part B: Engineering</i> , <b>2016</b> , 102, 100-111	10	18
95	Application of Markov modelling and Monte Carlo simulation technique in failure probability estimation A consideration of corrosion defects of internally corroded pipelines. <i>Engineering Failure Analysis</i> , <b>2016</b> , 68, 159-171	3.2	28
94	Multi-objective robust optimisation of unidirectional carbon/glass fibre reinforced hybrid composites under flexural loading. <i>Composite Structures</i> , <b>2016</b> , 138, 264-275	5.3	51
93	Markov chain modelling for time evolution of internal pitting corrosion distribution of oil and gas pipelines. <i>Engineering Failure Analysis</i> , <b>2016</b> , 60, 209-228	3.2	32
92	Stochastic modelling of perfect inspection and repair actions for leak failure prone internal corroded pipelines. <i>Engineering Failure Analysis</i> , <b>2016</b> , 60, 40-56	3.2	10
91	A Markovian approach for modelling the effects of maintenance on downtime and failure risk of wind turbine components. <i>Renewable Energy</i> , <b>2016</b> , 96, 775-783	8.1	25
90	Modelling the effects of production rates and physico-chemical parameters on pitting rate and pit depth growth of onshore oil and gas pipelines. <i>Corrosion Engineering Science and Technology</i> , <b>2016</b> , 51, 342-351	1.7	5

89	Robustness for unidirectional carbon/glass fibre reinforced hybrid epoxy composites under flexural loading. <i>Composite Structures</i> , <b>2015</b> , 128, 354-362	5.3	11
88	Determination of filler content for natural filler polymer composite by thermogravimetric analysis. <i>Journal of Thermal Analysis and Calorimetry</i> , <b>2015</b> , 122, 227-233	4.1	25
87	Pipeline failures in corrosive environments – A conceptual analysis of trends and effects. <i>Engineering Failure Analysis</i> , <b>2015</b> , 53, 36-58	3.2	96
86	Estimation of Internal Pit Depth Growth and Reliability of Aged Oil and Gas Pipelines – A Monte Carlo Simulation Approach. <i>Corrosion</i> , <b>2015</b> , 71, 977-991	1.8	16
85	Effect of oil palm shell powder on the mechanical performance and thermal stability of polyester composites. <i>Materials &amp; Design</i> , <b>2015</b> , 65, 823-830		38
84	Flexural strength of bidirectional hybrid epoxy composites reinforced by E glass and T700S carbon fibres. <i>Composites Part B: Engineering</i> , <b>2015</b> , 72, 65-71	1.0	62
83	Recent progress in electrospun nanofibers: Reinforcement effect and mechanical performance. <i>Journal of Polymer Science, Part B: Polymer Physics</i> , <b>2015</b> , 53, 1171-1212	2.6	53
82	Predictive Modelling of Internal Pitting Corrosion of Aged Non-Piggable Pipelines. <i>Journal of the Electrochemical Society</i> , <b>2015</b> , 162, C251-C259	3.9	19
81	Tensile strength of pine needles and their feasibility as reinforcement in composite materials. <i>Journal of Materials Science</i> , <b>2014</b> , 49, 8057-8062	4.3	7
80	The Effect of Alkali Treatment of OPKS Filler on Mechanical Property of Polyester-Composite. <i>Advanced Materials Research</i> , <b>2014</b> , 980, 86-90	0.5	6
79	Advanced Composites with Natural Reinforcement. <i>Advances in Materials Science and Engineering</i> , <b>2014</b> , 2014, 1-2	1.5	
78	Flexural and tensile moduli of unidirectional hybrid epoxy composites reinforced by S-2 glass and T700S carbon fibres. <i>Materials &amp; Design</i> , <b>2014</b> , 54, 893-899		49
77	Flexural and tensile strengths of unidirectional hybrid epoxy composites reinforced by S-2 glass and T700S carbon fibres. <i>Materials &amp; Design</i> , <b>2014</b> , 54, 955-966		60
76	Sustainable asset integrity management: Strategic imperatives for economic renewable energy generation. <i>Renewable Energy</i> , <b>2014</b> , 67, 143-152	8.1	11
75	Flexural Properties of E Glass and TR50S Carbon Fiber Reinforced Epoxy Hybrid Composites. <i>Journal of Materials Engineering and Performance</i> , <b>2013</b> , 22, 41-49	1.6	51
74	A simulation study of the Japanese b – <i>Proceedings of the Institution of Mechanical Engineers, Part P: Journal of Sports Engineering and Technology</i> , <b>2013</b> , 227, 265-272	0.7	
73	Flexural properties of glass and carbon fiber reinforced epoxy hybrid composites. <i>Proceedings of the Institution of Mechanical Engineers, Part L: Journal of Materials: Design and Applications</i> , <b>2013</b> , 227, 308-317	1.3	8
72	Optimal design for the flexural behaviour of glass and carbon fibre reinforced polymer hybrid composites. <i>Materials &amp; Design</i> , <b>2012</b> , 37, 450-457		116

71	Flexural properties of macadamia nutshell particle reinforced polyester composites. <i>Composites Part B: Engineering</i> , <b>2012</b> , 43, 2751-2756	10	26
70	Flexural properties of S-2 glass and TR30S carbon fiber-reinforced epoxy hybrid composites. <i>Polymer Composites</i> , <b>2012</b> , 33, 773-781	3	40
69	Flexural properties of hybrid composites reinforced by S-2 glass and T700S carbon fibres. <i>Composites Part B: Engineering</i> , <b>2012</b> , 43, 573-581	10	110
68	Flexural Properties of Wheat Straw Reinforced Polyester Composites. <i>American Journal of Materials Science</i> , <b>2012</b> , 1, 71-75		7
67	EFFECT OF $\beta$ -CALCIUM ORTHOPHOSPHATE ADDITION ON HIGH- TEMPERATURE PLASTIC DEFORMATION OF HYDROXYAPATITE WITH SUBMICROMETER-SIZED GRAINS. <i>Phosphorus Research Bulletin</i> , <b>2012</b> , 27, 11-17	0.3	
66	Formation of silicon carbide layer on the vapor-grown carbon nanofiber by sol-gel and carbothermal reduction techniques <b>2011</b> ,		1
65	Influence of flaw distribution on single fibre fragmentation. <i>Proceedings of the Institution of Civil Engineers: Engineering and Computational Mechanics</i> , <b>2011</b> , 164, 163-169	0.3	0
64	Superplastic deformation of hydroxyapatite ceramics with B <sub>2</sub> O <sub>3</sub> or Na <sub>2</sub> O addition fabricated by pulse current pressure sintering. <i>Journal of the European Ceramic Society</i> , <b>2011</b> , 31, 2641-2648	6	13
63	Fabrication of dense $\beta$ -calcium orthophosphate with submicrometer-sized grains and its high-temperature superplastic deformation. <i>Journal of Materials Science</i> , <b>2011</b> , 46, 1956-1962	4.3	
62	Fabrication of Highly-Densified Hydroxyapatite Ceramic with Boron Oxide Addition and Its Superplastic Deformation. <i>IOP Conference Series: Materials Science and Engineering</i> , <b>2011</b> , 18, 022020	0.4	1
61	Effect of Surface-Modified Si-Al-C Fibre Addition on the Mechanical Properties of Silicon Carbide Composite. <i>Advances in Science and Technology</i> , <b>2010</b> , 71, 127-132	0.1	2
60	Preparation of submicrometer-sized porous spherical hydroxyapatite agglomerates by ultrasonic spray pyrolysis technique. <i>Journal of the Ceramic Society of Japan</i> , <b>2010</b> , 118, 462-466	1	22
59	Processing of a porous titanium alloy from elemental powders using a solid state isothermal foaming technique. <i>Journal of Materials Science: Materials in Medicine</i> , <b>2010</b> , 21, 3103-7	4.5	22
58	Fabrication of silicon carbide composites with carbon nanofiber addition and their fracture toughness. <i>Journal of Materials Science</i> , <b>2010</b> , 45, 6052-6058	4.3	9
57	PREPARATION OF POROUS SPHERICAL HYDROXYAPATITE AGGLOMERATES INTERACTED WITH CYCLODEXTRIN. <i>Phosphorus Research Bulletin</i> , <b>2010</b> , 24, 54-61	0.3	1
56	Fabrication and Properties of Recycled Cellulose Fibre-Reinforced Epoxy Composites. <i>Composite Interfaces</i> , <b>2009</b> , 16, 659-669	2.3	50
55	Effect of colloidal silica addition on the formation of porous spherical .ALPHA.-calcium orthophosphate agglomerates by spray pyrolysis technique. <i>Journal of the Ceramic Society of Japan</i> , <b>2009</b> , 117, 363-368	1	3
54	FABRICATION OF FLUORAPATITE CERAMIC MATERIAL WITH SUBMICROME -45- TER-SIZED GRAINS AND ITS HIGH-TEMPERATURE PLASTIC DEFORMATION. <i>Phosphorus Research Bulletin</i> , <b>2009</b> , 23, 45-51	0.3	

53	Mechanical and Thermal Properties of Silicon Carbide Composites with Chopped Si-Al-C Fiber Addition. <i>Key Engineering Materials</i> , <b>2008</b> , 403, 257-260	0.4	2
52	Flexural Failure of Unidirectional Hybrid Fibre-Reinforced Polymer (FRP) Composites Containing Different Grades of Glass Fibre. <i>Advanced Materials Research</i> , <b>2008</b> , 41-42, 357-362	0.5	21
51	Influence of Compressive Pressure, Vacuum Pressure, and Holding Temperature Applied during Autoclave Curing on the Microstructure of Unidirectional CFRP Composites. <i>Advanced Materials Research</i> , <b>2008</b> , 41-42, 323-328	0.5	10
50	Mechanical and Physical Properties of Recycled Cellulose Fibre-Reinforced Epoxy Eco-Composites. <i>Advanced Materials Research</i> , <b>2008</b> , 41-42, 317-322	0.5	1
49	The effect of processing parameters on the flexural properties of unidirectional carbon fibre-reinforced polymer (CFRP) composites. <i>Materials Science &amp; Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , <b>2008</b> , 498, 65-68	5.3	33
48	Compressive failure of unidirectional hybrid fibre-reinforced epoxy composites containing carbon and silicon carbide fibres. <i>Composites Part A: Applied Science and Manufacturing</i> , <b>2007</b> , 38, 1070-1074	8.4	18
47	Microstructure-Property Relationships in Human Adult and Baby Canine Teeth. <i>Key Engineering Materials</i> , <b>2006</b> , 309-311, 23-26	0.4	4
46	Mapping the Microstructure-Property Relationships in Cortical Bone. <i>Key Engineering Materials</i> , <b>2006</b> , 309-311, 523-526	0.4	
45	Preparation of Hollow and Spherical Calcium Orthophosphate Agglomerates: Effect of Organic Compound Addition to the Spraying Solution. <i>Key Engineering Materials</i> , <b>2006</b> , 309-311, 129-132	0.4	2
44	Properties of Calcium Phosphate Powder Prepared from Phosphoryl Oligosaccharides of Calcium. <i>Key Engineering Materials</i> , <b>2006</b> , 309-311, 515-518	0.4	4
43	Thermal properties of silicon carbide composites fabricated with chopped Tyranno SiAlC fibres. <i>Journal of the European Ceramic Society</i> , <b>2006</b> , 26, 703-710	6	12
42	In situ neutron diffraction investigation on the phase transformation sequence of kaolinite and halloysite to mullite. <i>Physica B: Condensed Matter</i> , <b>2006</b> , 385-386, 555-557	2.8	12
41	Effect of chopped SiAlC fiber addition on the mechanical properties of silicon carbide composite. <i>Journal of Materials Science</i> , <b>2006</b> , 41, 7466-7473	4.3	5
40	MICROSTRUCTURES OF SPHERICAL CALCIUM-PHOSPHATE AGGLOMERATES PREPARED BY SPRAY-PYROLYSIS AND FREEZE-DRYING TECHNIQUES. <i>Phosphorus Research Bulletin</i> , <b>2006</b> , 20, 47-60	0.3	4
39	Distribution of fibre pullout length and interface shear strength within a single fibre bundle for an orthogonal 3-D woven Si-Ti-C-O fibre/Si-Ti-C-O matrix composite tested at 1100°C in air. <i>Journal of the European Ceramic Society</i> , <b>2005</b> , 25, 599-604	6	3
38	Effect of variable radius on the initial creep rate of ceramic fibres. <i>Journal of Materials Science</i> , <b>2005</b> , 40, 6187-6193	4.3	4
37	Multiple Cracking and Tensile Behavior for an Orthogonal 3-D Woven Si-Ti-C-O Fiber/Si-Ti-C-O Matrix Composite. <i>Journal of the American Ceramic Society</i> , <b>2004</b> , 84, 1565-1574	3.8	31
36	Mirror Constant for Tyranno Silicon-Titanium-Carbon-Oxygen Fibers Measured in Situ in a Three-Dimensional Woven Silicon Carbide/Silicon Carbide Composite. <i>Journal of the American Ceramic Society</i> , <b>2004</b> , 85, 691-693	3.8	4

35	Best estimate of Weibull modulus obtained using linear least squares analysis: An improved empirical correction factor. <i>Journal of Materials Science</i> , <b>2004</b> , 39, 1441-1444	4.3	21
34	Morphological and microstructural changes during the heating of spherical calcium orthophosphate agglomerates prepared by spray pyrolysis. <i>Particuology: Science and Technology of Particles</i> , <b>2004</b> , 2, 200-206		9
33	The effect of rare-earth oxide addition on the hot-pressing of magnesium silicon nitride. <i>Journal of the European Ceramic Society</i> , <b>2002</b> , 22, 777-783	6	18
32	Densification and microstructural developments during the sintering of aluminium silicon carbide. <i>Journal of Materials Science</i> , <b>2002</b> , 37, 335-342	4.3	22
31	Sinterability of magnesium silicon nitride powder with yttrium oxide addition coated using the homogeneous precipitation method. <i>Journal of Materials Science</i> , <b>2002</b> , 37, 737-744	4.3	6
30	Comparison between predicted and experimental stress/strain behavior for a 3-D woven SiC/SiC composite tested between room temperature and 1300 °C. <i>Journal of Materials Science Letters</i> , <b>2002</b> , 21, 461-463		
29	Mechanical and thermal properties of silicon-carbide composites fabricated with short Tyranno <sup>®</sup> Si-Zr-C-O fibre. <i>Journal of Materials Science</i> , <b>2001</b> , 36, 3679-3686	4.3	21
28	Bundle to bundle variation of mean fiber radius for Tyranno <sup>®</sup> LoxM Si-Ti-C-O fibers. <i>Journal of Materials Science Letters</i> , <b>2001</b> , 20, 505-507		9
27	Effect of radius variation on the mean strength of brittle fibers. <i>Journal of Materials Science Letters</i> , <b>2001</b> , 20, 1103-1105		8
26	Empirical correction factor for the best estimate of Weibull modulus obtained using linear least squares analysis. <i>Journal of Materials Science Letters</i> , <b>2001</b> , 20, 997-999		25
25	Fiber/matrix interface shear strength estimated from fiber pullout length data for Tyranno <sup>®</sup> Si-Zr-C-O fiber composites with different SiC-based matrices and interfaces. <i>Journal of Materials Science Letters</i> , <b>2001</b> , 20, 2127-2130		
24	Sinterability of SiAlON powder prepared by carbothermal reduction and simultaneous nitridation of ultrafine powder in the Al <sub>2</sub> O <sub>3</sub> -SiO <sub>2</sub> system. <i>Journal of Materials Science</i> , <b>2001</b> , 36, 165-172	4.3	6
23	Scanning electron microscopy study of failure in glass-sealed SiC/SiC-based composite (NUSK-CMC) creep tested at 1100 and 1200°C in air. <i>Advanced Composite Materials</i> , <b>2001</b> , 10, 357-367	2.8	1
22	Microprobe fluorescence spectroscopy evaluation of stress fields developed along a propagating crack in an Al <sub>2</sub> O <sub>3</sub> /CaO 6Al <sub>2</sub> O <sub>3</sub> ceramic composite. <i>Journal of Materials Research</i> , <b>2001</b> , 16, 2798-2804	2.5	6
21	Flexural properties of a hybrid polymer matrix composite containing carbon and silicon carbide fibres. <i>Advanced Composite Materials</i> , <b>2001</b> , 10, 77-96	2.8	30
20	Case study of failure in a glass-sealed SiC/SiC-based composite creep tested at 1100°C in air. <i>Materials Letters</i> , <b>2001</b> , 48, 205-209	3.3	4
19	Estimation of the fracture toughness of Tyranno Si-Ti-C-O fibres from flaw size and "fracture mirror" data measured in situ a 3-D woven SiC/SiC composite. <i>International Journal of Materials and Product Technology</i> , <b>2001</b> , 16, 189	1	8
18	Stress/Strain Behavior of a 3-D Woven Composite Based on the SiC/SiC System.. <i>Journal of the Ceramic Society of Japan</i> , <b>2001</b> , 109, 643-646		2

17	Tensile creep behavior of 3-D woven Si-Ti-C-O fiber/SiC-based matrix composite with glass sealant. <i>Journal of Materials Science</i> , <b>2000</b> , 35, 785-793	4.3	18
16	Comparison of fibre/matrix interface strength for a 3D woven SiC/SiC composite. <i>Composite Interfaces</i> , <b>2000</b> , 7, 479-485	2.3	1
15	Effect of sintering conditions on mechanical and physical properties of MgO ceramic reinforced with chopped SiC fibre. <i>Materials Letters</i> , <b>2000</b> , 43, 203-207	3.3	4
14	Mechanical properties in compression of CVI-densified porous carbon/carbon composite. <i>Composites Science and Technology</i> , <b>1999</b> , 59, 97-104	8.6	38
13	Optical microscopy of a 3-D woven SiC/SiC-based composite. <i>Composites Science and Technology</i> , <b>1999</b> , 59, 429-437	8.6	17
12	Fibre strength parameters measured in situ for ceramic-matrix composites tested at elevated temperature in vacuum and in air. <i>Composites Science and Technology</i> , <b>1999</b> , 59, 801-811	8.6	23
11	Fibre and interfacial properties measured in situ for a 3D woven SiC/SiC-based composite with glass sealant. <i>Composites Part A: Applied Science and Manufacturing</i> , <b>1999</b> , 30, 587-591	8.4	32
10	Fracture behaviour of boride-dispersed composites fabricated by hot-pressing amorphous Ni60Mo30B10 powder. <i>Journal of Materials Science</i> , <b>1998</b> , 33, 4727-4732	4.3	4
9	Creep Behavior and Modeling of SiC-Based PC Ceramic Matrix Composites with Glass Sealant in High Temperature Air. <i>Key Engineering Materials</i> , <b>1998</b> , 164-165, 197-200	0.4	3
8	In situ Properties of 3-D Woven SiC/SiC-Based Composite. <i>Key Engineering Materials</i> , <b>1998</b> , 164-165, 201-204	0.4	1
7	Microstructural investigation of low-density carbon-carbon composites. <i>Journal of Materials Science</i> , <b>1994</b> , 29, 338-344	4.3	45
6	Mechanical properties in flexure and tension of low density carbon-carbon composites. <i>Carbon</i> , <b>1994</b> , 32, 1449-1456	10.4	18
5	Mechanical properties in compression of low density carbon/carbon composites. <i>Composites</i> , <b>1994</b> , 25, 229-236		20
4	A Comparative Study of the Microstructure -Property Relationship in Human Adult and Baby Teeth. <i>Ceramic Engineering and Science Proceedings</i> , 145-152	0.1	
3	Influence of Oxidation on the Micro-Mechanical Properties of a 3-D Woven SiC/SiC Composite Tested in Air at 1100 °C. <i>Ceramic Transactions</i> , 175-186	0.1	
2	Influence of Geometrical Irregularities on the Creep Behaviour of Ceramic Fibres. <i>Ceramic Transactions</i> , 163-174	0.1	
1	Tensile and in Situ Fibre Properties of 3-D SiC/SiC-Based Composite Tested at Elevated Temperature in Vacuum and Air with and Without an Oxidation Protection System. <i>Ceramic Engineering and Science Proceedings</i> , 275-282	0.1	1