## CITATION REPORT List of articles citing



DOI: 10.1177/1420326x05050347 Indoor and Built Environment, 2005, 14, 59-68.

Source: https://exaly.com/paper-pdf/38766579/citation-report.pdf

Version: 2024-04-25

This report has been generated based on the citations recorded by exaly.com for the above article. For the latest version of this publication list, visit the link given above.

The third column is the impact factor (IF) of the journal, and the fourth column is the number of citations of the article.

#	Paper	IF	Citations
17	Physically Based Modelling of the Material and Gaseous Contaminant Interactions in Buildings: Models, Experimental Data and Future Developments. <i>Advances in Building Energy Research</i> , <b>2008</b> , 2, 57-93	1.8	25
16	Identification of Odor-Active Organic Sulfur Compounds in Gypsum Products. <i>Clean - Soil, Air, Water</i> , <b>2009</b> , 37, 459-465	1.6	5
15	An Experimental Study for Examining the Effects of Environmental Conditions on Diffusion Coefficient of VOCs in Building Materials. <i>Clean - Soil, Air, Water</i> , <b>2009</b> , 37, 436-443	1.6	21
14	Characterisation of VOC and Formaldehyde Emission from Building Materials in a Static Environmental Chamber: Model Development and Application. <i>Indoor and Built Environment</i> , <b>2011</b> , 20, 217-225	1.8	37
13	Integrating human health impact from indoor emissions into an LCA: a case study evaluating the significance of the use stage. <i>International Journal of Life Cycle Assessment</i> , <b>2013</b> , 18, 636-646	4.6	19
12	A rapid and accurate method, ventilated chamber C-history method, of measuring the emission characteristic parameters of formaldehyde/VOCs in building materials. <i>Journal of Hazardous Materials</i> , <b>2013</b> , 261, 542-9	12.8	52
11	The effect of humidity on formaldehyde emission parameters of a medium-density fiberboard: Experimental observations and correlations. <i>Building and Environment</i> , <b>2016</b> , 101, 110-115	6.5	33
10	The combined effects of temperature and humidity on initial emittable formaldehyde concentration of a medium-density fiberboard. <i>Building and Environment</i> , <b>2016</b> , 98, 80-88	6.5	43
9	A Pre-assessment and Control Tool for Indoor Air Quality (PACT-IAQ) Simulation in Actual Buildings. <i>Procedia Engineering</i> , <b>2017</b> , 205, 219-225		6
8	Spatial Clustering Group-Based OFDMA Multiple Access Protocol with Carrier Sensing for the Next-generation WLANs. <b>2018</b> ,		1
7	Improved C-history method for rapidly and accurately measuring the characteristic parameters of formaldehyde/VOCs emitted from building materials. <i>Building and Environment</i> , <b>2018</b> , 143, 570-578	6.5	27
6	Predicting Indoor Emissions of Cyclic Volatile Methylsiloxanes from the Use of Personal Care Products by University Students. <i>Environmental Science &amp; Environmental Science &amp;</i>	10.3	27
5	Improving material selection for residences using volatile organic compound simulation at design stage: Field verifications from a unique case study. <i>Building and Environment</i> , <b>2019</b> , 157, 277-283	6.5	3
4	Predicting the emission characteristics of VOCs in a simulated vehicle cabin environment based on small-scale chamber tests: Parameter determination and validation. <i>Environment International</i> , <b>2020</b> , 142, 105817	12.9	33
3	Development of a procedure for estimating the parameters of mechanistic VOC emission source models from chamber testing data. <i>Building Simulation</i> , <b>2021</b> , 14, 269-282	3.9	9
2	Bibliometric Study on Particle Emissions of Natural and Alternative Building Materials. <b>2022</b> , 495-507		
1	Sampling Volatile Organic Compound Emissions from Consumer Products: A Review. 1-22		1