

An efficient approach to temporarily separate foulants  
function for thermal energy recovery from sewage

Separation and Purification Technology

259, 118130

DOI: [10.1016/j.seppur.2020.118130](https://doi.org/10.1016/j.seppur.2020.118130)

Citation Report

#	ARTICLE	IF	CITATIONS
1	Optimizing the recovery pathway of a net-zero energy wastewater treatment model by balancing energy recovery and eco-efficiency. Applied Energy, 2021, 298, 117157.	10.1	21
2	The influence of height-to-width ratio of feed inlet on flow field characteristics and separation performance of the hydrocyclone with spiral inlet. International Journal of Coal Preparation and Utilization, 2022, 42, 1597-1614.	2.1	2
3	Experiment of hydrocyclone under different inlet velocity and its wear analysis of wall and particle. Powder Technology, 2022, 405, 117541.	4.2	3
4	A novel hydrocyclone for use in underground DNAPL phase separation. Science of the Total Environment, 2022, 842, 156866.	8.0	8
5	Physical Separation: Reuse Pollutants and Thermal Energy from Water. Water (Switzerland), 2023, 15, 1196.	2.7	0
6	Numerical investigation of hydrocyclone inlet configurations for improving separation performance. Powder Technology, 2024, 434, 119384.	4.2	1
7	Intensification of low-grade phosphate ore purification using a hydrocyclone with venturi-style inlet. Journal of Industrial and Engineering Chemistry, 2024, , .	5.8	0